

39967-39

2/17/2010

1 of 9

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY
WASHINGTON, D.C. 20460



Office of Pesticide Programs

Lanxess Corporation
111RIDC Park West Drive
Pittsburgh, PA 15275-1112

FEB 17 2010

Attention: Luanne Jeram
Senior Regulatory Affairs Specialist

Subject: Biochek 410
EPA Registration No. 39967-39
Notification Dated January 21, 2010

This will acknowledge receipt of your notification, submitted under the provisions of FIFRA Section 3(c)(9).

Proposed Notification

- Label Change per PR Notice 2007-4

General Comments

Based on a review of the submitted material, the following comments apply:

The Notification is in compliance with PR Notice 98-10 and is acceptable. This information has been added to your file.

If you have any questions concerning this letter, please contact Martha Terry at (703) 308-6217.

Sincerely

A handwritten signature in cursive script that reads "Martha Terry".

Marshall Swindell
Product Manager (33)
Regulatory Management Branch 1
Antimicrobials Division (7510P)

2019

United States Environmental Protection Agency Washington, DC 20460		<input type="checkbox"/> Registration <input type="checkbox"/> Amendment <input checked="" type="checkbox"/> Other	OPP Identifier Number _____
Application for Pesticide - Section I			
1. Company / Product Number <u>39967-39</u>		2. EPA Product Manager <u>Swindell</u>	
4. Company / Product (Name) <u>Biochek 410</u>		3. Proposed Classification <input checked="" type="checkbox"/> None <input type="checkbox"/> Restricted	
5. Name and Address of Applicant (include ZIP Code) <u>LANXESS Corporation</u> <u>111 RIDC Park West Drive</u> <u>Pittsburgh, PA 15275-1112</u> <input type="checkbox"/> Check of this is a new address		6. Expedited Review. In accordance with FIFRA Section 3(c)(3) (b)(I), my product is similar or identical in composition and labeling to: EPA Reg. No. _____ Product Name _____	
Section - II			
<input type="checkbox"/> Amendment - Explain Below. <input type="checkbox"/> Final printed labels in response to Agency letter dated _____			
<input type="checkbox"/> Resubmission in response to Agency letter dated _____ <input type="checkbox"/> "Me Too" Application			
<input checked="" type="checkbox"/> Notification - Explain below. <input type="checkbox"/> Other - Explain below.			
Explanation: Use additional page(s) if necessary. (For section I and Section II.) <small>Notification of label change per PR Notice 2007-4. This notification is consistent with the guidance in PR Notice 2007-4 and the requirements of EPA's regulations at 40 CFR §§ 156.10, 156.140, 156.144, 156.146, and 156.156. No other changes have been made to the labeling or the Confidential Statement of Formula for this product. I understand that it is a violation of 18 U.S.C. Sec. 1001 to willfully make any false statement to EPA. I further understand that if the amended label is not consistent with the requirements of 40 CFR §§ 156.10, 156.140, 156.144, 156.146, and 156.156, this product may be in violation of FIFRA and I may be subject to enforcement action and penalties under sections 12 and 14 of FIFRA."</small>			
Section - III			
1. Material This Product Will Be Packaged In:			
Child-Resistant Packaging <input type="checkbox"/> Yes <input type="checkbox"/> No <i>* Certification must be submitted</i>	Unit Packaging <input type="checkbox"/> Yes <input type="checkbox"/> No If "Yes" Unit Packaging wgt. _____	Water Soluble Packaging <input type="checkbox"/> Yes <input type="checkbox"/> No If "Yes" Package Wgt. _____	2. Type of Container <input type="checkbox"/> Metal <input type="checkbox"/> Plastic <input type="checkbox"/> Glass <input type="checkbox"/> Paper <input type="checkbox"/> Other (Specify) _____
3. Location of Net Contents Information <input type="checkbox"/> Label <input type="checkbox"/> Container		4. Size(s) retail Container _____	
5. Location of Label Directions _____		6. Manner in Which Label is affixed to Product <input type="checkbox"/> Lithograph <input type="checkbox"/> Other _____ <input type="checkbox"/> Paper glues <input type="checkbox"/> Stenciled	
Section - IV			
1. Contact Point (Complete items directly below for identification of individual to be contacted, if necessary. To process this application.)			
Name <u>Luanne Jeram</u>		Title <u>Senior Regulatory Affairs Specialist</u>	
		Telephone No. (Include Area Code) <u>412-809-4773</u>	
Certification I certify that the statements I have made on this form and all attachments thereto are true, accurate and complete. I acknowledge that any knowingly false or misleading statement may be punishable by fine or imprisonment or both under applicable law.			6. Date Application Received (Stamped) <div style="text-align: center;"> </div>
2. Signature <u>Luanne Jeram</u>		3. Title <u>Senior Regulatory Affairs Specialist</u>	
4. Typed Name <u>Luanne Jeram</u>		5. Date <u>1/21/10</u>	

LANXESS
Energizing Chemistry

Luanne Jeram
Material Protection Products
Regulatory Affairs
111 RIDC Park West Drive
Pittsburgh, PA 15275-1112

Phone 412-809-4773
Fax 412-809-1068
luanne.jeram@lanxess.com
www.US.LANXESS.com

Dear Mr. Heyward:

Specifically enclosed are:

1. Application form (EPA Form 8570-1)
2. Proposed label highlighting the updated statements in yellow – 1 copy
3. Proposed label – 1 copy

Please feel free to contact me at 412-809-4773 with any questions.

Sincerely,

Sincerely,
Luanne Jeram
Luanne Jeram

Luanne Jeram
Senior Regulatory Affairs Specialist

BIOCHEK[®] 410

AN INDUSTRIAL PRESERVATIVE TO INHIBIT THE GROWTH OF BACTERIA, FUNGI AND YEASTS IN AQUEOUS PAINTS, LATEX EMULSIONS, METALWORKING FLUIDS, PIGMENT SLURRIES, JOINT CEMENTS, HOUSEHOLD PRODUCTS AND PRINTING FLUIDS

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER. CORROSIVE. Causes irreversible eye damage. Harmful if inhaled. Harmful if swallowed or absorbed through skin. Avoid breathing vapor or spray mist. Prolonged or frequently repeated skin contact may cause allergic reaction in some individuals. Remove contaminated clothing and wash before reuse.

Handlers must wear: Long-sleeved shirt and long pants; socks and shoes; goggles or face shield; Chemical resistant gloves (such as rubber or any waterproof material); and either a respirator with an organic vapor (OV) cartridge, or a canister with any N, P, R or HE prefilter or a dust/mist filtering respirator (MSHA/NIOSH) approval number prefix TC-21 or a NIOSH approved respirator with any N, P, R or HE prefilter.

Discard clothing or other absorbent materials that have been drenched or heavily contaminated with this product's concentrate. Do not reuse them. Follow manufacturer's instructions for cleaning/maintaining PPE. If no such instructions for washables exist, use detergent and hot water. Keep and wash PPE separately from other laundry.

Wash hands thoroughly before eating drinking, chewing gum, using tobacco, or using the toilet. Remove contaminated clothing immediately if pesticide gets inside. Then wash thoroughly and put on clean clothing. Remove personal protective equipment immediately after handling this product. Wash outside of gloves before removing. As soon as possible wash thoroughly.

ENVIRONMENTAL HAZARDS

This product is toxic to fish and wildlife. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans, or public waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

IN CASE OF EMERGENCY, CALL: CHEMTREC 800-424-9300

EPA Reg. No.: 39967-39

EPA Est. No.:

ACTIVE INGREDIENTS: 1,2-Dibromo-2,4-dicyanobutane -----19%
1,2-Benzisothiazolin-3-one -----6%

INERT INGREDIENTS: -----75%
TOTAL 100%

KEEP OUT OF REACH OF CHILDREN DANGER

FIRST AID

IF IN EYES: Hold eyes open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing. Call a poison control center or doctor for treatment advice.

IF SWALLOWED: Call a poison control center or doctor immediately for treatment advice. Have person sip a glass of water if able to swallow. Do not induce vomiting unless told by a poison control center or doctor.

IF ON SKIN: Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control center or doctor for treatment advice.

IF INHALED: Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth, if possible. Call a poison control center or doctor for treatment advice.

NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage. Measures against circulatory shock, respiratory depression and convulsion may be needed.

The LANXESS Pittsburgh Emergency Response Telephone Number is 800-410-3063.

*Biochek is a registered trademark of LANXESS Corporation

Mix well before using this product.

INTERNATIONAL 703-527-3887

Net Contents:

Lot No.:

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

Do not apply in a way that will contact workers or other persons. The amount necessary for desired protection varies, depending on exposure conditions. For further application information refer to the Product Bulletin.

STORAGE AND DISPOSAL

Keep container closed when not in use. Do not contaminate water, food, or feeds by storage or disposal.

Ship and store Biochek 410 at temperatures between 0-42 °C (32-108 °F). Freezing the product may cause a temporary water separation, which can be corrected by mechanical agitation.

Store away from heat. At temperatures above 42 °C (108 °F), the active ingredients in the dispersion may separate out.

PESTICIDE DISPOSAL: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State pesticide environmental control agency, or the hazardous waste representative at the nearest regional office for guidance.

CONTAINER DISPOSAL: Nonrefillable container. Do not reuse or refill this container. Offer for recycling if available or reconditioning if appropriate. Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in sanitary landfill, by incineration or, if allowed by State and Local authorities, by burning. If burned, stay out of smoke.

LANXESS

LANXESS Corporation

111 RIDC Park West Drive • Pittsburgh, PA 15275-1112

LABEL TEXT DATE: DRAFT 1/21//2010

4089

LANXESS

Energizing Chemistry

Product Information

BIOCHEK 410
EPA Registration Number: 39967-39

Page 1
BIOCHEK 410
39967-39

[illegible]

60f9

BIOCHEK® 410 **Industrial Preservative**

PRODUCT BENEFITS

- Broad spectrum
- Excellent long-term preservation
- FDA approved
- Wide pH range (2.0 – 9.5)

GENERAL DESCRIPTION

BIOCHEK 410 is an industrial preservative which effectively inhibits the growth of bacteria, fungi and yeasts in aqueous systems including paints, adhesives, latex emulsions, metalworking fluids, pigment slurries, joint cements, household products, and printing fluids. **BIOCHEK 410** is intended to protect products during storage. Chemically, **BIOCHEK 410** is a 19% dispersion of 1,2-dibromo-2,4-dicyanobutane and 6% 1,2-benzisothiazolin-3-one, shown in order in the chemical diagram below. For a general description of the typical chemical and physical properties, see the **BIOCHEK 410** Material Safety Data Sheet.

APPLICATION

The growth of microorganisms in aqueous systems during shipment, storage and handling can be detrimental to effectiveness. Such growth can affect such properties as odor, color viscosity and introduce microbial growth into production equipment and processes. **BIOCHEK 410** is effective in controlling such contamination and can improve the effectiveness and extend the life of materials treated if used according to the instructions given below.

TYPICAL LEVELS OF USE

Laboratory testing and customer use shows **BIOCHEK 410** is typically effective when applied at concentrations shown. The exact amount necessary for the preservation of any given formulation will depend on the components, storage time, temperature, etc., and can be determined through actual testing coordinated by your LANXESS Corporation representative. All concentrations are based on the total formulation weight.


Product Use Level	
Adhesives	500 – 8000 ppm
Latex Emulsions	500 – 8000 ppm
Metalworking Fluids	500 – 4000 ppm
Aqueous Paints	500 – 4000 ppm
Pigment Slurries	500 – 2000 ppm
Joint Cements	2000 – 8000 ppm
Household Products	500 – 4000 ppm

FDA STATUS AND APPROVALS

BIOCHEK 410 has FDA approval under 21 CFR 175.105, 176.170 and 176.180.
BIOCHEK 410 is approved by the German BGVV, Recommendation XXXVI.

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.



Taf9

Adhesives

BIOCHEK 410 is formulated to facilitate incorporate by pumping into the makeup water. **BIOCHEK 410** can be incorporated by pouring if necessary. Where the adhesive is heated, **BIOCHEK 410** should be added during the cool-down cycle to minimize any evaporative loss. Adhesives for which **BIOCHEK 410** provides effective in-can preservation are starch, epoxy, polyester, polyvinyl acetate, styrene butadiene, methyl cellulose, acrylic, polyvinyl alcohol, hydroxyethyl cellulose, dextrin and casein. Such adhesives include, but are not limited to, those used in manufacturing process, construction projects, packaging materials.

Effective protection is achieved between 500 – 8000 ppm. Optimum effective concentration can vary with properties of the material being preserved. Testing to determine the appropriate level for your product is highly recommended.

Aqueous paints

BIOCHEK 410 is formulated to facilitate incorporate by pumping into the makeup water. **BIOCHEK 410** can be incorporated by pouring if necessary. **BIOCHEK 410** should be incorporated into the makeup water during the grind.

BIOCHEK 410 is an effective in-can preservative for all type of aqueous paints and coatings when used at levels of 500 – 4000 ppm. The optimum effective concentration can vary with properties of the material being preserved. Testing to determine the appropriate level for your product is highly recommended.

Latex emulsions


BIOCHEK 410 is formulated to facilitate incorporate by pumping into the makeup water. **BIOCHEK 410** can be incorporated by pouring if necessary. Pump or pour using moderate agitation immediately following cool-down of the emulsion, and prior to pumping the emulsion into storage tank facilities. Latex emulsions that are preserved by **BIOCHEK 410** include polyvinyl acetate, acrylic, vinyl acrylic and styrene butadiene. These emulsions are the raw materials used in the formulation of paints, adhesives, joint cements, pigments and household products.

Effective protection is achieved between 500 – 8000 ppm. Optimum effective concentration can vary with properties of the material being preserved. Testing to determine the appropriate level for your product is highly recommended.

Dispersed pigments

BIOCHEK 410 is formulated to facilitate incorporate by pumping into the makeup water. **BIOCHEK 410** can be incorporated by pouring if necessary. Pump or pour using moderate agitation immediately following cool-down of the dispersed pigment and prior to pumping to the storage tank. **BIOCHEK 410** is an effective in-can preservative to protect the pigment during handling, transportation and storage. Dispersed pigments are used to impart color to many products such as paints and coatings, adhesives and plastics.

Effective protection is achieved between 500 – 2000 ppm. Optimum effective concentration can vary with properties of the material being preserved. Testing to determine the appropriate level for your product is highly recommended.



Household products and waxes, polishes, and inks

BIOCHEK 410 is formulated to facilitate incorporate by pumping into the makeup water. **BIOCHEK 410** can be incorporated by pouring if necessary. Incorporate by pumping or pouring with agitation into the makeup water blend. These products include, but are not limited to, dishwashing liquids, furniture and floor waxes and polishes, cleaners and treatment products and over-the counter inks sold to custom color decorative household projects.

Effective protection is achieved between 500 – 8000 ppm. Optimum effective concentration can vary with properties of the material being preserved. Testing to determine the appropriate level for your product is highly recommended.

Joint cements

BIOCHEK 410 is formulated to facilitate incorporate by pumping into the makeup water. **BIOCHEK 410** can be incorporated by pouring if necessary. Incorporate by pumping or pouring with agitation into the makeup water blend. These products include mortar-like sealers that are used to construct walls.

Effective protection is achieved between 2000 – 8000 ppm. Optimum effective concentration can vary with properties of the material being preserved. Testing to determine the appropriate level for your product is highly recommended.

Metalworking fluids


BIOCHEK 410 is formulated to facilitate incorporate by pumping, but can be poured. Pump or pour **BIOCHEK 410** into the final diluted fluid either prior to its addition to the system at a level that will provide adequate protection in the diluted system, or after the system has been filled. **BIOCHEK 410** should be thoroughly mixed into the system to assure efficacy. If **BIOCHEK 410** is added to the concentrate, testing should be conducted to assure compatibility.

Effective protection is achieved between 500 – 4000 ppm. Optimum effective concentration can vary with properties of the material being preserved. Testing to determine the appropriate level for your product is highly recommended.

Printing fluids

BIOCHEK 410 is formulated to facilitate incorporate by pumping, but can be poured. Add to fluid concentrates during, or at the end of, mixing prior to filling at concentrations from 30 – 5000 ppm by weight. These printing fluids may be further diluted with water by printers so that the final concentration of **BIOCHEK 410** is 10 – 2000 ppm by weight. This product includes all types of printing fluid products such as, but not limited to printing, copier and computer inks.

Optimum effective concentration should be determined by testing in your specific application.



90f9

() ()

MATERIALS COMPATIBILITY

Positive displacement pumps are preferred for handling the product.

STORAGE AND HANDLING

Read the label and MSDS for complete handling information before using this product.

BIOCHEK 410 is available in pails, drums and bins.

If you need assistance or information, please call your nearest LANXESS representative, or our Pittsburgh office at 800-LANXESS.

INTERNATIONAL (703)-527-3887

HAVE THE PRODUCT CONTAINER OF LABEL WITH YOU WHEN CALLING A POISON CONTROL CENTER OR DOCTOR OR GOING FOR TREATMENT.

LANXESS Corporation
111 RIDC Park West Drive
Pittsburgh, PA 15275
412-809-1000

