UNITED STATES ENVIRONMENTAL PROTECTION AGENCY WASHINGTON, D.C. 20460



EPA United States Environmental Protection Office of Pesticide Programs Agency

Lanxess Corporation 111RIDC Park West Drive Pittsburgh, PA 15275-1112

APR - 9 2009

Attention: Luanne Jeram

Regulatory Affairs MPP

Subject: TCMTB 30 G

EPA Registration No.39967-72 Amendment Dated March 20, 2009

The amendment, submitted in connection with registration under the Federal Insecticide, Fungicide and Rodenticide Act (FIFRA), as amended, to change the primary name, is acceptable.

OLD PRODUCT NAME: Preventol TC 30

NEW PRODUCT NAME: TCMTB 30 G

Please note that the request to change the alternate brand name from "TCMTB 30 G" to "Preventol TC 30" is acceptable.

A stamped copy of the "accepted" product labeling is enclosed for your records.

If you have any questions concerning this letter, please contact Martha Terry at (703) 308-6217.

Sincerely

Marshall Swindell

Product Manager (33)

Regulatory Management Branch 1 Antimorobials Division (7510P)

Enclosure

TCMTB 30 G

For the preservation of Leather, Hides and Skins, Pulp and Paper Mills, Bateriostatic Paper (Non-food contact), Coatings, Caulks, Sealants, Wallcovering Adhesives. Drilling Fluids, Cutting Fluids, Petroleum Secondary Recovery, Cooling Water and Cooling Towers and Wastewater Treatment Systems.

> ACTIVE INGREDIENT: 2-(Thiocyanomethylthio)benzothiazole [CAS# 21564-17-0]------30.0% INERT INGREDIENTS ------100.0%

KEEP OUT OF REACH OF CHILDREN DANGER

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

Causes irreversible eye damage. May be fatal if inhaled. Harmful if swallowed. Do not get in eyes, on skin, or on clothing. Do not breathe vapor or spray mist. Wear protective eyewear (such as goggles or face shield). Wear a respirator with an organic-vapor removing cartridge with a prefilter approved for pesticides (MSHA/NIOSH approval number prefix TC-23C), or a canister approved for pesticides (MSHA/NIOSH approval number prefix TC-14G), or a NIOSH approved respirator with an organic vapor (OV) cartridge or canister with any N, R, P or HE prefilter. Prolonged or frequently repeated skin contact may cause allergic reactions in some individuals. Wear long-sleeved shirt and long pants, socks, shoes and chemical resistant gloves (such as butyl rubber or nitrile rubber). Avoid contact with skin or clothing. Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, using tobacco or using the toilet. Remove and wash contaminated clothing before reuse.

STORAGE AND DISPOSAL

Do not contaminate water, food or feed by storage or disposal.

PESTICIDE STORAGE: Product should be stored in an area that is not subject to extreme temperatures. Store in a cool, dry place and in such a manner as to prevent cross contamination with other pesticides, fertilizers, food, and feed. Leaking or damaged drums should be placed in overpack drums for disposal. Spills should be absorbed in sawdust or sand and disposed of in a sanitary landfill.

PESTICIDE DISPOSAL: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the hazardous waste representative at the nearest EPA Regional office for quidance.

CONTAINER DISPOSAL: Empty residue into application equipment. Triple rinse (or equivalent) then offer drum for recycling or reconditioning, or puncture. Dispose of drum and liner in a sanitary landfill; by incineration or, if allowed by State and Local authorities, by burning. If burned, stay out of smoke.

The LANKESS Pittsburgh Emergency Response Telephone Number is 800-410-3063

IN CASE OF EMERGENGY, CALL: CHEMTREC 800-424-9300

EPA REGISTRATION NUMBER: 39967-72

🖟 EPÅ ESTÅBLISHMENT NUMBER:

LANXESS

LANXESS Corporation 111 RIDC Park West Drive • Pittsburgh, PA 15275-1112

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling. TCMTB 30 G is intended for use in Leather, Pulp and Paper Mills, Coatings, Caulks, Sealants, Wall Covering Adhesives, Drilling and Cutting Fluids, Cooling Waters and Cooling Towers, Petroleum Secondary Recovery and Waste Water Treatment Systems. Please see the TCMTB 30 G label supplement for dosage instructions. Not registered for use in the state of California

FIRST AID

IF IN EYES: Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control center or doctor for treatment advice.

IF INHALED: Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth, if possible. Call a poison control center or doctor for further treatment advice.

IF ON SKIN OR CLOTHING: Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control center or doctor for treatment advice. IF SWALLOWED: Call a poison control center or doctor immediately for treatment advice. Have person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by the poison control center or doctor. Do not give anything to an unconscious person. Note to Physician: Probable mucosal damage may contraindicate the use of gastric lavage. Medical Treatment; First aid eye irrigation should be repeated and continued until a sterile balanced buffered solution is available for continuous eye irrigation. Irrigation with a solution such as normal saline or Ringer's lactate should be continued until the pH of the ocular surface is neutralized, usually 1-2 liters of fluid. If any symptoms persist or recur, consultation with an ophthalmologist is advised.

Have the product container or label with you when calling a poison control center or doctor or when going in for treatment. For emergency information concerning this product, call the National Pesticide Information Center at 1-800-858-7378, 6:30 AM to 4:30 PM Pacific time (PT), seven days a week. During other times, call the poison control center 1-800-222-1222.

ENVIRONMENTAL HAZARDS

This pesticide is toxic to fish, aquatic invertebrates, oysters and shrimp. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans, or other waters unless in accordance with the requilibration of a National Pollutant Discharge Elimination System (NPDES) permit and the permithing authority has been notified in writing prior to the discharge. Do not discharge effluent containing this product to sewer systems with the reviewer by notifying the local sewage treatment plant authority. For guidance, contact your State Water Board or Registral Different authority. not contaminate water by cleaning of equipment or disposal of waste. EPA Letter Dated:

INTERNATIONAL 703-527-3887 **Net Contents:** Lot No.:

Under the Federal Insecticide. Fungicide, and Rodenticide Act as

- APR -- 9-2009

LABEL TEXT DATE 24768/69d, for the pezticide, registered under EPA Reg. No. 39967-12

Energizing Chemistry

Product Information

TCMTB 30 G

EPA Registration Number 39967-72

ACCEPTED with COMMENTS EPA Letter Dated:

APR - 9 2009

Under the Federal Insecticide, Fungicide, and Rodenticide Act as amended, for the pesticide, registered under EPA Reg. No. 39967-12

> TCMTB 30 G 39967-72 Page 1

TCMTB 30 G

TCMTB 30 G IS EFFECTIVE AGAINST A VARIETY OF MOLD AND FUNGI FOR THE PRESERVATION OF LEATHER HIDES AND SKIN, COATINGS, CAULKS, SEALANTS, WALL-COVERING ADHESIVES, CUTTING FLUIDS, DRILLING FLUIDS. PRESERVATION FOR MATERIALS IN PAPER INDUSTRY (PULP AND PAPER MILLS), COOLING TOWERS, COOLING WATER SYSTEMS, PETROLEUM SECONDARY RECOVERY AND WASTEWATER TREATMENT SYSTEMS.

Chemical and Physical Data

Active Ingredient:

2-(Thiocyanomethylthio)benzothiazole

Common Name:

ТСМТВ

Chemical Name:

2-(Thiocyanomethylthio)benzothiazole

Minimum Purity: Density (25°C):

29.8% 1.130 g/ml

Flash Point:

82.8°C

ACCEPTED
with COMMENTS
EPA Letter Dated:

APR - 9 2009

Under the Federal Insorticide, and Pode are Act as

DANGER

Directions for Use

It is a violation of federal law to use this product in a manner inconsistent with its labeling.

The following guidance is given as an approximation for each use pattern, but field-testing is recommended to achieve optimum effectiveness.

LEATHER

TCMTB 30 G is recommended for the prevention of mold, bacteria and fungi in the storage, transport and processing of wet leather stock such as pickled, vegetable, chrome or alternative metal or metal free tanned hides and skins. Dosage rates of 0.025-0.2~% (250-2,000~ppm) are recommended on a weight basis to prevent microbial growth on processed hides and skins. The dosage level used will depend on storage conditions and the length of protection required. A dilution of 1 part TCMTB 30 G plus 5 parts water can be prepared by adding TCMTB 30 G to water with agitation. The diluted product may then be added to the pickling liquor, or the tanning liquor at the start of the tanning processor or to the rinse water in a post tanning refloat. The product can also be applied during the fatliquouring process to prevent fungal growth at 0.025-0.2% based on the split and shaved weight of leather being processed. For preservation of leather finishing pastes and fatliquours. TCMTB 30 G can be added at dosage rates of 0.1-0.25% (1000-2500~ppm) based on the weight of the treated paste or fatliquor and mixed thoroughly to ensure adequate dispersion.

PULP and PAPER MILLS

Pulp Mills: To protect wood chips from fungal degradation during storage. TCMTB 30 G should be used at 0.5 to 2 pounds/ton of oven-dried wood. It can be applied through a water shower located in the pneumatic conveyor carrying chips from the chipper to the storage pile. For preservation of wet lap or sheet pulp. TCMTB 30 G is used at 0.5 to 4 pound/ton of oven-dried fiber. It is applied to the surfaces of the dewatered pulp by means of applicator rolls.

PAPER MILLS: To control bacterial and fungal growth on paper and paperboard machines, TCMTB 30 G is added to the white water or stock at 0.1 to 0.5 pound/ton of dry paper or paperboard produced.

BACTERIOSTATIC PAPER (Non-food contact): To make mold resistant paper or paperboard. TCMTB 30 G is used at 0.05 to 0.1 pound/1000 sq ft (0.1 to 0.3 pound/3000 sq ft) of surface. For coated paper or board, TCMTB 30 G is incorporated in the coating mix prior to application of the coating. For uncoated paper or board, TCMTB 30 G is dispersed in water, surface-sizing solution, or other solvent and applied to the surface to be protected by means of an applicator roll. For the preservation of agricultural mulch paper, TCMTB 30 G is used at 1.5 to 5 pounds/ton air-dried paper. It is applied to the surfaces of mulch paper by tub-sizing methods or by means of applicator rolls before the paper is coated.

COATINGS, CAULKS, SEALANTS AND WALLCOVER ADHESIVES

TCMTB 30 G may be added to coatings, caulks, sealants and wallcover adhesives at levels of 0.5-5% based on total formulation weight. Ensure adequate mixing. TCMTB 30 G will inhibit the growth of fungi, mold and mildew, that often cause discoloration in these products. When used in solvent-based formulations, TCMTB 30 G can be dissolved in aromatic solvents or combinations of aromatic and aliphatic and added in the let down or added directly to the finished products. For water-thinned latex emulsion formulations, TCMTB 30 G can be premixed with the wetting agent and added to pigment slurry or added to the let down or finished product.

DRILLING FLUIDS

DRILLING FLUIDS: To inhibit bacterial and fungal degradation of the fluids or muds used in the drilling of wells, TCMTB 30 G is incorporated in the drilling fluid at concentrations of 0.05 – 0.25% based on the total wet weight of the fluid.

CUTTING FLUIDS

CUTTING FLUIDS: TCMTB 30 G may be used to inhibit bacterial and fungal degradation of water-based, water-soluble or emulsifiable cutting fluids and coolants used in metalworking operations. TCMTB 30 G should be added to the diluted cutting fluid at a rate that will provide 150 to 250 parts per million TCMTB 30 G (weight/weight) after final dilution with water. Higher concentrations (1000 to 1250 ppm) of TCMTB 30 G are required to prevent fungal growth on the inside walls of the diluted metalworking fluid storage tanks.

PETROLEUM SECONDARY RECOVERY

TCMTB 30 G 39967-72 Page 3 ACCEPTED with COMMENTS EPA Letter Dated:

APR - 9 2009

Under the Federal Insecticide, Fungicide, and Rodenticide Act as amended, for the pesticide, registered under EPA Reg. No. 39967-72

6

PETROLEUM SECONDARY RECOVERY: TCMTB 30 G can be used to control sulfate-reducing bacterial, slime-forming bacteria and fungi in oil-field water, polymer, or micellar floods, water-disposal systems, and other oil-field water systems at dosage rates of 0.2 to 3.7 fluid ounces of TCMTB 30 G per 1000 gallons of water treated. Additions should be made continuously or intermittently by means of a metering pump at the free water knockouts, before or after injection pumps and injection well headers. *Continuous Feed Method*: When system is noticeably fouled, add 0.6 to 3.7 ounces of TCMTB 30 G per 1000 gallons of water continuously until desired degree of control is achieved. Then treat with 0.2 to 1.2 fluid ounces per 1000 gallons of water continuously, or as needed to maintain control. *Intermittent or Slug Method*: When system is noticeably fouled, or to maintain control, add 0.6 to 3.7 fluid ounces TCMTB 30 G per 1000 gallon of water for 4 to 8 hours per days and 1 to 4 times per week, or as needed to maintain control.

COOLING WATER AND COOLING TOWERS

COOLING WATER: TCMTB 30 G will control algae, bacteria, and fungi in industrial recirculating cooling water systems. Before treatment is begun, the system should be cleaned thoroughly to remove old algal growth, microbiological slime, and other deposits. The system should then be drained, flushed, refilled with water, and treated with an initial dose of 0.6 to 3.7 ounces of TCMTB 30 G per 1000 gallons of water. Subsequent additions of 0.2 to 1.2 fluid ounces should be made every 1 to 5 days, depending on amount of bleedoff and severity of microbiological fouling.

COOLING TOWERS: TCMTB 30 G is used to protect cooling tower wood against soft or surface rot and internal or dry rot. It is applied by painting a dispersion containing 0.5 to 0.7% TCMTB 30 G in water onto the clean wood surfaces. The amount applied should provide 0.6 to 0.8 pound TCMTB 30 G per 1000 sq ft of wood surface. Soft or surface rot can also be inhibited by periodic shock doses of TCMTB 30 G to the recirculating cooling water at the tower basin or cold well. The dosage should provide 1.25 pounds of TCMTB 30 G per 1000 gallon of water and the bleedoff should be stopped for 4 to 6 hours after treatment. The shock treatment should be repeated every four months.

WASTE WATER TREATMENT SYSTEMS

WASTE WATER TREATMENT SYSTEMS: TCMTB 30 G can control bacteria and fungal slime in waste water systems and effluents. The quantity of TCMTB 30 G required varies with the degree of fouling. It should be added at a rate that will provide 10 to 30 ppm TCMTB 30 G (weight/weight) of the waste water. This addition can be made at various points in the system including the influent to the clarifier or the holding basins or ponds.

NOT REGISTERED FOR USE IN CALIFORNIA

ACCEPTED
with COMMENTS
EPA Letter Dated:

APR - 9 2009

Under the Federal Insecticide, Fungicide, and Rodenticide Act as amended, for the pesticide, registered under EPA Reg. No. 39 94118

LANXESS Corporation 111 RIDC Parkwest Drive

> TCMTB 30 G 39967-72 Page 4

Pittsburgh, PA 15275

The conditions of your use and application of our products, technical assistance and information (whether verbal, written or by way of production evaluations), including any suggested formulations and recommendations, are beyond our control. Therefore, it is imperative that you test our products, technical assistance and information to determine to your own satisfaction whether they are suitable for your intended uses and applications. This application-specific analysis at least must include testing to determine suitability from a technical as well as health, safety and environmental standpoint. Such testing has not necessarily been done by LANXESS Corporation. All information is given without warranty or guarantee. It is expressly understood and agreed that the customer assumes and hereby expressly releases LANXESS from all liability, in tort, contract or otherwise, incurred in connection with the use of our products, technical assistance and information. Any statement or recommendation not contained herein is unauthorized and shall not bind LANXESS. Nothing herein shall be construed as a recommendation to use any product in conflict with patents covering any material or its use. No license is implied or in fact granted under the claims of any patent.

1/09

ACCEPTED with COMMENTS EPA Letter Dated:

APR - 9 2009

Under the Federal Insecticide, Fungicide, and Rodenticide Act as amended, for the pesticide, registered under EPA Reg. No. 39967-13