

39967-91

4/10/2013

1/11

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY
WASHINGTON, D.C. 20460

APR 10 2013



Office of Pesticide Programs

Lanxess Corporation
111 RIDC Park West Drive
Pittsburgh, PA 15275-1112

Attention: Barbara Sadler
Regulatory Affairs Specialist

Subject: **Preventol IT 14 PRESERVATIVE**
EPA Registration No.39967-91
Notification Dated January 21, 2013

The amendment, submitted in connection with registration under section 3©(7)(A) of the Federal Insecticide, Fungicide and Rodenticide Act (FIFRA), as amended, to add additional use sites to the product label, is acceptable, provided that you:

1. Submit and/or cite all data required for registration/reregistration of your product under FIFRA sec. 3©(5) and sec. 4 uses when the Agency requires all registrants of similar products to submit such data.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA sec. 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

A stamped copy of the "accepted" product labeling is enclosed for your records. Submit two (2) copies of final printed labeling before you release the product for shipment.

If you have any questions concerning this letter, please contact Martha Terry at (703) 308-6217.

Sincerely,

Marshall Swindell
Product Manager (33)
Regulatory Management Branch 1
Antimicrobials Division (7510P)

Enclosure

PREVENTOL® IT 14 PRESERVATIVE

FOR THE PRESERVATION OF PAINTS AND COATINGS; PIGMENT AND MINERAL SLURRIES; ADHESIVES AND TACKIFIERS; POLYMER EMULSIONS, METALWORKING FLUIDS, BUILDING MATERIALS, FOUNTAIN SOLUTIONS, INKS, AND PHOTOPLATE PROCESSING; PAPER-MILL PROCESS WATER, RECIRCULATING COOLING WATER SYSTEMS, BREWERY PASTEURIZER AND CAN WARMER SYSTEMS; HYDRAULIC FLUIDS, OIL FIELDS INJECTION WATERS, AIR WASHER SYSTEMS; RECIRCULATING ELECTRODEPOSITION SYSTEMS, METAL-CLEANING FLUIDS, COMMERCIAL PHOTOPROCESSING SYSTEMS, AQUEOUS COMPONENTS, ULTRA FILTRATION AND REVERSE OSMOSIS SYSTEMS, INDUSTRIAL WASTEWATER TREATMENT SYSTEMS AND SEWAGE SYSTEMS, INDUSTRIAL PROCESS WATER SYSTEMS AND SEMI-SOLID/SOLID HOUSEHOLD CONSUMER, INDUSTRIA, JANITORIAL PRODUCTS

ACTIVE INGREDIENT: 5-chloro-2-methyl-4-isothiazolin-3-one ----- 11.14%

2-Methyl-4-isothiazolin-3-one ----- 3.56%

INERT INGREDIENTS ----- 85.3%

TOTAL ----- 100.0%

KEEP OUT OF REACH OF CHILDREN DANGER

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER. CORROSIVE. Causes irreversible eye damage and skin burns. May be fatal if absorbed through the skin. Harmful if swallowed or inhaled. Do not get in eyes, on skin, or on clothing. Avoid breathing vapor or spray mist. Prolonged or frequently repeated skin contact may cause allergic reaction in some individuals. Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, using tobacco or using the toilet. Mixers, loaders and other exposed to this product must wear: Chemical resistant apron over long sleeved shirt and long pants, chemical resistant gloves such as nitrile or butyl rubber, shoes plus socks, goggles and face shield. Remove and wash contaminated clothing before reuse. Discard clothing or other absorbent material that have been drenched or heavily contaminated with this product. Do not reuse them. Follow manufacturer's instructions for cleaning/maintaining PPE. If no such instructions exist for washables, use detergent and hot water. Keep and wash PPE separately from other laundry. Users should remove clothing immediately if pesticide gets inside. Then wash thoroughly and put on clean clothing. Users should remove personal protective equipment immediately after handling this product. Wash the outside of gloves before removing. As soon as possible, wash thoroughly and change into clean clothing.

FIRST AID

IF IN EYES: Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control center or doctor for treatment advice.

IF ON SKIN OR CLOTHING: Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control center or doctor for treatment advice.

IF SWALLOWED: Call a poison control center or doctor immediately for treatment advice. Have person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by the poison control center or doctor. Do not give anything to anyone who is unconscious or unable to breathe on their own.

IF INHALED: Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth, if possible. Call a poison control center or doctor for further treatment advice.

NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage.

Have the product container or label with you when calling a poison control center or doctor or when going in for treatment.

The LANXESS Pittsburgh Emergency Response Telephone Number is 800-410-3063
IN CASE OF EMERGENCY, CALL: CHEMTREC 800-424-9300

LANXESS

LANXESS Corporation
111 RIDC Park West Drive • Pittsburgh, PA 15275-1112

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

Detailed directions for use can be found in the PREVENTOL® IT 14 Preservative Information Sheet. Obtain and read this information before undertaking the use of PREVENTOL® IT 14 Preservative in order to avoid process mistakes.

PHYSICAL AND CHEMICAL HAZARDS

This product is corrosive to mild steel.

STORAGE AND DISPOSAL

Do not contaminate water, food or feed by storage or disposal.

PESTICIDE STORAGE: Do not store or transport in unlined metal containers. Product should be stored in an area that is not subject to extreme temperatures. Store in a cool, dry place and in such a manner as to prevent cross contamination with other pesticides, fertilizers, food, and feed. Do not apply this product in a way that will contact workers or other persons.

PESTICIDE DISPOSAL: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the hazardous waste representative at the nearest EPA Regional office for guidance.

CONTAINER DISPOSAL: Nonrefillable container. Do not reuse or refill this container.

Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill or by incineration, or if allowed by State and Local authorities, by burning. If burned, stay out of smoke.

ENVIRONMENTAL HAZARDS

This pesticide is toxic to aquatic plants, fish and aquatic invertebrates. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to the discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA. Do not contaminate water by cleaning of equipment or disposal of waste.

With COMMENTS in EPA Letter

PREVENTOL is a registered trademark of LANXESS Corporation

INTERNATIONAL 703-527-3888 APR 10 2013 EPA Reg. No. 39967-91
EPA EST. No. 39967-91
Net Contents: Under the Federal Insecticide, Fungicide, and Rodenticide Act, amended for the pesticide registered under EPA Reg. No. 39967-91
Lot No.:

LABEL TEXT DATE: 1/16/2013

2
11

LANXESS

Energizing Chemistry

Product Information

ACCEPTED
With COMMENTS
in EPA Letter Dated:

APR 10 2013
under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended, for the pesticide,
registered under EPA Reg. No.

39967-91

PREVENTOL® IT 14 PRESERVATIVE

EPA Registration Number 39967-91
CAS Number: 26172-55-4 and 2682-20-4

.....
.....
.....
.....
.....
.....
.....
.....
.....
.....
.....
.....
.....
.....

4/11

PREVENTOL® IT 14 Preservative

FOR THE PRESERVATION OF PAINTS AND COATINGS, PIGMENT AND MINERAL SLURRIES, ADHESIVES AND TACKIFIERS, POLYMER EMULSIONS, METALWORKING FLUIDS, BUILDING MATERIALS, FOUNTAIN SOLUTIONS, INKS, AND PHOTOPLATE PROCESSING, PAPER MILL PROCESS WATER, RECIRCULATING COOLING WATER SYSTEMS, BREWERY PASTEURIZER AND CAN WARMER SYSTEMS, HYDRAULIC FLUIDS, OIL FIELDS INJECTION WATERS, AIR WASHER SYSTEMS, RECIRCULATING ELECTRODEPOSITION SYSTEMS, METAL CLEANING FLUIDS, COMMERCIAL PHOTOPROCESSING SYSTEMS, ELECTRODEPOSITION PAINT COMPONENTS, LIQUID HOUSEHOLD CONSUMER, INDUSTRIAL, JANITORIAL PRODUCTS, SEMI-SOLID/SOLID HOUSEHOLD CONSUMER, INDUSTRIAL, JANITORIAL PRODUCTS, PRESERVATIVE FOR AQUEOUS COMPONENTS, ULTRA FILTRATION REVERSE OSMOSIS SYSTEMS, INDUSTRIAL WASTEWATER TREATMENT SYSTEMS AND SEWAGE SYSTEMS, INDUSTRIAL ROCESS WATER SYSTEMS, FUEL PRESERVATION

DIRECTIONS FOR USE

It is a violation of federal law to use this product in a manner inconsistent with its labeling.

The following guidance is given as an approximation for each use pattern, but field-testing is recommended to achieve optimum effectiveness.

ACCEPTED
with COMMENTS
in EPA Letter Dated:
APR 10 2013

Under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended, for the pesticide,
registered under EPA Reg. No.
39967-91

PAINTS AND COATINGS

PREVENTOL® IT 14 Preservative is an in-container preservative for the control of microorganisms in water-based coatings such as paints, paper and wood coatings used for architectural, product finishes and special-purpose coatings. Add 0.044 – 0.225 pound of PREVENTOL® IT 14 Preservative to each 1000 pounds of fluid to provide 44 to 225 ppm product (6.2 - 32 ppm active isothiazolones).

PIGMENT AND MINERAL SLURRIES

PREVENTOL® IT 14 Preservative is an in-container preservative for the control of microorganisms in the manufacture and storage of dispersed pigments and mineral slurries such as kaolin clay, montmorillite clay, titanium dioxide, calcium carbonate, calcium sulfate, barium sulfate, magnesium silicate, carbon black, iron oxide, and diatomaceous earth used in paint and paper production. Add 0.044 – 0.225 pound of PREVENTOL® IT 14 Preservative to each 1000 pounds of fluid to provide 44 to 225 ppm product (6.2 - 32 ppm active isothiazolones).

ADHESIVES AND TACKIFIERS

PREVENTOL® IT 14 Preservative is an in-container preservative for the control of microorganisms in water-soluble and water-dispersed adhesives such as animal glues, plant glues, starch-based glues, natural rubber latexes, polyvinyl acetate, styrene butadiene, and acrylic latexes. PREVENTOL® IT 14 Preservative is a preservative for tackifiers derived

5/11

from rosin and hydrocarbon resins. Add 0.044 – 0.225 pound of PREVENTOL® IT 14 Preservative to each 1000 pound of fluid to provide 44 to 225 ppm product (6.2 - 32 ppm active isothiazolones).

POLYMER EMULSIONS

PREVENTOL® IT 14 Preservative is used for the control of microorganisms in the manufacture and storage of synthetic and natural polymer emulsions and latexes including: acrylics; styrene/butadiene; carboxylated styrene/butadiene; ethylene/vinyl acetate including PVA; and biopolymers intended for industrial use, such as xanthan gum, gum arabic, guar gum, protein-derived polymers, starches, and casein-derived polymers. Add 0.044 – 0.45 pound PREVENTOL® IT 14 Preservative to each 1000 pounds of fluid to provide 44 to 450 ppm product (6.2 - 63 ppm active isothiazolones). To ensure uniform mixing, add PREVENTOL® IT 14 Preservative to polymer emulsion or latex solutions slowly with agitation.

METALWORKING FLUIDS

PREVENTOL® IT 14 Preservative is used for the control of microorganisms in soluble and emulsifiable type aqueous metal working fluid (MWF) solutions and emulsions. Add 0.23 – 1.3 pounds per 1000 gallons of MWF every four weeks for maintenance of a non-fouled system. For a noticeably fouled system, use an initial dose of 0.6 to 1.3 pounds per 1000 gallons of MWF followed by subsequent maintenance dosages as listed above. PREVENTOL® IT 14 Preservative should be dispensed into the use dilution of the metal working fluid using a metering pump or by manual pouring and uniformly dispersed throughout the system.

BUILDING MATERIALS

PREVENTOL® IT 14 Preservative is an in-container preservative for the control of microorganisms in building materials such as grouts, mastics, caulks, joint cements, concrete admixtures and spackling. Add 0.044 – 0.225 pound of PREVENTOL® IT 14 Preservative to each 1000 pounds of building material to provide 44 to 225 ppm product (6.2 - 32 ppm active isothiazolones).

FOUNTAIN SOLUTIONS, INKS, AND PHOTOPLATE PROCESSING

PREVENTOL® IT 14 Preservative controls microorganisms in fountain solutions, inks, and photoplate processing such as stabilizer solutions. PREVENTOL® IT 14 Preservative is used for water-based printing inks such as flexographic, gravure, screen and ink jet types. PREVENTOL® IT 14 Preservative is used for the control of microorganisms in printing ink components such as resins, plasticizers, water soluble dyes, pigments, gelling agents, waxes, surfactants, and thickeners.

PREVENTOL® IT 14 Preservative is added to achieve the recommended dosage range of 1000 – 10000 ppm for ink, ink components, fountains solutions and photoplate processing chemicals. The optimum level range for acidic fountain solutions is 2000 to 5000 ppm; the optimum use level for basic fountain solutions is 5000 to 8000 ppm.

ACCEPTED
with COMMENTS
in EPA Letter Dated:
APR 10 2013
under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended, for the pesticide,
registered under EPA Reg. No.
39967-91

PAPER MILL PROCESS WATER

Add as a slug dose 0.048 to 0.17 pound of PREVENTOL® IT 14 Preservative per ton (dry basis) of pulp or paper produced for the control of microbial slime in the production paper. Repeat daily as needed. Heavily fouled systems should be boiled out prior to initial dosing. PREVENTOL® IT 14 Preservative should be added at a point such as the beater, hydropulper, fan pump, or broke storage pump to ensure uniform mixing.

RECIRCULATING COOLING WATER SYSTEMS

Add 0.032 - 0.196 pound PREVENTOL® IT 14 Preservative per 1000 gallons of cooling water in the system weekly to maintain microbial control. Add PREVENTOL® IT 14 Preservative to a point in the cooling water system to ensure uniform mixing. For noticeably fouled systems dose as initial treatment with 0.13 - 0.79 lb PREVENTOL® IT 14 Preservative per 1000 gallons cooling water. Repeat as necessary to achieve control.

INDUSTRIAL RECIRCULATING PROCESS WATER SYSTEMS

For the control of microbial biofilms, bacteria, algae and fungi, add PREVENTOL® IT 14 Preservative to: **Industrial process water systems, industrial recirculating closed loop water cooling systems.** Add PREVENTOL® IT 14 Preservative weekly in the reservoir, recirculating line or some other point in the system to ensure uniform mixing.

INITIAL DOSE: When the system is noticeable fouled, apply 14.8 – 88 ppm PREVENTOL® IT 14 Preservative (0.12 – 0.74 pound or 1.9 – 11.3 fluid ounces of PREVENTOL® IT 14 Preservative per 1000 gallon of water in the system). Repeat until control is achieved. Badly fouled systems should be cleaned before treatment is begun.

SUBSEQUENT DOSE: When microbial control is evident, add PREVENTOL® IT 14 Preservative (0.03 – 0.186 pound or 0.45 – 0.28 fluid ounces per 1000 gallon of water in the system) weekly or as needed to maintain control.

ACCEPTED
with COMMENTS
In EPA Letter Dated:
APR 10 2013

under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended, for the pesticide,
registered under EPA Reg. No.

INDUSTRIAL WASTEWATER TREATMENT SYSTEMS AND SEWAGE SYSTEMS

PREVENTOL® IT 14 Preservative is recommended for the control of microbial biofilms, bacteria, fungi and algae in industrial wastewater treatment and sewage systems. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority.

INITIAL DOSE: When the system is noticeable fouled, apply 14.8 – 88 ppm PREVENTOL® IT 14 Preservative (0.12 – 0.74 pound or 1.9 – 11.3 fluid ounces of PREVENTOL® IT 14 Preservative per 1000 gallon of water in the system). Repeat until control is achieved. Badly fouled systems should be cleaned before treatment is begun.

SUBSEQUENT DOSE: When microbial control is evident, apply 3.5 – 22 ppm PREVENTOL® IT 14 Preservative (0.03 – 0.186 pound or 0.45 – 0.28 fluid ounces per 1000 gallon of water in the system) or as needed to maintain control.

39967-91

LIQUID HOUSEHOLD CONSUMER, INDUSTRIAL, JANITORIAL PRODUCTS

PREVENTOL® IT 14 Preservative is added at a level of 0.04 to 0.15 pounds (18 – 68 grams) to each 1000 pounds of product to be protected to provide 6 to 22 ppm of active isothiazolinones. For the control of bacteria and fungi in liquid soaps, liquid cleaners, liquid detergents, liquid laundry products, liquid dishwashing detergents, waxes, polishes, liquid fabric treatments /

7/11

ACCEPTED
with COMMENTS
in EPA Letter Dated:

APR 10 2013

under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended, for the pesticide,
registered under EPA Reg. No.
39967-91

refresher products, liquid air fresheners / deodorizers, car care products, and other similar cleaners.

SEMI-SOLID/SOLID HOUSEHOLD CONSUMER, INDUSTRIAL, JANITORIAL PRODUCTS

PREVENTOL® IT 14 Preservative is added at a level of 0.04 to 0.15 pounds to each 1000 pounds of product to be protected to provide 6 – 22 ppm of active isothiazolinones. For the control of bacteria and fungi in semi-solid/solid detergents, semi-solid laundry products, semi-solid/solid soaps, semi-solid/solid cleaners, semi-solid/solid fabric treatment / refresher products, semi-solid/solid air fresheners / deodorizers, car care products, and other similar cleaners.

PRESERVATIVE FOR AQUEOUS COMPOSITION

PREVENTOL® IT 14 Preservative is recommended as an in-container preservative for the control of bacteria and fungi in aqueous products such as fiber glass sizing solutions, aqueous emulsions and dispersions including stabilized oil/water emulsions, surface preparation compound, foam control products, nutrient solutions and pesticide formulations. Add 0.05 to .33 pounds (22g to 150g) of PREVENTOL® IT 14 Preservative to each 1000 pounds of aqueous product to provide 7 – 50 ppm active isothiazolones)

TREATMENT OF ELECTRODEPOSITION PAINT COMPONENTS

INITIAL DOSE OF PAINT COMPONENTS:

PREVENTOL® IT 14 Preservative should be added to the resin, pigments, or other components of the electrodeposition paint at a level to ensure that the final use-dilution fluid will contain 33 to 233 ppm product (5 – 35 ppm active isothiazolones)

SUPPLEMENTAL TANKSIDE DOSING OF ELECTRODEPOSITION SYSTEM

If additional microbial control is necessary, PREVENTOL® IT 14 Preservative may b added to the electrodeposition system tank side to supplement microbicide incorporated through paint components.

INITIAL DOSE: If the system becomes noticeably fouled, add 66 to 233 ppm PREVENTOL® IT 14 Preservative (0.67 – 2.3 gallons per 10,000 gallon of fluid in the system). This will provide 10 – 35 ppm active ingredients. Repeat until control is achieved.

SUBSEQUENT DOSE: When microbial control is evident, add 33 to 100 ppm PREVENTOL® IT 14 Preservative (0.33 – 1.0 gallon per 10,000 gallon of fluid in the system) weekly or as needed.

NOTE: Regardless of the manner of incorporation, the total active ingredient level in the system should at no time exceed 35 ppm (equivalent to 233 ppm PREVENTOL® IT 14 Preservative or 2.3 gallons per 10,000 gallon system fluid).

ULTRA FILTRATION UNITS AND REVERSE OSMOSIS SYSTEM

PREVENTOL® IT 14 Preservative is recommended for the control of microbial biofilms, bacteria and fungi in ultra filtration units such as reverse osmosis systems. Add 0.1 – 33 ppm PREVENTOL® IT 14 Preservative (0.15 – 5 ppm active ingredient) into industrial ultra filtration or reverse osmosis systems by either continuous or periodic injection. Compatibility of PREVENTOL® IT 14 Preservative with reverse osmosis membranes should be confirmed with

membrane manufacturers. For the control of bacteria and fungi in carbon beds, add 1.0 – 33 ppm of PREVENTOL® IT 14 Preservative (0.15 – 5 ppm active ingredient) by either continuous or batch feed. For periodic membrane cleaning, add 0.04 – 0.10 pounds of PREVENTOL® IT 14 Preservative to every 120 gallon of cleaning solution (6 – 15 ppm active ingredient). Badly fouled systems should be cleaned before treatment is begun.

FUEL PRESERVATION

PREVENTOL® IT 14 Preservative is recommended for the control of bacteria and fungi in liquid hydrocarbon fuels and oils such as: crude oils, aviation fuels, kerosene, heating oil, diesel fuels, residual fuel oils, coal slurries, liquefied petroleum gases and petrochemical feedstock.

PREVENTOL® IT 14 Preservative is recommended for REFINERY AND TERMINAL USE ONLY. PREVENTOL® IT 14 Preservative should be directly dispensed into a fuel tank, storage tank or a flowing stream of fuel in a manner to ensure uniform distribution of the preservative in the fuel system. Slug does or continuous feed methods are recommended.

CURATIVE DOSE: When the system is noticeable fouled, add 11 -21 gallons of PREVENTOL® IT 14 Preservative per 1 million gallons of fluid in the system. This will provide 11 to 21 ppm PREVENTOL® IT 14 Preservative. Repeat until control is achieved. A shock dose of up to 42 gallons of PREVENTOL® IT 14 Preservative per 1 million gallons of fluid is recommended in the case of extreme contamination. Grossly contaminated systems should be physically cleaned to remove debris.

MAINTENANCE DOSE: When the system is not noticeably fouled, add 5 – 16 gallons of PREVENTOL® IT 14 Preservative per 1 million gallons of fluid to maintain the system. This will provide 5 – 16 ppm of PREVENTOL® IT 14 Preservative. Repeat every 4 – 6 weeks or when microbial contamination is detected.

ACCEPTED
with COMMENTS
in EPA Letter Dated:
APR 10 2013

FOR USE IN AVIATION FUEL, THE FEDERAL AVIATION ADMINISTRATION MUST BE CONSULTED AS TO THE ACCEPTABILITY OF THE ADDITIVE FOR USE IN SPECIFIC ENGINES AND/OR AIRCRAFT.

under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended, for the pesticide,
registered under EPA Reg. No.

BREWERY PASTEURIZER AND CAN WARMER SYSTEMS

Add 0.032 - 0.196 lb PREVENTOL® IT 14 Preservative per 1000 gallons of water in the system weekly or as needed to maintain control of microorganisms. For noticeably fouled systems dose as initial treatment with 0.13 - 0.79 lb PREVENTOL® IT 14 Preservative per 1000 gallons of water. Repeat as necessary to achieve control. The total active isothiazolone in the system should never exceed 248 ppm PREVENTOL® IT 14 Preservative.

39967-91

HYDRAULIC FLUIDS

PREVENTOL® IT 14 Preservative is used as a preservative for use in the manufacture and use of water-based hydraulic fluids and invert emulsion hydraulic fluids typically prepared by emulsifying 40% by volume water in 60% by volume mineral oil using an oil soluble emulsifying agent.

For the maintenance of a non-fouled system, use PREVENTOL® IT 14 Preservative at 0.76 – 1.2 pounds per 1000 gallons hydraulic fluid every eight weeks. For a noticeably fouled system use an initial dose of 1.1 – 2.0 pounds PREVENTOL® IT 14 Preservative per 1000 gallons fluid to be followed by subsequent maintenance dosing. PREVENTOL® IT 14 Preservative should

be dosed into the circulating use-dilution of the hydraulic fluid using a metering pump or by manual pouring, and uniformly dispersed throughout the system.

OIL FIELDS INJECTION WATERS

Add 2.4 to 6.2 pounds PREVENTOL® IT 14 Preservative per 1000 barrels of water weekly or as needed to maintain control of slime-forming and sulfate reducing bacteria in oil and gas field water systems including enhanced recovery injection fluids, fracturing, completion and drilling fluids. An initial dose of 6.1 to 12.5 lb PREVENTOL® IT 14 Preservative per 1000 barrels of water may be used until microbial control is achieved. Dose again after three days or as needed until microbial control is achieved. Add at a point in the system to ensure adequate mixing. PREVENTOL® IT 14 Preservative may be used for terrestrial and off-shore oil drilling muds and packer fluids.

AIR WASHER SYSTEMS

For use only in industrial air washing systems with effective mist eliminating elements. Badly fouled air washer systems must be cleaned before initial dosing. Add PREVENTOL® IT 14 Preservative to the air washer sump or chill water sump to ensure uniform mixing for the control of microorganisms.

Intermittent or slug dosing:

INITIAL DOSING: when system is noticeably fouled, add 0.26 – 0.71 pound PREVENTOL® IT 14 Preservative to 1000 gallons of air washer water.

MAINTENANCE DOSING: when microbial control is evident, dose 0.12 – 0.20 pound PREVENTOL® IT 14 Preservative to 1000 gallons of air washer water. Repeat treatment as needed depending on the severity of contamination.

Continuous dosing method:

INITIAL DOSEING: when system is noticeably fouled, add 0.26 – 0.71 pound PREVENTOL® IT 14 Preservative to 1000 gallons of air washer water. Maintenance dosing: Add a continuous dose of 0.12 – 0.20 pound PREVENTOL® IT 14 Preservative to 1000 gallons air washer make-up water. Repeat treatment as needed depending on the severity of contamination.

ACCEPTED COMMENTS
in EPA Letter Dated:
APR 10 2013
Under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended, for the pesticide,
registered under EPA Reg. No.
39967-91

RECIRCULATING ELECTRODEPOSITION SYSTEMS

PREVENTOL® IT 14 Preservative is used as a tankside additive for the control of microorganisms in recirculating systems and associated rinse systems. Alternatively, PREVENTOL® IT 14 Preservative may be added through the components of the electrodeposition paint prior to their addition to the electrodeposition system.

TANKSIDE ADDITION TO ELECTRODEPOSITION SYSTEMS: PREVENTOL® IT 14 Preservative should be dispensed into the recirculating rinse system, ultrafilter permeate, or final distilled rinse system at a point to insure uniform mixing.

INITIAL DOSE: When the system is noticeably fouled, add 71-248 ppm PREVENTOL® IT 14 Preservative. This provides 10 to 35 ppm of active isothiazolone. Repeat until microbial control is achieved.

10/11

SUBSEQUENT DOSE: When microbial control is evident, add 35-106 ppm PREVENTOL® IT 14 Preservative weekly or as needed to maintain the system. This provides 5-15 ppm of active isothiazolone.

METAL CLEANING FLUIDS

PREVENTOL® IT 14 Preservative is used as a preservative in the manufacture and use of alkaline, acid and emulsion based metal cleaning fluids typically used in electroplating, phosphatizing, galvanizing and general metal cleaning operations. For addition to a metal cleaning concentration, add PREVENTOL® IT 14 Preservative at a level to ensure that the final use-dilution fluid will contain 44 – 225 ppm product (6.2 – 32 ppm isothiazolone). For direct addition to a fouled system, add 0.48 – 2.3 pounds PREVENTOL® IT 14 Preservative to each 1000 gallons of use-dilution metal cleaning fluid every three to four weeks to provide 44 – 225 ppm product (6.2 – 32 ppm isothiazolone). PREVENTOL® IT 14 Preservative should be dispensed into the use-dilution of the metal cleaning fluid using a metering pump or by manual pouring and uniformly disperse throughout the system.

COMMERCIAL PHOTOPROCESSING SYSTEMS

PREVENTOL® IT 14 Preservative is recommended to prevent slime formation or accumulation in filters and ion exchange resin tanks of commercial photoprocessing systems.

For the maintenance of a non-fouled system, use PREVENTOL® IT 14 Preservative at 0.23 – 0.46 pound per 1000 gallon fluid every eight weeks. For a noticeably fouled system, use an initial dose 0.46-1.15 pounds per 1000 gallon fluid to be followed by subsequent maintenance dosing. Increased frequency of treatment may be required depending upon rate of dilution of the preservative with makeup fluid, the nature and severity of contamination, level of control required, filtration effectiveness, system design, etc. PREVENTOL® IT 14 Preservative should be dispensed into the final rinse or used water collection tank for adequate distribution.

NOTE: PREVENTOL® IT 14 Preservative may be added to those products formulated as concentrates which are in turn diluted for use at a level to ensure that the final use-dilution product will contain between 0.04% to 0.15% PREVENTOL® IT 14 Preservative.

REMARKS

If you need assistance or information, please call your nearest LANXESS representative, or our Pittsburgh office at 800-LANXESS.

**IN CASE OF EMERGENCY, CALL: CHEMTREC 1-800-424-9300
INTERNATIONAL (703)-527-3887**

HAVE THE PRODUCT CONTAINER OF LABEL WITH YOU WHEN CALLING A POISON CONTROL CENTER OR DOCTOR OR GOING FOR TREATMENT.

LANXESS Corporation
111 RIDC Park West Drive
Pittsburgh, PA 15275

ACCEPTED
with COMMENTS
in EPA Letter Dated:
APR 10 2013
under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended, for the pesticide,
registered under EPA Reg. No.
39967-91

11/11

412-809-1000

The conditions of your use and application of our products, technical assistance and information (whether verbal, written or by way of production evaluations), including any suggested formulations and recommendations, are beyond our control. Therefore, it is imperative that you test our products, technical assistance and information to determine to your own satisfaction whether they are suitable for your intended uses and applications. This application-specific analysis at least must include testing to determine suitability from a technical as well as health, safety and environmental standpoint. Such testing has not necessarily been done by LANXESS Corporation. All information is given without warranty or guarantee. It is expressly understood and agreed that the customer assumes and hereby expressly releases LANXESS from all liability, in tort, contract or otherwise, incurred in connection with the use of our products, technical assistance and information. Any statement or recommendation not contained herein is unauthorized and shall not bind LANXESS. Nothing herein shall be construed as a recommendation to use any product in conflict with patents covering any material or its use. No license is implied or in fact granted under the claims of any patent.

1/13

ACCEPTED
with **COMMENTS**
in EPA Letter Dated:
APR 10 2013
under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended, for the pesticide,
registered under EPA Reg. No.
39967-91

.....
.....
.....
.....
.....
.....
.....
.....
.....
.....
.....