



UNITED STATES ENVIRONMENTAL PROTECTION AGENCY
WASHINGTON, DC 20460

OFFICE OF CHEMICAL SAFETY
AND POLLUTION PREVENTION

April 13, 2015

Sarah Plittman
Lanxess
111 RIDC West Park Drive
Pittsburg, PA 15275

Subject: Label Amendment – Add ‘not for use in California’ statement and correct typos
Product Name: Preventol D7
EPA Registration Number: 39967-93
Application Date: January 5, 2015
Decision Number: 499898

Dear Ms. Plittman:

The amended label referred to above, submitted in connection with registration under the Federal Insecticide, Fungicide and Rodenticide Act, as amended, is acceptable. This approval does not affect any conditions that were previously imposed on this registration. You continue to be subject to existing conditions on your registration and any deadlines connected with them.

A stamped copy of your labeling is enclosed for your records. This labeling supersedes all previously accepted labeling. You must submit one copy of the final printed labeling before you release the product for shipment with the new labeling. In accordance with 40 CFR 152.130(c), you may distribute or sell this product under the previously approved labeling for 18 months from the date of this letter. After 18 months, you may only distribute or sell this product if it bears this new revised labeling or subsequently approved labeling. “To distribute or sell” is defined under FIFRA section 2(gg) and its implementing regulation at 40 CFR 152.3.

Should you wish to add/retain a reference to the company’s website on your label, then please be aware that the website becomes labeling under the Federal Insecticide Fungicide and Rodenticide Act and is subject to review by the Agency. If the website is false or misleading, the product would be misbranded and unlawful to sell or distribute under FIFRA section 12(a)(1)(E). 40 CFR 156.10(a)(5) list examples of statements EPA may consider false or misleading. In addition, regardless of whether a website is referenced on your product’s label, claims made on the website may not substantially differ from those claims approved through the registration process. Therefore, should the Agency find or if it is brought to our attention that a website contains false or misleading statements or claims substantially differing from the EPA approved registration, the website will be referred to the EPA’s Office of Enforcement and Compliance.

Your release for shipment of the product constitutes acceptance of these conditions. If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA section 6. If you have any questions, please contact Elizabeth Watkins by phone at 703-347-0241, or via email at Watkins.Elizabeth@epa.gov.

Sincerely,

Elizabeth H. Watkins for

John Hebert, Chief
Regulatory Management Branch I
Antimicrobials Division (7510P)
Office of Pesticide Programs

Enclosure

PREVENTOL® D 7

FOR INDUSTRIAL USE AS A PRESERVATION TO INHIBIT THE GROWTH OF BACTERIA, FUNGI, AND YEAST IN PAINTS AND COATINGS, PIGMENT AND MINERAL SLURRIES, ADHESIVES AND TACKIFIERS, POLYMER EMULSIONS*, METAL WORKING FLUIDS*, BUILDING MATERIALS, FOUNTAIN SOLUTIONS*, INKS AND PHOTOPLATE PROCESSING, PAPER MILL PROCESS WATER, RECIRCULATING COOLING WATER SYSTEMS, BREWERY PASTEURIZER AND CAN WARMER SYSTEM*, HYDRAULIC FLUIDS*, OIL & GAS FIELDS INJECTION WATERS*, AIR WASHER SYSTEMS*, RECIRCULATING ELECTRODEPOSITION SYSTEMS*, METAL CLEANING FLUIDS*, COMMERCIAL PHOTOPROCESSING SYSTEMS, LIQUID HOUSEHOLD CONSUMER*, INDUSTRIAL JANITORIAL PRODUCTS*, SEMI-SOLID/SOLID HOUSEHOLD CONSUMER*, INDUSTRIAL JANITORIAL PRODUCTS*, PRESERVATIVE FOR AQUEOUS COMPOSITIONS*, TEXTILE PROCESSING CHEMICALS*, ULTRA FILTRATION UNITS AND NON-MEDICAL/NON-POTABLE REVERSE OSMOSIS SYSTEMS*, INDUSTRIAL WASTEWATER TREATMENT SYSTEMS AND SEWAGE SYSTEMS*, INDUSTRIAL PROCESS WATER SYSTEMS*, FUEL PRESERVATION*

KEEP OUT OF REACH OF CHILDREN

DANGER

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER. CORROSIVE. Causes irreversible eye damage and skin burns. Harmful if swallowed or inhaled. Do not get in eyes, on skin, or on clothing. Avoid breathing vapors or spray mist. Prolonged or frequently repeated skin contact may cause allergic reaction in some individuals. Mixers, loaders and others exposed to this product must wear: long sleeved shirt and long pants; chemical resistant gloves such as nitrile or butyl rubber; shoes plus socks; goggles and face shield; and chemical resistant apron. Discard clothing or other absorbent materials that have been drenched or heavily contaminated with this product's concentrate. Do not reuse them. Follow manufacturer's instructions for cleaning/maintaining PPE. If no such instructions for washables exist, use detergent and hot water. Keep and wash PPE separately from other laundry. User should wash hands before eating drinking, chewing gum, using tobacco, or using the toilet. User should remove clothing/PPE immediately if pesticide gets inside. Then wash thoroughly and put on clean clothing. User should remove PPE immediately after handling this product. Wash outside of gloves before removing. As soon as possible wash thoroughly and change into clean clothing.

ENVIRONMENTAL HAZARDS

This product is toxic to fish and wildlife. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans, or public waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA. Do not contaminate water by cleaning of equipment or disposal of waste.

IN CASE OF EMERGENCY, CALL: CHEMTREC 800-424-9300
INTERNATIONAL 703-527-3887

EPA Reg. No.: 39967-93
EPA Est. No.:

Net Contents:
Lot No.:

ACTIVE INGREDIENTS:

5-chloro-2-methyl-4-isothiazolin-3-one -----1.1%
2-Methyl-4-isothiazoline-3-one -----0.4%
INERT INGREDIENTS: -----98.50%
TOTAL 100%

KEEP OUT OF REACH OF CHILDREN DANGER

FIRST AID

IF IN EYES: Hold eyes open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing. Call a poison control center or doctor for treatment advice.

IF ON SKIN OR CLOTHING: Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control center or doctor for treatment advice.

IF INHALED: Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth, if possible. Call a poison control center or doctor for treatment advice.

IF SWALLOWED: Call a poison control center or doctor immediately for treatment advice. Have a person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by the poison control center or doctor. Do not give anything to an unconscious person.

NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage. Measures against circulatory shock, respiratory depression and convulsion may be needed.

Have the product container or label with you when calling a poison control center or doctor for treatment. You may also contact 1-800-410-3036 for emergency medical treatment information.

The LANXESS Pittsburgh Emergency Response Telephone Number is 800-410-3063.

® Preventol is a registered trademark of LANXESS Corporation

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling. Do not apply in a way that will contact workers or other persons.

The amount necessary for desired protection varies, depending on exposure conditions. For further application information refer to the Product Bulletin.

STORAGE AND DISPOSAL

Keep container closed when not in use.

PESTICIDE STORAGE: Product should be stored in an area that is not subject to extreme temperatures; store in a cool, dry place. Do not contaminate water, food, or feed by storage, disposal or cleaning of equipment. Do not apply this product in a way that will contact workers or other persons.

PESTICIDE DISPOSAL: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State pesticide environmental control agency, or the hazardous waste representative at the nearest regional office for guidance.

CONTAINER DISPOSAL: Non-refillable container. Do not reuse or refill this container. Offer for recycling if available or reconditioning if appropriate. Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, by incineration or, if allowed by State and Local authorities, by burning. If burned, stay out of smoke.


Mix well before using this product.

* NOT FOR USE IN THE STATE OF CALIFORNIA

LANXESS Corporation

111 RIDC Park West Drive • Pittsburgh, PA 15275-1112

Label date 1/5/2015



LANXESS

Energizing Chemistry

Product Information

PREVENTOL® D 7

EPA Registration Number 39967-93
CAS Number: 55965-84-9

PREVENTOL® D 7

39967-93

Page 1

PREVENTOL® D 7

FOR INDUSTRIAL USE AS A PRESERVATION TO INHIBIT THE GROWTH OF BACTERIA, FUNGI, AND YEAST IN PAINTS AND COATINGS, PIGMENT AND MINERAL SLURRIES, ADHESIVES AND TACKIFIERS, POLYMER EMULSIONS, METAL WORKING FLUIDS*, BUILDING MATERIALS, FOUNTAIN SOLUTIONS*, INKS AND PHOTOPLATE PROCESSING*, PAPER MILL PROCESS WATER, RECIRCULATING COOLING WATER SYSTEMS, BREWERY PASTEURIZER AND CAN WARMER SYSTEM*, HYDRAULIC FLUIDS*, OIL & GAS FIELDS INJECTION WATERS*, AIR WASHER SYSTEMS*, RECIRCULATING ELECTRODEPOSITION SYSTEMS*, METAL CLEANING FLUIDS*, COMMERCIAL PHOTOPROCESSING SYSTEMS, LIQUID HOUSEHOLD CONSUMER*, INDUSTRIAL JANITORIAL PRODUCTS*, SEMI-SOLID/SOLID HOUSEHOLD CONSUMER*, INDUSTRIAL JANITORIAL PRODUCTS*, PRESERVATIVE FOR AQUEOUS COMPOSITIONS*, TEXTILE PROCESSING CHEMICALS*, ULTRA FILTRATION UNITS AND NON-MEDICAL/NON-POTABLE REVERSE OSMOSIS SYSTEMS*, INDUSTRIAL WASTEWATER TREATMENT SYSTEMS AND SEWAGE SYSTEMS*, INDUSTRIAL PROCESS WATER SYSTEMS*, FUEL PRESERVATION*

* NOT FOR USE IN THE STATE OF CALIFORNIA

DIRECTIONS FOR USE

It is a violation of federal law to use this product in a manner inconsistent with its labeling.

The following guidance is given as an approximation for each use pattern, but field-testing is recommended to achieve optimum effectiveness.

LIQUID HOUSEHOLD CONSUMER, INDUSTRIAL, JANITORIAL PRODUCTS

(NOT FOR USE IN THE STATE OF CALIFORNIA)

PREVENTOL® D 7 is added at a level of 0.4 to 1.5 pounds (181 – 680 grams) to each 1000 pounds (45400 g) of product to be protected to provide 6 to 22.5 ppm of active isothiazolinones. For the control of bacteria and fungi in liquid soaps, liquid cleaners, liquid detergents, liquid laundry products, liquid dishwashing detergents, waxes, polishes, liquid fabric treatments/ refresher products, liquid air fresheners/deodorizers, car care products, and other similar cleaners.

SEMI-SOLID/SOLID HOUSEHOLD CONSUMER, INDUSTRIAL, JANITORIAL

PRODUCTS (NOT FOR USE IN THE STATE OF CALIFORNIA)

PREVENTOL® D 7 is added at a level of 0.4 to 1.5 pounds to each 1000 pounds of product to be protected to provide 6 to 22.5 ppm of active isothiazolinones. For the control of bacteria and fungi in semi-solid/solid detergents, semi-solid/solid laundry products, semi-solid/solid soaps, semi-solid/solid cleaners, semi-solid/solid fabric treatment/refresher products, semi-solid/solid air fresheners/deodorizers, car care products, and other similar cleaners.

PREVENTOL® D 7

39967-93

Page 2

PRESERVATIVE FOR AQUEOUS COMPOSITIONS (NOT FOR USE IN THE STATE OF CALIFORNIA)

PREVENTOL[®] D 7 is recommended as an in-container preservative for the control of bacteria and fungi in aqueous products such as aqueous emulsions and dispersions including stabilized oil/water emulsions, surface preparation compound, foam control products, nutrient solutions and pesticide formulations. Add 0.5 to 3.3 pounds (227g to 1.5kg) of PREVENTOL[®] D 7 to each 1000 pounds (454 g) of aqueous product to provide 7ppm to 50ppm active isothiazolones.

TEXTILE PROCESSING CHEMICALS (NOT FOR USE IN THE STATE OF CALIFORNIA)

PREVENTOL[®] D 7 is recommended for the control of bacteria and fungi in the manufacture and storage of textile processing chemicals such as fiber lubricants, spin finishes, sizes, dyestuff, textile printing inks, dispersants, thickeners, dye fixatives, hand builders and weighters. These textile processing chemicals are commonly used in the production of natural and synthetic fibers and fabrics. Add 0.4 – 1.67 pounds (181 – 758 grams) of PREVENTOL[®] D 7 to each 1000 pounds of fluid to provide 400 – 1667 ppm product (6 -25 ppm active isothiazolone)

PAINTS AND COATINGS

PREVENTOL[®] D 7 is recommended as an in-container preservative for the control of microorganisms in water-based coatings such as paints, paper and wood coatings used for architectural product finishes and special-purpose coatings. The preservative is best incorporated into the products just following the initial additional of water or other liquid components sufficient to dissolve the preservative. If incorporation happens at a later stage in production; stir to ensure homogeneous distribution of the preservative throughout the product. Add 0.425 – 1.675 pounds of PREVENTOL[®] D 7 to each 1000 pounds of fluid to provide 425 to 1,675 ppm product (6.375 - 25 ppm active isothiazolones).

ULTRA FILTRATION UNITS AND NON-MEDICAL/NON-POTABLE REVERSE OSMOSIS

SYSTEM (NOT FOR USE IN THE STATE OF CALIFORNIA)

PREVENTOL[®] D 7 is recommended for the control of microbial biofilms, bacteria and fungi in ultra filtration units and non-medical/non-potable reverse osmosis systems. Use PREVENTOL[®] D 7 in potable water or dialysis is prohibited. Add 10 – 333 ppm of PREVENTOL[®] D 7 (0.15 – 5 ppm active ingredient) into industrial ultra filtration or reverse osmosis systems by either continuous or periodic injection. Compatibility of PREVENTOL[®] D 7 with reverse osmosis membranes should be confirmed with membrane manufacturers.

For the control of bacteria and fungi in carbon beds, add 10 – 333 ppm of PREVENTOL[®] D 7 (0.15 – 5 ppm active ingredient) by either continuous or batch feed.

For periodic membrane cleaning, add 0.4 – 1.0 lbs of PREVENTOL[®] D 7 to every 120 gallon of cleaning solution (6-15ppm active ingredient)

Badly fouled systems should be cleaned before treatment is begun

PIGMENT AND MINERAL SLURRIES

PREVENTOL[®] D 7 is an in-container preservative for the control of microorganisms in the manufacture and storage of dispersed pigments and mineral slurries such as kaolin clay, montmorillite clay, titanium dioxide, calcium carbonate, calcium sulfate, barium sulfate, magnesium silicate, carbon black, iron oxide, and diatomaceous earth used in paint and

PREVENTOL[®] D 7

39967-93

Page 3

paper production. Add 0.425 – 1.675 pounds of PREVENTOL® D 7 to each 1000 pounds of fluid to provide 425 to 1,675 ppm product (6.375 -25 ppm active isothiazolones).

ADHESIVES AND TACKIFIERS

PREVENTOL® D 7 is recommended as an in-container preservative for the control of microorganisms in water-soluble and water-dispersed adhesives such as animal glues, plant glues, starch-based glues, natural rubber latexes, polyvinyl acetate, styrene butadiene, and acrylic latexes. PREVENTOL® D 7 is a preservative for tackifiers derived from rosin and hydrocarbon resins. Add 0.425 – 1.675 pounds of PREVENTOL® D 7 to each 1000 pound of fluid to provide 425 to 1,675 ppm product (6.375 - 25 ppm active isothiazolones).

POLYMER EMULSIONS

PREVENTOL® D 7 is recommended for the control of microorganisms in the manufacture and storage of synthetic and natural polymer emulsions and latexes including: acrylics; styrene/butadiene; carboxylated styrene/butadiene; ethylene/vinyl acetate including PVA; and biopolymers intended for industrial use, such as xanthan gum, gum arabic, guar gum, protein-derived polymers, starches, and casein-derived polymers. Add 0.43 – 3.3 pounds PREVENTOL® D 7 to each 1000 pounds of emulsion to provide 425 to 3,350 ppm product (6.375 - 50 ppm active isothiazolones). To ensure uniform mixing, add PREVENTOL® D 7 to polymer emulsion or latex solutions slowly with agitation.

BUILDING MATERIALS

PREVENTOL® D 7 is recommended as an in-container preservative for the control of microorganisms in building materials such as grouts, mastics, caulks, joint cements, concrete admixtures and spackling. Add 0.425 – 1.675 pounds of PREVENTOL® D 7 to each 1000 pounds of building material to provide 425 to 1,675 ppm product (6.375 - 25 ppm active isothiazolones).

PAPER MILL PROCESS WATER

Add as a slug dose apply 0.44 to 1.5 pounds of PREVENTOL® D 7 per ton (dry basis) of pulp or paper produced for the control of microbial slime in the production paper. Repeat daily as needed. Heavily fouled systems should be boiled out prior to initial dosing. PREVENTOL® D 7 should be added at a point such as the beater, hydropulper, fan pump, or broke storage pump to ensure uniform mixing.

INDUSTRIAL RECIRCULATING PROCESS WATER SYSTEMS

(NOT FOR USE IN THE STATE OF CALIFORNIA)

For the control of microbial biofilms, bacteria, algae and fungi, add PREVENTOL[®] D 7 to:

Industrial process water systems, industrial recirculating closed loop water cooling systems, retort water systems, industrial scrubbing systems, evaporative condenser water systems, hydrostatic sterilizer water systems, air conditioner/refrigeration condensate water systems, coal slurry systems, immersion ultrasonic tank water, laboratory equipment water baths and influent water filtration systems Add PREVENTOL[®] D 7 at some point in the system to ensure uniform mixing

INITIAL DOSE: When the system is noticeable fouled, apply 148 – 883 ppm PREVENTOL[®] D 7 (1.26 – 7.54 pound or 19 – 110 fluid ounces of PREVENTOL[®] D 7 per 1000 gallon of water in the system). Repeat until control is achieved. Badly fouled systems should be cleaned before treatment is begun.

SUBSEQUENT DOSE: When microbial control is evident, add 35 – 219 ppm PREVENTOL[®] D 7 pounds (0.3 – 1.87 pound or 4.4 – 27 fluid ounces of PREVENTOL[®] D 7 per 1000 gallon of water in the system) weekly or as needed to maintain control

INDUSTRIAL WASTEWATER TREATMENT SYSTEMS AND SEWAGE SYSTEMS

(NOT FOR USE IN THE STATE OF CALIFORNIA)

PREVENTOL[®] D 7 is recommended for the control of microbial biofilms, bacteria, fungi and algae in industrial wastewater treatment and sewage systems. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority

INITIAL DOSE: When the system is noticeable fouled, apply 148 – 883 ppm PREVENTOL[®] D 7 (1.26 – 7.54 pound or 19 – 112 fluid ounces of PREVENTOL[®] D 7 per 1000 gallon of water in the system). Repeat until control is achieved. Badly fouled systems should be cleaned before treatment is begun.

SUBSEQUENT DOSE: When microbial control is evident, add 35 – 219 ppm PREVENTOL[®] D 7 (0.3 – 1.87 pound or 4.4 – 28 fluid ounces of PREVENTOL[®] D 7 per 1000 gallon of water in the system) or as needed to maintain control.

RECIRCULATING COOLING WATER SYSTEMS

Add 0.3 – 1.87 pounds PREVENTOL[®] D 7 per 1000 gallons of cooling water in the system weekly to maintain microbial control. Add PREVENTOL[®] D 7 to a point in the cooling water system to ensure uniform mixing. For noticeably fouled systems dose as initial treatment with 1.26 – 7.46 pounds PREVENTOL[®] D 7 per 1000 gallons cooling water. Repeat as necessary to achieve control.

BREWERY PASTEURIZER AND CAN WARMER SYSTEMS

(NOT FOR USE IN THE STATE OF CALIFORNIA)

Add 0.31 – 1.92 pounds PREVENTOL[®] D 7 Preservative per 1000 gallons of water in the system weekly or as needed to maintain control of microorganisms. For noticeably fouled systems dose as initial treatment with 1.27 – 7.75 pounds PREVENTOL[®] D 7 per 1000 gallons of water. Repeat as necessary to achieve control.

PREVENTOL[®] D 7

39967-93

Page 5

HYDRAULIC FLUIDS (NOT FOR USE IN THE STATE OF CALIFORNIA)

PREVENTOL[®] D 7 is used as a preservative for use in the manufacture and use of water-based hydraulic fluids and invert emulsion hydraulic fluids typically prepared by emulsifying 40% by volume water in 60% by volume mineral oil using an oil soluble emulsifying agent.

For the maintenance of a non-fouled system, use PREVENTOL[®] D 7 at 7.2 – 8.8 pounds per 1000 gallons hydraulic fluid every eight weeks. For a noticeably fouled system use an initial dose of 8.8 – 15.4 pounds PREVENTOL[®] D 7 per 1000 gallons fluid to be followed by subsequent maintenance dosing. PREVENTOL[®] D 7 should be dosed into the circulating use-dilution of the hydraulic fluid using a metering pump or by manual pouring, and uniformly dispersed throughout the system.

OIL & GAS FIELDS INJECTION WATERS (NOT FOR USE IN THE STATE OF CALIFORNIA)

Add 23.5 to 58.0 pounds PREVENTOL[®] D 7 per 1000 barrels of water weekly or as needed to maintain control of slime-forming and sulfate reducing bacteria in oil and gas field water systems including enhanced recovery injection fluids, fracturing, completion and drilling fluids. An initial dose of 58.0 to 116.8 pounds PREVENTOL[®] D 7 per 1000 barrels of water may be used until microbial control is achieved. Dose again after three days or as needed until microbial control is achieved. Add at a point in the system to ensure adequate mixing.

FUEL PRESERVATION (NOT FOR USE IN THE STATE OF CALIFORNIA)

PREVENTOL[®] D 7 is recommended for the control of bacteria and fungi in liquid hydrocarbon fuels such as: aviation fuels, kerosene, heating oil, diesel fuels and residual fuel oils, crude oil, coal slurries, liquefied petroleum gases, and petrochemical feedstock. PREVENTOL[®] D 7 should be directly dispensed into a fuel tank, storage tank, or flowing stream of fuel in a manner to ensure uniform distribution of the preservative in the fuel system. Slug dose or continuous feed methods are recommended.

DOUSAGE: When microbial contamination is detected, add PREVENTOL[®] D 7 in order to achieve and maintain a final system concentration of 100 – 400 ppm (v/v) volume to volume.

FOR USE IN AVIATION FUEL, THE FEDERAL AVIATION ADMINISTRATION MUST BE CONSULTED AS TO THE ACCEPTABILITY OF THE ADDITIVE FOR USE IN SPECIFIC ENGINES AND/OR AIRCRAFT.

AIR WASHER SYSTEMS (NOT FOR USE IN THE STATE OF CALIFORNIA)

For use only in industrial air washing systems with effective mist eliminating elements. Badly fouled air washer systems must be cleaned before initial dosing. Add PREVENTOL[®] D 7 to the air washer sump or chill water sump to ensure uniform mixing for the control of microorganisms.

Intermittent or slug dosing: Initial dosing: when system is noticeably fouled, add 1.26 – 7.46 pounds PREVENTOL[®] D 7 to 1000 gallons of air washer water.

Maintenance dosing: When microbial control is evident, dose 0.3 – 1.86 pounds PREVENTOL[®] D 7 to 1000 gallons of air washer water.

Repeat treatment as needed depending on the severity of contamination.

Continuous dosing method: Initial dosing: when system is noticeably fouled, add 1.26 – 7.46 pounds PREVENTOL[®] D 7 to 1000 gallons of air washer water.

PREVENTOL[®] D 7

39967-93

Page 6

Maintenance dosing: Add a continuous dose of 0.3 – 1.86 pounds PREVENTOL® D 7 to 1000 gallons air washer make-up water.
Repeat treatment as needed depending on the severity of contamination.

RECIRCULATING ELECTRODEPOSITION SYSTEMS

(NOT FOR USE IN THE STATE OF CALIFORNIA)
PREVENTOL® D 7 is used as a tankside additive for the control of microorganisms in recirculating systems and associated rinse systems. Alternatively, PREVENTOL® D 7 may be added through the components of the electrodepositon paint prior to their addition to the electrodepositon system.

TANKSIDE ADDITION TO ELECTRODEPOSITION SYSTEMS: PREVENTOL® D 7 should be dispensed into the recirculating rinse system, ultrafilter permeate, or final distilled rinse system at a point to insure uniform mixing. If additional microbial control is necessary PREVENTOL® D 7 may be added to the electrodepositon system tank side to supplement microbicide incorporated through paint components.

Initial dose: When the system is noticeably fouled, add 667-2333 ppm PREVENTOL® D 7 (6.7 – 23.3 gallons per 10,000 gallons of fluid is the system). This provides 10 to 35 ppm of active isothiazolone. Repeat until microbial control is achieved.

Initial dose of Paint Components: PREVENTOL® D 7 should be added to the resin, pigments, or other component of the elcetrodeposition paint at a level to ensure that the final use-dilution fluid will contain 333 – 2333 ppm product (5 – 35 ppm active ingredient).

Subsequent dose: When microbial control is evident, add 333 -1000 ppm PREVENTOL® D 7 (3.3 – 10 gallons per 10,000 gallons of fluid in the system) weekly or as needed to maintain the system. This provides 5-15 ppm of active isothiazolone. A change of frequency of treatment may be required depending upon the rate of dilution of the preservative with the makeup fluids, the nature and severity of contamination, level of control required, filtration effectiveness and system design.

NOTE: Regardless of the manner of incorporation, the total active ingredient level in the system should at no time exceed 35 ppm (equivalent to 2333 ppm PREVENTOL® D 7 23.3 gallons per 10,000 gallons of fluid in the system)

METAL CLEANING FLUIDS (NOT FOR USE IN THE STATE OF CALIFORNIA)

PREVENTOL® D 7 is used as a preservative in the manufacture and use of alkaline, acid and emulsion based metal cleaning fluids typically used in electroplating, phosphatizing, galvanizing and general metal cleaning operations. For addition to a metal cleaning concentration, add PREVENTOL® D 7 at a level to ensure that the final use-dilution fluid will contain 425 – 1675 ppm product (6.375 – 25 ppm isothiazolone). For direct addition to a fouled system, add 3.6 – 14.0 pounds PREVENTOL® D 7 to each 1000 gallons of use-dilution metal cleaning fluid every three to four weeks to provide 425 – 1675 ppm product (6.375 – 25 ppm isothiazolone). PREVENTOL® D 7 should be dispensed into the use-dilution of the metal cleaning fluid using a metering pump or by manual pouring and uniformly disperse throughout the system.

COMMERCIAL PHOTOPROCESSING SYSTEMS

PREVENTOL[®] D 7 is recommended to prevent slime formation or accumulation in filters and ion exchange resin tanks of commercial photoprocessing systems.

For the maintenance of a non-fouled system, use PREVENTOL[®] D 7 at 2.21 – 4.2 pounds per 1000 gallon fluid in the system once weekly, or as needed to maintain control of slime. every eight weeks. For a noticeably fouled system, use an initial dose 4.2 – 10. pounds per 1000 gallon fluid to be followed by subsequent maintenance dosing. Increased frequency of treatment may be required depending upon rate of dilution of the preservative with makeup fluid, the nature and severity of contamination, level of control required, filtration effectiveness, system design, etc. PREVENTOL[®] D 7 should be dispensed into the final rinse or used water collection tank for adequate distribution.

PHOTOPLATE PROCESSING, FOUNTAIN SOLUTIONS AND INK COMPONENTS

(NOT FOR USE IN THE STATE OF CALIFORNIA)

PREVENTOL[®] D 7 is recommended for the control of bacteria, fungi and microbial biofilms in photoplate processing chemicals, fountain solutions, and printing inks and ink components.

PREVENTOL[®] D 7 should be added to achieve 0.1% to 0.3% (15 – 45 ppm active ingredient). For fountain solution, add PREVENTOL[®] D 7 at concentration levels to ensure that the final use-dilution of the product will contain 0.1% - 0.3% (15-45 ppm active ingredient).

To insure uniform mixing, add PREVENTOL[®] D 7 to latex or solution slowly with agitation. The actual concentrations required will depend upon such factors as the specific substance to be treated, frequency of repeated microbial contamination expected and level of protection required.

METALWORKING FLUIDS (NOT FOR USE IN THE STATE OF CALIFORNIA)

PREVENTOL[®] D 7 is recommended for the control of bacteria, fungi and microbial biofilms in soluble and emulsifiable-type aqueous metalworking fluids. For maintenance of a non-fouled system, use PREVENTOL[®] D 7 at 32 fluid ounce per 1000 gallon of emulsion (2 pounds) every 4 weeks or 32-146 fluid ounces per 1000 gallon emulsion (2-10 pound) every 8-12 weeks. This corresponds to (3.84-17.5 ppm active ingredient). For a noticeably fouled system, use an initial dose of 64-146 fluid ounce per 1000 gallon emulsion (4-10 pounds) to be followed by subsequent maintenance dosages depending upon the treatment interval noted above. This corresponds to (7.75-17.5 ppm active ingredient).

PREVENTOL[®] D7 may be added to those products formulated as concentrates which are in turn diluted for use at a level to ensure that the final use-dilution product will contain between 0.04% to 0.15% PREVENTOL[®] D7.

REMARKS

If you need assistance or information, please call your nearest LANXESS representative, or our Pittsburgh office at 800-LANXESS.

PREVENTOL[®] D 7

39967-93

Page 8

**IN CASE OF EMERGENCY, CALL: CHEMTREC 1-800-424-9300
INTERNATIONAL (703)-527-3887**

**HAVE THE PRODUCT CONTAINER OF LABEL WITH YOU WHEN CALLING A POISON
CONTROL CENTER OR DOCTOR OR GOING FOR TREATMENT.**

LANXESS Corporation
111 RIDC Park West Drive
Pittsburgh, PA 15275
412-809-1000

The conditions of your use and application of our products, technical assistance and information (whether verbal, written or by way of production evaluations), including any suggested formulations and recommendations, are beyond our control. Therefore, it is imperative that you test our products, technical assistance and information to determine to your own satisfaction whether they are suitable for your intended uses and applications. This application-specific analysis at least must include testing to determine suitability from a technical as well as health, safety and environmental standpoint. Such testing has not necessarily been done by LANXESS Corporation. All information is given without warranty or guarantee. It is expressly understood and agreed that the customer assumes and hereby expressly releases LANXESS from all liability, in tort, contract or otherwise, incurred in connection with the use of our products, technical assistance and information. Any statement or recommendation not contained herein is unauthorized and shall not bind LANXESS. Nothing herein shall be construed as a recommendation to use any product in conflict with patents covering any material or its use. No license is implied or in fact granted under the claims of any patent.

1/15