399167-101

4/29/2014

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY WASHINGTON, D.C. 20460



APR 2 9-2014

OFFICE OF PREVENTION, PESTICIDES AND TOXIC SUBSTANCES

LANXESS Corporation 111 RIDC Park West Drive Pittsburgh, Pennsylvania 15275-1112 Attn: Luanne Jeram

Subject: Amended Reregistration Label N-521 P EPA Registration Number 39967-101 EPA Decision Number 430133

The Agency, in accordance with the Federal Insecticide, Fungicide and Rodenticide Act (FIFRA), as amended, has completed reviewing all of the information submitted with your application to support the reregistration of the above referenced product in connection with the Dazomet RED, and has concluded that your submission is acceptable.

NOTE: This product is <u>**not**</u> being reregistered under sections 3(c)5 and 4(g) of FIFRA at this time.

Please note that the record for this product currently contains the Confidential Statements of Formulation (CSFs) listed below. Any previously dated CSFs are superseded.

- Basic CSF, dated November 23, 2010

A copy of your label stamped "Accepted" is enclosed along with copies of the acute toxicity and product chemistry reviews completed for the subject product. Products shipped after 12 months from the date of this amendment or the next printing of the label whichever occurs first, must bear the new revised label. Your release for shipment of the product bearing the amended label constitutes acceptance of these conditions. If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA sec. 6(e). If you have any questions about this letter, please contact Karen Leavy at <u>leavy.karen@epa.gov</u>.

(.

Sincerely,

Marshall Swindell


Product Manager 33 ['] Regulatory Management Branch I Antimicrobials Division (7510P)

·			·· <u>······</u> ······	· · · · · · · · · · · · · · · · · · ·		Л
DIRECTIONS FOR USE It is a violation of Federal Law to use this product in a manner inconsistent with its labeling. Do not apply in a way that will contact workers or other persons. The amount necessary for desired protection varies, depending on exposure conditions. For further applications information refer to the Product Bulletin. RECOMMENDATIONS NOTE: N-5521® P should not be used in formulations containing mercurials or other components that are not compatible with sulfur compounds.	STORAGE AND DISPOSA L. Do not contaminate water, food or feed by storage or disposal. Open dumping is prohibited. Keep away from heat and flame, protect from temperatures in excess of 140°F. Do not reuse container. STORAGE: Keep container tightly closed when not in use. Do not store near food or feedstuffs. Can be stored at temperatures as low as minus 50°F.	PESTICIDE DISPOSAL : Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal law. If these wastes cannot be disposed of by use according the label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste Representative at the nearest EPA regional Office for guidance.	PVA BAGS: Water soluble bags are dissolved completely in the processes. Unused product should be disposed of according to pesticide disposal instructions. Obtain and read the Material Safety Data Sheet Section 13. CONTAINER HANDLING AND DISPOSAL	FIBER DRUMS (or FIBER BOXES) WITH PLASTIC LINERS: Completely empty liner by shaking and tapping sides and bottom to loosen clinging particles. Empty residue into application equipment. Then dispose of liner in a sanitary landfill or by incineration if allowed by state and local authorities. If fiber dum/box is contaminated and cannot be reused, dispose of in the same manner.		- 1
PRECAUTIONARY STATEMENTS PRECAUTIONARY STATEMENTS DANGER HAZARDS TO HUMANS AND DOMESTIC ANIMALS Corrosive. Causes skin burns. Do not get in eyes, on skin, or on conthing. May be fatal if swallowed. Harmful if absorbed through skin or inhaled. Avoid breathing dust. Wear coveralls over long sleeved shirt and long pants, socks, shoes and chemical resistant gloves (such as made out of any waterproof material, selection category A). User Safety Recommendations Wash hands before, eating, drinking, chewing gum, using tobacco, or using the toilet. Remove clothing.	Remove PPE after handling this product. Wash the outside of gloves before removing. As soon as possible, wash thoroughly and change into clean clothing. As soon as possible, wash thoroughly and change into clean clothing. As soon as possible, wash thoroughly and change into clean clothing. As soon as possible, wash thoroughly and change into clean clothing. As soon as possible, wash thoroughly and change into clean clothing. As soon as possible, wash thoroughly and change into clean clothing. As soon as possible, wash thoroughly and change into clean clothing. As soon as possible, wash thoroughly and change into clean clothing. As soon as possible, wash thoroughly and change into clean clothing. As soon as possible, wash thoroughly and change into clean clothing.	<i>If Immediately for treatment advice.</i> Have person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by a poison control center or doctor. Do not give anything by mouth to an unconscious person. <i>If Imhaled:</i> Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth if possible. Call a poison control con	<i>If in Eyes:</i> Hold eyes open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 15 minutes, then continue rinsing eyes. Call a poison control center or doctor for treatment advice. HOTLINE NUMBER Have the product container or tabel with you when calling a	poison control center or doctor, or going for treatment. Poison Control Centers:1-800-222-1222. You may also contact 1-800- 410-3063 for emergency medical treatment information. NOTE TO PHYSICIAN Probable mucosal may contraindicate the use of gastric lavage. This product is corrosive to the skin. Treat symptomatically.	ENVIRONMENTAL HAZARDS This product is toxic to fish. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA.	· ·
N-521 P Fungicide/Bactericide Inhibits and controls growth of slime forming fungi and bacteria PRESERVES AQUEOUS SYSTEMS	Active Ingredient: Tetrahydro-3,5-dimethyl-2H1,3,5-thiadiazine-2-thione 98% Inert Ingredients Total DANGER	KEEP OUT OF REACH OF CHILDREN MAY BE HARMFUL IF SWALLOWED	LOT NO.:	NET WT.: Under the Federal Insectiode, Fungicide, and Rodenticide Act as armended, Fungicide, and pesticide, registered upon the EPA Reg. No. 379492	Energizing Chemistry LANXESS Corporation 111 RIDC Park West Drive Pittsburgh, PA 15275-1112	3/20/14

1

2





-101

Product Information

N-521[®] P

EPA Registration Number 39967-101

N-521® P 39967-101 Page 1

N-521[®] P

FOR INDUSTRIAL USE AS A PRESERVATIVE TO INHIBIT AND CONTROL THE GROWTH OF SLIME FORMING FUNGI AND BACTERIA IN PULP AND PAPER MILL SYSTEMS, OILFIELD DRILLING MUDS AND WORKOVER OR COMPLETION FLUIDS, OILFIELD WATER TREATMENT AND WATER FLOODS, FOR THE PRESERVATION OF CLAY SLURRIES, ADHESIVES, COATINGS AND HIGH VISCOSITY SUSPENSIONS, RECIRCULATING COOLING WATER, BUILDING MATERIALS

DIRECTIONS FOR USE

It is a violation of federal law to use this product in a manner inconsistent with its labeling.

The following guidance is given as an approximation for each use pattern, but field-testing is recommended to achieve optimum effectiveness.

PULP AND PAPER MILL SYSTEMS

N-521[®] P is effective in inhibiting the growth of slime forming fungi and bacteria in pulp and paper mill systems. Add 0.09 to 0.38 pounds of N-521[®] P per ton of finished product. The exact amount necessary for effective control will vary depending on the ingredients; temperature and equipment used in the mill system and should be determined by actual test. Systems, which show considerable slime fouling, should be cleaned thoroughly prior to treatment. <u>METHOD OF ADDITION:</u> N-521[®] P should be added at a point in the system (raw stock chest, beater and / or refiner chest, or machine chest-wirepit) where there will be sufficient time and agitation for thorough dispersion.

FOR INDUSTRIALLY PREPARED WATER-BASED SUSPENSIONS (PIGMENT SLURRIES, ADHESIVES, POLYMERS AND STARCHES) USE: FOR THE PRESERVATION OF CLAY SLURRIES, ADHESIVES, COATINGS AND HIGH VISCOSITY SUSPENSIONS

N-521[®] PAC-24 is effective in inhibiting the growth of fungi and bacteria which cause microbiological degradation and slime formation in slurries of starch, clay, calcium carbonate or titanium dioxide; paper coatings; and high viscosity suspensions (polymers, starches, adhesives, clay slurries, glues, coating, resin emulsions) during processing at use levels of 0.01% to 0.5% by weight. This material can be packaged in pre-measured water-soluble polyvinyl plastic bags for accurate additions and safe handling. Add 1 to 50 pre-measured PVA one pound bags per 10,000 lbs of material. The most effective product usage rate within the effective range of 0.01% to 0.5% by weight must be determined by actual test on each specific

N-521[®] P 39967-101 Page 2 formulation and situation since performance will vary depending on the ingredients in the formulation being preserved, its storage conditions, and the length of preservation time required.

<u>METHOD OF ADDITION</u>: For preservation of aqueous systems, N-521[®] P should be added at a point in the processing where there will be sufficient time and agitation for thorough dispersion.

OILFIELD DRILLING MUDS AND WORKOVER OR COMPLETION FLUIDS

N-521[®] PAC-24 is effective in the control of slime-forming and/or spoilage bacteria in oilfield drilling mud and completion fluids. Calculate the number of pounds of N-521[®] P needed to produce a concentration of 520 ppm (0.18lb/bbl) in the drilling mud circulation system. Because of the wide variation in drilling mud composition and bacterial contamination, greater or lesser amounts of N-521[®] P may be prescribed.

<u>METHOD OF ADDITION</u>: For best results add N-521[®] P in a thin stream to the mud pit while the drilling fluid is circulating. As the total volume increases, due to greater well depth, add additional N-521[®] P to maintain the proper concentration.

OILFIELD WATER TREATMENT AND WATER FLOODS

N-521[®] P is effective in the control of slime-forming and/or spoilage bacteria in oilfield water treatment and water floods. Calculate the total volume of water to be treated. Using this volume, calculate the number of pounds of N-521[®] P needed to produce a concentration of approximately 625 ppm N-521[®] P. For water-soluble bags add 1 pound of N-521[®] P per each 191 gallons of total volume will produce a concentration of approximately 625 ppm N-521[®] P. For water-soluble bags add 0.73 pounds of N-521[®] P to each 1000 gallons of total volume each week. For water-soluble bags, add 1 pound of N-521[®] P to each 1363 gallons of total volume. Because of the wide variation in waters found in the oilfield, greater or lesser amounts of N-521[®] P maybe required in a particular location.

RECIRCULATING COOLING WATER SYSTEMS

N-521[®] P is effective for control of algae, fungi, and slime forming bacteria. Dosages for recirculating cooling water systems will depend on the condition of the system prior to treatment initiation. Systems, which are heavily contaminated, should be cleaned first. Apply N-521[®] P to the cleaned system when growth is first noticed.

<u>INITIAL DOSE</u>: Calculate the total volume of water to be treated. Using this volume, calculate the number of pounds of N-521[®] P needed to produce a concentration of 7.5 – 15 ppm N-521[®] P per each 1000 gallons of water in the system. For water soluble bags add 1 pound of N-521[®] P per each 8,000 – 16,000 gallons of water in the system. This doses maybe a continuous treatment or applied once, twice or three times weekly or as required to control the growth of slime forming organisms.

<u>SUBSEQUENT DOSAGE</u>: When microbial control is evident add 1.25 – 7.5 ppm of N-521[®] P per 1000 gallons of water in the system as a continuous treatment daily or every three days as required to maintain control. For water-soluble bags, add 1 pound of N-521[®] P per each 16,000 – 96,000 gallons of water in the system.

N-521[®] P 39967-101 Page 3

Ø

BUILDING MATERIALS

N-521[®] P is effective for the control of bacteria, yeast and fungi in water based and water dispersed construction products. N-521[®] P can be fed at a concentration of 200 – 2000 ppm either directly to the finished building material or to one of the raw materials, which may include lignin, molasses, polymer or biopolymer dispersions, emulsions, or solutions used in formulation of building industry materials. EFFECTIVE DOSAGES:

Caulking materials	200 – 2000 ppm
Concrete admixtures	200 – 2000 ppm
Concrete and masonry additives	200 – 2000 ppm
Other materials and auxiliaries	200 – 2000 ppm

REMARKS

If you need assistance or information, please call your nearest LANXESS representative, or our Pittsburgh office at 800-LANXESS.

IN CASE OF EMERGENCY, CALL: CHEMTREC 1-800-424-9300 INTERNATIONAL (703)-527-3887

HAVE THE PRODUCT CONTAINER OF LABEL WITH YOU WHEN CALLING A POISON CONTROL CENTER OR DOCTOR OR GOING FOR TREATMENT.

LANXESS Corporation 111 RIDC Park West Drive Pittsburgh, PA 15275 412-809-1000

The conditions of your use and application of our products, technical assistance and information (whether verbal, written or by way of production evaluations), including any suggested formulations and recommendations, are beyond our control. Therefore, it is imperative that you test our products, technical assistance and information to determine to your own satisfaction whether they are suitable for your intended uses and applications. This application-specific analysis at least must include testing to determine suitability from a technical as well as health, safety and environmental standpoint. Such testing has not necessarily been done by LANXESS Corporation. All information is given without warranty or guarantee. It is expressly understood and agreed that the customer assumes and hereby expressly releases LANXESS from all liability, in tort, contract or otherwise, incurred in connection with the use of our products, technical assistance and information. Any statement or recommendation not contained herein is unauthorized and shall not bind LANXESS. Nothing herein shall be construed as a recommendation to use any product in conflict with patents covering any material or its use. No license is implied or in fact granted under the claims of any patent.

3/20/14

N-521[®] P 39967-101 Page 4