

PRO-LINE

KEEP OUT OF REACH OF CHILDREN.

DANGER!

SEE SIDE PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS.

YACHT FINISHES

PRECAUTIONARY STATEMENTS

Hazardous to Humans and Domestic Animals. Corrosive causes eye and skin damage. Do not get in eyes, on skin or on clothing. Wear goggles or face shield and rubber gloves when handling. Harmful if swallowed or absorbed through skin. Avoid breathing vapors or spray mist. When used in confined areas or applied by spraying wear a respirator jointly approved by the National Institute for Occupational Safety and Health under the provision of 29 CFR 11.

Statements of Practical Treatment

In case of contact with eyes: Immediately flush eyes with water for at least 15 minutes. Call a physician.

In case of contact with skin: Immediately wash skin with plenty of soap and water. Get medical attention if irritation persists.

Environmental Hazards

Do not contaminate water by cleaning of equipment or disposal of wastes. Follow all safety and health precautions established by local, state and federal agencies.

Physical or Chemical Hazards

Flammable. Keep away from heat and open flame. Flash Point 73°F.



VINYL ANTIFOULING PAINT 1077-04-E BLACK

ACTIVE INGREDIENTS

BIS (TRIBUTYL) TIN OXIDE 4.1%
TRIBUTYL TIN FLUORIDE 17.8%

INERT INGREDIENTS

TOTAL 100.0%
TIN AS METALLIC 7.66%

NET 121.6 FL. OZ. .95 GAL.

EST. NO. 40238CA01
EPA REGISTRATION
NO. 40238-1

STORAGE AND DISPOSAL

- 1. PROHIBITIONS:** Do not contaminate potable water, food, or feed by storage or disposal. Open burning is prohibited.
- 2. PESTICIDE DISPOSAL:** Pesticide spray mixture or rinsate that cannot be used or chemically reprocessed should be disposed of according to procedures approved by federal, state or local disposal authorities.
- 3. CONTAINER DISPOSAL:** Triple rinse and recycle, recycling, reconditioning, or disposal approved and fill or bury in a safe place.
- 4. GENERAL:** Consult federal, state or local disposal authorities for alternative procedures.

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with the labeling.

PRO-LINE VINYL ANTIFOULING

#1077-01	#1077-02	#1077-03	#1077-04
WHITE	BLUE	RED	BLACK

SURFACE MUST BE FREE OF ALL SURFACE CONTAMINATION AND MOISTURE.

APPLICATION: May be brushed, rolled or sprayed.

ALUMINUM: Bare aluminum must be sandblasted or handsanded and primed with 3-coats of EPOXY PRIMER #4018, giving a total dry mil thickness of at least 10-MILS prior to applying antifouling. See Note.

STEEL: Bare steel should be sandblasted to a #10 MARINE BLAST to remove all rust and mil scale. After sandblasting apply 3-coats of EPOXY PRIMER #4001, giving a total dry mil thickness of at least 10-MILS prior to applying antifouling. See Note.

FIBERGLASS HULL UNPAINTED: Scrub hull with a solution of warm water and TSP. Rinse with fresh water, sand hull lightly with 80-grit Garnet Paper. Remove dust with clean rag. Apply a uniform light coat of #4000 Primer. See note prior to applying antifouling paints!

WOOD: Over bare wood apply 1ST COAT OF ANTIFOULING thinned with PRO-LINE #20 (one-quart per gallon of antifouling). Apply 2ND COAT unthinned.

OLD ANTIFOULING: May be applied over most aged antifouling paint when surface is thoroughly clean and dry.

RECOAT TIME: 2-HOUR MINIMUM — NO MAXIMUM between anti-foulings.

LAUNCH TIME: 4-HOURS

THINNING: Under normal conditions thinning is not recommended.

NOTE: WHEN ANTIFOULING IS APPLIED OVER EPOXY PRIMERS, THE ANTIFOULING MUST BE APPLIED WITHIN 3-8 HOURS AFTER EPOXY PRIMER. THE CORRECT TIME IS WHEN YOU CAN TOUCH THE EPOXY AND LEAVE A FINGER PRINT AND YET NO EPOXY WILL ADHERE TO YOUR FINGER.

This product is effective in preventing marine growth, such as barnacles, bugulas, etc.

NON-PHOTO CHEMICAL REACTIVE

PRO-LINE PAINT MANUFACTURING CO.

14 MARINE TANKERS BLVD. LONG BEACH, CALIF. 90801

PHONE (714) 232-8968 — LONG BEACH (213) 432-7961

ACCEPTED

DISCONTINUED