

EPA ESTABLISHMENT NO. 40238CA01

# PRO-LIN

KEEP OUT OF REACH OF CHILDREN

**DANGER!**

SEE PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS

## YACHT FINISHES

### PRECAUTIONARY STATEMENTS

**WARNING:** Hazards to Humans and Domestic Animals

**HAZARDS TO HUMANS:** Corrosive. Causes skin burns. Wear protective clothing such as gloves, long sleeved cotton shirt, long pants and hat. Causes eye irritation. May be fatal if swallowed. Harmful if absorbed through skin or inhaled. This product may be a dermal sensitizer.

Avoid contact with skin, eyes or clothing. Avoid breathing vapor, spray mist, dust or chips from sanding. Wash thoroughly with soap and water after handling and before eating or smoking. Use with adequate ventilation. Never give anything by mouth to an unconscious person. Call a physician immediately. Avoid storage and usage near food and feed products. When used in confined areas or while spraying and/or sanding boat surface, wear a mask or a respirator jointly approved by the Mining Enforcement and Safety Administration and the National Institute for Occupational Safety and Health, under the provisions of 30 CFR 11.

### ENVIRONMENTAL HAZARDS:

This material is toxic to fish. Do not contaminate waters by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter waters. Dispose wastes, debris, in an approved landfill.

### Physical or Chemical Hazards

**FLAMMABLE. FLASH POINT APPROXIMATELY 80 F.**

Keep away from heat and open flame.

Pesticide container or rinse solution that cannot be used according to label instructions must be disposed of according to Federal or approved State procedures under Subtitle C of the Resource Conservation and Recovery Act.



### 1025-03-E RED SEVEN SEAS COPPER BOTTOM ANTIFOULING PAINT

For protecting underwater hull surfaces from marine fouling and slime.

#### ACTIVE INGREDIENTS

BIS(TRIBUTYL)TINOXIDE 1.44%

CUPROUS OXIDE 35.98%

**INERT INGREDIENTS 62.58%**

TOTAL 100.00%

COPPER AS METALLIC 32.57%

Contains Petroleum Distillates

**NET CONTENTS: LBS. Gal.**

EPA REGISTRATION NO 40238-1

# NE<sup>®</sup>

MENTS

S



NG PAINT

me

44%

98%

58%

00%

57%

**FOLLOW ALL SAFETY AND HEALTH REGULATIONS: PRACTICAL TREATMENT**

**IF SWALLOWED:** Drink promptly a large quantity of milk, egg whites, gelatin solution or if these are not available drink large quantities of water. Avoid alcohol. Get medical attention.

**IF IN EYES:** Flush with plenty of water. Get medical attention.

**IF ON SKIN:** Wash with plenty of soap and water. Get medical attention.

**IF INHALED:** Remove victim to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. Get medical attention.

**NOTE TO PHYSICIAN:** Probable mucosal damage may contraindicate the use of gastric lavage.

**WARRANTY:** Pro Line warrants that the contents of this container conform to the product's description on this label.

**THERE ARE NO WARRANTIES WHICH EXTEND BEYOND THE DESCRIPTION ON THE FACE HEREOF. IN NO EVENT SHALL PRO-LINE BE LIABLE FOR ANY INCIDENTAL SPECIAL OR CONSEQUENTIAL DAMAGES OF ANY NATURE WHATSOEVER INCLUDING WITHOUT LIMITATIONS LOSS OR USE OF LOST PROFITS.**

This product may not carry the implied warranties of the uniform commercial code.

**STORAGE AND DISPOSAL**

- PROHIBITIONS:** Do not contaminate potable water, food or feed by storage or disposal. Open dumping is prohibited.
- PESTICIDE DISPOSAL:** Pesticide spray mixture or residue that cannot be used or chemically reprocessed should be disposed of according to procedures approved by federal, state or local disposal authorities.
- CONTAINER DISPOSAL:** Dispose in approved landfill.

**DIRECTIONS FOR USE OF PRO-LINE #1025 SERIES**

It is a violation of Federal law to use this product in a manner inconsistent with its labeling. This labeling must be in the possession of the user at the time of pesticide application. **THE SURFACE MUST BE FREE OF ALL SURFACE CONTAMINATION AND MOISTURE.**

## SEVEN SEAS COPPER BOTTOM ANTIFOULING PAINT

**APPLICATION:** May be brushed, rolled or sprayed. **Stir well before using.**

**ALUMINUM:** These products ARE NOT FOR USE ON ALUMINUM.

**STEEL:** Bare steel should be sandblasted to a #10 MARINE BLAST to remove all rust and mill scale. After sandblasting, apply 4 coats of EPOXY PRIMER #4000 series, giving a total dry mil thickness of at least 12 MILS. See note prior to applying antifouling paints.

**FIBERGLASS HULL — UNPAINTED:** Scrub hull with a solution of warm water and TSP. Rinse with fresh water, sand hull lightly with 20 grit Garnet Paper. Remove dust with clean rag. Apply a uniform light coat of #4000 Primer. See note prior to applying antifouling paints.

**WOOD:** Over bare wood, apply first coat of ANTIFOULING thinned with PRO-LINE #7 (one quart per gallon of antifouling). Apply second coat unthinned.

**OLD ANTIFOULING:** May be applied over most aged soft-sloughing type antifouling paints when surface is tight, clean and dry. Do not apply over vinyl antifouling paints.

**FERRO-CEMENT:** Not recommended.

**RECOAT TIME:** 12 hour minimum -- no maximum between antifouling paints.

**LAUNCH TIME:** 8 hours after last coat of antifouling paint.

**THINNING:** Thinning may be necessary in colder climates where viscosity may increase.

**THINNER:** PRO-LINE #7.

**NOTE:** When antifouling is applied over Epoxy Primers, the antifouling must be applied within 3-5 hours after last coat of Epoxy Primer.

This product is effective in preventing marine growth, such as barnacles, bugulas, etc. Can be used in sweet and salt waters.

### NON-PHOTOCHEMICALLY REACTIVE

### PRO-LINE PAINT MANUFACTURING CO.

2646 MAIN STREET, SAN DIEGO, CALIFORNIA 92113-3697

PHONE (619) 232-8968

LONG BEACH (213) 432-7961

Mr. E. Soeterik  
Pro-Line Paint Company  
2640 Main Street  
San Diego, CA 92113

1983

Dear Mr. Soeterik:

Subject: Antifouling Paints Label Improvement Program (LIP)  
Pro-Line 1025-03-L Red  
Your submission dated February 23, 1983

The amendment referred to above, submitted in connection with registration under FIFRA is acceptable, provided that you:

1. Make the labeling changes listed below before you release the product for shipment bearing the amended labeling:
  - a. Delete WARNING and replace with DANGER under the heading Precautionary Statements.
  - b. Delete the quotation marks (") around contains petroleum distillates.
  - c. You can delete "this labeling must be in the possession...of pesticide application."
  - d. Delete "sweet and." this term is not clear and is inconsistent with the claim for preventing marine growth.
  - e. Correct the EPA Registration No. to 40238-3.
  - f. Correct the ingredient declaration to read:  
bis (tributyltin) oxide
2. Submit one (1) copy of your final printed labeling before you release the product for shipment.

CONCURRENCES							
NAME							
SIGNATURE							
DATE							

-2-

A stamped copy of the labeling is enclosed for your records.

Sincerely yours,

Richard F. Mountfort *RFM*  
Product Manager (23)  
Fungicide-Herbicide Branch  
Registration Division (TS-767)

Enclosure