

111 40238-7 104  
UNITED STATES ENVIRONMENTAL PROTECTION AGENCY

JUN 19 1992

Pro-Line Paint Company  
2646 Main Street  
San Diego, CA 92113-3697

Attention: Mr. E. Soeterik

Subject: Red Vinyl Antifouling Paint Formula 121  
EPA Registration No. 40238-7  
Amendment Dated January 22, 1992  
4-15

The amendment referred to above submitted in connection with registration under the Federal Insecticide, Fungicide, and Rodenticide Act, as amended, is acceptable provided that you revise your storage and disposal statement to read as follows:

**STORAGE AND DISPOSAL**

Do not contaminate water, food, feed by storage or disposal. Open dumping is prohibited.

**PESTICIDE DISPOSAL**

Paint that cannot be used according to label instructions must be disposed of according to federal, state or local procedures under the Resources Conservation and Recovery Act.

**CONTAINER DISPOSAL**

Dispose of container by triple rinse and recycling or puncturing and disposing in a sanitary landfill or by other approved State and local procedures. If burned stay out of smoke.

The heading "STORAGE AND DISPOSAL" must be of the same type size as the child hazard warning statement.

**CONCURRENCES**

SYMBOL								
SURNAME								
DATE								

A stamped copy of the label is enclosed for your records.

If you have any questions concerning this letter, please contact Marshall Swindell at (703) 305-6908.

Sincerely yours,



John H. Lee  
Product Manager 31  
Antimicrobial Programs Branch  
Registration Division (H7505C)

01

CAL.-REGISTRATION 40238-7-AA

EPA REGISTRATIO

# PRO-LINE®

KEEP OUT OF REACH OF CHILDREN.

**DANGER!**

SEE LABEL FOR ABOUT DANGERS AND PRECAUTIONARY STATEMENTS

## Technical Coatings

FOLLOW ALL SAFETY REGULATIONS: P

IF SWALLOWED: If swallowed, do not induce vomiting. If necessary, give milk, egg whites, or water if available. Drink large amounts of water. Get medical attention.

IF IN EYES: Flush eyes with water for at least 15 minutes. Get medical attention.

IF ON SKIN: Wash with soap and water. Get medical attention if irritation persists.

IF INHALED: Remove to fresh air. If breathing is difficult, give artificial respiration. Get medical attention.



**RED VINYL**

**ANTIFOULING PAINT FORMULA 121  
MILITARY SPECIFICATION**

MIL-P-15931C, TYPE 11, CLASS 2 PRO-LINE NO. 1060

For protecting underwater hull surfaces from marine fouling and slime

**ACTIVE INGREDIENTS**

CUPROUS OXIDE

**INERT INGREDIENTS**

TOTAL

FREE ELEMENTAL COPPER

CONTAINS PETROLEUM DISTILLATES

**ACCEPTED with COMMENT WARRANTY:** Pro-Line warrants that the product conforms to the description on this label in EPA Label Data.

**THERE ARE NO WARRANTIES MADE BY PRO-LINE BE LIABLE FOR ANY INCIDENTAL DAMAGES OF ANY NATURE WITHOUT LIMITATIONS OF ANY KIND.**

Under the Federal Insecticide, Fungicide, and Rodenticide Act, as amended, for this product may not carry the implied warranty of merchantability or fitness for a particular purpose.

66 90% Fungicide, and 33 10% Fungicide, and 100 00% Fungicide, and 67% Fungicide.

**STORAGE AND DISPOSAL**

**PROHIBITIONS:** Do not contaminate water, food, or feed by storage or disposal. Open dumping is prohibited.

**PESTICIDE DISPOSAL:** Pesticide should not be released into the environment. It should be used in chemically reprocessed sludge or other procedures approved by federal, state, or local authorities.

**CONTAINER DISPOSAL:** Dispose in accordance with local, state, or federal regulations.

**NET CONTENTS: LBS. Gal.**

[REDACTED]

**EPA ESTABLISHMENT NO. 40238CAC**

[REDACTED]

[REDACTED]

**PRECAUTIONARY STATEMENTS**

**WARNING:** (Hazards to Humans and Domestic Animals)

**HAZARDS TO HUMANS:** Causes eye irritation. Harmful if absorbed through skin. Avoid contact with skin, eyes or clothing. Wear protective clothing such as gloves, long-sleeved cotton shirt, long pants and hat. May be fatal if swallowed or inhaled. Do not breathe dust, vapor or spray

mist. Wash contaminated clothing before reuse. Never give anything by mouth to an unconscious person. Call a physician immediately. Avoid storage and usage near food and feed products. When used in confined areas or while spraying and/or sanding boat surface, wear a mask or a respirator jointly approved by the Mining Enforcement and Safety Administration and the National Institute for Occupational Safety and Health, under the provisions of 30 CFR 11.

**ENVIRONMENTAL HAZARDS:**

This material is toxic to fish. Do not contaminate waters by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter waters. Dispose wastes debris in an approved landfill.

**Physical or Chemical Hazards**

**FLAMMABLE. FLASH POINT APPROXIMATELY 80 F.**

**Keep away from heat and open flame.**

Pesticide, container or rinse solution that cannot be used according to label instructions must be disposed of according to Federal or approved State procedures under Subtitle C of the Resource Conservation and Recovery Act

[REDACTED]

5-24

## FOLLOW PRO-LINE PAINT BOTTOM COATING GUIDE DIRECTIONS FOR USE OF PRO-LINE PAINT

It is a violation of Federal law to use this product in a manner inconsistent with its labeling. This label must be in the possession of the user at the time of pesticide application.  
**THE SURFACE MUST BE FREE OF ALL SURFACE CONTAMINATION AND MOISTURE.**

### RED VINYL ANTIFOULING PAINT FORMULA 121 - PRO-LINE #1060

**APPLICATION:** May be brushed, rolled or sprayed. *Stir well before using.*

**ALUMINUM:** These products ARE NOT FOR USE ON ALUMINUM.

**STEEL:** Bare steel should be sandblasted to a # 10 MARINE BLAST to remove all rust and mil scale. After sandblasting, apply 4 coats of EPOXY PRIMER #4000 series, giving a total dry mil thickness of at least 12 MILS. *See note prior to applying antifouling paints!*

**FIBERGLASS HULL — UNPAINTED:** Scrub hull with a solution of warm water and TSP. Rinse with fresh water, sand hull lightly with 80-grit Garnet Paper. Remove dust with clean rag. Apply a uniform coat of #4000 Primer. *See note prior to applying antifouling paints!*

**WOOD:** Over bare wood, apply first coat of ANTIFOULING thinned with PRO-LINE #20 (one quart per gallon of antifouling). Apply second coat unthinned.

**OLD ANTIFOULING:** May be applied over most aged soft-sloughing type antifouling paints when surface is tight, clean and dry. Do not apply over vinyl antifouling paints.

**FERRO-CEMENT:** Not recommended

**RECOAT TIME:** 2 hour minimum — no maximum between antifouling paints.

**LAUNCH TIME:** 4 hours after last coat of antifouling paint.

**THINNING:** If necessary use either #4 or #20 thinner.

**NOTE:** When antifouling is applied over Epoxy Primers, the antifouling must be applied within 3-5 hours after last coat of Epoxy Primer.

This product is effective in preventing marine growth, such as barnacles, bugulas, etc. Can be used in sweet and salt waters.

### NON-PHOTOCHEMICALLY REACTIVE PRO-LINE PAINT MANUFACTURING CO.

2646 MAIN STREET, SAN DIEGO, CALIFORNIA 92113-3697 • (619) 232-8968  
1168 HARBOR, LONG BEACH, CALIFORNIA • (213) 432-7961

**WARNING:** DETECTABLE AMOUNTS OF CHEMICALS OR SUBSTANCES KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER, BIRTH DEFECTS, OR OTHER REPRODUCTIVE HARM MAY BE FOUND IN CHEMICAL PRODUCTS, PETROLEUM PRODUCTS AND THEIR VAPORS. FOLLOW APPLICABLE DIRECTIONS AND USE CARE WHEN HANDLING CHEMICAL AND PETROLEUM PRODUCTS. (CALIFORNIA HEALTH AND SAFETY CODE SECTION 25249.6)