**EPA ESTABLISHMENT NO. 40238CA01** 

**EPA REGISTRATION NO. 40238-7** 

KEEP OUT OF REACH OF CHILDREN.

WARNING

SEE SIDE PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS

## **Technical Coatings**

PRECAUTIONARY STATEMENTS

WARNING: (Hazards to Humans and Domestic Animals) HAZARDS TO HUMANS: Causes eye irritation. Harmful if absorbed through skin. Avoid contact with skin, eyes or clothing. Wear protective clothing such as gloves, longsleeved cotton shirt, long pants and hat. May be fatal if swallowed or inhaled. Do not breathe dust, vapor or spray

mist. Wash contaminated clothing before reuse. Never give anything by mouth to an unconscious person. Call a physician immediately. Avoid storage and usage near food and feed products. When used in confined areas or while spraying and/or sanding boat surface, wear a mask or a respirator jointly approved by the Mining Enforcement and Safety Administration and the National Institute for Occupational Safety and Health, under the provisions of 30 CFR 11.

#### **ENVIRONMENTAL HAZARDS:**

This material is toxic to fish. Do not contaminate waters by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter waters. Dispose wastes debris in an approved landfill.

Physical or Chemical Hezards

FLAMMABLE, FLASH POINT APPROXIMATELY 80° F.

Keep avey from heat and open flame.

Pesticide, container or ricse solution that cannot be used according to label instructions must be disposed of according to Federal or approved State procedures under Subtiffe C of the Resource Conservation and Recovery Act.





#### **RED VINYL**

#### **ANTIFOULING PAINT FORMULA 121** MILITARY SPECIFICATION

MIL-P-15931C, TYPE I CLASS 2 PRO-LINE NO. 1069 For protecting underwater hull surfaces from marine fouling and slime.

ACTIVE INGREDIENTS	
CUPROUS OXIDE	66.90%
NERT INGREDIENTS	33.10%
TOTAL	100.00%
FREE ELEMENTAL COPPER	

CONTAINS PETROLEUM DISTILLATES

ıΞ 28 Д 63 Ш O

#### FOLLOW ALL SAFETY AND HEALTH REQULATIONS: PRACTICAL TREATMENT

IF SWALLOWED: Drink promptly a large quantity of milk, egg whites, gelatin solution or if these are not available, drink large quantities of water. Avoid alcohol. Get medical attention.

IF IN EYES: Flush with plenty of water. Get medical attention.

IF ON SKIN: Wash with plenty of soap and water. Get medical attention.

IF INHALED: Remove victim to fresh air, if not breathing, give artificial respiration, preferably mouth-tomouth Get medical attention

WARRANTY: Pro-Line warrants that the contents of this container conform o the product's description on this label.

THERE ARE NO WARRANTIES WHICH EXTEND BEYOND THE DESCRIPTION ON THE FACE HEREOF. IN NO EVENT SHALL PRO-LINE BE LIABLE FOR ANY INCIDENTAL SPECIAL OR CONSE-QUENTIAL DAMAGES OF ANY NATURE WHATSOEVER INCLUDING WITHOUT LIMITATIONS LOSS OR USE OF LOST PROFITS.

his product may not carry the implied warranties of the uniform commercial code.

등 국 통화 Do not contaminate water, food, feed by storage or disposal. Open dumping is prohibited. PESTICIDE DISPOSAL

Paint that cannot be used according to label instructions must be disposed of according to Federal, State or local procedures under the Resources Conservation and Recovery Act. CONTAINER DISPOSAL

Dispose of container by triple ringe and recycling or puncturing and disposing in a sanitary landfill or by other approved State and local procedures. If burned stay out of smoke.

**NET CONTENTS:** 

Gal.

40 Ð W 80

<u>}</u>

Œ

### **EPA ES**

# FOLLOW PRO-LINE PAINT BOTTOM COATING GUIDE DIRECTIONS FOR USE OF PRO-LINE PAINT

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

This label must be in the possession of the user at the time of pesticide application.

THE SURFACE MUST BE FREE OF ALL SURFACE CONTAMINATION AND MOISTURE.

## RED VINYL ANTIFOULING PAINT FORMULA 121 - PRO-LINE #1060

APPLICATION: May be brushed, rolled or sprayed. Stir well before using.

ALUMINUM: These products ARE NOT FOR USE ON ALUMINUM.

STEEL: Bare steel should be sandblasted to a # 10 MARINE BLAST to remove all rust and mil scale. After sandblasting, apply 4 coasts of EPOXY PRIMER #4000 series, giving a total dry mil thickness of at least 12 MILS. See note prior to applying antifouling paints!

FIBERGLASS HULL — UNPAINTED: Scrub hull with a solution of warm water and TSP. Rinse with fresh water, sand hull lightly with 80-grit Gamet Paper. Remove dust with clean rag. Apply a uniform coat of #4000 Primer. See note prior to applying antifouling paints!

WOOD: Over bare wood, apply first coat of ANTIFOULING thinned with PRO-LINE #20 (one quart per gallon of antifouling). Apply second coat unthinned.

OLD ANTIFOULING: May be applied over most aged soft-sloughing type antifouling paints when surface is tight, clean and dry. Do not apply over vinyl antifouling paints.

FERRO-CEMENT: Not recommended

RECOAT TIME: 2 hour minimum — no maximum between antifouling paints.

LAUNCH TIME: 4 hours after last coat of antifouling paint.

THINNING: If necessary use either #4 or #20 thinner.

NOTE: When antifouling is applied over Epoxy Primers, the antifouling must be applied within 3-5 hours after last coat of Epoxy Primer.

This product is effective in preventing marine growth, such as barnacles, bugulas, etc. Can be used in sweet and salt waters.

### **NON-PHOTOCHEMICALLY REACTIVE**

### PRO-LINE PAINT MANUFACTURING CO.

2646 MAIN STREET, SAN DIEGO, CALIFORNIA 92113-3697 • (619) 232-8968 1168 HARBOR, LONG BEACH, CALIFORNIA • (213) 432-7961

WARNING: DETECTABLE AMOUNTS OF CHEMICALS OR SUBSTANCES KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER, BIRTH DEFECTS, OR OTHER REPRODUCTIVE HARM MAY BE FOUND IN CHEMICAL PRODUCTS. PETROLEUM PRODUCTS AND THEIR VAPORS, FOLLOW APPLICABLE DIRECTIONS AND USE CARE WHEN HANDLING CHEMICAL AND PETROLEUM PRODUCTS. (CALIFORNIA HEALTH AND SAFETY CODE SECTION 25249.6)

PRECAUTIONA
WARNING: (Ha:
HAZARDS TO F
if absorbed throi
clothing. Wear p
sleeved cotton:
swallowed or int
mist. Wash cont
mouth to an ui
storage and use
areas or while:
respirator joint
Administration.

Health, under th

This material is equipment or d during paint reapproved landfi Physical or Ch-FLAMMABLE.

Pesticide, conts instructions mu procedures und