

IP 2 40238-8 1045

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY

JUN 13 1992

Pro-Line Paint Company
2646 Main Street
San Diego, CA 92113-3697

Attention: Mr. E. Soeterik

Subject: Black Vinyl Antifouling Paint Formula 129
EPA Registration No. 40238-8
Amendment Dated January 22, 1992
4-15

The amendment referred to above submitted in connection with registration under the Federal Insecticide, Fungicide, and Rodenticide Act, as amended, is acceptable provided that you revise your storage and disposal statement to read as follows:

STORAGE AND DISPOSAL

Do not contaminate water, food, feed by storage or disposal. Open dumping is prohibited.

PESTICIDE DISPOSAL

Paint that cannot be used according to label instructions must be disposed of according to federal, state or local procedures under the Resources Conservation and Recovery Act.

CONTAINER DISPOSAL

Dispose of container by triple rinse and recycling or puncturing and disposing in a sanitary landfill or by other approved State and local procedures. If burned stay out of smoke.


The heading "STORAGE AND DISPOSAL" must be of the same type size as the child hazard warning statement.

CONCURRENCES							
SYMBOL							
SURNAME							
DATE							

A stamped copy of the label is enclosed for your records.

If you have any questions concerning this letter, please contact Marshall Swindell at (703) 305-6908.

Sincerely yours,



John H. Lee
Product Manager 31
Antimicrobial Programs Branch
Registration Division (H7505C)

CAL.-REGISTRATION 40238-8-AA

EPA REGISTRATION

PRO-LINE®

KEEP OUT OF REACH OF CHILDREN

DANGER!

SEE REVERSE SIDE FOR ADDITIONAL REGULATORY STATEMENTS

Technical Coatings

FOLLOW ALL SAFETY REGULATIONS: PRACTICE

IF SWALLOWED: Drink milk, egg whites, gelatin available; drink large quantities. Get medical attention.

IF IN EYES: Flush with plenty of water. Get medical attention.

IF ON SKIN: Wash with plenty of water. Get medical attention.

IF INHALED: Remove victim to fresh air. Give artificial respiration if necessary. Get medical attention.



BLACK VINYL ANTIFOULING PAINT FORMULA 129 MILITARY SPECIFICATION

MILITARY TYPE 11, CLASS 2 PRO-LINE NO. 1069
Protects painted surfaces from marine fouling and slime.

ACTIVE INGREDIENTS	55.70%
INERT INGREDIENTS	44.30%
ENVIRONMENTAL COPPER	100.00%
WAS PETROLEUM DISTILLATES	55.8%

ACCEPTED WARRANTY. Pro-Line warrants that the contents of this product conform to the product's description on this label with COMMENTS in EPA Letter Dated JUN 19 1992.

JUN 19 1992

Under the Pesticide and Fungicide, and is excluded, for purposes of the Act, as defined under EPA 40238-8

THERE ARE NO WARRANTIES WHICH EXTEND BEYOND THE DESCRIPTION ON THE FACE HEREOF. PRO-LINE WILL NOT BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES OF ANY NATURE WHATSOEVER WITHOUT LIMITATIONS OF LOSS OR USE.

STORAGE AND DISPOSAL: This product may not carry the implied warranties of the manufacturer.

PROHIBITIONS: Do not contaminate potable water or discharge. Open dumping is prohibited.

PESTICIDE DISPOSAL: Pesticide spray may be disposed of in any approved secondary disposal site. Follow procedures approved by federal, state or local authorities.

CONTAINER DISPOSAL: Dispose in approved manner.

NET CONTENTS: LBS. Gal.

BEST AVAILABLE COPY

[REDACTED]
EPA ESTABLISHMENT NO. 40238CA
[REDACTED]
[REDACTED]

PRECAUTIONARY STATEMENTS

WARNING: (Hazards to Humans and Domestic Animals)

HAZARDS TO HUMANS: Causes eye irritation. Harmful if absorbed through skin. Avoid contact with skin, eyes or clothing. Wear protective clothing such as gloves, long-sleeved cotton shirt, long pants and hat. May be fatal if swallowed or inhaled. Do not breathe dust, vapor or spray mist.

Wash contaminated clothing before reuse. Never give anything by mouth to an unconscious person. Call a physician immediately. Avoid storage and usage near food and feed products. When used in confined areas or while spraying and/or sanding boat surface, wear a mask or a respirator jointly approved by the Mining Enforcement and Safety Administration and the National Institute for Occupational Safety and Health, under the provisions of 30 CFR 11.

ENVIRONMENTAL HAZARDS:

This material is toxic to fish. Do not contaminate waters by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter waters. Dispose wastes debris in an approved landfill.

Physical or Chemical Hazards

FLAMMABLE. FLASH POINT APPROXIMATELY 80° F.

Keep away from heat and open flame.

Pesticide container or rinse solution that cannot be used according to label instructions must be disposed of according to Federal or approved State procedures under Subtitle C of the Resource Conservation and Recovery Act.

[REDACTED]

AVAILABLE

FOLLOW PRO-LINE PAINT BOTTOM COATING GUIDE DIRECTIONS FOR USE OF PRO-LINE PAINT

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.
This label must be in the possession of the user at the time of pesticide application.
THE SURFACE MUST BE FREE OF ALL SURFACE CONTAMINATION AND MOISTURE.

BLACK VINYL ANTIFOULING PAINT FORMULA 129 - PRO-LINE #1069

APPLICATION: May be brushed, rolled or sprayed. **Stir well before using.**

ALUMINUM: These products ARE NOT FOR USE ON ALUMINUM.

STEEL: Bare steel should be sandblasted to a # 10 MARINE BLAST to remove all rust and mil scale. After sandblasting, apply 4 coats of EPOXY PRIMER #4000 series, giving a total dry mil thickness of at least 12 MILS. *See note prior to applying antifouling paints!*

FIBERGLASS HULL — UNPAINTED: Scrub hull with a solution of warm water and TSP. Rinse with fresh water, sand hull lightly with 80-grit Garnet Paper. Remove dust with clean rag. Apply a uniform coat of #4000 Primer. *See note prior to applying antifouling paints!*

WOOD: Over bare wood, apply first coat of ANTIFOULING thinned with PRO-LINE #20 (one quart per gallon of antifouling). Apply second coat unthinned.

OLD ANTIFOULING: May be applied over most aged soft-sloughing type antifouling paints when surface is tight, clean and dry. Do not apply over vinyl antifouling paints.

FERRO-CEMENT: Not recommended

RECOAT TIME: 2 hour minimum — no maximum between antifouling paints.

LAUNCH TIME: 4 hours after last coat of antifouling paint.

THINNING: If necessary use either #4 or #20 thinner.

NOTE: When antifouling is applied over Epoxy Primers, the antifouling must be applied within 3-5 hours after last coat of Epoxy Primer.

This product is effective in preventing marine growth, such as barnacles, bugulas, etc. Can be used in sweet and salt waters.

NON-PHOTOCHEMICALLY REACTIVE PRO-LINE PAINT MANUFACTURING CO.

2646 MAIN STREET, SAN DIEGO, CALIFORNIA 92113-3697 • (619) 232-8968
1168 HARBOR, LONG BEACH, CALIFORNIA • (213) 432-7961

WARNING: DETECTABLE AMOUNTS OF CHEMICALS OR SUBSTANCES KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER, BIRTH DEFECTS, OR OTHER REPRODUCTIVE HARM MAY BE FOUND IN CHEMICAL PRODUCTS PETROLEUM PRODUCTS AND THEIR VAPORS. FOLLOW APPLICABLE DIRECTIONS AND USE CARE WHEN HANDLING CHEMICAL AND PETROLEUM PRODUCTS. (CALIFORNIA HEALTH AND SAFETY CODE SECTION 25249.6)