

U.S. ENVIRONMENTAL PROTECTION AGENCY OFFICE OF PESTICIDES PROGRAMS REGISTRATION DIVISION (TS-767) WASHINGTON, DC 20460  <b>NOTICE OF PESTICIDE:</b> <input checked="" type="checkbox"/> REGISTRATION <input type="checkbox"/> REREISTRATION <i>(Under the Federal Insecticide, Fungicide,          and Rodenticide Act, as amended)</i>	EPA REGISTRATION NO. 40238-11  TERM OF ISSUANCE  NAME OF PESTICIDE PRODUCT Vinyl Waterbase Anticorrosive Primer	DATE OF ISSUANCE <b>JAN 02 1987</b>
NAME AND ADDRESS OF REGISTRANT (Include ZIP code)  <div style="border: 1px solid black; height: 100px; width: 100%;"></div>		
<b>NOTE:</b> Changes in labeling formula differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Registration Division prior to use of the label in commerce. In any correspondence on this product always refer to the above U.S. EPA registration number.		
On the basis of information furnished by the registrant, the above named pesticide is hereby Registered/Reregistered under the Federal Insecticide, Fungicide, and Rodenticide Act.		
A copy of the labeling accepted in connection with this Registration/Reregistration is returned herewith.		
Registration is in no way to be construed as an indorsement or approval of this product by this Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.		
<div style="border: 1px solid black; height: 400px; width: 100%;"></div>		
<div style="display: flex; justify-content: space-between;"> <span><input checked="" type="checkbox"/> ATTACHMENT IS APPLICABLE</span> </div> <div style="display: flex; justify-content: space-between;"> <span>SIGNATURE OF APPROVING OFFICIAL</span> <span>DATE</span> </div>		

2

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA section 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

A stamped copy of the label is enclosed for your records.

John H. Lee  
Product Manager (31)  
Disinfectants Branch  
Registration Division (TS-767C)

Enclosures

EPA ESTABLISHMENT NO. 40238CA01

PRO-

KEEP OUT OF REACH OF

WARNING

SEE SIDE PANEL FOR ADDITIONAL PRE

Technical C

**PRECAUTIONARY STATEMENTS**

**WARNING:** (Hazards to Humans and Domestic Animals)  
**HAZARDS TO HUMANS:** Causes eye irritation. Harmful if absorbed through skin. Avoid contact with skin, eyes or clothing. Wear protective clothing such as gloves, long-sleeved cotton shirt, long pants and hat. May be fatal if swallowed or inhaled. Do not breathe dust, vapor or spray mist. Wash contaminated clothing before reuse. Never give anything by mouth to an unconscious person. Call a physician immediately. Avoid storage and usage near food and feed products. When used in confined areas or while spraying and/or sanding boat surface, wear a mask or a respirator jointly approved by the Mining Enforcement and Safety Administration and the National Institute for Occupational Safety and Health, under the provisions of 30 CFR 11.

**ENVIRONMENTAL HAZARDS:**

This material is toxic to fish. Do not contaminate waters by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter waters. Dispose wastes debris in an approved landfill.

**Physical or Chemical Hazards**

**NON-FLAMMABLE**

Pesticide, container or rinse solution that cannot be used according to label instructions must be disposed of according to Federal or approved State procedures under Subtitle C of the Resource Conservation and Recovery Act.

ACCEPTED

JAN 02 1987



Accepted for the  
Registration under EPA Reg. No.

40238-17

888

**VINYL WATER BASE ANTI**

For protecting underwater hull surfaces from

**ACTIVE INGREDIENT**

CUPROUS OXIDE

**INERT INGREDIENTS**

**TOTAL**



**FOLLOW ALL SAFETY AND HEALTH REGULATIONS: PRACTICAL TREATMENT**

**IF SWALLOWED:** Drink promptly a large quantity of milk, egg whites, gelatin solution or if these are not available, drink large quantities of water. Avoid alcohol. Get medical attention.

**IF IN EYES:** Flush with plenty of water. Get medical attention.

**IF ON SKIN:** Wash with plenty of soap and water. Get medical attention.

**IF INHALED:** Remove victim to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. Get medical attention.

**WARRANTY:** Pro-Line warrants that the contents of this container conform to the product's description on this label.

**THERE ARE NO WARRANTIES WHICH EXTEND BEYOND THE DESCRIPTION ON THE FACE HEREOF. IN NO EVENT SHALL PRO-LINE BE LIABLE FOR ANY INCIDENTAL SPECIAL OR CONSEQUENTIAL DAMAGES OF ANY NATURE WHATSOEVER INCLUDING WITHOUT LIMITATIONS LOSS OR USE OF LOST PROFITS.**

This product may not carry the implied warranties of the uniform commercial code.

**STORAGE AND DISPOSAL**

- 1 PROHIBITIONS:** Do not contaminate potable water, food or feed by storage or disposal. Open dumping is prohibited.
- 2 PESTICIDE DISPOSAL:** Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.
- 3 CONTAINER DISPOSAL:** Dispose in approved landfill.

This labeling must be in the possession of the user at the time of pesticide application.  
**THE SURFACE MUST BE FREE OF ALL SURFACE CONTAMINATION AND MOISTURE.**

## VINYL WATER BASE ANTIFOULING PAINT

### PRO-LINE 888

**APPLICATION:** Pro-Line 888 may be brushed, rolled or sprayed. Stir well before using.

**ALUMINUM:** These products ARE NOT FOR USE ON ALUMINUM!

**STEEL:** Bare steel should be sandblasted to a #10 MARINE BLAST to remove all rust and mil scale. After sandblasting, apply 4 coats of EPOXY PRIMER #4000 series, giving a total dry mil thickness of at least 12 MILS. See note prior to applying antifouling paints!

**FIBERGLASS HULL — UNPAINTED:** Wipe hull with Pro-Line #25 Fiberglass Hull Cleaner, sand hull lightly with 80-grit Garnet Paper. Remove dust with clean rag. Apply a uniform light coat of #4000 Primer. See note prior to applying antifouling paints!

**WOOD:** Over bare wood, apply first coat of Pro-Line 888 ANTIFOULING thinned with fresh water (one quart per gallon of antifouling). Apply second coat unthinned.

**OLD ANTIFOULING:** Pro-Line 888 may be applied over most aged antifouling paints when surface is light, clean and dry.

**FERRO-CEMENT:** Not recommended.

**RECOAT TIME:** 2 hour minimum — no maximum between antifouling paints.

**LAUNCH TIME:** 4 hours after last coat of antifouling paint.

**THINNING:** If necessary, use fresh water only.

**NOTE:** When Pro-Line 888 antifouling is applied over Epoxy Primers, the antifouling must be applied within 3-5 hours after last coat of Epoxy Primer.

This product is effective in preventing marine growth, such as barnacles, bugulas, etc.

Can be used in fresh or salt waters.

## NON-PHOTOCHEMICALLY REACTIVE PRO-LINE PAINT MANUFACTURING CO.

2646 MAIN STREET, SAN DIEGO, CALIF. 92113-3697

PHONE (619) 232-8968

LONG BEACH (213) 432-7961