EPA ESTABLISHMENT NO. 40238CA01

KEEP OUT OF REACH OF CHILDREN.

WARNING

SI E SIDE PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS

YACHT FINISHES







CACCEPTED

ENVIRONMENTAL HAZARDS:

PRECAUTIONARY STATEMENTS

WARNING: (Hazards to Humans and Domestic Animals)

HAZARDS TO HUMANS: Causes eye irritation. Harmful.

if absorbed through skin. Avoid contact with skin, eyes or

clothing. Wear protective clothing such as gloves, 'ong-

sleeved cotton shirt, long pants and hat. May be fatal if

swallowed or inhaled. Do not breathe dust, vapor or spray

mist. Wash contaminated clothing before reuse. Never

give anything by mouth to an unconscious person. Call a

This material is toxic to fish. Do not contaminate waters by cleaning of equipment or disposal of wastes. Do n it allow chips and dust generated during paint removal to enter waters. Dispose wastes debris in an approved landfill.

physician immed stely. Avoid storage and usage near food and feed products. When used in confined areas or while spraying and/or sanding boat surface.

Physical or Chemical Hazards

NON-FLAMMABLE

(crafts) marine vessels.

1-17 Pesticide, container or rinse solution that cannot be used according to label instructions must be disposed of according to Federal or approved State procedures under Subtitle C of the Resource Conservation and Recovery Act.

888 WATER BASE ANTIFOULING PAINT

For protecting underwater hull surfaces from marine fouling and slime.

ACTIVE INGREDIENT	
CUPRUS OXIDE	63.60%
INERT INGREDIENTS	36.40%
TOTAL10	00.00%
"REE ELEMENTAL COPPER	.64%

"CONTAINS METHANOL"

FOLLOW ALL SAFETY AND HEALTH REGULATIONS: PRACTICAL TREATMENT IF SWALLOWED: Drink promptly a large quantity of

6,77 - 1 --

EPA REGISTRATION NO. 40238-11

milk, egg whites, gelatin solution or if these are not available, drink large quantities of water. Avoid alcohol, Get medical attention.

IF IN EYES: Flush with plenty of water. Get medical attention.

IF ON SKIN: Wash with plenty of soap and water. Get medical attention.

IF INHALED: Remove victim to fresh air. If not breathing, give artificial respiration, preferably mouth-tomouth. Get medical attention.

WARRANTY: Pro-Line warrants that the contents of this container conform to the product's description on this label.

THERE ARE NO WARRANTIES WHICH EXTEND BEYOND THE DESCRIPTION ON THE FACE HEREOF. IN NO EVENT SHALL PRO-LINE BE LIABLE FOR ANY INCIDENTAL SPECIAL OR CONSEQUENTIAL DAMAGES OF ANY NATURE WHATSOEVER INCLUDING WITHOUT LIMITATIONS LOSS OR USE OF LOST PROFITS.

This product may not carry the implied warranties of the uniform commer-In DPA Letter Hated cial code.

STORAGE AND DISPOSAL

1. PROHIBITIONS: Do not contaminate water, food or feed by storage or disposal. Open dumping is prohibited.


Under the Federal in Secretary of excess pesticide, spray mixture, or rinsate is a violation of Federal Funcicide, and indental Adw. If these wastes cannot be disposed of by use according to label as amended, for the postelestructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.


3 CONTAINER DISPOSAL: Dispose in approved landfill.

NET CONTENTS:

LBS. Gal.







DIRECTIONS FOR USE OF PRO-LINE #888 SERIES

It is a violation of Federal law to use this product in a manner inconsistent with its labeling. This labeling must be in the possession of the user at the time of pesticide application.

THE SURFACE MUST BE FREE OF ALL SURFACE CONTAMINATION AND MOISTURE.

WATER BASE ANTIFOULING PAINT PRO-LINE 888

APPLICATION: Pro-Line 888 may be brushed, rolled or sprayed. Stir well before using.

ALUMINUM: These products ARE NOT FOR USE ON ALUMINUM.

STEEL: Bare steel should be sandblasted to a #10 MARINE BLAST to remove all rust and mil scale.

After sandblasting, apply 4 coats of EPOXY PRIMER #4000 series, giving a total dry mil thickness of at least 12 MILS. See note prior to applying antifouling paints!

FIBERGLASS HULL — UNPAINTED: Wipe hull with Pro-Line #25 Fiberglass Hull Cleaner, sand hull lightly with 80-grit Garnet Paper. Remove dust with clean rag. Apply a uniform light coat of #4000 Primer. See note prior to applying antifouling paints!

WOOD: Over bare wood, apply first coat of Pro-Line 888 ANTIFOULING thinned with fresh water (one quart per gallon of antifouling). Apply second coat unthinned.

OLD ANTIFOULING: Pro-Line 888 may be applied over most aged antifouling paints when surface is tight, clean and dry.

FERRO-CEMENT: Not recommended.

RECOAT TIME: 2 hour minimum — no maximum between antifouling paints.

LAUNCH TIME: 4 hours after last coat of antifouling paint.

THINNING: If necessary, use distilled water only, or Pro-Line #66 Thinner.

NOTE: When Pro-Line 888 antifouting is applied over Epoxy Primers, the antifouting must be applied within 3-5 hours after last coat of Epoxy Primer.

This product is effective in preventing marine growth, such as barnacles, bugulas, etc.

Can be used in fresh or salt waters.

NON-PHOTOCHEMICALLY REACTIVE

PRO-LINE PAINT MANUFACTURING CO.

2646 MAIN STREET, SAN DIEGO, CALIFORNIA 92113-3697

PHONE (619) 232-8968

LONG BEACH (213) 432-7961

