



PENTA 5

For Use In the Preservation of Wood Structures

ONLY FOR INDUSTRIAL/AGRICULTURAL USE

| | |
|-------------------------------------|---------------|
| ACTIVE INGREDIENTS: | |
| Pentachlorophenol | 4.4% |
| Other Chlorophenols | .6% |
| Mineral Spirits | 90.0% |
| INERT INGREDIENTS: | 5.0% |
| Total | 100.0% |

KEEP OUT OF REACH OF CHILDREN

WARNING

See Side Panels for Additional Warnings

ACCEPTED

SEP 7 1982

Under the Federal Insecticide, Fungicide, and Rodenticide Act, as amended, for this product to register under EPA Reg. No. 40831-38

EPA Reg. No. 40831-38

EPA Est. No. 40831-MT-01

BEST DOCUMENT AVAILABLE

NET CONTENTS: 1 5 30 55 GALLONS

FALLS CHEMICALS INC., GREAT FALLS, MONTANA 59403

PRECAUTIONARY STATEMENTS

HAZARD TO HUMANS AND DOMESTIC ANIMALS: "WARNING"
Harmful if swallowed or absorbed through the skin. Causes skin irritation. Do not breathe vapor, fumes or spray mist. Do not get into eyes, on skin or on clothing. Wear protective clothing and rubber gloves when handling freshly treated lumber. Wash thoroughly. Keep away from children or pets and livestock.

ENVIRONMENTAL HAZARD: This product is toxic to fish and wildlife. Do not apply directly to water. Do not apply when weather conditions favor drift of spray from areas treated. Apply this product only as specified on this label.

PHYSICAL OR CHEMICAL HAZARD: Do not use or store near fire or flame. Keep container closed when not in use.

STATEMENT OF PRACTICAL TREATMENT

If swallowed: Call a physician or Poison Control Center immediately. If possible, vomiting should be induced under medical supervision. Drink one or two glasses of water and induce vomiting by touching the back of throat with finger. Do not induce vomiting or give anything by mouth to an unconscious person.

If Inhaled: Remove victim to fresh air. Apply artificial respiration if indicated.

If On Skin: Remove contaminated clothing and wash affected areas with soap and water.

If In Eyes: Flush eyes with plenty of water. Call a physician immediately.

STORAGE AND DISPOSAL

**Do not reuse empty container. Wrap container and
put in trash collection.**

0
5
3

DIRECTIONS FOR USE


It is a violation of federal law to use this product in a manner inconsistent with its labeling

Penta 5 is an outstanding wood preserver, termite killer and repellent. It will penetrate the wood both deeply and thoroughly. Especially refined and blended for low viscosity, Penta 5 is easy to handle and ready to use by the Brush, Spray or Dip method. It is equally effective for above or below ground use.

Brush or Spray Method-Apply two coats, either hot or cold. Brush or spray all ends and joints of wood for at least 3 to 4 feet. Allow several hours for Penta 5 to penetrate the wood between applications.

Dipping Method-Use either hot or cold. Fence posts and heavy timbers should be dipped for best results. Posts should be free of bark, dry and well seasoned. Dip for 12 to 48 hours.

BUILDINGS-Remove all loose wood from under and around buildings. Timbers to be placed in touch with foundation should be brushed or sprayed heavily with Penta 5. Wood intended for use in contact with the soil should be brushed or sprayed with at least two coats or dipped not less than 12 to 48 hours.



FOUNDATIONS - SUBTERRANEAN TERMITES - DIRECTIONS FOR INDUSTRIAL/
AGRICULTURAL USE.

TERMITE CONTROL IN EXISTING STRUCTURES
Buildings with Basements or Crawl-Spaces

First remove all wood debris and wood forms. Around piers, pipes, chimney bases and along foundations of poured concrete dig a trench 6 inches wide and 4 inches deep. For brick and block foundations dig the trench about 12 inches deep. If footing is more than 12 inches deep, make holes with a crowbar, pipe or a rod about one foot apart that extend from the trench bottom to the top of the footing. Make holes closer in hard-packed clay soils. NEVER DIG BELOW THE TOP OF THE FOOTING. Apply the emulsion (or solution) in the trench at a rate of 4 gallons per 10 linear feet per foot of depth. Apply half of this to the back-fill. Likewise, treat along the inside of foundations of crawl-space buildings. Cover treated soil with a thin layer of untreated soil.

For raised porches, terraces, and entrance slabs, drill holes at one foot intervals, 6 inches from the foundation, and pour one-half gallon of emulsion (or solution) into each hole. Refill holes. Slabs with heat ducts or radiating heat pipes should be treated by commercial pest control operator.

The object is to establish a treated soil barrier which will prevent termite entry. Other critical areas may also require treatment, particularly if there are inaccessible areas, basements or slab-type construction. It is suggested that you contact the Agricultural Cooperative Extension Service for advice or consult a Commercial Pest Control Service.

Avoid contamination of public and private water supplies by following these precautions. Do not allow a hose or any type of faucet extension to reach into the termite chemical solution while filling or mixing this material with water. Use anti-back-flow or anti-siphonage equipment on all filling equipment. These devices can be purchased at hardware or plumbing supply stores. Use of anti-back-flow equipment will help to insure that the user of this toxic chemical will not contaminate domestic water supplies. Refer to Federal (Federal Housing Administration), state, and local specifications for safe distances of treatment areas from wells. Soil in the vicinity of wells, cisterns or ponds should not be treated if it is water saturated, subject to excessive saturation due to an accumulation of water or if the soil to be treated around the perimeter of the structure is at a grade lower than surrounding yard or property area. If this is the situation treat as follows: Do Not Apply Under Pressure. Soil should be removed

to an area safe from well or domestic water contamination, treated, allowed to stand undisturbed for two to four hours then returned to the trench which has been lined with 4 mil. plastic sheeting. Be careful not to puncture the plastic sheeting when returning soil to the trench. Do not treat structures that contain cisterns or wells.

WARRANTY STATEMENT

This product shall conform with quantities and formulas indicated hereon, within accepted tolerances as permitted by appropriate governmental authorities, and is reasonably fit for the purpose stated on the label when used in accordance with directions under normal conditions of use. No warranty extends to the use of this product contrary to label instructions, or under abnormal conditions, or under conditions not reasonably foreseeable by Falls Chemicals Inc. In no case shall Falls Chemicals Inc. be liable for consequential, special or indirect damages resulting from use or handling of this product. All such risks shall be assumed by buyer. FALLS CHEMICALS INC. MAKES NO WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY OTHER EXPRESSED OR IMPLIED WARRANTIES EXCEPT AS STATED ABOVE.