

" UNDER NO.

## **DIRECTIONS FOR USE** GENERAL CLASSIFICATION

O BOX 487 - BIRMINGHAM, ALABAMA 35201 - TELEPHONE (205) 251 8503 4095

CSCO-CIDE 205

TIVE INGREDIENT oly (oxyethylene (dimethyliminio) ethyleneimethyliminio) ethylene dichloride] ..... JERT INGREDIENT ..... 95.0%

his product contains 0.42 lb. of active ingredient per gallon and eighs 8.39 lb per gallon.

## KEEP OUT OF REACH OF CHILDREN CAUTION

## PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

CAUTION Harmful if swallowed. Avoid breathing vapors. Avoid ontact with skin, eyes, or clothing.

"IRST AID: If swallowed, drink promptly a large quantity of milk, gg whites, gelatin solution, or, if these are not available, drink large quantities of water. Avoid alcohol. Call a physician immediately. ENVIRONMENTAL HAZARDS: This pesticide is toxic to fish. Keep

out of lakes, streams, or ponds. Permits may be required for discharges containing this pesticide into lakes, streams, ponds or public water. For guidance, contact the regional office of the Environmental Protection Agency.

It is a violation of Federal law to use this product in a manner /inconsistent with its labeling.

NORTH THE PREMAL INSECTIONS
LINGUISTE AND REDESTICIDE ACT.
FOR ECONOMIC PORON REQUIRED SCO-CIDE 205 is used to control algae, bacteria, and fungi in recirculating commercial and industrial water cooling towers. Prior to its use, systems must be cleaned to remove alga! growth, microbiological slime, and other deposits

> An initial slug addition of 13.5 to 36.3 fluid ounces of CSCO-CIDE 205 per 1000 gallons of water to provide a concentration of 96 to 240 parts per million of CSCO-CIDE 205, based on the total weight of water in the system, is recommended. Repeat initial dosage until control is evident.

> Subsequent slug additions of 3.6 to 36.3 fluid ounces of CSCO-CIDE 205 per 1000 gallons of water (24 to 240 parts per million of CSCO-CIDE 205) should be employed every 2 to 5 days or as needed. The frequency of addition depends upon the relative amount of bleedoff and the severity of the microbiological problem. Slug additions should be made in the sump of water cooling towers.

STORAGE & DISPOSAL: Keep container closed when not in use. Do not contaminate water, food, or feed by storage, disposal, or cleaning of equipment. The container must be triple rinsed (or equivalent) and offered for recycling, reconditioning, or disposal in an approved landfill or buried in a safe place. Rinsate that cannot be used or reprocessed should be disposed of in a landfill approved for pesticides or buried in a safe place away from water supplies. Open dumping is prohibited.

> Manufactured by: Chemical Solvent Company P. O. Box 487 Birmingham, AL 35201

**EPA REG NO 40959-1 NET CONTENTS** 

EPA EST. NO. . ...