

BYASYDE 610

ACCEPTED

JUL 1978

UNDER THE FEDERAL INHERITANCE
PUNISHMENT AND REFORMATION
ACT FOR ECONOMIC PUNISHMENT
ED UNDER NO.

ACTIVE INGREDIENT

Poly[oxyethylene (dimethyliminio) ethylene-
(dimethyliminio) ethylene dichloride] 10%

INERT INGREDIENT

90.0%

This product contains 0.85 lb. of active ingredient per gallon
and weighs 8.49 lb. per gallon.

KEEP OUT OF REACH OF CHILDREN

CAUTION

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

CAUTION: Harmful if swallowed. Avoid breathing vapors.
Avoid contact with skin, eyes, or clothing.

FIRST AID: If swallowed, drink promptly a large quantity of
milk, egg whites, gelatin solution, or, if these are not
available, drink large quantities of water. Avoid alcohol. Call
a physician immediately.

ENVIRONMENTAL HAZARDS: This pesticide is toxic to fish.
Keep out of lakes, streams, or ponds. Permits may be
required for discharges containing this pesticide into lakes,
streams, ponds or public water. For guidance, contact the
regional office of the Environmental Protection Agency.

DIRECTIONS FOR USE GENERAL CLASSIFICATION

It is a violation of Federal law to use this product in a
manner inconsistent with its labeling.

BYASYDE 610 is used to control algae, bacteria, and fungi
in recirculating commercial and industrial water cooling
towers. Prior to its use, systems must be cleaned to remove
algal growth, microbiological slime, and other deposits.

An initial slug addition of 6.13 to 15.32 fluid ounces of
BYASYDE 610 per 1000 gallons of water to provide a concentra-
tion of 48 to 120 parts per million of **BYASYDE 610**, based
on the total weight of water in the system, is recommended.
Repeat initial dosage until control is evident.

Subsequent slug additions of 1.53 to 15.32 fluid ounces of
BYASYDE 610 per 1000 gallons of water (12 to 120 parts per
million of **BYASYDE 610**) should be employed every 2 to 7
days or as needed. The frequency of addition depends upon
the relative amount of bleedoff and the severity of the
microbiological problem. Slug additions should be made to
the sump of water cooling towers.

STORAGE & DISPOSAL: Keep container closed when not in
use. Do not contaminate water, food, or feed by storage,
disposal, or cleaning of equipment. The container must be
triple rinsed (or equivalent) and offered for recycling, re-
conditioning, or disposal in an approved landfill or buried in a
safe place. Rinseate that cannot be used or reconditioned
should be disposed of in a landfill approved for pesticides,
buried in a safe place away from water supplies. Open flame
burning is prohibited.

Manufactured by:

Charles F. Keith Associates
1761-C McCoba Drive
Smyrna, GA 30080

EPA REG. NO. 41716-1 EPA EST. NO.
NET CONTENTS: 30 GALLONS