

US ENVIRONMENTAL PROTECTION AGENCY OFFICE OF PESTICIDES PROGRAMS REGISTRATION DIVISION (TS-767) WASHINGTON, DC 20460	EPA REGISTRATION NO.	DATE OF ISSUANCE
	41875-1	MAR 30 1987
	TERM OF ISSUANCE	
NOTICE OF PESTICIDE: <input type="checkbox"/> REGISTRATION <input type="checkbox"/> REREGISTRATION <i>(Under the Federal Insecticide, Fungicide, and Rodenticide Act, as amended)</i>	NAME OF PESTICIDE PRODUCT	
	Super Tropical Antifouling P-18	

NAME AND ADDRESS OF REGISTRANT (Include ZIP code)

All Purpose Marine Paints, Inc.
 58 Van Dyke Street
 Brooklyn, NY 11231

NOTE: Changes in labeling formula differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Registration Division prior to use of the label in commerce. In any correspondence on this product always refer to the above U.S. EPA registration number.

On the basis of information furnished by the registrant the above named pesticide is hereby Registered/Reregistered under the Federal Insecticide, Fungicide, and Rodenticide Act.

A copy of the labeling accepted in connection with this Registration/Reregistration is returned herewith.

Registration is in no way to be construed as an indorsement or approval of this product by this Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.

This product is conditionally registered in accordance with FIFRA section 3(c)(7)(A) provided that you:

1. Submit/cite all data required for registration/reregistration or your product under FIFRA section 3(c)(5) when the Agency requires all registrants of similar products to submit such data.
2. Make the labeling changes listed below before you release the product for shipment:
 - a. Add the words "EPA Registration No. 41875-1."
 - b. In the "Directions" section, insert the words "Always wear a mask or respirator . . ."
 - c. In the "Right Panel," replace the word "Caution" with the word "Note" in the sentence "Caution: P-18 Super Tropical Antifouling . . . sprayed."
 - d. Add the sentence "Do not contaminate water, food, or feed by storage or disposal" as the second sentence of the "Storage Instructions."

ATTACHMENT IS APPLICABLE

BEST AVAILABLE COPY

SIGNATURE OF APPROVING OFFICIAL	DATE
---------------------------------	------

- e. Delete from the "disposal instructions" the following instructions:

Wastes resulting from the use of the product may be disposed of on site or at an approved waste disposal facility.

- f. Delete the sentence "Dispose of container in a sanitary landfill, or by other procedures approved by State and local authorities" and replace with the statement below.

Container Disposal


Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by State and local authorities.

- g. Return the statement "For Commercial Use Only" to the label (as it appeared on the label initially submitted March 15, 1985).

3. Submit five (5) copies of your final printed labeling before you release the product for shipment. Refer to the A-79 Enclosure for a further description of final printed labeling.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA section 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

A stamped copy of the label is enclosed for your records.

John H. Lee 
Product Manager (31)
Disinfectants Branch
Registration Division (TS-767C)

Enclosures

BEST AVAILABLE COPY

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND
DOMESTIC ANIMALS

WARNING: Causes eye irritation. Harmful if absorbed through skin. Avoid contact with skin, eyes or clothing. Wear protective clothing such as gloves, long-sleeved cotton shirt, long pants and hat. May be fatal if swallowed or inhaled. Do not breathe vapor or spray mist. Wear a mask or respirator jointly approved by the Mining Enforcement and Safety Administration and the National Institute for Occupational Safety and Health. Remove contaminated clothing and wash before re-use. Wash thoroughly with soap and water after handling.

STATEMENT OF PRACTICAL TREATMENT

IF SWALLOWED: Drink promptly a large quantity of milk, egg whites, gelatin solution or, if these are not available, drink large quantities of water. Avoid alcohol. Get medical attention.

IF IN EYES: Flush with plenty of soap and water. Get medical attention.

IF ON SKIN: Wash with plenty of soap and water. Get medical attention.

IF INHALED: Remove victim to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. Get medical attention.

ENVIRONMENTAL HAZARD

This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill.

PHYSICAL OR CHEMICAL HAZARD

Keep away from heat or open flame.

BEST AVAILABLE COPY

all
MARI

ACCEPTED
with COMMENTS
In EPA Letter Dated:

MAR 30 1987

Under the Federal Insecticide,
Fungicide, and Rodenticide Act
as amended, for the products
registered under EPA Reg. No.

41875-1

KEEP

high speed powerboats as well as slow speed boats with excellent results.
DIRECTIONS FOR USE: It is a violation of Federal Law to use this paint in a manor inconsistent with its labeling.

SURFACE PREPARATION AND COMPATIBILITY: Surface preparation directions must be followed exactly in order to insure adhesion. Surface must always be clean and dry prior to painting. Copolymer, soft vinyl and hard epoxy antifoulings are the suitable paints for overcoating with P18 Super Tropical Antifouling. It is important that these paints be in excellent condition to allow overcoating.

GENERAL APPLICATION PROCEDURES: Apply at least 2 full coats of P18 Super Tropical Antifouling by brush, spray or (solvent resistant) 3/8" nap roller. Do not apply thin coats. Keep in mind that the life of the paint is directly related to the number of coats applied. If during application, thinning is required, use 100 All Purpose Thinner to improve handling.

MIXING AND THINNING INSTRUCTIONS: Shake and mix well. Stir continuously while using. Thin only when necessary with 100 All Purpose Thinner (not to exceed 10% by volume).

MINIMUM DRY AND LAUNCHING TIMES: Minimum drying time between coats and before launching must be 16 hours. Maximum drying time before recoating or launching is two weeks.

THEORETICAL COVERAGE: 400 square feet per gallon, per coat.

CLEAN-UP: For tools, equipment, etc., use 100 All Purpose Thinner.

PREVIOUSLY PAINTED SURFACES: Copolymer, soft vinyl and hard epoxy antifoulings are suitable paints for overcoating with P18 Super Tropical Antifouling. It is important that these paints be in excellent condition to allow overcoating. Excessive amounts of old paint should be removed.

BARE WOOD: Sand well with 80-120 grit production paper; wipe surface clean. Apply first coat of P18 Super Tropical Antifouling after it has been thinned (10%) with 100 All Purpose Thinner. Apply second and third coat (do not thin unless necessary) after a 16 hour dry between coats.

ALUMINUM & STEEL: Sand blast to S.P.C. 4 near white metal, then apply 3 or 4 coats of Coal Tar Epoxy Primer C-200. A minimum of 14 mils of primer is required. P18 Super Tropical Antifouling should be applied as soon as the last coat of Coal Tar Epoxy is tacky. Two coats of P18 Super Tropical Antifouling is required. Contact your All Purpose representative for alternate systems.

CAUTION: If P18 Super Tropical Antifouling is to be sprayed, it should only be applied by competent professional spray applicators utilizing the proper solvents and safety equipment.

THEORETICAL COVERAGE: 400 square feet per gallon, per coat.

CLEAN-UP: For tools, equipment, etc., use 100 All Purpose Thinner.

PREVIOUSLY PAINTED SURFACES: Copolymer, soft vinyl and hard epoxy antifouling are suitable paints for overcoating with P18 Super Tropical Antifouling. It is important that these paints be in excellent condition to allow overcoating. Excessive amounts of old paint should be removed.

BARE WOOD: Sand well with 80-120 grit production paper; wipe surface clean. Apply first coat of P18 Super Tropical Antifouling after it has been thinned (10%) with 100 All Purpose Thinner. Apply second and third coat (do not thin unless necessary) after a 16 hour dry between coats.

ALUMINUM & STEEL: Sand blast to S.P.C. 4 near white metal, then apply 3 or 4 coats of Coal Tar Epoxy Primer C-200. A minimum of 14 mils of primer is required. P18 Super Tropical Antifouling should be applied as soon as the last coat of Coal Tar Epoxy is tacky. Two coats of P18 Super Tropical Antifouling is required. Contact your All Purpose representative for alternate systems.

CAUTION: If P18 Super Tropical Antifouling is to be sprayed, it should only be applied by competent professional spray applicators utilizing the proper solvents and safety equipment.

STORAGE INSTRUCTIONS

Store indoors below 110°F in original container. Keep away from open flame.

DISPOSAL INSTRUCTIONS

Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture, or resins is a violation of Federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or The Hazardous Waste representative at the nearest EPA Regional Office for guidance.

Wastes resulting from the use of this product may be disposed of on site or at an approved waste disposal facility.

Dispose of container in a sanitary landfill, or by other procedures approved by state and local authorities.