

A-780 DRY CHLORINATING PRODUCT

ACTIVE INGREDIENT

[*mor,o*-(TRICHLORO) tetra-(MONOPOTASSIUM DICHLORO)]-PENTA-S-TRIAZINETRIONE.....100%

KEEP OUT OF REACH OF CHILDREN

DANGER

PRACTICAL TREATMENT: (FIRST AID): If swallowed feed bread soaked in milk followed by olive oil or cooking oil. Call a physician immediately.

If on skin: Brush off excess chemical and flush skin with cold water for at least 15 minutes. If irritation persists, get medical attention.

If in Eyes: Flush with cold water for at least 15 minutes. Get medical attention.

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER: Highly corrosive. Causes skin and eye damage. May be fatal if swallowed or not get in eyes, on skin or on clothing. Wear goggles or face shield and rubber gloves when handling. Irritating to nose and throat. Avoid breathing dust. Remove and wash contaminated clothing before reuse.

ENVIRONMENTAL HAZARDS: This product is toxic to fish. Do not discharge into lakes, streams, ponds, or public waters unless in accordance with an NPDES Permit. For guidance contact the regional office of EPA.

PHYSICAL AND CHEMICAL HAZARDS

STRONG OXIDIZING AGENT: Strong Oxidizing Agent. Mix only with water. Use clean dry utensils. Do not add this product to any dispensing device containing remnants of any other product. Such use may cause a violent reaction leading to fire or explosion. Contamination with moisture, organic matter, or other chemicals may start a chemical reaction, with generation of fire and explosion. In case of contamination or decomposition, do not reseal container. If possible, isolate container in open air or well ventilated area. Flood with large volumes of water, if necessary.

NET CONTENTS 50 LBS.

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

A-780 is used to control algae, bacteria, and fungi in recirculating commercial and industrial water, cooling towers. Prior to its use, systems must be cleaned to remove algae growth, microbiological slimes, and other deposits.

An initial slug addition of 8 to 16 ounces of A-780 per 1000 gallons of water to provide a concentration of 60 to 120 parts per million to A-780, based on the total weight of water in the system, is recommended. Repeat initial dosage until control is evident.

Subsequent slug additions of 4 to 12 ounces of A-780 per 1000 gallons of water (30 to 90 parts per million of A-780) should be employed every 2 to 5 days or as needed. The frequency of addition depends upon the relative amount of bleedoff and the severity of the microbiological problem. Slug additions should be made in the sump of water cooling towers.

STORAGE & DISPOSAL: Keep container closed when not in use. Do not contaminate water, food, or feed by storage, disposal, or cleaning of equipment. Store in dry place. Do not allow water to get into container. Keep containers off wet floors. Do not reuse empty container. Triple rinse (or equivalent) and dispose of container in an incinerator or in an approved landfill, or bury in a safe place. Open dumping is prohibited.

United Worth Hydrochem Corporation
P. O. Box 366
Fort Worth, Texas 76101

EPA REG. NO. 41879-3

EPA EST. NO. 41879-TX-1

UNDER THE FEDERAL INSURANCE
 WORKERS COMPENSATION ACT
 AND ROYALTY ACT
 FOR ECONOMIC RECOVERY
 ACT OF 1980
 RECEIVED
 MAY 2 1980

41879-3

ACCEPTED

27