



United States
Environmental Protection Agency
Washington, DC 20460

☐ Registration
☐ Amendment
☒ Other

OPP Identifier Number

218951

Application for Pesticide - Section I

1. Company/Product Number 42177-22	2. EPA Product Manager PM#	3. Proposed Classification <input type="checkbox"/> None <input type="checkbox"/> Restricted
4. Company/Product (Name) Olympic Universal Chlorinator Cartridge		
5. Name and Address of Applicant (Include ZIP Code) ALLIANCE PACKAGING, INC. 3309 E. Carpenter Frwy. Irving, Texas 75062 <input type="checkbox"/> Check if this is a new address	6. Expedited Review. In accordance with FIFRA Section 3(c)(3) (b)(i), my product is similar or identical in composition and labeling to: EPA Reg. No. _____ Product Name _____	

Section - II

<input type="checkbox"/> Amendment - Explain below.	<input type="checkbox"/> Final printed labels in response to Agency letter dated _____
<input type="checkbox"/> Resubmission in response to Agency letter dated _____	<input type="checkbox"/> "Me Too" Application.
<input checked="" type="checkbox"/> Notification - Explain below.	<input type="checkbox"/> Other - Explain below.

Explanation: Use additional page(s) if necessary. (For section I and Section II.)

Change the hole punch instructions in Directions for Use under E-Z Clor Feeders.

Section - III

1. Material This Product Will Be Packaged In:				2. Type of Container	
Child-Resistant Packaging <input type="checkbox"/> Yes <input type="checkbox"/> No	Unit Packaging <input type="checkbox"/> Yes <input type="checkbox"/> No	Water Soluble Packaging <input type="checkbox"/> Yes <input type="checkbox"/> No		<input type="checkbox"/> Metal	
* Certification must be submitted		If "Yes" Unit Packaging wgt.	No. per container	If "Yes" Package wgt	No. per container
				<input type="checkbox"/> Plastic	
				<input type="checkbox"/> Glass	
				<input type="checkbox"/> Paper	
				<input type="checkbox"/> Other (Specify) _____	
3. Location of Net Contents Information <input type="checkbox"/> Label <input type="checkbox"/> Container		4. Size(s) Retail Container		5. Location of Label Directions <input type="checkbox"/>	
6. Manner in Which Label is Affixed to Product <input type="checkbox"/> Lithograph <input type="checkbox"/> Paper glued <input type="checkbox"/> Stenciled				<input type="checkbox"/> Other _____	

Section - IV

1. Contact Point (Complete items directly below for identification of individual to be contacted, if necessary, to process this application.)		
Name Thomas R. Kincaid	Title General Manager	Telephone No. (Include Area Code) 214/438-6744
Certification I certify that the statements I have made on this form and all attachments thereto are true, accurate and complete. I acknowledge that any knowingly false or misleading statement may be punishable by fine or imprisonment or both under applicable law.		6. Date Application Received (Stamped)
2. Signature 	3. Title General Manager	
4. Typed Name Thomas R. Kincaid	5. Date October 25, 1995	



OLYMPIC UNIVERSAL CHLORINATOR CARTRIDGE

For use in erosion feeders

ACTIVE INGREDIENT: Trichloro-s-Triazinetrione.....97.0%

INERT INGREDIENT:.....3.0%

Available Chlorine 89%

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER: Corrosive. Causes irreversible eye damage and skin burns. May be fatal if absorbed through the skin. May be fatal if inhaled. Do not breathe dust or spray mists. Irritating to nose and throat. Harmful if swallowed. Do not get in eyes, on skin, or on clothing. Wear goggles or face shield, protective clothing and rubber gloves when handling this product. Wash thoroughly with soap and water after handling and before eating, drinking or using tobacco. Remove contaminated clothing and wash before reuse.

STATEMENT OF PRACTICAL TREATMENT: IF

SWALLOWED: drink promptly large quantities of water. Do not induce vomiting. Avoid alcohol. Never give anything by mouth to an unconscious person. Call a physician or poison control center immediately. **If in eyes:** Hold eyelids open and flush with a steady, gentle stream of water for 15 minutes. Get medical attention. **If on skin:** Wash with plenty of soap and water. Get medical attention. **If inhaled:** Remove victim to fresh air. If not breathing, give artificial respiration, preferably, mouth-to-mouth. Get medical attention. **Note to Physician:** Probable mucosal damage may contraindicate the use of gastric lavage.

CHEMICAL HAZARDS: Strong oxidizing agent. Do not use moist or damp utensils. Contamination with moisture, dirt, organic matter, or other chemicals or any foreign matter may start a chemical reaction with generation of heat, liberation of hazardous gases, and possible generation of fire.

ENVIRONMENTAL HAZARDS: This pesticide is toxic to fish and aquatic organisms. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

SPECIAL PRECAUTIONS

1. This product has a powerful chlorine odor. Hold away from face when opening to avoid breathing fumes.
2. Prolonged contact between this product in its undissolved state and vinyl liners or painted surfaces will result in bleaching of the vinyl or paint. Introduce this product through the skimmer or in a prescribed feeder to avoid discoloration of liner or paint.
3. When adding this product to skimmer or feeder make sure there are no other chemicals present as a violent reaction may occur. It is always dangerous to mix chemicals.
4. Use this product as directed as per instructions on label. Do not take advice from others or experiment by yourself.
5. If this product is used to shock or superchlorinate a pool, after treatment it is important to brush walls and floor to expose algae that may be in the cracks or wrinkles that might protect algae from high chlorine residual. Such protected algae will begin to reproduce again when high chlorine residual falls. **NOTE:** Re-entry into treated swimming pool is prohibited above levels of 3 ppm.

6. This product, because of its potent formulation, can be dangerous if not used properly. Do not mix with any other chemicals. This could result in a violent chemical reaction. Do not add water to this product in a closed container. Do not add this product to a small amount of water in a pail. When adding this product to skimmer make sure pump is on and water is circulating so that material is drawn into recirculation system. Do not allow buildup of dry material in skimmer as gases generated may cause an explosion.

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

FOR USE IN E-Z CLOR® FEEDERS:

1. Adjust pool water to 7.2 to 7.6 pH level as determined by a test kit.
2. If the pool has not been stabilized, add stabilizer (cyanuric acid) according to instructions on label.
3. Select the numerically coded dimple on the lower side of the cartridge according to the gallon capacity of your pool as determined by the chart below.
Approx. Gallons
(in Thousands) 5 10 15 20 30
Dimple Number 1 3 5 7 9
4. Punch out appropriate dimple selected from the chart above as well as all dimples below selected number on both sides of the cartridge.
5. Punch out all eight (8) clear dots on bottom of cap. Push punch through to hit and turn to get clean full size holes.
6. After the cartridge has been in use for 24 hours, check the chlorine residual level. Chlorine residual should be checked frequently and always maintained between 1.0 and 1.5 ppm.

If the residual is below 1.0 ppm, remove the cartridge and punch out next higher numbered dimple. Reinsert the cartridge.

If the chlorine residual is above 1.5 ppm, remove the cartridge and cover the highest numerically coded hole with black electrical tape.

Make additional adjustments as required to maintain desired 1.0 to 1.5 ppm free chlorine residual.

**KEEP OUT OF
REACH OF CHILDREN
DANGER**

See first aid precautions.

NET WEIGHT: 4 lbs. (1.81 kg.)

FOR USE IN GUARDEX OR ANTHONY FEEDERS:

1. Adjust pool water to 7.2 to 7.6 pH level as determined by a test kit.
2. If the pool has not been stabilized, add stabilizer (cyanuric acid) according to instructions on the stabilizer label.
3. Cut a 1/4" diameter hole in the dimple indicated by the letter "X" on the side of the cartridge where the wide and narrow portions of the cartridge converge. Also cut away completely the three vertical elongated tabs on the lower sides of the cartridge.
4. To make the initial height setting of the cartridge in the feeder, select the number on the graduated scale on the side of the cartridge according to the gallon capacity of your pool as determined by the chart below:

Approx. Gallons (in thousands)	10	15	20	25	30	35
Number	1	2	3	4	5	6

5. Insert the cartridge into the feeder until the top of the feeder lip is aligned with the number on the graduated scale selected from the chart above. Then rotate the cartridge clockwise in the feeder until it stops—about a quarter of a revolution.
6. After the cartridge has been in use for 24 hours, check the chlorine residual level. Chlorine residual should be checked frequently and always maintained between 1.0 to 1.5 ppm.
If the residual level is below 1.0 ppm, readjust the height setting to the next higher number on the graduated scale (e.g. 1 to 2). The cartridge will now be positioned deeper in the feeder.
If the residual level is above 1.5 ppm, readjust the height setting to the next lower number on the graduated scale (e.g. 6 to 5). The cartridge will now be positioned higher in the feeder.


NOTE: The pH of the slow dissolving tablet is on the acid side and will tend to reduce the pH and alkalinity of the pool water. Proper pH should be maintained between 7.2 to 7.6 as determined by a test kit and by periodic additions of sodium carbonate or sodium bicarbonate.

STORAGE AND DISPOSAL

Keep product dry in a tightly closed container when not in use. Store in a publicly well-ventilated area away from heat or open flame. Keep contents and container dry and off wet floors. In case of decomposition, isolate container, if possible, and flood with large amounts of water to dissolve all material before discarding. Place in total isolation or suitable approved landfill area. EPA REG. NO. 42177-22
EPA EST. NO. 42177-TX-1

ALLIANCE PACKAGING, INC.
3309 East Carpenter Frwy., Irving, TX 75062

BEST AVAILABLE COPY



DIRECTIONS FOR USE FOR USE IN E-Z CLOR FEEDERS:

REPLACE:

3. Select the alphabetically coded dimple on the lower side of the cartridge according to the gallon capacity of your pool as determined by the chart below:

Approx. Gallons (In Thousands)	5	10	15	25	35
Dimple Letter	A	B	C	D	E

4. Cut a 1/4" diameter hole in the dimple selected from the chart above and also cut away completely the three vertical elongated tabs on the lower side of the cartridge.

5. Place the cartridge in the feeder.

6. After the cartridge has been in use for 24 hours, check the chlorine residual level. Chlorine residual should be checked frequently and always maintained between 1.0 and 1.5 ppm.

If the residual is below 1.0 ppm, remove the cartridge and cover the alphabetically coded hole with black electrical tape. Then, cut a new 1/4" diameter hole in the next higher dimple (e.g. A to B). Reinsert the cartridge and test residual again after 24 hours.

If the chlorine residual is above 1.5 ppm, remove the cartridge and cover the alphabetically coded hole with black electrical tape. Then, cut a new 1/4" diameter hole in the next lower dimple (e.g. E to D). Reinsert the cartridge and test residual again after another 24 hours.

WITH:

3. Select the numerically coded dimple on the lower side of the cartridge according to the gallon capacity of your pool as determined by the chart below.

Approx. Gallons (In Thousands)	5	10	15	20	30
Dimple number	1	3	5	7	9

4. Punch out appropriate dimple selected from the chart above as well as all dimples below selected number on both sides of the cartridge.

5. Punch out all eight (8) clear dots on bottom of cap. Push punch through to hilt and turn to get clean full size holes.

6. After the cartridge has been in use for 24 hours, check the chlorine residual level. Chlorine residual should be checked frequently and always maintained between 1.0 and 1.5 ppm.

If the residual is below 1.0 ppm, remove the cartridge and punch out next higher numbered dimple. Reinsert the cartridge.

If the chlorine residual is above 1.5 ppm, remove the cartridge and cover the highest numerically coded hole with black electrical tape.

Make additional adjustments as required to maintain desired 1.0 to 1.5 ppm free chlorine residual.