

UNIVERSAL CHLORINATOR CARTRIDGE

For use in erosion feeders

INERT INGREDIENT: . Available Chlorine 90%

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER: Corrosive. Causes irreversible eye damage and skin burns. May be tatal if absorbed through skin. May be fatal if absorbed through the skin. May be fatal if inhaled. Do not breathe dust or spray through the skin, hay be later in infraed. Do not greatine dust or spray mists. Irritating to nose and throat. Harmful if swallowed. Do not get in eyes, on skin, or on clothing. Wear goggles or face shield, protective clothing and rubber gloves when handling this product. Wash thoroughly with soap and water after handling and before eating, drisking or using tobacco. Remove contaminated clothing and wash before reuse

STATEMENT OF PRACTICAL TREATMENT:

If SWALLOWED: Orink promptly large quantities of water. Do not induce vomiting, Avoid alcohol. Never give anything by mouth to an uncorrectous person. Call a physician or poison control center immediately. IF IN EYES: Hold eyelids open and flush with a steady, gentle stream of water for 15 minutes. Get medical attention. IF ON SKIN: Wash with plenty of soap and water. Get medical attention. If INHALED: Remove victim to fresh air. If not breathing, give artificial secondarian conferably mouth-la-mouth. Get medical attention. respiration, preferably, mouth-to-mouth. Get medical attention. NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage

"HEMICAL HAZARDS: Strong oxidizing agent. Do not use st or damp utensits. Contamination with moisture, dirt, organic atter, or other chemicals or any foreign matter may start a chemical reaction with generation of heat, liberation of hazardous gases, and possible generation of fire.

ENVIRONMENTAL HAZARIDS: This pesticide is toxic to fish and aquatic organisms. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollitary Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guid-ance contact your State Water Board or Regional Office of the EPA.

SPECIAL PRECAUTIONS

- This product has a powerful chlorine odoc Hold away from face when opening to avoid breathing furnes.
- 2. Prolonged contact between this product in its undissolved state and vinyl liners or painted surfaces will result in bleaching of the vinyl or paint. Introduce this product through the skimmer or in a prescribed feeder to avoid discoloration of liner or paint.
- 3. When adding this product to slommer or feeder make sure there are no other chemicals present as a violent reaction may occur. It is aways dangerous to mix chemicals
- Use this product as directed as per instructions on label. Do not take advice from others or experiment by yourself.
- If this product is used to shock or superchlorinate a pool, after treatment it is important to brush walls and floor to expose algae

that may be in the cracks or wrinkles that might protect algae from high chlorine residual. Such protected algae will begin to reproduce again when high chlorine residual falls.

NOTE: Re-entry into treated swimming pool is prohibited above levels of 3 port.

6. This product, because of its potent formulation, can be dangerous if not used properly. Do not mix with any other chemicals. This could result in a violent chemical reaction. Do not add water to this product in a closed container. Do not add this product to a small amount of water in a pail. When adding this product to skimmer make sure pump is on and water is circulating so that material is drawn into recirculation system. Do not allow buildup of dry material in skimmer as gases generated may cause an explosion.

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in manner inconsistent with its labeling.

FOR USE IN E-Z CLOR® FEEDERS:

- 1. Adjust pool water to 7.2 to 7.6 pH level as determined by a test kit,
- 2. If the pool has not been stabilized, add stabilizer (cyanurie acid) according to instructions on label.
- 3. Select the numerically coded dimple on the lower side of the cartridge according to the gallon capacity of your pool as determined by the chart below:

Approx. Gallons (In Thousands) 10 Dimple No. 3

- Punch out appropriate dimple selected from the chart above as well as all dimples below selected number on both sides of the cartridge.
- 5. Punch out all eight (8) clear dots on bottom of cap.
 Push punch through to hilt and turn to get clean full size holes.
- 6. After the cartridge has been in use for 24 hours, check the chlorine residual level. Chlorine residual should be checked frequently and always maintained between 1.0 and 1.5 ppm.

If the residual is below 1.0 ppm, remove the cartridge and punch out next higher numbered dimple. Reinsert the car-

If the chlorine residual is above 1.5 ppm, remove the cartridge and cover the highest numerically coded hole with black electrical tape.

Make additional adjustments as required to maintain desired 1.0 to 1.5 ppm free chlorine.

FOR USE IN GUARDEX OR ANTHONY FEEDERS:

- Adjust pool water to 7:2 to 7.6 pH level as determined by a test
- 2. If the pool water has not been stabilized, add stabilizer (cyanuric acid) according to instructions on the stabilizer label,
- Cut a 1/4" diameter hole in the dimple indicated by the letter "X" on the side of the cartridge where the wide and narrow portions of the cartridge converge. Also cut away completely the three vertical elongated tabs on the lower sides of the cartridge.
- To make the Initial height setting of the cartridge in the feeder. select the number on the graduated scale on the side of the car-tridge according to the gallon capacity of your pool as determined by the chart below:

Approx Gallons (in Thousands) 15 2 10 20 35 Number 3

- Insert the cartridge into the feeder until the top of the feeder lip is aligned with the number on the graduated scale selected from the chart above. Then rotate the cartridge clockwise in the feeder until it stops-about a quarter of a revolution.
- After the cartridge has been in use for 24 hours, check the chlorine residual level. Chlorine residual should be checked frequently and always maintained between 1.0 to 1.5 ppm. If the residual level is below 1.0 ppm, readjust the height setting

to the next higher number on the graduated scale (e.g. 1 to 2). The cartridge will now be positioned deeper in the feeder.

If the residual level is above 1.5 ppm, readjust the height setting to the next lower number on the graduated scale (e.g. 6 to 5). The cartridge will now be positioned higher in the feeder.

NOTE: The pH of the slow dissolving tablet is on the acid side and will lend to reduce the pH and alkalimity of the pool water. Proper pH should be maintained between 7.2 to 7.6 as determined by a test kit and by periodic additions of sedium carbonate or sodium bicarbon-

STORAGE AND DISPOSAL

Keep product dry in a tightly closed container when not in use. Store in a cool, dry, well ventilated area away from heat or open flame. Keep contents and container dry and off wet floors. In case of decomposition isolate container, if possible, and flood with large amounts of water to dissolve all material before discarding. Place in trash collection or dispose in approved landfill area.

÷

EPA REG. NO. 42177-22 EPA EST. NO. 5185-GA-1 Manufactured For: Alliance Packaging, Inc. 4

KEEP OUT OF REACH OF CHILDREN DANGER

See first aid precautions. NET WEIGHT: 4 lbs. (1.81 kg.)

