

42447-1

ALCO # 27 CREOSOTE WOOD PRESERVATIVE

Active Ingredient	21.5%
Creosote Oil	78.5%
Inert Ingredients	100.0%

This product contains 1.7 lbs. of
creosote per gallon.

Albany Press Registered Stock Label 236-A

42447-1

PRECAUTIONARY STATEMENTS
Hazardous to humans and domestic animals.

WARNING
Use only with adequate ventilation.
Wear rubber gloves and protective clothing during use and handling of treated wood. Harmful if swallowed. Do not breathe vapor or spray mist. May cause skin irritation. Do not get in eyes, on skin or clothing.
Avoid prolonged or repeated skin contact. Cleanse hands thoroughly after each use.

ENVIRONMENTAL HAZARD
This pesticide is toxic to fish. Keep out of lakes, ponds or streams. Do not contaminate water by cleaning of equipment or disposal of waste.

PHYSICAL & CHEMICAL HAZARD
Do not use or store near heat, spark or open flame.

KEEP OUT OF REACH OF CHILDREN
WARNING
Statement of Practical Treatment
If swallowed, do not induce vomiting. Call poison control and physician immediately. If contact with skin, wash thoroughly with soap and water. Remove contaminated clothing and shoes. Get medical attention if irritation persists. Launder clothing before reuse. If in eyes, flush thoroughly with plenty of water for fifteen minutes. Get medical attention. If inhaled, remove to fresh air.
See side panel for additional precautionary statements.

Net Contents: 1 U.S. GALLON (3.785 LITERS)

NATIONAL VARNISH CO.
609 St. Jean
Detroit, Michigan 48214

Establishment No. 42447MI01

E.P.A. Registration No. 42447-1

68

MAR 10 1981

Under the Federal Insecticide,
Fungicide, and Rodenticide Act,
as amended, for the pesticide
registered under
EPA Reg. No. 42447-1

DIRECTIONS FOR USE

It is in violation of Federal Law to use this product in a manner inconsistent with the labelling.

STORAGE & DISPOSAL
DO NOT REUSE CONTAINER. WRAP
IN PLASTIC BAG AND DISCARD IN
TRASH COLLECTION.

ALCO #27 Creosote Wood Preservative is a combination of coal tar, creosote oil, hydrocarbon cut-back and oils.

It is ready to use from the container for treatment of wood. This product will delay the onset of rot and decay. Frequent inspection and retreatment will be necessary to maintain control.

Wood should be clean and dry before application. Posts should be soaked for 12 to 24 hours, depending on the seasoning of the wood. If the compound is applied with a paint brush, limit this method of application to small dimension lumber.

Apply at least two (2) flood coats. This product should be limited to sites where retreatment may be readily accomplished. Periodic inspection and reapplication may be necessary to maintain protection. Do not use on wood intended for use inside dairy barns, silos or other structures that may come in contact with food, feed or livestock.

FOR OUTSIDE USE ONLY

WARRANTY

Our recommendations for use of this product are based upon tests believed to be reliable. The use of this product being beyond the control of the manufacturer, no guarantee, expressed or implied, is made as to the effects of such or the results to be obtained if not used in accordance with directions or established safe practice. The buyer must assume all responsibility, including injury or damage resulting from its misuse as such, or in combination with other materials.