

UNDER THE FELFRAL INSECTICIDE FUNGICIDE AND RODENTICIDE ACT FOR ECONOMIC TO UNDER NO.



CHEMICAL & SERVICE INC.

A-540

ACTIVE INGREDIENT Poly[oxyethylene (dimethyliminio) ethylene		ylene
INERT INGREDIENT	• • • • • • • • • • • • • • • • • • • •	<u>88.0</u> %
This product contains tb. pe	1.02 r gatlon.	lb. of active ingredient per gallon and

KEEP OUT OF REACH OF CHILDREN CAUTION

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

CAUTION: Harmful if swallowed. Avoid breathing vapors. Avoid contact with skin, eyes, or clothing.

FIRST AID: If swallowed, drink promptly a large quantity of milk, egg whites, gelatin solution, or, if these are not available, drink large quantities of water. Avoid alcohol. Call a physician immediately.

ENVIRONMENTAL HAZARDS: This pesticide is toxic to fish. Keep out of lakes, streams, or ponds. Permits may be required for discharges containing this pesticide into takes, streams, ponds or public water. For guidance, contact the regional office of the Environmental Protection Agency.

		}	o'	
	DIRE	CTIO AL CI		
It is a violation of nconsistent with its	Feder	rai lav		
A-540				_ is us
and fungi in recirculation its use, systems mu	st be cl	ean ed	to ren	nove i

nd industria o remove slimb, and other deposits. An initial slug addition of the counces of ________A-540 ounces of _ of water to provide a concentration of. A-540 base in the system, is recommended. Repeat initial dos Subsequent slug additions of . A-540 per 1000 100 parts per million of _ employed every 2 to 5 days, or as needed. The i upon the relative amount of bleedoff and the sev problem. Slug additions should be made in the sure A-540 is used to air-washing systems that maintain effective mist ei to its use, systems should be cleaned to remove deposits. An initial slug dose of ... Ă-540 mended. Repeat initial dosage until control is evid tions of 14.44 to 35.63 fluid ounces of per 1000 gallons of water should be employed each The frequency of addition depends upon the relat severity of the bacterial problem. Slug additions m to the water collection trays of the airwash system.

STORAGE & DISPOSAL: Keep container closed contaminate water, food, or feed by storage, equipment. Do not reuse empty container. Triple dispose of container in an incinerator or in an apsafe place. Rinsate that cannot be used or reprocess a landfill approved for pesticides or buried in a supplies. Open dumping is prohibited.

	Manufactured by:
	Delta Chemical & Service
	13910 N.W. 19th Aver
	Opa-Locka, FL 3305
EPA REG. NO. 4255	6-1. EPA EST
	NET CONTENTS:



UNDER THE FEDERAL INSECTICIDE FUNGICIDE AND RODENZICIDE ACC. FOR ECONOMIC POSSOR RECEIVED.

13810 N.W. 18th Ave. Ope Looks, Me. 33064

885-88<u>00</u>

CAL & SERVICE INC.

A-540

DIENT Iimethyliminio) e	thylene-
hylene dichloride	12.0 %
ENT	
ns 1.02	ib. of active ingredient per gallon and
.ib. per gallon.	

OUT OF REACH OF CHILDREN CAUTION

PRECAUTIONARY STATEMENTS DS. TO HUMANS AND DOMESTIC ANIMALS

ul if swallowed. Avoid breathing vapors. Avoid contact with ing.

wallowed, drink promptly a large quantity of milk, egg ution, or, if these are not available, drink large quantities of o'. Call a physician immediately.

AL HAZARDS: This pesticide is toxic to fish. Keep out of ponds. Permits may be required for discharges containing takes, streams, ponds or public water. For guidance, contact of the Environmental Protection Agency.

DIRECT	IONS	FOR	USE
ENERAL	CLAS	SIFIC	CATION

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

A-540 is used to control algae, bacteria, and fungi in recirculating commercial and industrial water cooling towers. Prior to its use, systems must be cleaned to remove algal growth, microbiological slime, and other deposits. An initial slug addition of 5.0 to 12.5 fluid ounces of A-540 per 1000 gallons ounces of _ 40 to 100 parts per million of of water to provide a concentration of _ A-540 , based on the total weight of water in the system, is recommended. Repeat initial dosage until control is evident. 1.20 to 12.5 fluid ounces of Subsequent stug additions of ___ per 1000 gallons of water (___10__ to A-540 100 parts per million of . employed every 2 to 5 days, or as needed. The frequency of addition depends upon the relative amount of bleedoff and the severity of the microbiological problem. Slug additions should be made in the sump of water cooling towers. A-540 _ is used to control bacteria in industrial air-washing systems that maintain effective mist eliminating components. Prior to its use, systems should be cleaned to remove bacterial slime and other deposits. An initial slug dose of 21.37 to 35.63 fluid ounces of deposits. An initial slug dose of ____ _per 1000 gallons of water is recommended. Repeat initial dosage until control is evident. Subsequent slug additions of 14.44 to 35.63 fluid ounces of _ per 1000 gallons of water should be employed each 1 to 5 Jays, or as needed. The frequency of addition depends upon the relative amount of bleedoff and severity of the bacterial problem. Slug additions may be made to the sump or to the water collection trays of the airwash system.

STORAGE & DISPOSAL: Keep container closed when not in use. Do not contaminate water, food, or feed by storage, disposal, or cleaning of equipment. Do not reuse empty container. Triple rinse (or equivalent) and dispose of container in an incinerator or in an approved landfill, or bury in a safe place. Rinsate that cannot be used or reprocessed should be disposed of in a landfill approved for pesticides or buried in a safe place away from water supplies. Open dumping is prohibited.

Mai	nufactured by:
Deita Che	mical & Service, Inc.
13910 N	N.W. 19th Avenue
Opa-	Locka, Fl. 33054
EPA REG. NO. 42556-1	EPA EST. NO. 42556 FI A-1
	ET CONTENTS: 4.2

1