

PERMODIP #24 CLEAR WOOD PRESERVATIVE
DECKS — FENCES — STRUCTURAL LUMBER — PLYWOOD — OUTDOOR FURNITURE
GUTTERS — TIMBERS — STAIRS — ARCHITECTURAL MILLWORK — SIDING — SILLS

Permodip #24 Clear Wood Preservative prolongs the life of wood by protecting against moisture, rot and mildew, the natural enemies of wood. This water-reducible zinc naphthenate wood preservative seals and helps retard warping, swelling, shrinking and checking of the wood itself.

Permodip #24 Clear Wood Preservative can be recoated after overnight dry with either latex or oil base paint systems.

PREPARATION

Wood should be clear and dry, well seasoned and free of dirt. Mildew must be removed from all surfaces by using a solution of household bleach (5% water plus a cup of bleach per quart) in a 10 quart pail. Areas affected by mildew should be thoroughly scrubbed with this solution then rinsed with clean water and allowed to dry. Rubber gloves and goggles should be used for personal protection during this process.

APPLICATION

Permodip #24 Clear Wood Preservative should be applied to wood by brush, roller, spray or by dipping in a container. To remove wood preservative absorbed, the more effective treatment is to dip the wood.

Materials supplied at proper application is 1.5 lbs per sq ft. Wood immersion should be for three minutes, flipped.

A single coat is recommended for surfaces that are not stained.

On stained wood, a second coat will remain on the surface. It is recommended with in the hour. Excess material that soaks into the wood will be wiped off with a clean rag with mineral spirits.

Clean equipment, preferably with mineral spirits, immediately after completion of the fastening.

PRECAUTIONS

Do not apply over painted varnishes or other finishes. Do not apply over bark.

Use Permodip #24 Clear Wood Preservative in accordance with the label directions.

COVERAGE

Permodip #24 Clear Wood Preservative covers 100 sq ft per gallon.

PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS AND DOMESTIC ANIMALS

WARNING

CONTAINS PETROLEUM DISTILLATE AND ZINC NAPHTHENATE

FIRST AID PROCEDURE

Harmful if swallowed or absorbed through skin. Do not get in eyes. Wash thoroughly with plenty of water after handling. If SWALLOWED, DO NOT INDUCE VOMITING. CALL PHYSICIAN IMMEDIATELY. If ABSORBED THROUGH SKIN, Wash thoroughly with soap and water. If IN EYES, Flush with plenty of water and with immediate medical attention. **CONTAMINATED CLOTHING** should be removed and washed thoroughly before reusing.

ENVIRONMENTAL HAZARDS

This product is toxic to fish. Treatments should be made in tanks where the water is not used for drinking water. Do not discharge into streams, rivers, lakes, ponds, or other bodies of water. Apply this product in accordance with the label directions.

PHYSICAL OR CHEMICAL HAZARDS

Do not store in open or unsealed containers. Do not store in areas where children or pets can access. Use in well-ventilated areas. Do not use in enclosed spaces.

DIRECTIONS FOR USE

Use Permodip #24 Clear Wood Preservative in accordance with the label directions.

STORAGE AND DISPOSAL

Do not use empty container. Wrap container and put into trash collection.

California Products Corporation
 Cambridge, Massachusetts 02139

PREVENTS RETARD
WARPS
WELLING
SHRINKING
CHECKING

Q 42768-4
 No. 42768 MA1
PRESERVATIVE #24

17.33% (Minimum)
 82.67% (Maximum)
 Total 100.00%