

# Storm Stain<sup>®</sup>

ACCEPTED  
MAR 28 1991  
By the U.S. Environmental Protection Agency under the Federal Insecticide, Fungicide, and Rodenticide Act, as amended, for the purpose of registration.

108  
11-27-88-1  
P1121



Storm Stain  
11-27-88-1  
P1121

EPA Registration No. 42768-4  
EPA Establishment No. 42768 MA-  
STORM STAIN PRESERVATIVE #24  
CLEAR

Active Ingredient:	
Zinc Naphthenate	9.67% (Minimum)
(Equivalent to metallic zinc 1.1%)	
Inert Ingredients:	91.33% (Maximum)
Total	100.00%

Max. VOC Content: 350 grams/liter  
One U.S. Gallon  
(3.785 Liters) Net

## Penetrating Wood Preservative Formula II 200-24 Clear

Protects wood against  
moisture, mildew, fungus & rot

Retards warping,  
shrinking,  
swelling and  
checking

**KEEP OUT OF REACH OF CHILDREN**  
**WARNING! HARMFUL OR FATAL IF SWALLOWED.**  
COMBUSTIBLE. See other cautions on back panel.

BEST AVAILABLE COPY

## WOOD PRESERVATIVE

### #24 CLEAR-FORMULA II

Shingles — Shakes — Siding — Fencing — Decks and Rails — Windows — Timbers  
Gutters — Architectural Millwork — Sills — Outdoor Furniture — Log Homes  
Storage Sheds — Kennels — Plywood Lumber — — Paneling

STORM STAIN® #24 CLEAR WOOD PRESERVATIVE prolongs the life of wood by protecting against moisture, rot and mildew, the natural enemies of wood. This water-reducible, zinc naphthenate wood preservative seals and helps retard warping, swelling, shrinking and checking of the wood itself.

STORM STAIN #24 CLEAR WOOD PRESERVATIVE can be recoated after overnight dry with either latex or oil base paint systems.

STORM STAIN #24 CLEAR WOOD PRESERVATIVE protects the wood against moisture and mildew but does not prevent the natural color changes that gradually occur when the surface of the wood is continuously exposed to ultra violet rays from the sun.

#### PREPARATION

Wood should be clean and dry, well seasoned and free of bark. Mildew must be removed from all surfaces, utilizing a solution of 50% household bleach, 50% water, plus a cup of trisodium phosphate in a 10 quart pail. Areas affected by mildew should be thoroughly scrubbed with this solution, then hosed down with clean water and allowed to dry. Rubber gloves and goggles should be used for personal protection during this process.

#### APPLICATION

STORM STAIN #24 Clear Wood Preservative should be applied liberally by brush, roller, spray, or by dipping in a container. The more wood preservative absorbed, the more effective the protection. Do not thin — Material is supplied at proper application consistency.

Wood immersion should be for three minutes if dipped.

A single coat is recommended for surfaces to be painted or stained.

On porous or rough wood that will remain clear, a second coat is recommended within the hour. **EXCESS MATERIAL NOT ABSORBED SHOULD BE WIPED OFF WITH A DAMP RAG WITHIN MINUTES.**

Clean equipment, preferably with mineral spirits, immediately after completion of job for fast cleanup.

#### PRECAUTIONS

Do not apply over painted, varnished or stained surfaces.

Do not apply over bark.

Use STORM STAIN #12 Green Wood Preservative for surfaces directly in contact with soil or water.

#### COVERAGE

100-300 square feet — depending on porosity of wood and method of application

#### PRECAUTIONARY STATEMENTS

##### HAZARDS TO HUMANS AND DOMESTIC ANIMALS

**WARNING: CONTAINS PETROLEUM DISTILLATE AND ZINC NAPHTHENATE**

**FIRST AID PROCEDURE:** Harmful if swallowed or absorbed through skin. Do not get in eyes, on skin or on clothing. Wash thoroughly after handling.

**IF SWALLOWED:** Do not induce vomiting. CALL PHYSICIAN IMMEDIATELY. — **IF ABSORBED THROUGH SKIN:** Wash thoroughly with soap and water. — **IF IN EYES:** Flush with plenty of water and get immediate medical attention. — **CONTAMINATED CLOTHING** should be removed and washed thoroughly before reusing.

**ENVIRONMENTAL HAZARDS:** This product is toxic to fish. Treated effluent should not be discharged where it will drain into lakes, streams, ponds or public waters. Do not contaminate water by cleaning of equipment or disposal of wastes. Apply this product only as specified on the label.

**PHYSICAL OR CHEMICAL HAZARDS:** Do not pour, spill or store near heat or open flame. Use only with adequate ventilation. Close container after each use.

**DIRECTIONS FOR USE:** It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

**STORAGE AND DISPOSAL:** Do not use empty container. Wrap container and put into trash collection.

Made in U.S.A.

**California Products Corporation**

169 WAVERLY STREET

P.O. BOX 569

CAMBRIDGE, MA 02139-0569