

42768-11, PM21 1072

Storm Stain[®]



KEEP OUT OF REACH OF CHILDREN

CAUTION

Active Ingredient
 3-Iodo-2-Propynyl Butyl
 urbamate.....0.50%

Inert Ingredients.....99.50%

100.00%

EPA Reg. No. 42768-
 EPA Est. No. 42768 MA-1

See back panel for additional
 precautionary statements.

Urethane Latex
 Stain & Wood
 Preservative

Semi-Transparent

- Seals wood fibres against moisture
- Protects stain film against mildew & fungus
- Helps prevent wood rot

One U.S. Gallon
 (3.785 Liters) Net
 NET WEIGHT: 9.0 lbs.

ACCEPTED

SEP 19 1988

Under the Federal Insecticide,
 Fungicide, and Rodenticide Act,
 as amended, for the pesticide
 registered under
 EPA Reg. No. 42768-11

STORM STAIN URETHANE LATEX STAIN & WOOD PRESERVATIVE

206

SEMI-TRANSPARENT

Shakes — Shingles — Clapboards — Siding — Beams — Fences
Lawn Furniture — Decks — Barnboard — Wood Products

These lightly pigmented urethane latex exterior wood stains enrich the natural graining and configurations of shingles, shakes, and rough sawn siding and clapboards. STORM STAIN'S Semi-Transparent formulation provides light color with excellent fade resistant and urethane acrylic resins for long term water repellancy. The wood preservative that is in the formulation functions as a mildew and fungus growth inhibitor and helps prevent wood rot. Two coats of STORM STAIN Semi-transparent latex stain are recommended for maximum protection on most new or unfinished woods. A single coat is recommended for decks, porches, railings and outdoor furniture. STORM STAIN Solid Color latex stain is excellent for coating over previously stained surfaces, but Semi-Transparent stains should not be used over such previously painted or varnished surfaces. When recoating previously stained surfaces, use the same or a darker color for proper hide and appearance.

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

HAZARD: IF SWALLOWED OR INHALED, AVOID BREATHING SPRAY MIST. AVOID CONTACT WITH EYES, SKIN OR CLOTHING. WASH THOROUGHLY WITH SOAP AND WATER AFTER HANDLING AND BEFORE SMOKING OR EATING. REMOVE CONTAMINATED CLOTHING AND WASH BEFORE REUSE.

STATEMENT OF PRACTICAL TREATMENT

IF ON SKIN: WASH WITH PLENTY OF SOAP AND WATER. GET MEDICAL ATTENTION IF IRRITATION PERSISTS.

IF SWALLOWED: DRINK 1 OR 2 GLASSES OF WATER AND INDUCE VOMITING BY TOUCHING BACK OF THROAT WITH FINGER. DO NOT INDUCE VOMITING OR GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. AVOID ALCOHOL. CALL A PHYSICIAN IMMEDIATELY.

IF INHALED: REMOVE VICTIM TO FRESH AIR. APPLY ARTIFICIAL RESPIRATION, PREFERABLY MOUTH TO MOUTH, IF INDICATED.

IF IN EYES: FLUSH WITH PLENTY OF WATER. GET MEDICAL ATTENTION IF IRRITATION PERSISTS.

ENVIRONMENTAL HAZARDS

THIS PRODUCT IS TOXIC TO FISH. DO NOT APPLY DIRECTLY TO WATER. DO NOT CONTAMINATE WATER BY CLEANING OF EQUIPMENT OR DISPOSAL OF WASTES.

DIRECTIONS FOR USE: It is a violation of Federal law to use this product in a manner inconsistent with its labeling. This product is not recommended for use on wood used for ground, food, feed or potable water contact. Covers desirable plants and shrubs to avoid possible injury. This product can be used where dairy and farm animals may come in contact with the treated wood. Surfaces which may come into continuous contact with the skin should be coated with a varnish or lacquer.

SURFACE PREPARATION

All surfaces must be clean and thoroughly dry before application of STORM STAIN Semi-Transparent Latex Stain.

Prior to staining, remove all mold from affected areas by scrubbing with a solution of 50% household bleach and 50% water. Use rubber gloves and safety goggles for personal protection during this process. Hose down with clean water and allow to dry. Apply to shingles, shakes, rough sawn siding, plywood and clapboards with the rough side out to allow stain to penetrate properly. Smooth planed clapboards or siding should be rough sanded thoroughly to break the smooth "mill glaze" and allow proper penetration of the stain.

APPLICATION

Stir STORM STAIN until all pigment is fully incorporated into the liquid. Material should be inter-mixed by pouring back and forth or by pouring into a large container and stirring before doing large areas, to insure color uniformity.

This material can be applied by synthetic bristle brush, roller, pad applicator or spray gun. Stain only a few rows of siding or shingles at one time. Always start from the top and work across towards a natural break or edge such as a window or door. On vertical siding start a few boards at the top and go all the way to the bottom. Avoid over lapping.

On hot summer days a small amount of water can be added to Urethane Latex STORM STAIN to maintain a wet edge.

Apply stain on the shady side of a building and not in direct sun whenever possible. These hot weather limitations do not apply to spray applications.

STORM STAIN Urethane Latex is self-priming on new wood. The type and porosity of the wood is the pre-determining factor in the selection of the number of coats necessary.

PRECAUTIONS

STORM STAIN Urethane Latex Stain should not be applied when air or surface temperatures are below 50° F or when rain is imminent.

Avoid applying over creosote stains.

Pressure treated wood should weather at least six months until "green" tint has oxidized away to avoid discoloration of stain topcoats.

Do not mix with other paints, stains, oils or solvents.

Clean equipment and brushes with warm soapy water, immediately after usage.

COVERAGE

Smooth Wood — 300 to 400 sq. ft. per gallon
Textured Wood — 100 to 200 sq. ft. per gallon

DRYING TIME

Touch — One Hour Recoat — Four Hours

STORAGE AND DISPOSAL

STORAGE: DO NOT STORE NEAR EXCESSIVE HEAT.

DISPOSAL: DO NOT REUSE CONTAINER. RINSE THOROUGHLY BEFORE DISCARDING IN TRASH. SECURELY WRAP ORIGINAL CONTAINER IN SEVERAL LAYERS OF NEWSPAPER AND DISCARD IN TRASH.

California Products Corporation

169 WAVERLY STREET
P.O. BOX 569
CAMBRIDGE, MA 02139-0569

Made in U.S.A.