

42768-12

PM21

1064

US ENVIRONMENTAL PROTECTION AGENCY OFFICE OF PESTICIDES PROGRAMS REGISTRATION DIVISION (TS-767) WASHINGTON, DC 20460	EPA REGISTRATION NO. 42768-12	DATE OF ISSUANCE SEP 19 1986
	TERM OF ISSUANCE	
NOTICE OF PESTICIDE: <input checked="" type="checkbox"/> REGISTRATION <input type="checkbox"/> REREGISTRATION (Under the Federal Insecticide, Fungicide, and Rodenticide Act, as amended)		
NAME OF PESTICIDE PRODUCT STORM STAIN INSECTICIDE AND FUNGICIDE PRESERVATIVE - semi-transparent Formula II		

NAME AND ADDRESS OF REGISTRANT (Include ZIP code)

<input type="checkbox"/> California Products Corporation 100 Beverly Street P.O. Box 100 Cheshire, CT 06110	<input type="checkbox"/>	160 18	170735 1
--	--------------------------	-----------	-------------

NOTE: Changes in labeling formula differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Registration Division prior to use of the label in commerce. In any correspondence on this product always refer to the above U.S. EPA registration number.

On the basis of information furnished by the registrant, the above named pesticide is hereby Registered/Reregistered under the Federal Insecticide, Fungicide, and Rodenticide Act.

A copy of the labeling accepted in connection with this Registration/Reregistration is returned herewith.

Registration is in no way to be construed as an indorsement or approval of this product by this Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.

This pesticide is conditionally registered in accordance with section 3(c)(7) of the Act. You:


1. Submit to the Agency, within the time required for registration/reregistration of your product under FIFRA section 3(c)(3) when the Agency requires all registrants of similar products to submit such data.
2. Add to the label the following information to you in accordance with the requirements:
 - a. Add the phrase "EPA Registration No. 42768-12."
 - b. On the front panel, the broad claim to protect against "molds" is not acceptable. A claim such as "protects against rot and mildew fungi" would be acceptable.
3. Submit five (5) copies of your final printed labeling before you release the product for shipment. Refer to the 4-79 Enclosure for a further description of final printed labeling.

ATTACHMENT IS APPLICABLE

SIGNATURE OF APPROVING OFFICIAL <i>Henry M. Lacey</i>	DATE 9/19/86
--	-----------------

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA section 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

A stamped copy of the label is enclosed for your records.


Henry M. Jacoby
Product Manager (21)
Fungicide-Herbicide Branch
Registration Division (TS-767C)

Enclosures

7/20/68

Storm Stain[®]

KEEP OUT OF REACH OF CHILDREN

WARNING

Active Ingredient
 3-Iodo-2-Propynyl Butyl
 Carbamate.....0.50%

Inert Ingredients.....99.50%

100.00%

EPA Reg. No. 42768-
EPA Est. No. 42768 MA-1

See side panels for additional pre-
cautionary statements.

1 U.S. Gallon
(3.785 Liters) Net
7.2 lbs/gal

Linseed Oil Stain & Wood Preservative

Semi-
Form
Protects
against rot
mildew, fu
& moisture

ACCI
with CC
to EPA 1

SEP:

Under the
Fungicide, s
as amended
registered u

Clear stain bases will protect the wood but will not prevent natural color changes that occur when wood is exposed to ultra violet rays from the sun.

**PRECAUTIONARY STATEMENT
HAZARDS TO HUMAN AND DOMESTIC ANIMALS**

WARNING: CONTAINS PETROLEUM DISTILLATES. USE ONLY WITH ADEQUATE VENTILATION. AVOID PROLONGED BREATHING OF VAPOR OR SPRAY MIST. HARMFUL IF SWALLOWED. CAUSES SUBSTANTIAL BUT TEMPORARY EYE INJURY. DO NOT GET IN EYES, ON SKIN OR ON CLOTHING. WEAR GOGGLES AND RUBBER GLOVES WHEN HANDLING, AND RUBBER GLOVES AND PROTECTIVE CLOTHING WHEN HANDLING FRESHLY TREATED LUMBER. WASH THOROUGHLY WITH SOAP AND WATER AFTER HANDLING. REMOVE CONTAMINATED CLOTHING AND WASH BEFORE RE-USE.

STATEMENT OF PRACTICAL TREATMENT

IF ON SKIN: WASH WITH PLENTY OF SOAP AND WATER. GET MEDICAL ATTENTION IF IRRITATION PERSISTS.

IF SWALLOWED: DO NOT INDUCE VOMITING. PROMPTLY DRINK A LARGE QUANTITY OF MILK, EGG WHITES OR GELATIN SOLUTION; IF THESE ARE NOT AVAILABLE, DRINK LARGE QUANTITIES OF WATER. AVOID ALCOHOL. GET MEDICAL ATTENTION IMMEDIATELY.

IF INHALED: REMOVE VICTIM TO FRESH AIR.

IF IN EYES: FLUSH WITH PLENTY OF WATER. GET MEDICAL ATTENTION.

ENVIRONMENTAL HAZARDS

THIS PRODUCT IS TOXIC TO FISH. DO NOT APPLY DIRECTLY TO WATER. DO NOT CONTAMINATE WATER BY CLEANING OF EQUIPMENT OR DISPOSAL OF WASTES.

PHYSICAL AND CHEMICAL HAZARDS

COMBUSTIBLE: DO NOT USE, POUR, OR SPILL NEAR HEAT OR OPEN FLAME. IN CASE OF FIRE, USE WATER SPRAY, FOAM, CARBON DIOXIDE OR DRY CHEMICAL.

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling. This product is for exterior use only and is recommended for usage on the sites listed above. This product is not recommended for use on wood used for ground, food, feed, or potable water contact nor for use on primed or previously painted surfaces. Cover desirable plants and shrubs to avoid possible injury. This product can be used where dairy and farm animals may come in contact with the treated wood. Surfaces that may come into continuous contact with the skin should be coated with a varnish or lacquer. For best results and uniformity of appearance, retreat once every three years.

SURFACE PREPARATION

All surfaces must be clean and thoroughly dry before application of STORM STAIN Semi-Transparent Oil Base Stain.

Prior to staining, remove all mildew from affected areas by scrubbing with a solution of 50% household bleach and 50% water. Use rubber gloves and safety goggles for personal protection during this process. Hose down with clean water and allow to dry.

Shingles, shakes, rough sawn siding, plywood and clapboards with the rough side out allow stain to penetrate properly. Smooth planed clapboards or siding should be rough sanded thoroughly to break the smooth "mill glaze" and allow proper penetration of the stain.

APPLICATION

Thoroughly stir this material until all pigment is fully incorporated into the liquid. Additional light stirring during application may be necessary to maintain color uniformity. Intermix contents of cans by pouring back and forth or by pouring into a large container and stirring before doing large areas.

DO NOT THIN OIL BASE STORM STAIN

Oil Base Stains, both Solid and Semi-Transparent, are best applied by natural bristle brushes, but can be rolled or sprayed.

Stain only a few boards or small area at a time. Vertical boards or shingles should be stained continuously from the top, always working to the edge of a board or shingle to avoid overlapping.

Horizontal siding should be started at the top and worked across, always working towards an edge or break such as a door or window. Avoid overlapping.

Stain colors vary with the type of wood so that a small board or an inconspicuous section of the house should be stained first to test the stain on the actual wood.

STORM STAIN is self-priming on wood surfaces. Cedar, Redwood, Cypress and some other woods contain a natural water soluble ingredient, "tannin", that will show as a reddish brown stain when it migrates to the surface of damp wood. Should these stains appear they can be removed by washing with a mild detergent solution and rinsing with clear water. Stains will also disappear naturally if left exposed to the sun for a period of time.

PRECAUTIONS

Do NOT use over previously painted or varnished surfaces. Temperatures of both air and surface should be at least 50° F during application and drying time. Do not mix with oil, water, or other types of paint or stain. Clean brushes and equipment with mineral spirits. Do NOT use oil base stains on hardboard or compressed fiber siding.

Pressure treated wood should weather at least six months until "green" tint has oxidized away to avoid discoloration of stain topcoats.

COVERAGE

200-400 sq. ft.
— depending on type of wood.

DRYING TIME

Tough — 4 Hours
Recoat — 24 Hours

STORAGE AND DISPOSAL

STORAGE: DO NOT STORE NEAR EXCESSIVE HEAT.

DISPOSAL: DO NOT REUSE CONTAINER. RINSE THOROUGHLY BEFORE DISCARDING IN TRASH. SECURELY WRAP ORIGINAL CONTAINER IN SEVERAL LAYERS OF NEWSPAPER AND DISCARD IN TRASH.

Made in U.S.A.

California Products Corporation

169 WAVERLY STREET
P.O. BOX 669
CAMBRIDGE, MA 02139-0569