

# Storm Stain<sup>®</sup>



KEEP OUT OF REACH OF CHILDREN

**WARNING**

Active Ingredient  
3-Iodo-2-Propynyl Butyl  
Carbamate.....0.50%

Inert Ingredients.....99.50%  
100.00%

EPA Reg. No. 42768-  
EPA Est. No. 42768 MA-1

See side panels for additional pre-  
cautionary statements.

## Linseed Oil Stain & Wood Preservative

### Solid Color Formula II

Protects against rot,  
mildew, fungus,  
moisture & U-V rays

ONE U.S. GALLON  
(3.785 LITERS)  
NET

8.76 lbs/gal

ACCEPT

NOV 24 1986

U: for the Federal In  
Fungicide and R  
as recorded, for the  
registered under  
EPA Reg. No. 42768-13

**PRECAUTIONARY STATEMENT  
HAZARD TO HUMAN AND DOMESTIC ANIMALS**

**WARNING:** CONTAINS PETROLEUM DISTILLATES. USE ONLY WITH ADEQUATE VENTILATION. AVOID PROLONGED BREATHING OF VAPOR OR SPRAY MIST. HARMFUL IF SWALLOWED. CAUSES SUBSTANTIAL BUT TEMPORARY EYE INJURY. DO NOT GET IN EYES, ON SKIN OR ON CLOTHING. WEAR GOGGLES AND RUBBER GLOVES WHEN HANDLING, AND RUBBER GLOVES AND PROTECTIVE CLOTHING WHEN HANDLING FRESHLY TREATED LUMBER. WASH THOROUGHLY WITH SOAP AND WATER AFTER HANDLING. REMOVE CONTAMINATED CLOTHING AND WASH BEFORE RE-USE.

**STATEMENT OF PRACTICAL TREATMENT**

**IF ON SKIN:** WASH WITH PLENTY OF SOAP AND WATER. GET MEDICAL ATTENTION IF IRRITATION PERSISTS.

**IF SWALLOWED:** DO NOT INDUCE VOMITING. PROMPTLY DRINK A LARGE QUANTITY OF MILK, EGG WHITES OR GELATIN SOLUTION. IF THESE ARE NOT AVAILABLE, DRINK LARGE QUANTITIES OF WATER. AVOID ALCOHOL. GET MEDICAL ATTENTION IMMEDIATELY.

**IF INHALED:** REMOVE VICTIM TO FRESH AIR.

**IF IN EYES:** FLUSH WITH PLENTY OF WATER. GET MEDICAL ATTENTION.

**ENVIRONMENTAL HAZARDS**

THIS PRODUCT IS TOXIC TO FISH. DO NOT APPLY DIRECTLY TO WATER. DO NOT CONTAMINATE WATER BY CLEANING OF EQUIPMENT OR DISPOSAL OF WASTES.

**PHYSICAL AND CHEMICAL HAZARDS**

**COMBUSTIBLE:** DO NOT USE, POUR, OR SPILL NEAR HEAT OR OPEN FLAME. IN CASE OF FIRE, USE WATER SPRAY, FOAM, CARBON DIOXIDE OR DRY CHEMICAL.

**DIRECTIONS FOR USE**

It is a violation of Federal law to use this product in a manner inconsistent with its labeling. This product is for exterior use only and is recommended for use on the sites listed above. This product is not recommended for use on wood used for ground, food, feed, or potable water contact nor for use on primed or previously painted surfaces. Cover desirable plants and shrubs to avoid possible injury. This product can be used where dairy and farm animals may come in contact with the treated wood. Surfaces that may come into continuous contact with the skin should be coated with a varnish or lacquer. For best results and uniformity of appearance, retreat once every three years.

**California Products Corporation**

169 WAVERLY STREET  
P.O. BOX 669  
CAMBRIDGE, MA 02139-0669

**SURFACE PREPARATION**

All surfaces must be clean and thoroughly dry before application of STORM STAIN Solid Color Or Base Stain.

Prior to staining, remove all mildew from affected areas by scrubbing with a solution of 50% household bleach and 50% water. Use rubber gloves and safety goggles for personal protection during this process. Hose down with clean water and allow to dry.

Shingles, shakes, rough saw siding, plywood and clapboards with the rough side out allow stain to penetrate properly. Smooth planed clapboards or siding should be rough sanded thoroughly to break the smooth "mill glaze" and allow proper penetration of the insect oil stain.

**APPLICATION**

Thoroughly stir this material until all pigment is fully incorporated into the liquid. Additional light stirring during application may be necessary to maintain color uniformly. Intermix contents of cans by pouring back and forth or by pouring into a large container and stirring before doing large areas.

**DO NOT THIN OIL BASE STORM STAIN**

Oil Base Stains, both Solid and Semi-Transparent, are best applied by natural bristle brushes, but can be rolled or sprayed.

Stain only a few boards or small area at a time. Vertical boards or shingles should be stained continuously from the top, always working to the edge of a board or shingle to avoid overlapping.

Horizontal siding should be started at the top and worked across, always working towards an edge or break such as a door or window. Avoid overlapping.

Stain colors vary with the type of wood so that a small board or an inconspicuous section of the house should be stained first to test the stain on the actual wood.

STORM STAIN is self-priming over most new wood surfaces. New or unfinished wood to be stained with STORM STAIN White or other light colors however, should be primed with STORM STAIN Universal Wood Primer to avoid natural tannin or sugar bleed through from the new wood.

**PRECAUTIONS**

Do NOT use over previously painted or varnished surfaces. Temperatures of both air and surface should be at least 50° F during application and drying time. Do not mix with oil, water, or other types of paint or stain. Clean brushes and equipment with mineral spirits. Do NOT use oil base stains on hardboard or compressed fiber siding.

Pressure treated wood should weather at least six months until "green" tint has oxidized away to avoid discoloration of stain topcoats.

**COVERAGE**

200-400 sq. ft.  
depending on type of wood.

**D: YING TIME**

To . . . - 4 Hours  
Retreat - 24 Hours

**STORAGE AND DISPOSAL**

**STORAGE:** DO NOT STORE NEAR EXCESSIVE HEAT.

**DISPOSAL:** DO NOT REUSE CONTAINER. RINSE THOROUGHLY BEFORE DISCARDING IN TRASH. SECURELY WRAP ORIGINAL CONTAINER IN SEVERAL LAYERS OF NEWSPAPER AND DISCARD IN TRASH.

Made In U.S.A.