PRECAUTIONARY STATEMENTS DANGER

HAZARDS TO HUMANS AND DOMESTIC ANIMALS


Do not get in eyes, on skin or on clothing, causes severe skin irritation, especially to broken skin, Causes eve damage. Harmful if swallowed. Wear goggles or faceshield and rubber gloves when handling this product. Remove and wash-contaminated clothing.

ENVIRONMENTAL HAZARDS

This pesticide is toxic to fish, **Do not dis**charge into lakes, streams, ponds or public waters unless in accordance with an NPDES permit. For guidance contact your Regional Office of the EPA.

STORAGE & DISPOSAL

Keep container closed when **not** in **use**. Do'not contaminate water, food or **ised** by storage disposal, or cleaning of equipment. The container must be triple rinsed for equivalent and offered for recycling, reconditioning or disposal in an approved landfill or buried in a safe place. Rindate, that cannot be used or reprocessed **should** be disposed of in a landfill approved for pesticides or buried in a safe place away from water **supplies**. Open dumping is prohibited



COMMERCIAL

n-Alkyl (50 C+: 10 C+: 40 C+) dimethyl benzyl ammonium chloride 16 0%

INERT INGREDIENT

3**4 0**

This product contains 1.31 lb. of active ingredient per gallon and weighs 8.18 lb. per gallon.

KEEP OUT OF REACH OF CHILDREN

DANGER

PRACTICAL TREATMENT

First Aid Skin and Eyes In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes. For eyes, call a physician, ingestion: if swallowed drink milk, egg whites, geletin solution, or, if these are not available, large quantities of water. Avoid alcohol. Call a physician

NOTE TO PHYSICIAN Probable mucosal damage may contraindicate the use of gastric lavage Measures against circulatory shock respiratory depression and convulsion may be needed

'See Side Panel For Additional Precautionary Statements

DIRECTIONS FOR USE GENERAL CLASSIFICATION

It is a violatio of Federal law to use this product in a manner incordistent with its labeling

Series 3020 i used to control algae, bacteria, and fungi in recir leating commercial and industrial water cooling towards a Prior to its use, systems must be cleaned to remove algal growth, microbiological stime, and other deposits. An initial slug addition of 16 0 to 32 0 fluid ounces of Series 3020 per 1000 gallons of water to provide a concentration of 30 to 40 parts per million of Series 3020, based on an active quaternary backs. Repeat initial dosage until control is evident.

. Subsequent slug ac utions of 4.0 to 12.0 fluid ounces of Series 3020 per 1000 gallons of water (5 to 15 parts per million of Series 3020 on an active quaternary basis) should the employed every 2 to 5 days, or as needed. The frequency of addition depends upon the relative amount of bleedoff and the severity of the microbiological problem. Slug additions should be made in the sump of water cooling towers.

Series 3020 is used to control bacteria in industrial air-washing systems that maintain effective mist eliminating components. Prior to its use, systems should be cleaned to remove bacterial slime and other deposits. An initial slug dose of 22.0 to 64 0 fluid ounces of Series 3020 per 1000 gallons of water is recommended. Repeat initial dosage until control is evident. Subsequent slug additions of 8.0 to 16.0 fluid ounces of Series 3020 per 1000 gallons of water should be employed each 1 to 5 days, or as needed. The frequency of addition depends upon the relative amount of bleedoff and severity of the bacterial problem. Slug additions may be made to the sump or to the water collection trays of the airwash system

Manufactured by
Ouatic Southern, Inc.
Suite C
n Trail Industrial Parkway
Norcross, Georgia 30071

EPA REGISTRATION NO. 43104-3
EPA ESTABLISHMENT NO. 43104 GA

Net Content: ___

39