

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS (AND DOMESTIC ANIMALS)

WARNING May be fatal if swallowed (inhaled or absorbed through the skin). Do not breath vapors. Causes eye irritation. Do not get in eyes, on skin or on clothing. In case of contact, immediately flush eyes or skin with plenty of water. If swallowed, do not induce vomiting. CALL PHYSICIAN IMMEDIATELY.

ENVIRONMENTAL HAZARDS

This product is toxic to fish. Treated effluent should not be discharged where it will drain into lakes, streams, ponds, or public water. Do not contaminate water by cleaning of equipment or disposal of wastes.

PHYSICAL OR CHEMICÁL HAZARDS

CAUTION Do not use or store near heat or open flame. Use with adequate ventilation. Avoid breathing vapors.



8% ZINC NAPHTHENATE

Preservative for Textiles and Wood

Total 100%

BEST DOCUMENT AVAILABLE

KEEP OUT OF REACH OF CHILDREN WARNING

Dussek Bros. (Canada) Ltd., Belleville, Ontario, Canada EPA Reg. No. 43437-3 EPA Est. No. 43437-CN-1

NET WT 400 LBS



515-5516

DIRECTIONS FOR USE

It is a violation of federal law to use this product in a manner inconsistent with its labeling.

STORAGE AND DISPOSAL

Prohibitions — Do not contaminate water, food or feed by storage or disposal. Open dumping is prohibited.

Pesticide disposal — Pesticide or rinsate that cannot be used or chemically reprocessed should be disposed of according to procedures approved by federal, state or local disposal authorities.

Container disposal — Reseal container and offer for reconditioning or triple rinse and offer for recycling, reconditioning or disposal in approved landfill or bury in a safe place.

APPLICATION PROCEDURES

8% Zinc naphthenate should be used at a level of 10 to 20 percent, applied as a dip or brush treatment to wood such as fence posts, patio decking, ladders, millwork, greenhouse benches and similar items. Lumber items should be totally immersed in the ready to use solution for a period of 3 seconds to 3 minutes depending on the absorbtion required or they may be sprayed or brushed until run off occurs. The wood should then be drained of excess solution and allowed to air dry until all solvent has evaporated and the wood is tree of solvent odor.

Fabric such as cotton duck should be immersed in the ready to use solution, passed through suitable squeeze rolls and dried by festooning or passing over dry-cans. Amount of product deposited can be determined by electrolytic or Spectro-photometric analysis. It is recommended that 0.8% to 1.5% Zinc be deposited in the treated fabric. Higher levels are recommended for those areas where extensive weathering and/or leaching are commonplace.

It is readily soluble in mineral spirits (Stoddard's solvent) and may be combined with standard solvent soluble water repellents such as petroleum waxes and/or resins. This product should not be used whe: it may be in contact with food or agricultural products.

更到

2/2

