

COPPER NAPHTHENATE

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS (AND DOMESTIC ANIMALS)

WARNING: May be fatal if swallowed, (inhaled or absorbed through the skin). Do not breath vapors. Causes eye irritation. Do not get in eyes, on skin or on clothing. In case of contact, immediately flush eyes or skin with plenty of water. If swallowed, do not induce vomiting. CALL PHYSICIAN IMMEDIATELY.

ENVIRONMENTAL HAZARDS

This product is toxic to fish. Do not apply directly to water, in areas where surface water is present or to intertidal areas below the mean high water mark. Do not contaminate water when disposing of equipment washwaters.

PHYSICAL OR CHEMICAL HAZARDS

Do not use or store near heat or open flame. Use with adequate ventilation. Avoid breathing vapors.

STATEMENTS OF PRACTICAL TREATMENT

- If swallowed, do not induce vomiting. Call physician immediately.
- If splashed in eyes, flush with clean water for 15 minutes and contact a physician.
- In case of skin contact, remove the product from the skin promptly by washing with vegetable oil or hand degreaser and then with soap and water.

DIRECTIONS FOR USE

It is a violation of federal law to use this product in a manner inconsistent with its labeling.

This preservative protects wood against fungal rot, decay, termites and wood-boring insects and is used for treatment of wood in ground contact and also for above ground uses.

Dussek Campbell's 8% Copper Naphthenate complies with the preservative standards as issued in the AWWPA Book of Standards. 8% Copper Naphthenate is a concentrate solution of Copper Naphthenate which should be diluted with suitable organic solvents such as petroleum hydrocarbons. It can be applied to wood such as utility poles, fence posts, cross ties, patio decking, millwork, landscape logs and timber, decking, greenhouse wood and stakes, bridge timber and other similar items.

PRESERVATIVE FOR TEXTILES AND WOOD

Active Ingredient:

Copper Naphthenate* 89%

Inert Ingredient: 11%

Total 100%

*Copper as metal 8%

KEEP OUT OF REACH OF CHILDREN

WARNING

SEE SIDE PANEL FOR ADDITIONAL
PRECAUTIONARY STATEMENTS.

EPA Reg. No. 43437-4

EPA Est. No. 43437-CN-1

Net Wt: 441 lbs.

Net _____ Gallons

ACCEPTED

JAN 31 1992

Under the Federal Insecticide,
Fungicide and Rodenticide Act,
as amended, for the pesticide
registered under
EPA Reg. No. 43437-4

SPECIFIC USES: For treatment by Pressure, Vacuum or Thermal Methods: Blend one (1) part by volume of 8% Copper Naphthenate with (7) parts by volume of Aliphatic Hydrocarbon Reducing Solvent. A Copper solution of 0.5% to 1.5% is recommended. Full details are provided in the AWWPA standards regarding desired retention levels and proper pressure treatment methods for different wood species. AWWPA Book of Standards should be consulted for recommended dilution concentration for each wood species. Use of this product in industrial settings requires adequate engineered ventilation and containment in the treating area and in the area where wood is dried.

SPECIFIC USES: For treatment by dipping or brushing:

Blend one (1) part by volume of 8% Copper Naphthenate with (9) parts by volume of Aliphatic Hydrocarbon Reducing Solvent when applying to wood such as fence posts, patio decking, ladders, millwork, greenhouse benches and similar items. Lumber and other structural members not to be placed in contact with soil should be immersed for a period of 3 minutes per inch of thickness or receive two or more coats by brush or spray. All lumber to be treated should be free of bark, dry and well seasoned. After treatment the wood should be drained of excess solution and allowed to air dry until all solvent has evaporated and the wood is free of solvent odor.

PRESERVATIVE FOR TEXTILES: 8% Copper Naphthenate is used to control rot and mildew in heavy duty textiles. For industrial duck, tents, truck and boat covers, rope and other non-rubber fabrics it is recommended that 0.8% to 1.2% Copper by weight be deposited in the treated fabric. Deposition depends on severity of exposure and degree of protection required. The preservative is normally applied in combination with waterproofing, fire retardants and pigments.

LIMITATIONS: FOR EXTERIOR USE ONLY:

Do not apply to logs used in the construction of log homes or for any interior application. Do not apply where the preservative may contaminate food, feed or drinking water.

STORAGE AND DISPOSAL

Pesticide Disposal: Rinse the emptied container thoroughly and use the rinsings for treatment. Wastes resulting from the use of this product may be disposed of on land or at an approved waste disposal site.

Container Disposal: Triple rinse and offer for recycling or reconditioning or puncture and dispose of in a sanitary landfill, or by other procedures approved by state or local authorities.

Prohibitions: Do not contaminate water, food or feed by storage or disposal.

 **Dussek Campbell Limited**
A Burmah Castrol Company
PO Box 385, 30 Dussek Street
Belleville, Ontario K8N 5A5

43437-4

01/31/1992

1/1