PRECAUTIONARY STATEMENTS Hazards to Humans and Domestic Animals.

KEEP OUT OF REACH OF CHILDREN DANGER - POISON

Auminum or magnesium phurphide power, granules or tablets may be tatal if sumiowed, Do not get in eves, on skin or on clothing. Do not eat, drink or smoke while handling aluminum or magnesium phosphide junicants. If a seeled container is opened, or if the material current in contact with moisture, water or acids, extremely toxic photohine cas will be released. If a natic odor a detected, you must monitor to determine whether phosphine gas is present above the accentable exposite limits (see section on respiratory ordection). Since an odor may not be detected under certain circumstances, the absence of a garlic odor does not mean that phosphine gas is absent. Observe proper application, seration, reentry and disposal procedures apacified elevenhere in the labeling to prevent oversponsure

ž

Physical/Chemical Hazards

Auminum phosphids in tablets, pallets, bags or partially spent dust will release phosphine cas I emosed to moisture from the air of I I comes into contact with water, acids and many other liquids. Pilino of lablets, pellets, bags or dust from their fragmentation may cause a temperature increase and contine the release of gas so that ignition could occur.

Always open container of aluminum phosphide products outdoors as under certain conditions, they may flash upon opening. When opening, point the container away from the face and body and slowly loosen the cap. Although the chances for flash are very remote, never open these containers in a flammable almosphere. These precautions will also reduce the applicator's exposure to chosphine ges.

Pure phosphine gas is practically insclubie in water, and oils, and is stable at normal furnication terroperatures, However, it may react with certain metals and cause corrosion, especially at higher temperatures and relative humidities, Metals such as cooper, brass and other cooper alloys, and precious metals such as gold and silver are susceptible to concision by phosphine. Thus, small electric motors, smoke detectors, brass sprinkler heads, batteries and bettery chargers, lork lifts, temperature monitoring systems, switching dears, communication devices, computers, calculators of other electrical equipment should be protected or removed before lumigation,

Phosphine gas will also react with certain metallic saits and, therefore, sensitive sems such as photographic film, some inorganic pigments, etc., should not be exposed.

ENVIRONMENTAL HAZARDS

This product is toxic to fish and wildlife. Do not discharge effluent containing this product into takes, streams, ponds, estuaries, oceans, or public waters, unless this product is specifically identified and addressed in a National Pollutant Discharge Elimination System (NPDES) permit. Do not discharge effluent containing this product to server systems without previously notifying the severage instiment plan authority. For guidance confact your State Water Board, or Regional Office of EPA.

"Environmental Hazarda"; This product is very highly toxic to widthe, Nontarget organiems exposed to phosphine gas in butrows will be killed. Do not apply directly to water or wetlands (swamps, bogs, marshee, and putholes). Do not conterninate water by cleaning of equipment or disposal of waster.

Clessified by Underwriter's Laboratories, Inc., as to fire hazard only when used as directed in the separate instruction that are part of the product labeling. L-Fume is noncombustible, but exposure to moist air or water releases flammable and toxic phosphine gas. Spontaneous ignition may result if contacted by water, add or chemicals.

RESTRICED USE PESTICIDE DUE TO ACUTE INHALATION TOXICITY OF HIGHLY TOXIC PHOSPHINE GAS

For retail sale to and use only by Certified Applicators for those uses covered by the applicators certification or persons trained in accordance with the attached product manual working under the direct supervision and in the physical presence of the Certified Applicator on sue or on the premises. Read and follow the label and the Quick phos product manual which contains complete instructions for the safe use of this pesticide.

QUICK-PHOS **ALUMINUM PHOSPHIDE FUMIGANT** BAGS

A furnisant for use against listed insects which infest listed raw Agriculture Commodities, Specified Processed Foods and Animal Feeds. (See Product Manual)

ACTIVE INGREDIENT:

Aluminum Phosphic	b	60%
INERT INGREDIENT	TS-	40%
	Total	. 100%
	AL 4841-7-1 A 4874	

Contents: 6 - 10 bags

Net Weight: 154 - 340 grams ea.

KE	EP OUT OF REACH OF CHILDRI	EN
	DANGER - PELIGRO - POISON	
RECALICIÓ	N AL USUARID: Studied no lee Ingles, no se este producto hasta que l	in of

etigeta se le hava sido explicado ampliamente. PRACTICAL TREATMENT STATEMENT

PRACTICAL TREATMENT STATEMENT Symptoms of overaposure to phosphine are headache, dizzinese, nausea, difficult breathing, vomifing and diaritea. In all cases of overaposure get medical attention immediately. Take victim to a doctor or emergency ineatment facility. It the gas from atumitum or magnesium phosphile is inhaled: Get exposed person to fresh at Keep werm and make sure person can break freshy. It breathing has stopped, give antificial respiration by mouth to mouth or other means of resulcation. Do not give anything

Argential regression by incursions person. If aluminum or megnesium phosphäle prwder, granules, pelleta or tablets are swattowed: Drink or administer one or two glesses of water and induce vortiling by touching back of throat with linger, or if available, symp of lpaces. Do not give anything by mouth if victim le unconscious or not sign.

If powder, granules or tablets of aluminum or megnesium phosphide get on skin: Brush material of cluthes and shoes in a well ventilited sees. Allow clothes to serale in a ventilisted area prior to laundering. Wesh conterninated bare skin throughly with scep and water. It is even: Flush with planty of water, Gat readical altertion, SEE SIDE PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS

SEE SIDE PANELS FOR ADDITIONAL PRECAUTIONARY STATEMENTS

MANUFACTURED BY: Invento Corporation, Worl Bombay, India 400 018

MANUFACTURED FOR PHOS-FUNE CHEMICAL COMPANY, INC

12703 W. St., Overland Park, KS, 66210 EPA REGISTRATION NO. 43568-2 EPA ESTABLISHMENT NO. 41876-1Y-1

D'RECTIONS FOR USE:

"It is a violation of Federal Law to use the traduct in a more incomistent with its ta'reling

1 - - - 1

This furniciant is a highly haza dous material a d may only be used by individuals trained in its process use. Before using, read and rollow all precautions and directions on the label and in the product manual. See Product manual for OUICK-PHOS Applicator's Manual for complete une directions, available from FHOS FARE CHERICAL COMPANY, INC.

12/03 W SL Ouerland Path KS 65210

At least two trained persons must be present when the product is applied from within a space to be jurninated or during mentry into a jurnicated or partially -----

Prior to applying this product, you must trapact the site to be furnicated to determine if a can be made sufficiently cas tight. You should also develop a plan for monitoring (if not done before) how to most efficiently and safely apply the fumigant, emergency procedures, etc. Notity appropriate company employees and provide miswant safety information annually to local officials having lurisdiction (fine department, rescue squad, police, etc.) over the furnication site. Follow all local and state requiations. Take or mail applicator's (Carried)

Shibholde, barges, containers on ships, railroad cars and containers shipped plogyback by rail may be furnigated in transit. However, trucks, yans, trailers and similar transport vehicles cannot be moved over oublic roads or highways until the furnigation is completed. Do not furnigate commodities with this product when commoday temperature is below 40°F. (5°C.).

Protective Clophing, Wear dry gloves when handling unpackaged tablets or pellets, Wash hands thorwahly after use before smoking or eating.

Storage and Handling

Store in a dry, well ventilated area away from heat, under lock and key. Post as a pesticide storage area. Do not contaminate water, food or feed by storing peticides in the same area used to store these commodities. Do not store in buildings inhabited by humans or domestic animals.

Disposal Statements

General Disposet Statements. Do not contaminate water, food or feed by storage or disposal. Unsected or partially reacted aluminum phosphide is acutely hazardous, improver discussi of excess pesticide, spray mixture, or rinsate a a violation of Federal Law, If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance. For specific instructions, see Soil and Leak Procedures. Papers 30-31 of Product Manual.

Some local and state waste disposal regulations may vary from the following recommendations. Dispose) procedures should be reviewed with appropriate authorities to ensure compliance with local regulations. Contact your State Petiticide or Environmental Control Agency or Hazardous Waste Specialist at the nearest EPA Regional Office for guidance.

Triple rines itusks and stoppers with water. Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landial, or by other procedures approved by state and local authorities. Rinsate may be disposed of In a sanitary server, sunitary landfill or by other approved procedures. It is also permissible to remove lids and expose empty flashs outdoors until residue in the flask is meeted. Then puncture and dispose of in a sanitary landfill or other approved site, or by other procedures approved by state and local authorities,

If properly exposed, the residual dust remaining after a lumigation with aluminum phosphide will be gravish white and contain only a small amount of unreacted material, However, residual dust from incompletely exposed aluminum phosphide will require special care.

DISPOSAL OF BAGS: See Product Manual, Page 30

See Product Manual, "Spill & Leak Procedures", page 30 and 31 of Applicator's Manual

NOT REVIEWED

In Accordance with PR Notice 82-24 Based on Draft Labeling Dated 3-24

label and PHOS-FUME CHEMICAL CO. product manual of off the premises. read and follow the which contains complete instructions for the safe use of this pesticide.

3

TO ACCOPTION WITH TR Notice St Based on Draft Landling Dated

ŧ

APPLICATION PROCEDURES 2 **EXPOSURE GUIDE** FOR

QUICK - PHOS

BAG PELLETS TABLETS

PHOSPHINE FUMIGANTS FOH USE AGAINST LISTED INSECTS WHICH INFEST LISTED RAW AGRICULTURAL COMMODITIES, ANIMAL FEEDS, PROCESSED FOODS. NON-FOOD PRODUCTS, AND STORED TOBACCO

PHOS-FUME CHEMICAL COMPANY

12703 W. 117th Street Overland Park, KS. 66210

EPA No.___ 43568-1-2-3



DUE TO ACKO INHALATION TOXICITY OF HIC TOXIC HYDROGEN PHOSPHIDE (PHOSPHINE, PH3) GAS

3

For retail sale and use only by certified applicators for those uses covered by the applicator certification or persons trained in accordance with the Applicators Manual working under the direct supervision and in the physical presence of the certified applicator. Physical presence means on site or on the premises.

Read and follow the label and the Applicators Manual which contains complete instructions for the safe use of this pesticide.

APPLICATOR'S MANUAL FOR QUICK-PHOS, TABLETS, PELLETS, AND BAGS

For use against insects which infest stored Commodities and Control of Burrowing Pests

KEEP OUT OF REACH OF CHILDREN

DANGER - POISON - PELIGRO

PELIGRO AL USUARIO: Si usted no lee ingles, no use este producto hasta que la etiqueta se la hay sido explicado ampliamente.

(TO THE USER: If you cannot read English, do not use this product until the label has been fully explained to you.

1

STATEMENT OF PRACTICAL TREATMENT Symptoms of overexposure are headache, dizziness, nausea, difficult breathing, vomiting, and diarrhea. In all cases of overexposure get medical attention immediately. Take victim to a doctor or emergency treatment facility.

If the gas or dust from aluminum phosphide is inhaled:

Get exposed person to fresh air. Keep warm and make sure person can breathe freely. If breathing has stopped give artificial respiration by mouth-to-mouth or other means of resuscitation. Do not give anything to an unconscious person.

If aluminum phosphide pellets, tablets, or bags are swallowed:

Drink or administer one or two glasses of water and induce vomiting by touching the back of of the throat with finger, or if available, syrup of ipecac. Do not give anything by mouth if victim is unconscious or not alert.

If powder or granules of aluminum phosphide get on skin or clothing:

Brush or shake material off clothes and shoes in a well ventilated area. Allow clothes to aerate in a ventilated area prior to laundering. Do not leave contaminated clothing in occupied and or confined areas such as automobiles, vans, motel rooms, etc. Wash contaminated skin thoroughly with soap and water

It dust from pellets or tablets gets in eyes: Flush with plenty of water. Get medical attention.

THIS PRODUCT IS ACCOMPANIED BY AN APPROVED LABEL AND APPLICATOR'S MANUAL. READ AND UNDERSTAND THE ENTIRE LABELING. ALL PARTS OF THE LABELING ARE EQUALLY IMPORTANT FOR SAFE AND EFFECTIVE USE OF THIS PRODUCT. CALL QUICK-PHOS, INC. OR EPA IF YOU HAVE ANY QUESTIONS OR DO NOT UNDERSTAND ANY PART OF THIS LABELING.

REFER TO THE APPLICATOR'S MANUAL FOR DETAILED PRECAUTIONS, RECOMMENDATIONS AND DIRECTIONS FOR USE.

WARRANTY

Seller warrants that the product conforms to its chemical description and when used according to label directions under normal conditions of use, it is reasonably fit for the purposes stated on the label. Seller makes no other warranty, either express or implied, and buyer assumes all risk should the product be used contrary to label instructions.

CLASSIFIED BY UNDERWRITERS LABORATORIES, INC.AS TO FIRE HAZARD ONLY WHEN USED SPECIFICALLY AS DIRECTED IN THE MANUFACTURER'S INSTRUCTIONS. QUICK-PHOS TABLETS, PELLETS, AND BAGS ARE NONCOMBUSTIBLE. BUT EXPOSURE TO MOIST AIR OR WATER RELEASES FLAMMABLE AND TOXIC PHOSPHINE (HYDROGEN PHOSPHIDE) GAS. SPONTANEOUS IGNITION MAY RESULT IF CONTACTED BY WATER, ACIDS, OR CHEMICALS.

TABLE OF CONTENT

1. INTRODUCTION

2. PRECAUTIONARY STATEMENTS

٦Ł -

- A. Hazards to Humans and Domestic Animals
- B. Statement of Practical Treatment
- C. Note to Physician
- D. Physical and Chemical Hazards

3. DIRECTIONS FOR USE

- A. General
- B. Efficacy
- C. Exposure Conditions
- D. Commodities Which May be Fumigated with L-F
- E. Recommended Dosages
- F. Application Procedures

4. PROTECTIVE CLOTHING

5. RESPIRATORY PROTECTION

- A. When Respiratory Protection Must be Worn
 B. Permissible Gas Concentration Ranges for Re atory Protection Devices
- C. Requirements for Availability of Respiratory Protection.
- 6. PLACARDING OF FUMIGATED AREAS
- 7. AERATION OF FUMIGATED COMMODITIE A. Foods and Feeds
 - B. Tobacco

8. APPLICATORS AND WORKER EXPOSUR

- A. Hydrogen Phosphide Exposure Limits
- B. Application of Furnigant
- C. Leakage from Fumigated Sites
- D. Aeration and Reentry
- E. Handling Unaerated Commodities
- F. Industrial Hygiene Monitoring
- 9. STORAGE INSTRUCTIONS

10. DISPOSAL INSTRUCTIONS A. General

- B. Directions Disposal of Residual Dust from QUI
- C. Directions for Deactivation of Residual Dust In QUICK-PHOS

SECTION 1

QUICK-PHOS lumigants are used to protect stored $_{\rm eff}$ bodities from damage by insects and for the control of burrowing pests. Fumigation of stored products with QUICK-PHOS in the manner prescribed – in the labeling does not contaminate the stored commodity.

OUICK-PHOS and other Aluminum Phosphide fumigants are acted upon by a'mospheric moisture to produce Hydrogen Phosphide (phosphine, PH3) gas. OUICK-PHOS tablets, pellets, and bags contain aluminum phosphide (ALP) as their active ingredient and will liberate hydrogen phosphide via the following chemical reaction:

Hydrogen phosphide gas is highly toxic to insect, burrowing pests humans, and other forms of animal life. In addition to its toxic properties, the gas will corrode certain metals and may ignite spontaneously in air at concentrations above its tower flammable limit of 1.8% (v/v). These hazards will be described in greater detail fater on its this Applicators Manual for _QUICK-PHOS pellets, tablets, and bags.

QUICK-PHOS also contains ammonium carbamate which liberates ammonia and carbon dioxide as follows:

$$NH_2COONH_4 \dots > 2NH_3 + CO_2$$

These gases are essentially nonflammable and act as inerting agents to reduce fire hazards. The ammonia gas also serves as a warning agent.

QUICK-PHOS is prepared in three forms, tablets, pellets, ands bags. The rounded tablets weigh approximately 3 grams and release 1 gram of hydrogen phosphide gas. They are about 10mm in diameter and are bulk packaged in reseatable aluminum flasks containing 100 or 500 tablets each. The pellets weigh approximately 0.6 gram and release 0.2 gram of hydrogen phosphide gas. They are about 10mm in diameter and are packaged in reseatable flasks containing about 1660 pellets.

The bags weigh 34 grams each and release 11 grams of hydrogen phosphide gas. They are packaged in aluminum containers of six, ten, or one hundred bags to the container. The bags are packaged in an oxygen free environment.

Upon exposure to air QUICK-PHOS pellets, tablets, and bags begin to react with atmospheric moisture to produce small quantities of hydrogen phosphide gas. This reaction starts slowly, gradually accelerates and then tapers off again as the aluminum phosphide is spent. QUICK-PHOS pellets react somewhat

faster than do the tat⁴ and bags. The rates of decomposition of Li thets. pellets and bags will vary depending upon moisture and temperature conditions. For example, when moisture and temperature of the funigated cosmodity are high, decomposition of QUICK-PHOS may be complete in less than 3 days However at lower ambient temperatures and relative humidaty levels. decomposition of QUICK-PHOS may require 5 days or more After decomposition, QUICK-PHOS leaves a gray-white powder composed almost entirely of aluminum hydroxide and other approved inert ingredients. Less with cause no problems if the fumigant has been added directly to commodity such as grain or bulk animal feed. However, the spent powder must usually be retrieved for disposal after space fumigations. If properly exposed, the spent QUICK-PHOS will normally contain only a small amount of unreacted aluminum phosphide and may be disposed without hazard. While not considered a hazardous waste, partially spent residual from incompletely expored OUICK PHOS will require special care. Precautions and instructions for further deactivation and disposal will be given later in this Manual

OUICK-PHOS pellets, tablets and bags are supplied in gas tight containers and their shell life is unlimited as long as the packaging remains infact. Once opened for fumigation, the flasks of tablets and pellets may be tightly resealed and stored for future use. QUICK-PHOS bags container cannot be resealed for future use. Storage and handling instructions will be given in detail later in the Applicators Manual.

A summary of safety recommendations is outlined below:

SAFETY RECOMMENDATION SUMMARY

- 1. Carefully read the labeling and follow instructions
- 2. Never fumigate alone from inside the storage structure.
- Person supervising must be a certilied fumigator an personnel assisting must be trained in the use of QUICK-PHOS. Never allow uninstructed personnel to handle QUICK-PHOS
- 4. Approved respiratory protection must be available for the fumigation of structures from within.
- Wear dry gloves of cotton or other material if contact with QUICK-PHOS tablets, pellets or bags is likely. Aerate used gloves and other contaminated clothing in a well ventilated area prior to laundering. Wash hands thoroughly after using QUICK-PHOS.
- 6. Open fumigant containers in open air only. Nevel open in a flammable atmosphere.
- 7. Do not allow QUICK-PHOS to contact liquid water or pile up.
- Dispose of empty containers and spent residual dust in a manner consistent with the label instructions.
- 9. Post warning placards on lumigated areas.

٠

- 10. Prior to fumigation, notify appropriate company employees. Provide to tocal officials (fire department, rescue squad, police, etc. on an annual basis relevant salety information for use in the event of an emergency.
- 11. Hydrogen phosphide lumigants are not to be used for vacuum lumigations.
- 12. Exposure to hydrogen phosphide must not exceed the eight hour TWA of 0.3 ppm during application, or a

5:2

*

concentration of 0.3 ppm after application i

- Fumigated areas must be aerated to 0.3 ppm hydrogen phosphide or less prior to reentry by unprotected workers.
- 14. Finished loods and leeds have been tumigated with OUICK-PHOS must be aerated for 48 hours prior to offering to the end use consumer.
- 15. Transfer of a treated commodity to another site without complete aeration is permissible provided that the new storage site is placarded it its concentration is above 0.3 ppm..
- 16. Keep containers of QUICK-PHOS tightly closed except while removing product for application.
- 17. Protect materials containing metals such as copper, silver, gold and their alloys and salts from corrosive exposure to hydrogen phosphide.
- Tablets, pellets and bags must not come in contact with any processed food that may be added directly to processed brewers rice, malt and corn grits used in the manufacture of beer.
- Do not use aluminum phosphide containers for any purpose other than recycling or reconditioning.
- 20. OSHA recommends preexposure screening of employees to detect impaired pulmonary function. They recommend that any employees developing this condition be referred for medical examination.

SECTION 2 PRECAUTIONARY STATEMENTS

A. Hazards to Humans and Domestic Animais

DANGER: Aluminum phosphide from QUICK-PHOS tablets, pellets or bags may be fatal it swallowed. Do not get in eyes, on skin or on clothing. Do not eat, drink or smoke while handling aluminum phosphide fumigants. If a sealed container is opened, or of the material comes in contact with moisture, water or acids, these products will release hydrogen phosphide (phosphine, PH3) which is an extremely toxic gas. If a garlic odor is detected refer to the Industrial Hygiene Monitoring section on page 28 of the Applicators Manual for appropriate monitoring procedures. Pure hydrogen phosphide gas is odortess: the garlic odor is due to contaminant. Since the odor of hydrogen phosphide may not be detected under some circumstances, the absence of a garlic odor does not mean that dangerous levels of hydrogen phosphide gas are absent. Observe proper reentry procedures specified elsewhere in the labeling to prevent overexposure.

B. Statement of Practical Treatment

Symptoms of overexposure are headache, dizziness, nausea, difficult breathing, vomiting, and diarrhea. In all cases of overexposure get medical attention immediately. Take victim to a doctor or emergency treatment facility.

It the gas or dust from aluminum phosphide is inhaled:

Get exposed person⁴ esh air. Keep warm and make sure person, preathe freely. If breathing has stopped, give artificial respiration by mouth-to-mouth or other means of resuscitation. Do not give anything by mouth to an unconscious person.

Il aluminum phosphide pellets tablets or bags are swallowed

Drink or administer one or two glasses of water and induce vomiting by touching back of throat with linger, or it available, syrup of ipecac. Do not give anything by mouth it victim is unconscious or not alert.

It powder or granules of aluminum phosphide get on skin or clothing: Brush or

shake material off clothes and shoes in a well ventilated area. Allow clothes to aerate in a ventilated area prior to laundering. Do not leave contaminated clothing in occupied and/or confined areas such as automobiles, vans, motel rooms, etc. Wash contaminated skin thoroughly with soap and water.

If dust from pellets, tablets or bags gets in eyes:

Flush with plenty of water. Get medical attention.

1

C. Note to Physician (we recommend that this section be given to the attending physician)

Aluminum phosphide tablets, pellets or bags react with moisture from the air, acids and many other liquids to release hydrogen phosphide (phosphine PHg) gas. Mild exposure by inhalation causes mataise (indefinite feeling of sickness) ringing in the ears, fatigue, nausea and pressure in the chest which is relieved by removal to tresh air. Moderate poisoning may occur within a few hours to several days resulting in pulmonary edema (fluid in lungs) and may lead to dizziness, cyanosis (blue or purple skin color), unconsciousness, and death.

In sufficient quantity, phosphine affects the liver, kidneys, lungs, nervous system and circulatory system. Inhalation can cause lung edema (fluid in lungs) and hyperemia (excess of blood in body parts), small perivascular brain hemorrhages and brain edema (fluid in brain). Ingestion can cause lung and brain symptoms but damage to the viscera (body cavity organs) is more common. Phosphine poisoning may result in (1)pulmonary edema, (2) liver elevated serum GOT, LDH and alkaline phosphatase, reduced prothrombin, hemorrhage, and jaundice (yellow skin color) and (3) kidney hematuria (blood in urine) and anuria (abnormal or lack of urination). Pathology is characteristic of hypoxia (oxygen deficiency in body tissue). Frequent exposure to concentration above permissible levels over a period of days or weeks may cause poisoning. Treatment is symptomatic.

The following measures are suggested for use by the physician in accordance with his own judgement:

In its milder forms, symptoms of poisoning may take some time (up to 24 horto make their appearance, and the following is suggested.

1. Give complete rest (or 1-2 days, during which the patient must be ker and warm.

2. Stop patient suffer from vomiting or increased () sugar, appropriate solutions should be administered.

Treatment with oxygen breathing equipment is recommended as is the administration of cardiac and circulatory stimulants.

In cases of severe poisoning (Intensive Care Unit recommended);

1. Where pulmonary edema is observed, steroid therapy should be considered and close medical supervision is recommended. Blood transfusions may be necessary.

2. In case of manifest pulmonary edema, venesection should be performed under vein pressure control. Heart glycosides (I.V.) (in case of hemoconcentration, venesection may result in shock). On progressive edema of the lungs: immediate intubation with a constant removal of edema fluid and oxygen over-pressure respiration, as well as any measures required for shock treatment. In case of kidney failure extracorporeal hemodialysis is necessary. Their is no specific antidote known for the poisoning.

3. Mention should be made of here of suicidal attempts by taking solid phosphide by mouth. After swallowing:

emptying of the stomach by vomiting, flushing of the stomach with diluted potassium permanganate solution of magnesium peroxide until flushing ceases to smell of carbide. Thereafter apply carbomedicinalis.

D. Physical and Chemical Hazards

Aluminum phosphide in tablets, pellets and bags will release hydrogen phosphide if exposed to moisture from the air or if it comes in contact with water, acids and many other liquids. Piling of tablets, pellets, or bags from their fragmentation may cause a temperature increase and confine the release of gas so that ignition could occur.

It is preferable to open containers of aluminum phosphide products in open air, as under certain conditions, they may flash upon opening. You may also wish to open containers near a tan or other appropriate

ventilation which will rapidly exhaust contaminated air.

When opening, point the container away from the face and body and slowly loosen the cap. Although the chances for a flash are remote never open the containers

in a flammable atmosphere. These precautions will also reduce the fumigator's exposure to hydrogen phosphide.

Pure phosphine (hydrogen phosphide) gas is practically insoluble in water, fats and oils, and is stable at normal fumigation temperatures. However, it may react with cortain metals and cause corrosion, especially

at higher temperatures and relative humidities. Metals such as copper, brass and other copper alloys, and precious metals such as gold and silver are susceptible to corrosion by phosphine. Thus, small electric motors, smoke detectors . brass sprinkler heads, batteries and battery chargers, fork lifts, temperature monitoring systems, switching gears, communication devices, computers, calculators and other electrical equipment should be protected or removed before fumigation. Hydrogen phosphide will also react with certain metallic

salts and therelore, sensitive items such as photographic film, some inorganic pigments, etc. should not be exposed.

SECTION 3 DIRECTIONS FOR USE

A. General

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

1. QUICK-PHOS tablets, pellets and bags are Restricted Use Pesticide due to the acute inhalation of hydrogen phosphide (phosphine PH 3) gas. These products are retail sale to and use only by certified applicators for uses covered by the applicators certification or person trained in accordance with the Applicators Manual working under the direct supervision and in the physical presence of the applicator. Physical presence means on site or on the premises.Read and follow the label and the QUICK-PHOS Applicators Manual which contains complete instructions for the safe use of this pesticide.

2. QUICK-PHOS is a highly hazardous material and should be used only by individuals trained in its proper use. Before using read and follow the label precautions and directions.

Additional copies of this Manual are available from:

PHOS-FUME CHEMICAL COMPANY, INC 12703 W. 117th St., Overland Park, KS 66210

Persons working with QUICK-PHOS should be knowledgeable of the hazards of this chemical and trained in the use of required respiratory equipment and detector device, emergency procedures and use of the fumigant.

3. At least two persons should be trained in the use of QUICK-PHOS must be present during fumigation of structure if entry into the structure is required for application of the fumigant. Two trained persons must also be present during reentry into fumigated or partially aerated structures. Only one trained person is required to be present when QUICK-PHOS is applied from outside the area to be treated.

4. Shipholds, barges, containers on ships, railroad cars and containers shipped piggyback by railway be fumigated intransit. However, trucks, vans, trailers and similar transport vehicles cannot be moved over public roads and highways until they are aerated and the warning placards removed.

5. Do not furnigate commodities with QUICK-PHOS when commodity temperature is below 40 degrees F. (5 degrees C.).

6. The site to be lumigated must first be inspected to determine if it can be sufficiently gas tight. Then a plan should be developed to provide for safe and efficient application of the tumigant to include emergency procedures etc.,

where n ed, and to decide how monitoring should conducted to prevent excessive exposures.

7. Wear dry gloves of cotton or other material while handling QUICK-PHOS tablets, pellets, or bags. Wash hands thoroughly after use.

8. Hydrogen phosphide gas may flash at concentration above its flammable limit. Therefore, always open QUICK-PHOS containers in open air and never in a flammable atmosphere. This precaution will not only prevent harm in the unlikely event of a flash but ,will reduce the applicators exposure to hydrogen phosphide gas.

9. Piling of tablets, pellets or bags or aduition of liquid water to QUICK-PHOS may speed up the reaction, cause a temperature increase and confine the gas to that ignition could occur.

10. As much as is possible protect unused QUICK-PHOS from excessive exposure to atmospheric moisture during application and tightly reseal the aluminum flask prior to returning tablets or pellets to storage. QUICK-PHOS bag containers once opened cannot be resealed for future use.

11. Hydrogen phosphide gas may react with certain metals and their salts to produce corrosion. Copper, copper alloys and precious metals such as silver and gold and gold are susceptible to corrosion and items containing these elements should be removed or protected prior to fumigation with QUICK PHOS.

12. Do not allow QUICK-PHOS or its residual dust to come in contact with processed foods or commodity packages intended for retailers except that QUICK-PHOS tablets, pellets or bags may be added directly to processed brewers rice, malt and corn grits used in the manufacture of beer.

13. Respiratory protection approved for the concentration to which the fumigator will be exposed must be available if QUICK-PHOS is to be applied from within the structure to be fumigated. Respiratory protection need not be available for uses such as outdoor application, addition of tablets or pellets to automatic dispensing devices, etc., if exposures above the TLV's will not be encountered.

A NIOSH/MSHA approved, full-face gas mask -hydroger phosphide canister combination may be used at levels up to 15 ppm. Above this level or in situations where the hydrogen phosphide concentration is unknown a NIOSH/MSHA approved, self contained breathing apparatus (SCBA) or its equivalent must be used.

14. Notify appropriate company employees prior to fur.igation.Provide to local officials (fire department, rescue squad, police, etc.) on annual basis relevant safety information for use in the event of an emergency.

B. Efficacy

QUICK-PHOS has been found effective against the following insects and their preadult stages - that is eggs, larvae, and pupae:

almond moth anooumois grain muth bean weevil bees cadelle cereal leaf beetle cigarette beetle confused flour beetle dermestid beetle . dried fruit beetle dried fruit moth European grain moth flat grain beetle truit flies granary weevil greater wax moth

hairy fungus beetle Hessian fly Indian meal moth khapra beetle lesser grain borer maize weevil Mediterranean flour moth pink bolworm raisin moth red flour beetle rice weevil rusty grain weevil saw-toothed grain beatle spider beates tobacco moth yellow meal worm

Although it is possible to achieve total control of the listed insect pests, this is frequently not realized in actual practice. Factors contributing to less than 100% control are leaks, poor gas distribution, unfavorable exposure conditions, etc. In addition, some insects are less susceptible to hydrogen procephide than others. If maximum control is to be attained extreme care must be taken in sealing, the higher dosages must be used, exposure periods must be lengthened, proper application procedures followed and temperature and humidity must be favorable.

C. Exposure Conditions

The following conditions may be used as a guide in determining the minimum length of the exposure period at the indicated temperatures:

Minimum Exposure Periods for QUICK-PHOS

Temperature	Pells	Tablets	Bags
below 40°E (5°C)	Do not fumigate	Do not fumigate	Do not fumigate
40°-53°F (5-12°C)	8 days (192 hours)	10 days (240 hours)	4 days (336 hours)
54°-59° F (12-15°)	4 days (96 hours)	5 days (120 hours)	7 days (168 hours)
60°-68° F (16-20°)	3 days (72 hours)	4 days (96 hours)	4 days (96 hours)
above 68° F (20°C)	2 days (<8 hours)	3 days (72 hours)	3 days (72 hours)

The length of the fumigation must be great enough so as to provide for adequate control of the insect pests which infest the commodity being treated. Additionally, the fumigation period should be long enough to allow for more or less complete reaction of QUICK-PHOS with moisture so that little or no unreacted aluminum phosphide remains. This will minimize exposures during further storage and/or processing of the treated bulk commodity as well as reduce hazards in the disposal of partially spent aluminum phosphide products remaining after space fumigations. The proper length of the fumigation period will vary with exposure conditions since, in general, insects are more difficult to

11

control it lower temperatures and the rate of h gen phosphide gas production by QUICK-PHOS is lower temperatures and humidities.

It should be noted that there is little to be gained by extending the exposure period if the structure to be fumigated has not been carefully sealed or if the distribution of gas is poor and insects are not subjected to lethal concentrations of hydrogen phosphide. Careful sealing is required to ensure that adequate gas levels are retained and proper application procedures must be followed to provide satisfactory distribution of hydrogen phosphide gas. Some structures can only be treated when completely tarped, while others cannot be properly sealed by any means and should not be fumigated. Exposure times must be lengthened to allow for penetration of gas throughout the commodity when fumigant is not uniformly added to the the mass, for example, by surface application or shallow probing. This is particularly important in the lumigation of bulk commodity contained in large < ______es.

Remember, exposure periods in the table are minimum periods and may not be adequate to control all stored products pests under all conditions nor will they always provide for total reaction of QUICK-PHOS, particularly if temperatures and commodity moisture levels or humidity are low during the fumigation.

D. Commodities Which May be Fumigated with QUICK-PHOS

QUICK-PHOS may be used for the fumigation of listed raw agricultural commodities, animal feed and feed ingredients, processed foods, tobacco and certain other nonfood items.

1. Raw Agricultural Commodities, Animal Feed and Feed Ingredients

QUICK-PHOS tablets, pellets and bags may be added directly to animal leed, feed ingredients and raw agricultural commodities stored in bulk. For these commodities not stored in bulk, QUICK-PHOS may be placed in moisture permeable envelopes, on trays, in bags, etc. and fumigated as with processed foods.

Raw Agricultural Commodities and Animal Feed and Feed Ingredients Which May be Fumigated with QUICK-PHOS

Almonds	Flower seed	Sesame Seed
Animal Feed	Grass Seed	Seed & Pod Vegetables
Vegetagbles	Sorghum	Barley
Millet	Brazil nuts	Oals
Soybeans	Cashews	Peanuts
Sunflower Seeds	Cocoa Beans	Pecans
Triticale	Colfee Beans	Pistachio nuts
Vegetable Seeds	Corn	Popcorn
Walnuts	Cottonseed	Rice
Wheat	Dates	rye
Filberts	Salllower Seed	

2. Processer bods

The listed processed loods may be fumigated with QUICK-PHCs. Under no condition shall any processed food or bagged commodity come in contact with QUICK-PHOS tablets, pellets, bags or residual dust except that QUICK-PHOS may be added directly to processed brewer's rice, malt and corn grits for use in the manufacturer of beer.

Processed Foods Which May be Fumigated with QUICK-PHOS

. !

Processed candy and Sugar Cereal Flours and Bakery Mixes Cereal Foods (including cookies, crackers, macaroni, noodles, pasta, pretzels, snack foods and spaghetti) Processed Cereals (including milled fractions and packaged cereals) Cheese and Cheese b, 2 Jucts Chocolate & Chocolate Products (assorted chocolate, chocolate liquor, cocoa, cocoa powder, dark chocolate coating and milk chocolate) Processed Coffee Corn Grits Cured, Dried and Processed Meat Products and Dried Fish Dates and Figs Dried Eggs and Egg Yolk Solids Dried Milk, Dried powdered milk, Nondairy Creamers, and Nonfat Dried Milk Dried or Dehydrated Fruits (apples, dates, figs, peaches, pears, prunes, raisins and sultanas) Processed Herbs, Spices, Seasonings and condiments Malt Processed Nuts (almond, apricot kernels, Brazil nuts, cashews, filberts, peanuts, pecans, pistachio nuts, and walnuts) Processed oats (including oatmeal) Rice (brewers rice grits, enriched and polished wild rice) Processed Tea Dried and Dehydrated Vegetables (beans, carrots, lentils, peas, potato products and spinach) Yeast (including primary yeast)

3. Nonfood commodities, including Tobacco

The listed nontood items may be lumigated with QUICK-PHOS. Tobacco and certain other of the nonfood commodities should not be contacted by tablets, pellets or residual dust.

4. Nonfood Commodities which may be Fumigated with QUICK-PHOS

Processed or Unprocessed Cotton, Wool and other Natural fibers or Cloth, Clothing Straw and Hay Feathers Human Hair, Rubberized Hair, Vulcanized hair Monair Leather Products, Animal Hides and Furs Tobacco Wood, Cut Trees, Wood Chips and Wood and Bamboo Products Seeds (grass seed, ornamental herbaceous plant seed and vegetable seed

E. Recommended Dosages

Hydrogen phosphide is a mobile gas will cenetrate to all parts of the storage structure. Therefore, dosade must be based upon the total volume of the space being treated and not on the amount of commodity it contains. The same amount of QUICK-PHOS is required to treat a 30,000 bushel silo whether it is empty or full of grain unless, of course, the surface of the commodity is sealed off by a tarpaulin. The following dosage ranges are recommended for bulk and space fumigations:

Dosage Guid-lines for Fumidations with QUICK-PHOS

Product	per 1000 cu. ft.*	per 1000 bu.*	
Bags	2 -6	2 - 6	
Pellets	100 - 725	120 - 900	
Tablets	20 - 145	25 - 180	

*Dosage range for dates, nuts & dried truits is 100-200 pellets, 20-40 tablets, 2-6 bags/1000 cu, ft.; 125-250 pellets, 25-50 tablets, 125-250 pellets, 2-6 bags/1000 bu.

These dosages are not to be exceeded. It is important to be aware that a shortened exposure period cannot be fully compensated for with an increased dosage of hydrogen phosphide.

The wide range of dosages listed above is required to handle the variety of fumigation situations encountered in practice. Some what higher dosages are usually recommended under cooler, drier conditions or where exposure periods are relatively short.

However, the major factor in selection of dosage is the ability of the structure to hold hydrogen phosphide gas during the fumigation . A good illustration of this point is comparison of the low dosages required to treat modern , well-sealed warehouses with the higher range used for poorly constructed buildings that cannot be sealed adequately. In certain other fumigations, proper distribution of lethal concentrations of gas to reach all parts of the structure becomes a very important factor in dose selection. An example where this may occur is in the treatment of grain stored in tall silos. Poor gas distribution frequently results when the fumigant cannot be uniformly added to the grain and it must be treated by surface application.

Although it is permissible to choose from the full range of dosages listed above, the following dosages are recommended for the various types of fumigations:

Recommended QUICK-PHOS Dosages for Various Types of Fumigations

Type of Fumigation	Bags	Pellets	Tablets
1. Space mills warehouse etc. Bagged Commodities Processed Fruits & nuts Stored tobacco	2-6/1000 cu. ft. 2-6/1000 cu. ft 2-6/1000 cu. ft. 2-6/1000 cu. ft.	100-300/1000 cu ft. 150-300/1000 cu, ft 100-200/1000 cu, ft 100-200-/1000 cu ft	2 0-60/1000 cu. ft. 30-60/1000 cu. ft 20-40/1000 cu. ft 20-40/1000 cu. ft
2. Bulk Stored Commo	odities		
Vertical storages	2-6/1000 cu ft.	150-300/1000 cu. ft	30-ຣັ0/1000 cu. It
	2-6/1000 cu ft	200-375/1000 cu. f	ເ 40 75/1000 cu ft
Tanks	2-6/1000 cu. lt.	150-350/1000 cu_ft.	30-70-/1000 cu_lt
	2-6/1000 cu. lt	200-450/1000 cu_ft	40-90/1000 cu_lt
Flat storages	2-6/1000 cu lt.	250-725/1000 cu ft	50-145/1000 cu_ft
	2-6/1000 cu, lt.	300-900/1000 cu ft	60-180/1000 cu_ft
Farm Bins	2-6/1000 cu. lt	350-725/1000 cu. ft	t 70-145/1000 cu ft
	2-6/1000 cu. lt.	450-900/1000 cu. ft	90-180/1000 cu, ft
Bunkers & larped	2-6/1000 cu. ft	150-400/1000 cu. f	t. 30-80/1000 cu. It
ground storages	2-6/1000 cu. ft.	200-500/1000 cu. f	t 40-100/1000 cu. It
Railcars	2-6/1000 cu. lt.	150-325/1000 cu fi	30-65/1000 cu. lt
	2-6/1000 cu. lt.	200 400/1000 cu i	lt. 4080/1000 cu lt
Barges	2-6/1000 cu. ft.	150-400/1000 cu. li	1 30-80/1000 cu. ft
	2-6/1000 cu. ft.	200-500/1000 cu. l	h. 40-100/1000 cu ft
Shipholds	2-6/1000 cu ft.	150-330/1000 cu. f	l. 30-66/1000 cu ft
	2-6/1000 cu, ft	200-375/1000 cu. f	h. 40-75/1000 cu ft

٦

Higher dosages are recommended in structures that are cose construction and in the fumigation of bulk stored commodities in which diffusion will be slc wed and result in poor distribution of hydrogen phosphide gas.

F. Application Procedures

1 General Statement

Regardless of the type of storage to be treated, there are several important factors common to all application procedures. A number of these points have been covered in other sections of the Applicator's Manual but are listed again in the following for completeness.

a. A plan should be devised for application, aeration and disposal of the fumigant so as to keep a minimum any exposures to hydrogen phosphide. See the requirements for Industrial Hygiene Monitoring under the Applicator and Worker Exposure section of this Applicators Manual.

b. QUICK-PHOS tablets or pellets should be applied so a to provide effective gas concentrations throughout the storage. When tablets or pellets are not applied uniformly to a bulk commodity (surface application in a tall silo or ships hold for example), exposure times should be lengthened to allow for penetration of gas throughout the storage.

c. The storage structure should be sealed so as to maintain a suitable gas concentration over the time period required for control of insect pests.

d. Ideally, exposure periods should be long enough to provide to adequate control of insect pests and also more less completely react the fumigant.

e. Piling of large numbers of tablets or pellets, whether applied to a bulk commodity or for space fumigation, may prevent complete breakdown of the product by limiting its access to moist air. This can result in decreased elficacy as a result of poor gas release and may leave an active residual for disposal which contains considerable amounts of unreacted aluminum phsophide.Piling of product may also result in increased hazard of fire if water should come into contact with the mass of aluminum phosphide.

f. Contact with liquid water should be carefully avoided when applying QUICK-PHOS for treatment of bulk commodities or space.

g. Aluminum phosphide fumigants should not be applied to confined spaces where the concentration of hydrogen phosphide may build up to exceed its lower flammable limit.

h. Observe the precautionary and safety statements mentioned in this manual.

The following instructions are intended to provide general guidelines for typical fumigations. These instructions are not intended to cover every type of situation nor are they meant to be restrictive. Other

procedures may be used if they are safe, effective and consistent with the properties of aluminum phosphide products.

2. Fumigatiot ' 'f Farm Bins

Leakage is the single most important cause of failures in the treatment of farm storages. Since these storages are often small, they usually have a higher leakage area in proportion to their capacity. Most wooden storage structures are so porous that they cannot be successfully fumigated unless they are completely tarped. Do not fumigate storages which will be entered by humans or animals prior to aeration. Do not fumigate areas which house sensitive equipment containing copper or other metals likely to be corroded by hydrogen phosphide gas.

Seal the bin as tightly as possible. It is recommended that the surface of the grain be covered with poly after QUICK-PHOS has been applied. Tarping the grain surface will greatly reduce the leak rate of the gas as well as reduce the amount of QUICK-PHOS required. Only the volume below the tarp must be dosed. If not tarped, the entire volume of the storage must be treated, whether full or empty.

QUICK-PHOS tablets, pellets, or bags may be scattered over the surface or probed into the grain using a rigid PVC pipe about 5 to 7 feet in length and having a diameter of 1 1/4 inches. Use about 20-50 tablets or 100-250 pellets or 60-150 bags. Immediately cover the surface of the grain with a plastic tarpaulin. Place no more than 25 percent of the total dose at the bottom if the bin is equipped with aeration fans. Caution: Make sure that the aeration duct is dry before adding QUICK-PHOS. Addition of QUICK-PHOS to water in an aeration duct may result in a fire. Seal the aeration fan with 4 mil plastic sheeting.

Post fumigation warning signs on entrances to the bin and near the ladder.

Following aeration of the bin, the surface of the grain may be sprayed with an approved protectant to discourage reinfestation.

3. Fumigation of Flat Storages

÷

a. Establish a plan for application of fumigant to the structure. Treatment of these types of storages may require considerable effort, therefore, sufficient manpower should be available to complete the work rapidly enough to prevent excessive exposure to hydrogen Phosphide gas. Vent flasks outside the storage, conduct fumigations during the cooler periods and employ other work practices to minimize exposures. It is often advisable to wear respiratory protection during application of fumigant to flat storages. Refer to the sections on Applicator and Worker Exposure and Respiratory Protection.

b. Seal any vents, cracks and other sources of leaks.

c. Apply tablets, pellets, or bags by surface application, shallow probing, deep probing or uniform addition as the bin is filled.

Storages requiring more than 24 hours to fill should not be treated by addition of fumigant to the commodity stream as large quantities of hydrogen phosphide may escape before the bin is completely sealed.

Probes should be inserted vertically at intervals along the length and width of the flat storage. Pellets, tablets or bags may be dropped into the probe at intervals as it is withdrawn. Curface application may be used if the bin case sufficiently gas tight to contain the fumigant gas long enough for it to penetrate the commodity. In this instance, it is advisable to place about 25 percent of the dosages in the floor level aeration ducts. Check the ducts prior to addition of QUICK-PHOS to make sure that they contain no liquid water.

d. Tarping the surface of the commodity is often advisable, particularly if the overhead of the storage cannot be well sealed.

e. Lock all entrances to the storage and post fum gation warning placards.

4. Fumigation of vertical Storages (concrete upright bins and other silos in which grain can be rapidly transferred

a. Close all openings and seal all cracks to make the structure as airtight as possible. Prior to the fumigation, seal the vents near the bin top which connects to adjacent bins.

b. Pellets, tablets may be applied continuously by hand or by an automatic dispenser on the headhouse/gallery belt or into the fill opening as the commodity is loaded into the bin. An automatic dispenser may also be used to add QUICK-PHOS into the commodity stream in the leg of the elevator.

c. Seal the bin deck openings after the fumigation has been completed.

d. Bins requiring more than 24 hours to fill should not be fumigated by continues addition into the commodity stream. These bins must be fumigated by probing surface application, or other appropriate means. Exposure periods should be lengthened to allow for diffusion of gas to all parts of the bins in QUICK-PHOS has not been applied uniformly throughout the commodity mass.

e. Place warning placards on the discharge gate and on all entrances.

5. Fumigation of Mills, Food Processing Plants and Warehouses

a. Using the label, calculate the length of the lumigation and dosage of tablets, pellets or bags to be applied based upon volume of the building, air and /or commodity temperature and the general tightness of the structure.

b. Carefully seal and placard the space to be fumigated .

c. Place trays or sheets of Kraft paper or foil, up to 12 sq. ft. (1.1 sq. M) in area, on the floor throughout the structure to hold QUICK-PHOS pellets or tablets. Bags should be spread evenly on the floor. Use total floor space.

d. Spread QUICK-PHOS on the sheets at a density no greater than 30 tablets per sq. II. This corresponds slightly more than one-half flask of tablets of one-half flask of pellets per 3' x 4" sheet. Check to see that QUICK-PHOS has not piled up and that it is spread evenly to minimize contact between the individual pellets, tablets, and bags.

e. Doors leading to the fumigated space should be closed, sealed, locked, and placarded with warning signs.

1. The lumigation period usually last from 2 to 5 days, depending upon the temperature. Upon completion of the exposure period, windows, doors, vents, etc. should be opened and the fumigated structure allowed to aerate for at least two hours before entering. When required , gas concentration readings may be taken using tow level detector tubes or similar devices to ensure safety of

personnel who reent is treated area. Refer to the section on App or and Worker Exposure.

g. Collect the spent bags, and QUICK-PHOS dust and dispose of it, with or without further deactivation, following the recommendations given under Disposal Instructions.

h. Remove fumigation warning placards from the aerated structure.

6. Fum!gation of Railcars, Containers, Trucks, Vans and other Transport Vehicles

Railcars, containers, trucks, vans and other transport vehicles loaded with bulk commoditins to which QUICK-PHOS tablets, pellets, or bags may be added directly are treated in essentially the same way as any other flat storage tacility. QUICK-PHOS may be added as the vehicle is being filled, the dose may be scattered over the surface after loading has been completed or the tablets, pellets, or bags may be probed below the surface, carefully seal any vents, cracks, or other leaks, particularly if the fumigation is to be carried out intransit. Remember, railcars and containers shipped piggyback by rail may be fumigated intransit, but it is not legal to move trucks, trailers, vans, etc. over public roads or highways until they are aerated. See section 6 of this Applicator's Manual for the recommendations on placarding. Notify the consignee if the commodity is to be shipped under fumigation with QUICK-PHOS. If the consignee is unfamiliar with proper handling of treated railcars, it is recommended that they be provided with the necessary information.

7. Tarpaulin and Bunker Fumigations

Use of plastic sheeting or tarpaulins to cover commodities is one of the easiest means for providing relatively gas tight enclosures which are very will suited for fumigation. Poly tarps are penetrated only very slowly by hydrogen phosphide gas, and tight coverings are readily formed from the sheets. The volume of these enclosures may vary widely from a few cubic feet, for example, a fumigation tarpaulin placed over a small stack of bagged commodity, to a plastic bunker storage capable of holding 600,000 bushels of grain or more

An enclosure suitable for fumigation may be formed by covering bulk or packaged commodity with poly sheeting. The sheets may be tarped together to provide a sufficient width of material to ensure that adequate sealing is obtained. If the flooring upon which the commodity rests is of wood or other porous material, it should be repositioned onto poly prior to covering for fumigation. The plastic covering of the pile may be sealed to the floor using sand or water snakes w, by shoveling soil or sand onto the ends of the plastic covering or by other suitable procedures. The poly covering should be reinforced by tape or other means around any sharp corners or edges int he stack so as to reduce the risk of tearing. Thinner poly, about 2 mil., is suitable for most indoor tarp fumigations and for sealing of windows, doors and other openings in structures. However, 4 mil poly or thicker is more suitable for outdoor applications where wind or other mechanical stresses are likely to be encountered.

Tablets , pellets or bags may be applied to the tarped stack or bunker storage of bulk commodity through slits in the poly covering. Probing or other mean dosing may be used. Avoid application of the amounts of QUICK-PHOS at any one point. The QUICK-PHOS should be acceed below the surface of the commodity if condensation or other source of moisture is likely to form beneath the poly. The slits in the covering should be carefully taped to prevent loss of gas once the dose has been applied. QUICK-PHOS bags are recommended for the treatment of bagged commodities and processed foods although tablets and pellets on trays or sheets of Kraft paper may be used. Care should be taken to see that the poly is not allowed to cover the QUICK-PHOS and prevent contact with moist air or confine the gas.

Distribution of hydrogen phosphide gas is generally not a problem in the treatment of bagged commodities and processed foods. However, fumigation of larger bunker storages containing bulk commodity will require proper application procedures to obtain adequate results.

Place warning placards at conspicuous on the enclosure.

8. Fumigation of Ships

a. General Information

1. IMPORTANT - shipboard, intransit ship or shiphold fumigation is also governed by U>S> Coast Guard Regulation 46 CFR 147A. Refer to this regulation prior to fumigation.

2. QUICK-PHOS tablets, pellets, and bags are classified by EPA as restricted use pesticides due to the acule inhalation toxicity of hydrogen Phosphide (phosphine, PH3) gas. These products are for retail sale to and use only by certified applicators for those uses covered by the applicators certification or persons trained in accordance with the Applicators Manual working under the direct supervision and in the physical presence of the certified applicator, physical presence means on site or on the premises. Read and follow the label and the PHOS-FUME CHEMICAL COMPANY, INC Applicators manual which contains complete instructions for the safe use of this pesticide.

b. Pre-Voyage Fumigation Procedures

1. Prior to fumigating a vessel for intransit cargo lumigation, the master of the vessel, or or his representative, and the fumigator must determine whether the vessel is suitably designed and configured so as to allow for safe occupancy by the ships crew throughout the duration of the fumigation. If it is determined that the design and configuration of the vessel does not allow safe occupancy by the ships crew throughout the duration of the fumigation, then the vessel will not be fumigated unless all crew members are removed from the vessel. The crew members will not be allowed to reoccupy the vessel until the vessel has been properly aerated and a determination has been made by the master or the vessel and the fumigator that the vessel is safe for occupancy.

 The person responsible for the fumigation must notify the master of the vessel, or his representative, of the requirements relating to personal protection equipment*, detection equipment that a person qualified in the use of this equipment must many the vessel with cargo under function. Emergency procedures, cargo ventilation, periodic monitoring and inspections, and first aid measures must be discussed with and understood by the master of the vessel or his representative.

*Personal protection equipment means a NIOSH/MSHA approved respirator or gas mask fitted with an approved canister for phosphine. The canister is approved for use up to 15 ppm. SCUBA or its equivalent must be used above 15 ppm or at unknown concentrations.

3. Seal all openings to the cargo hold or tank and lock or otherwise secure all openings, manways, etc., which might be used to the enter the hold. The overspace pressure relief system of each tank aboard tankers must be sealed by closing the appropriate valves and sealing the openings into the overspace with gas-tight materials.

4. Placard all entrances to the treated spaces with fumigation warning signs.

5. If the fumigation is not completed and the vessel aerated before the manned vessel leaves port, the person in charge of the vessel shall ensure that at least two units of personal protection equipment and one gas or vapor detection device, and a person qualified in their operation be on board the vessel during the voyage.

6. During the fumigation or until a manned vessel leaves port or the cargo is aerated, the person in charge of the fumigation shall ensure that a qualified person using gas or vapor detection equipment tests spaces adjacent to spaces containing fumigated cargo and all regularly occupied spaces for fumigant leakage. If leakage of the fumigant is detected, the person in charge if the fumigation shall take action to correct the leakage, or shall inform the master of the vessel, or his representative of the leakage so that corrective action can be taken.

7. Review with the master, or his representative, the precautions and procedures for during the voyage.

c. Application Procedures for Bulk Dry Cargo Vessels and Tankers

1. Apply tablets, pellets or bags by scattering uniformly over the commodity surface or they may shallow or deep probed into the commodity mass.

2. Immediately after application of the lumigant, close and secure all hatch covers, tank tops, butterworth valves, manways, etc.

d. Intransit Fumigation of Containers Abroad Ships

Intransit fumigations of containers on ships is also governed by U.S. Coast Guard Regulation 46 CFR 147A as modified by U.S. Coast Guard Special Permit 175. This permit which must be obtained p to the fumigation is available from:

U.S. Coast Guard Hazardous Materials Branch MTH-1 Washington, D.C. 20593-0001

Application procedures for fumigation of raw commodities or processed foods in containers and other transport vehicles are described in section 3a.

e. Precautions and Procedures during Voyage

1. Using appropriate gas detection equipment, monitor spaces adjacent to areas containing fumigated cargo and all regularly occupied areas for fumigant leakage. It leakage is detected, the area should be evacuated of all personnel, ventilated, and action taken to correct the leakage before allowing the area to be occupied.

2. Do not enter fumigated areas except under emergency conditions. If necessary to enter to enter a fumigated area, appropriate personal protection equipment must be used. Never enter fumigated areas alone. At least one other person, wearing personal protection equipment, should be available to assist in case of an emergency.

f. Precautions and Procedures During Discharge.

1. If necessary to enter hoids prior to discharge, test spaces directly above grain surface for fumigant concentration, using appropriate gas detection and personal safety equipment. Do not allow entry to fumigant areas without personal safety equipment, unless fumigant concentrations are at safe levels, as indicated by a suitable detector.

9. Fumigation of Barges

Barge lumigations are also regulated by U.S. Coast Guard regulation 46 CFR147A as modified by U.S. Coast Guard Special Permit 2-75. This permit which must be obtained prior to the fumigation is available from:

U.S. Coast Guard Hazardous Materials Branch MTH-1 Washington, D.C. 20593-0001

Leaks are a common cause of failures in the treatment of commodities aboard barges. Carefully inspect all hatch covers prior to application of QUICK-PHOS and seal, if necessary. Notify consignee if the barge is to be furnigated intransit.

10. Fumigai in Small Sealable Enclosures

Excellent results may be attained in the treatment of small enclosures since it is often possible to control the fumigation and also to make the enclosure virtually gas tight. Take care not to overdose during these fumigations. A single pellet will treat a space of from 1.4 to 10 cubic feet. From 6.9 to 50 cubic feet may be fumigated with a single QUICK-PHOS tablet or 1 QUICK-PHOS bag.

11. Treatment of Beehlves, Supers and other Beekeeping Equipment

QUICK-PHOS tablets, pellets and bags may used for the control of the greater wax moth in stored beehives, supers and other beekeeping equipment and for the destruction of bees, Africanized bees, and diseased bees including those infested with tracheal mites and foulbrood. The recommended dosage for this use is 30-45 tablets, 150-225 pellats or 3 bags per 1000 cu. It.

Fumigations may be performed in chambers at atmospheric pressure, under tarpaulins, etc. by placing bag and the tablets or pellets on trays or in moisture permeable envelopes. Do not add more than 2 tablets or 10 pellets to each envelope. Honey from treated hives or supers may only be used for bee food.

12. Burrowing Pest Control

a. List of Burrowing Pests

QUICK-PHOS tablets, pellets and bags may be used out of doors only for the control of the following burrowing rodents and moles: Marmot sp. -Woodchucks and yellow-belly Marmots (Rockchucks), Prairie Dogs (exce₁t Utah Prairie Dogs), Norway and Roof Rats, Mice, Ground Squirrels, Moles, Voles, Gophers, and Chipmunk.

b. Directions for Use

Add from one 1 to 4 QUICK-PHOS tablets, 5 to 20 pellets, or 2 to 6 bags to each burrow opening. Then seal tightly by shoveling soil over the entrance after first packing the opening with crumpled newspaper or something similar so as to prevent soil from covering the QUICK-PHOS and slowing its action. Subsurface tunnels or runways should be treated every 5 to 10 feet with a dose of 2 to 4 tablets. 10 to 20 pellets, and 2 to 6 bags.

Use lower rates in smaller burrows in tight soils under moist soil conditions and higher rates in larger burrows in porous soils when soil moisture is low. Addition of several cups of water to the burrow prior to dosing with QUICK-PHOS may improve efficacy in some porous soils. Treat reopened burrows and fresh runways a second time 1 to 3 days after the initial treatment.

QUICK-PHOS may be used out of doors only for control of burrowing pests. Do not use within 15 feet (5 meters) of inhabited structures. Do not apply to burrows which may open under or into occupied buildings. For use on all agricultural and noncropland areas.

c.Environmental Hazards

This product is very highly toxic to wildlife. Non-target organisms exposed to phosphirie gas in burrows will be killed. Do not apply directly to water or wetlands (swamps, bogs, marshes, and potholes). Do not contaminate water by cleaning of equipment, or disposal of wastes.

d.Endangered Species Restrictions

The use of QUICK-PHOS in a manner that may kill or otherwise harm an endangered or threatened species or adversely modify their habitat is a violation of Federal laws. The use of this product is controlled to prevent death or harm to endangered or threatened species that occur in the fcllowing counties or elsewhere in their range. Use of this product in the areas listed below os prohibited without first contacting and obtaining permission from the Endangered Species Specialist at the nearest regional offices of the U.S. Fish and Wildlife Service (FWS).

Areas inhabited by Endangered or Threatened Species

1. Black-footed Ferret - State of Arizona, Colorado, Kansas. Montana, Nebraska, New Mexico, North Dakota, Oklahoma, South Dakota, Texas, Ulah and Wyoming.

2. Blunt-nosed Leopard Lizard - Counties of Kern, Kings, Fiesno Madera, Merced and Tulare in the state of California.

3. Desert Tortoise - Washington County in the State of Utah

4. Eastern Indigo Snake - States of Florida and Georgia

5. San Joaquin Kit Fox - Counties of Kern, Kings Fresho, Merced, Monterey, San Benito, San Luis Obispo, Santa Barbara, Tulare and Ventura in the State of California

e. Special Local Restrictions

1. North Carolina

QUICK-PHOS tablets, pellets, and bags may only be used for control of rats and mice int eh state of North Carolina. Use against other pests is not permitted.

2. Oklahoma

A special permit for black-tailed prairie dog control by poisoning is required in Oklahoma. Contact the Oklahoma State Department of Wildlife Conservation to obtain this permit.

3. Wisconsin

A state permit is required for use of pesticides in Wisconsin to control small mammals, except rats or mice. Please contact your local Department of Natural Resources office for information.

4. Indiana

Use of QUICK-PHOS tablets, pellets, or bags for mole control is not iegal in the state if Indiana.

5. Missouri

A state permit is required fro use of pesticide in Missouri to control small mammals, except arts and mice.

Please contact the Missouri Department of Conservation office for information.

6. Kansas

A special for black-tailed prairie dog control by poisoning is required in Kansas. Contact the Kansas Fish and Game Commission to obtain this permit.

7. California

Use of QUICK-PHOS tablets, pellets, and bags for chipmunk control is not legal in the state of California.

Section 4 PROTECTIVE CLOTHING

Wear dry gloves of cotton or other material if contact with QUICK-PHOS tablets, pellets or bags is likely. Wash hands thoroughly after handling aluminum phosphide products. Aerate used gloves and other contaminated clothing in a well ventilated area prior to laundering.

Section 5 RESPIRATORY PROTECTION

A.When Respiratory Protection Must Be Worn

NIOSH/MSHA approved respiratory protection must be worn if worker exposure limits cannot be met through controls 'such as forced air ventilation) and/or worker practices. Respiratory protection is required if erposure is likely to exceed the TWA of 0.3 ppm during application, or a 0.3ppm ceiling at any time alterwards. For example, respiratory protection is required to be worn upon reentry into a partially aerated structure if the hydrogen Phosphide concentration is above ppm. When required, gas concentration measurements for safety purposes may be made using low level detector tubes. See the section on Applicator and Worker Exposure for Monitoring requirements. Information on hydrogen phosphide (phosphine, PH3) detector tubes may be obtained from . PHOS-FUME CHEMICAL COMPANY. INC

B. Permissible Gas Concentrations Ranges for Respiratory Protection Devices

A NIOSH/MSHA approved, full-faced has mask-hydrogen phosphide canister combination may be used at levels up to 15 ppm. or to escape from levels up to 1500 ppm. Above this level or situations where the hydrogen phosphide concentration is unknown, a NIOSH/MSHA approved, self-contained breathing apparatus (SCBA) or its equivalent must be used. The NIOSH/OSHA Pocket Guide, 8085 DHEW/NIOSH 78-210, lists these and other types of approved respirators and the concentration limits at which they may be used.

\cap

C. Requirements for Availability of Respiratory Protection

If QUICK-PHOS is to be applied from within the structure to be fumigated, an approved full-face mask

gas mask - phosphine canister combination or self-contained breathing apparatus (SCBA) or its equivalent must be available at the site of application in case it is needed. In addition, SCBA or its equivalent must be available locally, for example, at fire station or rescue if it is not available at the fumigation site.

Respiratory protection need not be available for applications from outside the area to be furnigated such as addition of tablets or pellets to automatic dispensing devices, outdoor applications, etc. if exposures above the permitted exposure limits will not be encountered.

If monitoring equipment is not available on a farm and application of fumigant cannot be made from outside the structure, an approved canister respirator must be worn during application from within the structure being treated.

Section 6 PLACARDING OF FUMIGATED AREAS

The applicator must placard or post all entrances to the structure under fumigation with signs bearing, in English and Spanish:

1. The signal wc. I DANGER/PELIGRO and the SKULL AND CROSSBONES symbol in red.

2. The statement "Area and/or commodity under fumigation, DO NOT ENTER/NO ENTRE".

3. The statement, This placard may only be removed after the lumigated area is aerated down to 0.3ppm hydrogen Phosphide or below. Transfer of incompletely aerated commodity to a new site is permissible provided that the new storage is placarded if it contains more than 0.3ppm. Workers must not be exposed to more than 0.3ppm hydrogen phosphide.

4. The date and time fumigation begins and is completed.

5. Name of furnigant used.

6. Name, address and telephone number of the applicator.

All entrances to a fumigated area must be placarded. Where possible, placards should be place : in advance of the fumigation to keep unauthorized persons away. For railroad hopper cars, placards must be placed on both sides of the car near the ladders and next to the top hatches into which the fumigant is introduced.

Do Not remove placards until the treated commodity is aerated down to 0.3 ppm hydrogen Phosphide or less. To determine whether aeration is complete, each fumigated site or vehicle must be monitored and shown to contain 0.3ppm or less hydrogen phosphide gas in the air space around and, if feasible, in the mass of the commodity. Transfer of incompletely aerated commodity to a new site is permissible. However, the new storage must be placarded if it contains more than 0.3ppm hydrogen phosphide. Workers who nandle incompletely aerated commodity must be informed and appropriate measures taken (i.e. ventilation or respiratory protection) to prevent exposures from exceeding 0.3ppm hydrogen phosphide. It is recommended that the persons responsible for removing placards be familiar with physical, chemical and toxicological properties of hydrogen phosphide. They should be also be knowledgeable in making gas concentration measurements, exposure limits and symptoms and first aid treatment for hydrogen phosphide poisoning.

Section 7 AERATION OF FUMIGATED COMMODITIES

A. Foods and Feeds

Tolerances for hydrogen phosphide residues have been established at 0.1ppm for animal feeds and 0.01ppm for finished foods. To guarantee compliance with these tolerances, it is necessary to aerate these commodities for 48 hours prior to offering to the end use consumer.

B. Tobacco

Tobacco must be aerated for at least three days (72 hours)when fumigated in hogshead and for at least

two days (48 hours) when fumigated in other containers. Tobacco fumigated in containers with plastic liners will probably require longer aeration periods to reach 0.3ppm.

Section 8 APPLICATOR AND WORKER EXPOSURE

A. Hydrogen Phosphide Exposure Limits

Exposure to hydrogen phosphide may not exceed 0.3ppm. measured as an eight hour time weighted average (TWA), for applicators and workers during application. Application is defined as the time period covering the opening of the first containers, applying the appropriate dosage of fumigant and closing up the site to be fumigated. All persons in the treated site and in adjacent indoor areas are covered by tis exposure standard.

After application, exposure for any person may not exceed a 0.3ppm ceiling for hydrogen phosphide. Such exposures may occur if the commodity or space under fumigation leaks, when treated commodity is transferred or handled, if an unaerated or partially aerated space is entered, etc.

B. Application of Fumigant

Depending upon temperature and humidily, QUICK-PHOS tablets, pellets and bags release hydrogen phosphide gas slowly upon exposure to moisture from the air. In most cases, this release is slow enough to permit applicators to deposit fumigant in the desired areas and then vacate the premises without significant exposure to the gas. If the fumigators is likely to exceed the eight hour TWA of 0.3ppm, approve respiratory protection must be worn. When required gas concentration measurements for safety purposes may be made using low level detector tubes. See the write-up below on Industrial Hygiene Monitoring. Information on hydrogen phosphide (phosphine, PH 3) detector tubes may be obtained from PHOS-FUME CHEMICAL COMPANY, INC

It is often advisable to user respiratory protection during application of fumigant under hot and humid conditions, particularly when considerable time must be spent inside the structure being treated.

C. Leakage from Fumigated Sites

Hydrogen phosphide is highly mobile and given enough time may penetrate seemingly gas tight materials such as concrete and cinder blocks. Therefore, adjacent, enclosed areas likely to be occupied should be examined to ensure that significant leakage has not occurred. Sealing of the lumigated site and/or air flow int eh occupied areas must be sufficient to meet exposure standards.

D. Aeration and Reentry

If the area is to be entered after fumigation, it must be aerated until the level of hydrogen phosphide gas is 0.3ppm or below. The area or site must be monitored to ensure that liberation of gas from the treated commodity does not result in the development of unacceptable levels of hydrogen phosphide. Do not allow reentry into treated areas by any persons before this time unless protected by an approved respirator.

E. Handling Unaerated Commodities

Workers must not be exposed to hydrogen phosphide in excess of 0.3ppm during moving storage or processing of incompletely aerated commodities.

F. Industrial Hygiene Monitoring

It is recommended that hydrogen phosphide exposures be documented in an operations log or manual for each site and operation where exposure may occur. The purpose of those monitoring is to prevent excessive exposures and to determine when and where respiratory protection is required. This mandatory although, once exposure have been adequately characterized, subsequent monitoring is not routinely required. However, spct checks should be made occasionally, especially if conditions change significantly or an unexpected garlic odor is detected. Gas measurements should be made in the workers breathing zone. Monitoring is not required for outdoor operations.

It monitoring shows that workers are exposed to concentrations in excess of the permitted limits, then engineering controls (such as forced air ventilation) and/ or appropriate work practices should be used, where possible, to reduce exposure to within permitted limits.

There are a number of devices on the market for measurement of hydrogen phosphide gas levels for industrial hygiene purposes. One of these is the hydrogen sampling pump. These devices are reliable, portable, simple to use do not require extensive training and are relatively rapidly, inexpensive and accurate. Low level industrial hygiene monitoring.

Section 9 STORAGE INSTRUCTIONS

Store QUICK-PHOS in a dry, well ventilated area away from heat under lock and key. Post as pesticide storage area. Do not contaminate water, food or feed by storing pesticides in the same areas used to store these commodities.

Do not store in buildings where humans or domestic animals reside. Keep out of reach of children.

PHOS-FUME CHEMICAL COMPANY, INC QUICK-PHOS tablets, pellets and bags are supplied in gas tight, resealable aluminum flasks. Do not expose the product to atmospheric moisture any longer than is necessary and seal tightly before returning opened flasks to storage.

The shelf life of QUICK-PHOS is virtually unlimited as long as the containers are tightly sealed.

Section 10 DISPOSAL INSTRUCTIONS

A. General

1. Do not contaminate water, food or feed by storage or disposal.

-2. Unreacted or partially reacted QUICK-PHOS is acutely hazardous. Improper disposal of excess pesticides is a violation of Federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance. For specific instructions, see Section 11 of this manual, Spill and Leak Procedure

3. Some local and state waste disposal regulations may vary form the following recommendations. Disposal procedures should be reviewed with appropriate authorities to ensure compliance with local regulations. Contact your state Pesticide or Environmental Control Agency or Hazardous Waste Specialist at the nearest EPA regional Office for guidance.

Triple rinse flasks and stoppers with water. Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill or by other procedures approved by state and local authorities. Rinsate may be disposed of in a sanitary landfill by pouring it out onto the ground or by other approved procedures. Or i, it is permissible to remove lids and expose empty flasks to atmospheric conditions until residue in flasks is reacted. Then puncture and dispose of in a sanitary landfill or other approved site, or by other procedures by state and local authorities.

If properly exposed, the residual dust remains after a lumigation with QUICK-PHOS will be a gravish-white powder. This will be a nonhazardous waste and contain only a small amount of unreacted aluminum phosphide. However, residual dust from incompletely exposed QUICK-PHOS, so called "green dust" will require special care.

B. Confinement of partially spent residual dust, as in a closed container,

or collection and storage of large quantities of dust may result in a fire hazard. Small amounts of hydrogen phosphide may be given off from unreacted aluminum phosphide, and confinement of the gas may result in a flash.

2. In open areas, small amounts of residual dust, up to about 5 to 8 kg., may be disposed of on site by burial or by spreading over the land surface away from inhabited buildings.

3. Spent residual dust from QUICK-PHOS may also be collected and disposed of at a sanitary landfill, incinerator or other approved sites or by other procedures approved by Federal, State or Local authorities. "Green Dust" must be further deactivated before disposal at a landfill.

4. From 2 to 3 kg (4 to 7 lbs) of spent dust from 2 to 3 flasks of QUICK-PHOS may be collected for disposal in a 1 gallon bucket. Larger amounts, up to about one-half case, may be collected in burlap, cotton or other types of porous cloth bags for transportation in an open vehicle to the disposal site. Do to collect dust from more than 7 flasks of tablets or 10 flasks of pellets (about 11 kg. or 25 lbs) in a single bag. Do not pile cloth bags together. Do not use this method for partially spent or "green"dust. Caution: Do not collect dust in large drums, dumpsters, plastic bags or other containers where confinement may occur.

C. Directions for Deactivation of Partially Spent Residual Dust from QUICK-PHOS

1. Partially spent dust must be deactivated prior to ultimate disposal. This is especially true in cases of incomplete exposure which has resulted in socalled "green dust" or following a fumigation which has produced large quantities of partially spent material. "Green dust" must be further deactivated prior to disposal in tandfills.

2. Residual dust from QUICK-PHOS may be deactivated as follows using the "Wet Method".

a. Deactivating solution is prepared by adding the appropriate amount of low sudsing detergent or surface active agent to a water in a drum or other suitable container. A 2% solution of detergent is suggested. The container should be filled with deactivating solution to within a few inches of the top.

b. Residual dust is poured slowly into deactivating solution and stirred so as to thoroughly wet all of the particles. This should be done in the open air and not int he (umigated structure. Dust from QUICK-PHOS tablets, pellets, or bags should be mixed into no less than 10 gallons of water-detergent solution for each case of material used. Wear appropriate respiratory protection during wet deactivation of partially spent dust.

c. Dispose of the deactivated dust-water suspension, with or without preliminary decanting, at a sanitary landfill or other suitable site approved by local authorities. Where permissible, the slurry may be poured out onto the ground. If the slurry has been held for 36 hours or more, it may be poured into a storm sewer.

d. Caution: Respiratory protection is required during wet deactivation of partially spent material. Do not cover the container at any time. Do not dispose of dust in a toilet. Do not allow quantities of dry residual dust from QUICK-PHOS to be collected or stored without deactivation.

3. Residual dust from QUICK-PHOS may also be deactivated as follows suing the "Dry Method."

a. Extension of the fumigation period is the simplest method for further deactivation of "green dust" or partially spent dust prior to ultimate disposal.

b. Small amoun partially spent dust, from 2 to 3 kg. (4 to 7 lbs,) be further deactivated by surrage in a 1-gallon bucket. Larger amounts of dust (about 11 kg. or 25 lbs) may be held for deactivation in porous cloth bags (burlap, cotton, etc.) Caution: Transport these bags in open vehicles, do not pile up bags and do not use this method for "green dust".

Section 11 SPILL AND LEAK PROCEDURE

A. General precautions and Directions

A spill other than incidental to application or normal handling, may produce high levels of gas and, therefore attending personnel must wear SCBA or its equivalent when the concentration of hydrogen phosphide gas is unknown. Other NIOSH/MSHA approved respiratory protection may be worn if the concentration is known. Do not use water at any time to clean up a spill of QUICK-PHOS. Water in contact with unreacted tablets, pellets or bags will greatly accelerate the production of hydrogen phosphide gas which could result in a toxic and/ or fire hazard. Wear cotton gloves or other material when handling aluminum phosphide.

Return all intact aluminum flasks to fiberboard cases or other packaging which has been suitably constructed and marked according to DOT regulations. Notify consignee and shipper of damaged cases.

If aluminum flasks have been punctured or damaged so as to teak, the container may be temporarily repaired with aluminum tape or the QUICK-PHOS may be transferred from the damaged flask to a sound metal container which should be sealed and properly labeled as aluminum phosphide. Transport the damaged containers to an area suitable for pesticide storage for inspection. Further instructions and recommendations may be obtained from PHOS-FUME CHEMICAL COMPANY, INC

If a spill has occurred which is only a few minutes old, collect the tablets, pellets and bags and place them back into the original flasks, if they are intact, and stopper tightly. Place the collected tablets, pellets, and bags in a sound metal container if the original flasks are damaged. Caution: these flasks may flash upon opening at some later time.

If the age of the spill is unknown or if the tablets, pellets, and bags have been contaminated with soil, debris, water, etc. gather up the spillage and place it into small open bucket having a capacity no larger than about 1 gallon. Do not add more than one flask of spilled material, 1 to 1.5 kg. (2 to 3 lbs) to the bucket. If in-site, wet deactivation is not feasible, these containers should be transported in open vehicles to a suitable area. Wet deactivation may then be carried out as described in 11g.Alternatively, small amounts of spillage from 4 to 5 flasks (4 to 8 kg. 9 to 18 lbs) may be spread out in an open area from inhabited buildings by atmospheric moisture.

B. Directions for Deactivation by the Wet Method

If the contaminated material is not to be held until completely reacted by exposure to atmospheric moisture, deactivate the product by the wet Method as follows:

1. Deactivating solution is prepared by adding the appropriate amount of low sudsing detergent or surface active agent to water in a drum or other suitable container. A 2% solution or 4 cups in 30 gallon is suggested. The container should be filled with deactivation solution to within a few inches of the top. 2. The tablets, pellets, or bags are pored storty into the deactivating solution and stirred so a thoroughly wet all of the QUAR PHOS. This should be done inthe open air. QUICK-PHOS tablets, pellets, and bags should be mixed into no less than about 15 gallons of water-detergent solution for each case of spent material. Wear appropriate respiratory during wet deactivation.

14. 7

3. Allow the mixture to stand, with occasional stirring, for about 36 hours. The resultant slurry will then be safe to dispose of.

4. Dispose c. the slurry of deactivated material, with or without preliminary decanting, at a sanitary landfill or other suitable site approved by local authorities. Where permissible, this slurry may be poured into a storm sever or out onto the ground.

,

>

5. Caution: Respiratory protection is required during wet deactivation of unexposed QUICK-PHOS. Never place pellets, tablets, or bags in a closed container such as a dumpster, sealed drum, plastic bag, etc. as flammable concentrations and a flash of hydrogen phosphide gas likely to develop.

6. The EPA has determined that prope; disposal of aluminum phosphide will cause no unreasonable effects to the environment.

FOR ASSISTANCE, CONTACT:

PHOS-FUME CHEMICAL COMPANY, INC 12703 W. 117th St., Overland Park, KS 66210

1051 CM12

PRECAUTIONARY STATEMENTS Hazards to Humans and Domestic Animals

KEEP OUT OF REACH OF CHILDREN DANGER - POISON

Alumnum or magnesium phosphide power, granules or tablets may be fatal if swallowed. Do not get in eyes, on skin or on clothing. Do not eait, drink or smoke while handling alumnum or magnesium phosphide furnigants. If a sealed container is opened, or if the material comes in contact with molsture, water or acids, estremsky toxic phosphine gas will be released. If a garke odor is delucted, you must montor to determine whether phosphine gas is present above the acceptable exposure limits (see section on respiratory protection). Since an odor may not be detected under certain circumstances, the absence of a garke odor does not mean that phosphine gas is absent. Observe proper application, aeration, reentry and disposal procedures specified elsewhere in the labeling to prevent oversposure.

Physical/Chemical Hazards

Alumnum phosphide in lables, pelses, bags or partially spent dust will release phosphine gas it exposed to moisture from the air or if it comes into contact with water, acids and many other liquids. Pling of tables, pelses, bags or dust from their fragmentation may cause a temporative increase and confine the release of gas so that ignition could occur.

Aways open container of aluminum phosphide products outdoors as under certain conditions, they may flash upon opening. When opening, point the container away from the face and body and slowly loosen the cap. Although the chances for flash are very remote, never open these containers in a flammable atmosphere. These precautions we also reduce the applicator's exposure to phosphine gas.

Pute phosphine gas is practically insoluble in water, and oils, and its stable at normal lumgation temperatures. However, it may react with certain metals and cause correction, especially at higher temperatures and relative humidues. Metals such as copper, brass and other copper alloys, and precioue metals such as gold and silver are susceptible to corrosion by phosphine. Thus, smale electric motors, smoke detectors, brass sprinkler heads, bateries and britery chargers, fork lifts, temperature moniforing systems, switching gears, communication devices, computers, calculations or other electrical equipment should be protected or removed belore lumination.

Phosphere gas will also react with certain metallic sals and, therefore, sensitive aerus such as photographic fam, some inorganic pigments, etc., should not be succesd.

ENVIRONMENTAL HAZARDS

This product is toxic to tesh and wildle. On not discharge effluont containing this product into takes, streams, ponds, estuaries, oceans, or public waters, unless this product is specifically identified and addressed in a National Politicant Discharge Ekmination System (NPDES) purmt. Do not discharge effluent containing this product to sever systems without previously notifying the sewage treatment plan authority. For guidance contact your State Water Board, or Regional Office of EPA.

"Environmental Hazards": This product is very highly toxic to wildele. Nontarget organisms exposed to phosphine gas in burrows will be lated. Do not apply directly to water or wellands (swamps, bogs, marshes, and potholes). Do not contaminate water by cleaning of equipment or disposal of wastes.

Classified by Underwrite's Laboratories, Inc., as to fire hazard only when used as directed in the separate instruction that are part of the product labeling. L-Furm is noncombustible, but exposure to most air or water releases flammable and toxic phosphine gas. Spontaneous lightion may result if contacted by water, and or chemicals.

RESTRICED USE PESTICIDE DUE TO ACUTE INHALATION TOXICITY OF HIGHLY TOXIC PHOSPHINE GAS

For retail sale to and use only by Certified Applicators for those uses covered by the applicators certification or persons trained in accordance with the attached product manual working under the direct supervision and in the physical presence of the Certified Applicator on site or on the premises. Read and follow the label and the Quick-phos product manual which contains complete instructions for the safe use of this pesticide.

QUICK-PHOS ALUMINUM PHOSPHIDE FUMIGANT BAGS ALUMINUM PHOSPHIDE FUMIGANT

A furnigant for use against listed insects which Infest listed raw Agriculture Commodales, Specified Processed Foods and Animal Feeds. (See Product Manual)

ACTIVE INGREDIENT:

Aluminum Phosphide		
INERT INGREDIENTS:		
	Total	100%
Contents: 6 - 10 bags	Net Weight:	154 - 340 grams ea.

	· · · · · · · · · · · · · · · · · · ·	
KE	EP OUT OF REACH OF CHILDRI	E.N
X	DANGER - PELIGRO - POISON	X

PRECAUCION AL USUARIO: Si usion no lee ingles, no se este producto hasta que la et elegeta se la haya sido explicado ampliamente." PRACTICAL TREATURENT STATEMENT

Symptoms of overexposure to phosphine are headache, dizzness, nausea, dificult beathing, vorning and diarthea. In all cases of overexposure get midical attention immediately. Take victim to a doctor or emergency treatment lacity. If the gas from alluminum or magnesum phosphide is inhaled: Get exposed person to fresh

If the gas from aluminum or magnesum phosphole is inhaled: Get exposed person to fresh ar. Keep warm and make sure person can breathe freely. It breathing has slopped, give anticial respiration by mouth to mouth or other means of resuscitation. Do not give anything by mouth to an unconscoup person.

If aluminum or magnesium phosphide powder, granules, pelius or tablets are swallowed: Drink or administer one or two glasses of water and induce vomeing by louching back of throat with linger, or if available, syrup of ipecac. Do not give anything by mouth if victuritie unconscrous or not alert.

If powder, granules or tablets of alumnium or magnesium phosphide get on skin: Brush material off clothes and shoes in a well venulated area, Allow clothes to aerate in a ventilated area prior to laundering. Wash containmated bare skin thoroughly with scop and waler. If in eyes: Flush with plenty of water. Get medical attention. SEE SIDE PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS

SEE SIDE PANELS FOR ADDITIONAL PRECAUTIONARY STATEMENTS

MANUFACTURED BY: Invente Corporation, Worli Bombey, India 400 018

MANUFACTURED FOR PHOS-FUME CHEMICAL COMPANY, INC

12703 W St., Overland Park, KS 66210 EPA REGISTRATION NO. 43568-2 EPA ESTABLISHMENT NO. 41876-1Y-1

DIRECTIONS FOR USE:

"It is a violation of Federal E.u. to use this product in a manner inconsistent with its labeling."

The lumigant is a highly hazardous material and gally only be used by individuals trained in the proper see Before usings read and follow all precautions and Jerectons on the Jobel and IN the product manual. See Product menual for QUICK PHOS Applicator's Mismuel for complete use directions evaluable from PHOS FIRME CHEMICAL COMPANY, INC

12703 W. SL, Overland Park, KS, 66210

At least two transed persons must be present when the product is applied from within a space to be furnigated or during reentry into a furnigated or partially availed site.

Prior to applying this product, you must inspect the site to be turnigated to determine it is can be made sufficiently gas tight. You should also develop a plan for monitoring (if not done before) how to most efficiently and safely apply the turnigant, emergency procedures, etc. Notily appropriate company employees and provide relevant safety information annually to local officials having presidential for department, rescue squad, police, etc.) over the turnigation site. Follow all local and state regulations. Take or mail applicators manual.

Shipholds, barges, containers on ships, railroad cars and containers shipped piggyback by rail may be furnigated in transit. However, trucks, vans, trailers and similar transport vehicles cannot be moved over public roads or highways until the turniga un is completed. Do not lurnigate commodules with this product when commodry lemperature is below 40°F. (5°C.).

Protective Clothing. Wear dry gloves when handling unpackaged tablets or pellats. Wash hands thoroughly after use balore smoking or eating.

Storage and Handling

Store in a dry, well ventualed area away from heat, under lock and lury. Post as a pesticide storage area. Do not contarninate water, food or feed by storing pesticides in the same area used to store these commodules. Do not store in buildings inhabled by humans or domestic annuals.

Disposal Statements

General Disposel Statements. Do not contaminate water, lood or leed by storage or disposal. Unreacted or partially reacted aluminum phosphile is acually hazardous. Improper disposal of excess positicide, spray mixture, or instate is a violation of Feural Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Presticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance. For specific instructions, see Spil and Leak Procedures. Pages 30-31 of Product Manuel.

Some local and state waste disposal regulations may vary from the following recommendations. Disposal procedures should be reviewed with appropriate authorities to ensure compliance with local regulations. Contact your State Pesticide or Environmental Control Agency or Hatardous Waste Specialist at the nearest EPA Resional Otics for guidance.

Trple rinse flaska and stoppers with water. Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authomies. Rinsa's may be disposed of in a sanitary sewer, sanitary landfill or by other approved procedures. It is also permissible to remove lide and expose empty flasks outdoors until residue in the flask is reacted. Then puncture and dispose of in a sanitary landfill or other approved bies, or by other procedures approved by state and local authorstee.

If property exposed, the residual dust remaining after a furnigation with alumnum phosphide we be grayish while and contain only a small amount of unreacted material. However, residual dust from incompletely exposed alumnum phosphide will require special case.

DISPOSAL OF BAGS: See Product Manual, Page 30

See Product Manual, "Spill & Linak Procedures" page 30 and 31 of Applicator's Manual.

ACCEPTED	
AUG 2 4 1987	
Under the P	