## RESTRICTED USE PESTICIDE DUE TO ACUTE INHALATION TOXICITY OF HIGHLY TOXIC HYDROGEN PHOSPHIDE (PHOSPHINE, PH3) GAS

For retail sale and use only by certified applicators for those uses covered by the applicator certification or persons trained in accordance with the Applicators Manuel working under the direct supervision and in the physical presence of the certified applicator. Physical presence means on alte or on the premises.

Read and follow the label and the Applicators Manuel which contains complete instructions for the safe use of this pesticide.

## **APPLICATOR'S MANUAL**


# **FUMIPHOS**

## TABLETS, PELLETS, AND BAGS

For use against insects which infest stored Commodities and Control of Burrowing Pests

Active Ingredient:

Aluminum Phosphide	60%
	Total100%



## KEEP OUT OF REACH OF CHILDREN

## DANGER - POISON - PELIGRO

PELIGRO AL USUARIO: Si usted no lee ingles, no use este producto hasta que la etiqueta se la haya sido explicado ampliamente.

(TO THE USER: If you cannot read English, do not use this product until the label and manual has been fully explained to you.)

### STATEMENT OF PRACTICAL TREATMENT

Symptoms of overexposure are headache, dizziness, nausea, difficult breathing, vomiting, and diarrhea. In all cases of overexposure get medical attention immedically. Take victim to a doctor or emergency treatment facility.

If the gas or dust from aluminum phosphide is inhaled:
Get exposed person to fresh air. Keep warm and make sure person can breathe freely. If breathing has stopped give artificial respiration by mouth-to-mouth or other means of resuscitation. Do not give anything by mouth to an unconscious person,

If aluminum phosphide pellets, tablets, or bags are swallowed:

Drink or administer one or two glasses of water and induce vomiting by touching the back of the throat with finger, or if available, syrup of ipecac. Do not give anything by mouth if victim is unconscious or not alert.

it powder or granules of atuminum phosphide get on skin or clothing: Brush or shake material off clothes and shoes in a well ventilated area, Allow clothes to aerate in a ventilated area prior to laundering. Do not leave contaminated clothing in occupied and or confined areas such as automobiles, vans, motel rooms, etc. Wash contaminated skin thoroughly with soap and water.

If dust from petiets or tablets gets in eyes; Flush with plenty of water, Get medical attention immediately.

THIS PRODUCT IS ACCOMPANIED BY AN APPROVED LABEL AND APPLICATOR'S MANUAL, READ / ND UNDERSTAND THE ENTIRE LABELING. ALL PARTS OF THE LABELING ARE EQUALLY IMPORTANT FOR SAFE AND EFFECTIVE USE OF THIS PRODUCT, CALL MIDLAND FUMIGANTS, OR EPA IF YOU HAVE ANY QUESTIONS OR DO NOT UNDERSTAND ANY PART OF THIS LABELING. REFER TO THE APPLICATOR'S MANUAL FOR DETAILED PRECAUTIONS, RECOMMENDATIONS AND DIRECTIONS FOR USE.

WARRANTY

Seller warrants that the product conforms to its chemical description and when used according to label directions under normal conditions of use, it is reasonably fit for the purposes stated on the label. Seller makes no other warranty, either express or implied, and buyer assumes all risk should the product be used contrary to label instructions.

CLASSIFIED BY UNDERWRITERS LABORATORIES, INC. AS TO FIRE HAZARD ONLY WHEN USED SPECIFI-CALLY AS DIRECTED IN THE MANUFACTURER'S INSTRUCTIONS, FUMIPHOS TABLETS, PELLETS, AND BAGS ARE NONCOMBUSTIBLE, BUT EXPOSURE TO MOIST AIR OR WATER RELEASES FLAMMABLE AND TOXIC PHOSPHINE (HYDROGEN PHOSPHICE) GAS. SPONTANEOUS IGNITION MAY RESULT IF CON-TACTED BY WATER, ACIDS, OR CHEMICALS.

## TABLE OF CONTENTS

### 1. INTRODUCTION

- 2. PRECAUTIONARY STATEMENTS
  A. Hazards to Humans and Domestic Animals
  - B. Statement of Practical Treatment

  - C. Note to Physician
    D. Physical and Chemical Hazards

### 3. DIRECTIONS FOR USE

- A. General B. Efficacy

- C. Exposure Conditions
  D. Commodities Which May be Furnigated with
- **FUMIPHOS** E. Recommended Dosages
- F. Application Procedures

#### 4. PROTECTIVE CLOTHING

#### **5. RESPIRATORY PROTECTION**

- A. When Respiratory Protection Must be Worn
  B. Permissible Gas Concentration Ranges for Respir
  C. Requirements for Availability of Respiratory Protection. Respiratory Protection Devices

#### **6. PLACARDING OF FUNIGATED AREAS**

## 7. AERATION OF FUNIGATED COMMODITIES

- A Foods and Feeds

### 8. APPLICATORS AND WORKER EXPOSURE

- A. Hydrogen Phosphide Exposure Limits B. Application of Furnigant C. Leekage from Furnigated Sites

- D. Aeration and Reentry
  E. Handling Unaerated Commodities
  F. Industrial Hygiene Monitoring

## 9. STORAGE INSTRUCTIONS

## 10. DISPOSAL INSTRUCTIONS

- A. General
- B. Directions Disposal of Residual Cust from FUMIPHOS
- C. Directions for Deactivation of Residual Dust from

## **FUMIPHOS**

## 11. SPILL AND LEAK PROCEDURES A. General Precautions and Directions

- 3. Directions for Deactivation by the Wet Method

### **SECTION 1** INTRODUCTION

FUMPHOS furrigants are used to protect stored commodities from damage by insects and for the control of burrowing pests. Furrigation of stored products with FUMIPHOS in the manner prescribed in the labeling does not contaminate the stored commodity.

FUNIPHOS and other Aluminum Phosphide furnigants are acted upon by atmospheric moisture to produce Hydrogen Phosphide (phosphine, PH3) gas, FUMIPHOS tablets, pellets, and bags contain aluminum phosphide (ALP) as their active ingredient and will liberate hydrogen phosphide via the following chemical reaction:

Hydrogen phosphide gas is highly toxic to insect, burrowing pests, humans, and other forms of animal life. In addition to its toxic properties, the gas will compde certain metals and may ignite spontaneously in air at concentrations above its lower flammable limit of 1.8% (wv). These hazards will be described in greater detail later on in this Applicators Manuel for FUMIPHOS pell-its, tablets, and begs.

FUMPHOS also contains army inium carbor tate which fiberates ammonia and carbon dioxide as follows:

These gases are essentially nonflammable and act as inerting agents to reduce fire hazards. The ammonia gas also serves as a warning agent.

FUMIPHOS is prepared in three forms, tablets, pellets, and begs. The rounded tablets weigh approximately 3 grams and release 1 gram of hydrogen phosphide gas. They are about 16mm in diameter and are bulk packaged in resealable aluminum flasks containing 100 or 500 tablets each. The pellets weigh approximately 6.6 gram and release 0.2 gram of hydrogen phosphide gas. They are about 16 mm in diameter and are packaged in resealable flasks containing about 1600 pellets.

The bags weigh 34 grams each and release 11 grams of hydrogen phosphide gas. They are packaged in metal containers of ten, or one hundred bags as the container, The bags are packaged in an oxygen free environ-

Upon exposure to air FUMIPHOS pellets, tablets, and bugs begin to react with atmospheric moisture to produce small quantities of hydrogen phosphide gas. This reaction starts slowly, gradually accelerates and then tapers off again as the atuminum phosphide is spent. FUMIPHOS pellets react somewhat fuster then do the tablets and bugs. The rates of decomposition of the tablets, pellets and hugs will very depending upon musture and temperature of the fumigated commodity are high, decomposition of FUMIPHOS may be complete in less than 3 days. However at lower ambient temperatures and relative humidity levels, decomposition of FUMIPHOS may require 5 days or mo.e. After decomposition, FUMIPHOS teaves a gray-white powder composed almost entirely of aluminum hydroxide and other approved inert ingredients. This will cause no problems if the furnigant has been added directly to commodity such as grain or butk animal feed. However, the spent powder must usually be retrieved for disposal after space furnigations. If properly exposed, the spent FUMIPHOS will normally contain only a small amount of unreacted aluminum phosphide and may be disposed without hazard. While not considered ... "szardous waste, partially spent residual from incompletely, exposed FUMIPHOS will require special care. Precautions and instructions for further deactivation and disposal will be given later in this Manual.

FUMPHOS peliets, tablets, and bags are supplied in gas light containers and their shall life is unlimited as long as the packaging remains intact. Once opened for tunigation, FUMIPHOS containers may be lightly resealed for future use. FUMPHOS 100 x 34 gram bag containers cannot be resealed for future use. Storage and handling instructions will be given in detail later in this Applicators Manual.



### A summary of safety recommendations is outlined below:

#### SAFETY RECOMMENDATION SUMMARY

- Carefully read the labeling and follow instructions
- Never furnigate alone from inside the storage structure.
- Person supervising must be a certified furnigator and personnel assisting must be trained in the use of ALP. Never allow uninstructed personnel to handle FUMIPHOS.
- Approved respiratory protection must be available for the furnigation of structures from within. Wear dry gloves of cotton or other material if contact with FUMIPHOS tablets, pellets or bags is likely Aerate used gloves and other conteminated clothing in a well ventilated area prior to laundering. Wash hands thoroughly after usir g FUMIPHOS.
- Open furnigant containers in open arronly. Never open in a flammable atmosphere Do not allow FUMIPHOS to contact liquid or pile up.
- Dispose of empty containers and spent residual dust in, a menner consistent with the label instructions.
- Post warning placards on lumigated areas,
- 10. Prior to fumigation, notify appropriate company employees. Provide to local officials (fire department, rescue squad, police, etc. on an annual basis relevant safety information for use in the event of an emergency.
- Hydrogen phosphide fumigants are not to be used for vacuum fumigations.
- Exposure to hydrogen phosphide must not exceed the eight hour TWA of 0.3 ppm during application, or a ceiling concentration of 0.3 ppm after application is completed.
- 13. Furnigated areas must be serated to 0.3 ppm hydrogen phosphide or less prior to reentry by unprotected workers.
- 14. Finished foods and feeds that have been furnigated with FUMIPHOS must be aerated for 48 hours.
- prior to offening to the end use consumer.

  Transfer of a treated commodity to another site with-out complete agration is permissible provided.
- that the new storage site is placarded if its concentration is abrive 0.3 ppm.,

  16. Keep containers of FUMPHOS tightly closed except while re-noving product for application.

  17. Protect materials containing metals such as copper, silver, gold and their alloys and salts from
- corrosive exposure to hydrogen phosphide.
- 18. Tablets , pellets and bags must not come in contact with any processed food except that may be added directly to processed brewers rice, malt and com grite used in the manufacture of beer.
- Do not use aluminum phosphilde containers for any purpose other then recycling or reconditioning OSHA recommends preexposure screening of employees to detect imp\_red pulmonary function. They recommend that any employees developing this condition be referred for medical examination.

#### **SECTION 2** PRECAUTIONARY STATEMENTS

1. 200

A. Hazards to Humans and Domestic Animals
DANGER: Aluminum phosphide from FUNIPHOS tablets, peliets or bags may be fatal if awallowed. Do not get in
eyes, on skin or on clothing. Do not eat, drink or smalls while handling aluminum phosphide furnigents. If a sealed
container is opened, or if the material comes in contact with moisture, water or acids, these products will release hydrogen phosphide (phosphine, PH3) which is an extremely toxic gas. If a garlic odor is detected refer to the industrial Hygiene Monitoring section on page 14 of the Applicators Manual for apprupriate monitoring procedures. Pure hydrogen phosphide gas is odorless: the garlic odor is due to contaminant. Since the odor of hydrogen phosphide may not be detected under some circumstances, the absence of a garlic odor does not mean that dangerous levels of hydrogen phosphide gas are absent. Observe proper reentry procedures specified elsewhere in the labeling to prevent overexposure.

St...ement of Practical Treatment Symptoms of overexposure are headache. dizziness, nausea, difficult breathing, vomiting, and diarrhea. In all cases of overexposure get medical attention immediately. Take victim to a doctor or emergency treatment facility.

If the gas or dust from aluminum phosphide is inhaled: Get exposed person to fresh air. Keep warm and make sure person can breathe freely. If breathing has stopped, give artificial respiration by mouth-to-mouth or other means of resuscitation. Do not give anything by mouth to an unconscious person.

If aluminum phosphide pellets, tablets or bags are swallowed Drink or administer one or two glasses of water and induce vomiting by touching back of throat with finger, or if available, syrup of ipecac. Do not give anything by mouth if victim is unconscious or not alert.

If powder or granules of aluminum phosphide get on skin or clothing: Brush or shake material off clothes and shoes in a well ventilated area. Allow clothes to serate in a ventilated area prior to laundering. Do not leave contaminated clothing in occupied and/or confined areas such as automobiles, vans, motel rooms, etc. Wash contaminated skin thoroughly with soap and water.

If dust from pellets, tablets or bags gets in eyes: Flush with plenty of water. Get medical attention.

C. Note to Physician (we recommend that this section be given to the attending physician)
Aluminum phosphide tablets, pellets or bags react with moisture from the air, acids and many other liquids to release hydrogen phosphide (phosphine PH3) gas. Mild exposure by inhalation causes malaise (indefinite feeling of sickness) ringing in the ears, fatigue, nausea and pressure in the chest which is relieved by removal to fresh air. Moderate poisoning may occur within a few hours to several days resulting in pulmonary edema (fluid in lungs) and may lead to dizziness, cyanosis (blue or purple skin color), unconsciousness, and death.

In sufficient quantity, phosphine affects the liver, kidneys, lungs, nervous system and circulatory system. Inhalation can cause lung edema (fluid in lungs) and hyperemia (excess of blood in body parts), small perivascular brain hemorrhages and brain edema (fluid in brain), Ingestion can cause lung and brain symptoms but damage to the viscera (body cavity organs) is more common. Phosphine poisoning may result in (1) pulmonary edema, (2) liver elevated serum GOT, LDH and alkaline phosphatase, reduced prothrombin, hemorrhage, and jaundice (yellow skin color) and (3) kidney hematura (blood in urine) and anuna (abnormal or lack of urination). Pathology is characteristic of hypoxia (oxygen deficiency in body tissue). Frequent expo. ure to concentration above permissible levels over a period of days or weeks may cause poisoning. Treatment is symptomatic.

The following measures are suggested for use by the physician in accordance with his own judgement: In its milder forms, symptoms of poisoning may take some time (up to 24 hours) to make their appearance, and the following is suggested.

Give complete rest for 1-2 days, during which the patient must be kept quiet and warm.
 Should patient suffer from vorniting or increased blood sugar, appropriate solutions should be administered.
 Treatment with oxygen breathing equipment is recommended as is the administration of cardiac and circulatory.

In cases of severe poisoning (Intensive Care Unit recommended):

Where pulmonary edema is observed, steroid Therapy should be considered and close medical supervision is recommended. Blood transfusions may be necessary.

 In case of manifest pulmonary edema, venesectior, should be performed under vein pressure control. Heart plycosides (I.V.) (in case of hemoconcentration, venesection may result in shock). On progressive edema of the lungs: immediate intubation with a constant removal of edema fluid and oxygen over-pressure respiration, as well as any measures required for shock treatment. In case of kidney failure extracorporeal hemodialysis is necessary.

There is no specific antidote known for the poisoning.

3. Mention should be made here of suicidal attempts by taking solid phosphide by mouth. After swallowing: emptying of the stomach by vomiting, flushing of the stomach with diluted potassium permanganate solution of magnesium peroxide until flust ing ceases to smell of carbide. Thereafter apply carbomedicinalis.

D. Physical and Chemical Hazards

Aluminum phosphide in tablets, pellets and bags will release hydrogen phosphide if exposed to moisture from the air or if it comes in contact with water, acids and many other liquids. Piling of tablets, pellets, or bags from their fragmentation may cause a temperature increase and confine the release of gas so that ignition could occur.

It is preferable to open containers of aluminum phosphide products in open air, as under certain conditions, they may tlash upon opening. You may also wish to open containers near a fan or other appropriate ventilation which will rapidly exhaust contaminated air. When opening, point the container away from the face and body and slowly toosen the cap. Although the chances for a flash are remote never open the containers in a flammable atmosphere. Those precautions will also reduce the furnigator's exposure to hydrogen phosphide.

ر آنهو

Pure phosphine (hydrogen phosphide) gas is practically insoluble in water, fats and oils, and is stable at normal furnigation temperatures. However, it may react with certain metals and cause corrosion, especially at higher normal rumsgation temperatures. However, it may react with certain metals and cause corroson, especially at higher temperatures and relative humidities. Metals such as copper, loss and other copper alloys, and precious metals such as gold and silver are susceptible to corrosion by phosphine. Thus, small electric motors, smoke detectors brass sprintder heads, batteries and battery chargers, fork lifts, temperature monitoring systems, switching gears, communication devices, computers, calculators and other electrical equipment should be protected or removed before furnigation. Hydrogen phosphide will also react with certain resultic salts and therefore, sensitive items such as a between the expectation. as photographic film, some inorganic pigments, etc. should not be exposed.

#### SECTION 3 DIRECTIONS FOR US

### A. General

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

1. FUMIPHOS tablets, pellets and bags are Restricted Use Pesticide due to the acute inhalation of hydrogen phosphide (phosphine PH 3) gas. These products are for retail sale to and use only by certified applicators for uses covered by the applicators certification or person trained in accordance with the Applicators Manual working under the direct supervision and in the physical presence of the applicator. Physical presence means on site or on the premises. Read and follow the label and the FUMIPHOS Applicators Manual which contains complete instructions for the safe use of this pesticide.

2. FUNIPHOS is a highly hazardous material and should be used only by individuals trained in its proper use.

Before using read and follow the label precautions and directions.

Additional copies of this Manual are available from: PHOSFUME CHEMICAL CO. a subsidiary of Midland Fumigant Co., Inc., 1805 S. 2nd St., Leavenworth, KS 66048.

Persons working with FUMIPHOS should be knowledgeable of the hazards of this chemical and trained in the use of

required respiratory equipment and detector device, emergency procedures and use of the furnigant.

3. A licensed furnigator must be present and at least two persons trained in the use of ALP should be present during furnigation of structure if entry into the structure is required for application of the furnigant. Two train persons must also be present during reentry into furnigated or partially aerated structures. Only one trained person is required to be present when FUMIPHOS is applied from outside the area in be related.

4. Shipholds, barges, containers on ships, railroad cars and containers shipped piggyback by railway may be fumigated intransit. However, trucks, vans, trailers and similar transport vehicles cannot be moved over public roads

and highways until they are aerated and the warning placards removed.

5. Do not furnigate commodities with FUMIPHOS when commodity temperature is 1 slow 40 degrees F. (5

6. The site to be furnigated must first be inspected to determine if it can be sufficiently gas tight. Then a plan should be developed to provide for safe and efficient application of the furnigant to include emergency procedures. etc., where required, and to decide how monitoring should be conducted to prevent excessive exposure

7. Wear dry gloves of cotton or other material while handling FUMIPHOS tablets, pellets, or bags. Wash hands

thoroughly after use.

8. Hydrogen phosphide gas may flash at concentration above its flammable limit. Therefore, always open FUMIPHOS containers in open air and never in a flammable atmosphere. This precaution will not only prevent harm in the unlikely event of a flash but ,will reduce the applicators exposure to hydrogen phosphide gas.

9. Piling of tablets, petiets or bags or addition of liquid to FUMIPHOS may speed up the reaction, cause a temperature increase and confine the gas so that ignition could occur.

10. As much as is possible protect unused FUMIPHOS from excessive exposure to atmospheric moisture.

during application and ghtly reseal the aluminum flask prior to returning tablets or pellets to storage. FUMPHOS bag containers oner upened carnot be resealed for suture use.

11. Hydrogen phosphide gas may react with certain metals and their safts to produce corrosion. Copper, copper alloys and precious metals such as silver and gold are susceptible to corrosion and items containing these elements should be removed or protected prior to furnigation with FUMPHOS.

12. Do not allow FUMIPHOS or its residual dust to come in contact with processed foods or commodity packages intended for retailers except that FUMIPHOS tablets, pellets or bags may be added directly to processed brewers rice, malt and corn grits used in the manufacture of beer.

13. Respiratory protection approved for the concentration to which the furnigator will be exposed must be available if FUMIPHOS is to be applied from within the structure to be furrigated. Respiratory protection need not be available for uses such as outdoor application, addition of tablets or pellets to automatic dispensing devices, tc., if exposures above the TLV's will not be encountered.

A NIOSH/MSHA approved, full-face gas mask -hydrogen phosphide canister combination may be used at levels up to 15 ppm. Above this level or in situations where the hydrogen phosphide concentration is unknown a NIOSH/MSHA approved, self-contained breathing appearatus (SCBA) or its equivalent must be used.

14. Notify appropriate company employees prior to furnigation. Provide to local officials (fire department,

rescue squad, police, etc.) on annual basis relevant safety information for use in the event of an emergency,

B. Efficacy
FUMPHOS has been found effective against the following insects and their preadult stages - that is eggs,

almond moth angeumols grain moth been weevil bees cadelle cereal leaf beede cigarette beetle confused flour beetle dermestid beetles dried fruit beedle dried fruit moth European grain moth llat gri iin beede fruit flies granary weevil greater wax moth

hairy fungus boods Hossian By Indian meal math khanra beede lesser grain borer maize weevil Mediterranea erranean flour moth pink bollworm raisin mosh red flour beet

r-toothed grain beetle spider beetles tobacco moth yellow meal worm

rusty grain weevil

rice weevil

Although it is possible to achieve total control of the listed insect pests, this is frequently not realized in actual practice. Factors contributing to less than 100% control are leaks, poor gas distribution, unfavorable exposure conditions, etc. In addition, some insects are less susceptible to hydrogen phosphide than others. If maximum control is to be attained extreme care must be taken in sealing, the higher dosages must be used, exposure periods must be lengthened, proper application procedures followed and temperature and humidity must be favorable.

C. Exposure Conditions
The following conditions may be used as a guide in determining the minimum length of the exposure period at the indicated temperatures:

#### Minimum Exposure Periods for FUMIPHOS

Temperature	Policis	Tablets	Bags
below 40°F (5°C)	Do not funigate	Do not furnigate	Do not furnigate 14 days (336 hours) 7 days (168 hours) 4 days (96 hours) 3 days (72 hours)
40°-53°F (5-12°C)	8 days (192 hours)	10 days (240 hours)	
54°-59° F (12-15°C)	4 days (96 hours)	5 days (120 hours)	
60°-68° F (16-20°C)	3 days (72 hours)	4 days (96 hours)	
above 68° F (20°C)	2 days (48 hours)	3 days (72 hours)	

The length of the furnigation must be great enough so as to provide for edequate control of the insect pests which infest the commodity being treated. Additionally, the furnigation period should be long—nough to allow for more or less complete reaction of FUMIPHOS with moisture so that little or no unreacted aluminum phosphide remains. This will minimize exposures during further storage and/or processing of the treated bulk commodity a: well as reduce hazards in the disposal of partially spent aluminum phosphide products remaining after space furnigations. The proper length of the furnigation period will vary with exposure conditions since, in general, insects are more difficult to control at lower temperatures and the rate of hydrogen phosphide gas production by FUMPHOS is less at lower temperatures and humidides.

It should be noted that there is little to be gained by extending the exposure period if the structure to be furnigated has not been carefully sealed or if the distribution of gas is poor and insects are not subjected to lethal concentrations of hydrogen phosphide. Careful sealing is required to ensure that adequate gas levels are retained and proper application procedures must be followed to provide satisfactory distribution of hydrogen phosphide gas. Some structures can only be treated when completely turped, while others cannot be properly sealed by any means and should not be furnigated. Exposure times must be lengthened to allow for penetration of gas throughout the commodity when furnigant is not uniformly added to the mass, for example, by surface application or shallow probing. This is particularly important in the lumigation of bulk commodity contained in large storages.

Remember, exposure periods in the table are minimum periods and may not be adequate to control all stored products pests under all conditions nor will they always provide for total reaction of FUMIPHOS, particularly if temperatures and commodity moisture levels or humidity are low during the furnigation.

D. Commodities Which May be Funigated with FUMPHOS

FUMIPHOS may be used for the funigation of listed raw agricultural commodities, animal feed and feed ingredients, processed toods, tobacco and certain other non-lood larms.

1. Raw Agricultural Commodition, Animal Food and Food Ingredients

FUMPHOS tablets, poliets and bags may be added directly to animal feed, feed ingredients and raw agricultural commodities stored in bulk. For these commodities not stored in bulk, FUMPHOS may be pieced in moisture permeable envelopes, on trays, in bage, etc., and furnigeted as with processed foods.

Raw Agricultural Commodities and Animal Feed and Feed Ingredients Which May be Furnigated with FLIMPHAS

Amonds Animal Food Barley Brazil Nuts Cacheus Cocos Beans Coffee Beans Com

Cottonseed Dates Filberts Flower Seed **Grass Seed** Legumes Milet

Poecom Rica Rye Sefformer Seed

Seed & Pod Vegetables Setame Seed Sorphum Soybeens Sunflower Seeds Triticale Vegetable Seeds Wainuts

2. Processed Foods
The listed processed foods may be furnigated with FUMIPHOS. Under no condition shall any processed food or bagged commodity come in contact with FUMIPHOS tablets, pellets, bags or residual dust except that FUMIPHOS may be added directly to processed brewer's rice, mait and com grits for use in the manufacturer of

Processed Foods Which May be Fumigeted with FUMIPHOS

Processed candy and Sugar Cereal Flours and Bakery Mixes

Cereal Foods (including cookles, crackers, macaroni, noodles, pasta, pretzels, snack foods and spaghetti)
Processed Cereals (including milled fractions and packaged cereals)

Cheese and Cheese By-products
Chocolate & Chocolate Products (assorted chocolate, chocolate liquor, cocoa, cocoa powder, dark chocolate costing and milk chocolate)
Processed Coffee

Com Grita

Cured, Dried and Processed Meat Products and Dried Fish Dates and Figs

Dried Eggs and Egg Yolk Solids
Dried Eggs and Egg Yolk Solids
Dried Milk, Dried powdered milk, Non-dairy Creamers, and Nonfat Dried Milk
Dried or Dehydrated Fruits (apples, dates, figs, peaches, pears, prunes, raisins and sultanas)
Processed Herbs, Spices, Seasonings and condiments

Processed Nuts (almond, apricot kernels, Brazil nuts, cashews, filterts, peanuts, pecans, pistachio nuts, and

Proce .sed cets (including cermeel) Pice (brewers rice grits, enriched and polished wild rice)

Processed Tea

Dried and Dehydrated Vegetables (beans, carrots, lentils, peas, poteto products and spinach)

Yeast (including primary yeast)

Nonfood commodities, including Tobacco
 The listed nonfood items may be furnigated with FUMIPHOS. Tobacco and certain other of the nonfood
 commodities should not be contacted by tablets, pellets or residual dust.

4. Nonfood Commodities which may be Furnigated with FUMPHOS Processed or Unprocessed Cotton, Wool and other Natural fibers or Cioth, Clothing

Straw and Hay

Feethers

Human Hair, Rubberized Hair, Vulcanized heir Mohair Leather Products, Animal Hides and Furs

Wood, Cut Trees, Wood Chips and Wood and Bamboo Products Paper and Paper Products Dried Plants and Flowers

Seeds (grass seed, ornamental herbaceous plant seed and vegetable seed)

E. Recommended Dosages
Hydrogen phosphide is a mobile gas will penetrate to all parts of the storage structure. Therefore, dosage must be based upon the total volume of the space boing treated and not on the amount of commodity it contains. The same amount of FUMMP-IOS is required to treat a 30,000 bushel allo whether it is empty or full of grain unless, of course, the surface of the commodity is sealed off by a tarpeutin. The following dosage ranges are recommended for bulk and space furnigations:

### Dosage Guidelines for Furnigations with FUMIPHOS

Product	per 1000 cu. lt.*	per 1000 bu.*
Bags	2 -6	2 - 6
Pellets	100 - 725	120 - 900
Tablets	20 - 145	25 - 180

\*Dosage range for dates, nuts & dried fruits is 100-200 pellets, 20-40 tablets, 2-6 bags/1000 cu. ft.; 125-250 pellets, 25-50 tablets, 125-250 pellets, 2-6 bags/1000 bu.

These dosages are not to be exceeded, it is important to be aware that a shortened exposure period cannot be fully compensated for with an increased dosage of hydrogen phosphide.

The wide range of dosages listed above is required to handle the variety of furnigation situations encountered in practice. Some what higher dosages are usually recommended under cooler, drier conditions or where exposure periods are relatively short.

However, the major factor in selection of dosage is the ability of the structure to hold hydrogen phosphide gas during the furnigation. A good illustration of this point is comparison of the low dosages required to treat modern, well-sealed warehouses with the higher range used for poorly constructed buildings that cannot be sealed adequately, in certain other furnigations, proper distribution of lethal concentrations of gas to reach all parts of the structure—becomes a very important factor—in dose selection. An example where this may occur is in the treatment of grain stored in tall sites. Poor gas distribution frequently results when the furnigant cannot be uniformly added to the grain and it must be treated by surface application.

Although it is permissible to choose from the full range of dosages listed above, the following dosages are recommended for the various types of furnigations:

## Recommended FUMIPHOS Dosages for Various Types of Fumigations

Type of Furnigation 1. Space	Bags	Pellets	Tablets
Mills, Warehouse, etc.	2-6/1000 cu. ft.	100-300/1000 cu. ft.	20-60/1000 cu. ft.
Bagged Commodities	2-6/1000 cu. ft.	150-300/1000 cu. ft.	30-60/1000 cu. ft.
Processed Fruits & nuts	2-6/1000 cu. ft.	100-200/1000 cu. ft.	20-40/1000 cu. ft.
Stored tobacco	2-6/1000 cu. ft.	100-200-/1000 cu. ft	20-40/1000 cu. ft.
2. Bulk Stored Commodities	2-6-1000 cu, ft,	150-300/1000 cu. ft.	30-70/1000 cu. ft.
Vertical storages	2-6/1000 BU	200-375/1000 BU	40-75/1000 BU
Tanks	2-6/1000 cu. ft.	150-350/1000 cu. ft.	30-60-/1000 cu. ft.
	2-6/1000 BU	200-450/1000 BU	40-90/1000 BU
Flat storages	2-6/1000 cu, ft.	250-725/1000 cu. ft.	50-145/1000 cu. ft.
	2-6/1000 BU	300-900/1000BU	60-180/1000 BU
Farm Bins	2-6/1000 cu, ft,	350-725/1000 cu. ft.	70-145/1000 cu. ft.
	2-6/1000 BU	450-900/1000 BU	90-160/1000 BU
Bunkers & tarped ground storages	2-6/1000 cu. ft.	150-400/1000 cu. ft.	30-80/1000 cu. ft.
	2-6/1000 BU	200-500/1000 BU	40-100/1000 BU .
Railcars	2-6/1000 cu, ft.	150-325/1000 cu. ft.	30-65/1000 cu. ft.
	2-6/1000 BU	200-400/1000 BU	40-80/1000 BU
Barges	2-6/1000 cu. ft.	150-400/1000 cu, lt.	30-80/1000 cu. ft.
	2-6/1000 BU	200-500/1000 BU	40-100/1000 BU
Shipholds	2-6/1000 cu. ft.	150-330/1000 cu. ft.	30-66/1000 cu. lt.
	2-6/1000 BU	200-375/1000 BU	40-75/1000 BU

Higher dosages are recommended in structures that are of loose construction and in the furnigation of bulk stored commodities in which diffusion will be slowed and result in poor distribution of hydrogen phosphide gas.

## F. Application Procedures 1. General Statement

Regardless of the type of storage to be treated, there are several important factors common to all application procedures. A number of these points have been covered in other sections of the Applicator's Manual but are listed again in the following for completeness.

a. A plan should be devised for application, seration and disposal of the furnigant so as to keep a minimum any exposures to hydrogen phosphide. See the requirements for industrial Hygiene Monitoring under the Applicator and Worker Exposure section of this Applicators. Manual.

FUMIPHOS tablets or pellets or bags should be applied so as to provide effective gas concentrations throughout the storage. When tablets or petlets or bags are not applied uniformly to a bulk commodity (surface application in a tall sito or ships hold for example), exposure times should be lengthened to allow for enetration of gas throughout the storage.

c. The storage structure should be seeled so as to maintain a suitable gas concentration over the time period required for control of insect pests.

d. Ideally, exposure periods should be long enough to provide for adequate control of insect pests and also more or less completely react the furnigant.

e. Piling of large numbers of tablets or pellets, whether applied to a bulk commodity or for space funigation,

may prevent complete breakdown of the product by limiting its access to moist air. This can result in decrea efficacy as a result of poor gas release and may leave an active residual for disposal which contains considerable amounts of unreacted aluminum phosphide. Piling of product may also result in increased hazard of fire if water should come into contact with the mass of aluminum phosphide.

Contact with liquid water should be carefully avoided when applying FUMIPHOS for treatment of bulk commodities or space.

g. Aluminum phosphide furnigants should not be applied to confined spaces where the concentration of hydrogen phosphide may build up to e: .eed its lower flammable limit,

Observe the precautionary and safety statements, mentioned in this manual.

The following instructions are intended to provide general guidelines for typical furnigations. These instructions are not intended to cover every type of situation, nor are they meant to be restrictive. Other procedures may be used if they are safe, effective and consistent with the properties of aluminum phosphide products.

2. Fumigations of Farm Bins

Leakage is the single most important cause of failures in the treatment of farm storages. Since these storages are often small, they usually have a higher leakage area in proportion to their capacity. Most wooden storage structures are so porous that they cannot be successfully furnigated unless they are completely tarped. Do not furnigate storages which will be entered by humans or animals prior to aeration. Do not furnigate areas which house sensitive equipment containing copper or other metals likely to be corroded by hydrogen phosphide gas.

Seal the bin as tightly as possible. It is recommended that the surface of the grain be covered with poly after FUMIPHOS has been applied. Tarping the grain surface will greatly reduce the leak rate of the gas as well as reduce the amount of FUMIPHOS received. Only the volume below the tarp riust be dosed. If not tarped, the entire volume of the storage must be treated, whether full or empty.

FUMIPHOS tablets, pellets, or bags may be scattered over the surface or probed into the grain using a rigid PVC pipe about 5 to 7 feet in length and having a diameter of 1 1/4 inches. Use about 20-50 tablets or 100-250 pellets or 60-150 bags. Immediately cover the surface of the grain vith a plastic tarpaulin, Place no more than 25 percent of the total dose at the borrom if the bin is equipped with aeration fans. Caution: Make sure that the aeration duct is dry before adding FUMIPHOS. Addition of FUMIPHOS to water in an aeration duct may result in a fire. Seal the aeration fan with 4 mil plastic sheeting.

Post furnigation warning signs on entrances to the bin and near the ladder.

Following aeration of the bin, the surface of the grain may be sprayed with an approved protectant to discourage reinfestation.

3. Fumigation of Flat Storages

a. Establish a plan for application of lumigant to the structure. Treatment of these types of storages may require considerable effort, therefore, sufficient manpower should be available to complete the work rapidly enough to prevent excessive exposure to hydrogen Phosphide gas. Vent flasks outside the storage, conduct lurnigations during the cooler periods and emolor other work practices to minimize exposures. It is often advisable to wear respiratory protection during application of furnigant to flat storages, Refer to the sections on Applicator and Worker Exposure and Respiratory Protection.

b. Seal any vents, cracks and other sources of leaks.

c. Apply tablets, pellets, or bags by surface application, shallow probing, decp probing or uniform addition as the bin is filled.

- as the bin is filled.

  Storages requiring more than 24 hours to fill should not be treated by addition of furnigant to the commodity stream as large quantities of hydrogen phosphide may escape before the bin is completely sealed.

  Probes should be inserted vertically at intervals along the length and width of the flat storage. Pellets, tablets or bags may be dropped into the probe at intervals as it is withdrawn.

  Surface application may be used if the bin can be sufficiently gas light to contain the furnigant gas long enough for it to penetrate the commodity. In this instance, it is advisable to place about 25 percent of the desages in the floor level aeration ducts. Check the ducts prior to addition of FUMIPHOS to make sure that they contain no Equid water.
- d. Tarking the surface of the commodity is often advisable, particularly if the overhead of the storage cannot be well sealed.

e. Lock all entrances to the storage and post furnigation warring placards,

- Fumigation of vertical Storages (concrete upright bins and other silos in which grain can be rapidly transferred
- a. Close all openings and seal all cracks to make the structure as airtight as possible. Prior to the furnigation, seal the vents near the bin top which connects to adjacent bins.
- b. Pellets, tablets may be applied continuously by hand or by an automatic dispenser on the headhouse/ gallery belt or into the fill opening as the commodity is loaded into the bin. An automatic dispenser may also be used to add FUMIPHOS into the commodity stream in the leg of the elevator.

16 3410

c. Seal the bin deck openings after the furnigation has been completed.
d. Bins requiring more than 24 hours to fill should not be furnigated by continued addition into the commodity stream. These bins must be furnigated by probing surface application, or other appropriate means. Exposure periods should be lengthened to allow for diffusion of gas to all parts of the bins in FUMIPHOS has not been applied uniformly throughout the commodity mass.

e. Place warning placards on the discharge gate and on all entrances.

5. Furnigation of Mills, Food Processing Plants and Warehouses
a. Using the label, calculate the length of the furnigation and dosage of tablets, pellets or bags to be applied based upon volume of the building, air and /or commodity temperature and the general tightness of the structure, b. Carefully seal and placard the space to be furnigated.

c. Place trays or sheets of Kraft paper or foil, up to 12 sq. ft. (1.1 sq. ft) in area, on the floor throughout the structure to hold FUMIPHOS pellets or tablets. Bags should be spread evenly on the floor. Use total floor space. d. Spread FUMIPHOS on the sheets at a density no greater than 30 tablets per sq. ft. This corresponds slightly more than one-half flask of tablets of one-half flask of pellets per 3" x 4" sheet. Check to see that

FUMIPHOS has not piled up and that it is spread evenly to minimize contact between the individual pellets, tablets, and bags.

e. Doors leading to the furnigated space should be closed, sealed, locked, and placarded with warning signs.

1. The furnigation period usually lasts from 2 to 5 days, depending upon the temperature, I foon completion of the exposure period, windows, doors, vents, etc. should be opened and the furnigated structure allowed to serate for at least two hours before entering. When required , gas concentration readings may be taken using low level detector tubes or similar devices to ensure safety of personnel who reenter the treated area. Refer to the section of Applicator and Worker Exposure. on Applicator and Worker Exposure.

g. Collect the spent bags, and FUMIPHOS dust and dispose of it, with or without further deactivation, following the recommendations given under Disposal Instructions.

h. Remove furnigation warning placerds from the aerated structure

 Furnigation of Railcars, Containers, Trucks, Vans and other Transport Vehicles
Railcars, containers, trucks, vans and other transport vehicles loaded with bulk commodities to which FUMIPHOS tablets, pellets, or bags may be added directly are treated in essentially the same way as any other flat storage facility. FUMIPHOS may be added as the vehicle is being filled, the dose may be scattered over the surface storage (actity). FOMIPHOS may be added as the vertice is being may, the dose may be scattered over the surface after loading has been completed or the tablets, pellets, or bags may be probed below the surface. Carefully seal any vents, cracks, or other leaks, particularly if the furnigation is to be carried out intransit. Remember, railcars and containers shipped piggyback by rail may be furnigated intransit, but it is not legal to move trucks, trailers, vans, etc. over public roads or highways until they are aerated. See section 6 of this Applicator's Manual for the recommendations on placarding. Notify the consignee if the commodity is to be shipped under furnigation, with FUMPHOS. If the consignee is unfamiliar with proper handling of treated railcars, it is recommended that they be provided with the necessary: 'ormation.

7. Tarpaulin and Bunker Fumigations
Use of plastic sheeting or tarpaulins to cover commodities is one of the easiest means for providing relatively gas tight enclosures which are very will suited for fumigation. Poly tarps are penetrated only very slowly by hydrogen phosphide gas, and light coverings are readily formed from the sheets. The volume of these enclosures may vary widely from a few cubic feet, for example, a furnigation terpaulin placed over a small stack of bagged commodity, to a plastic bunker storage capable of holding 600,000 bushels of grain or more.

An enclosure suitable for furnigation may be formed by covering bulk or packaged commodity with poly sheeting. The sheets may be tarped logether to provide a sufficient width of material to ensure that adequate

sealing is obtained, if the flooring upon which the commodity rests is of wood or other porous material, it should be repositioned onto poly prior to covering for lumigation. The plastic covering of the pile may be sealed to the floor using sand or water snakes, by shoveling soil or sand onto the ends of the plastic covering or by other suitable procedures. The poly covering should be reinforced by tape or other means around any sharp comers or edges in the stack so as to reduce the risk of tearing. Thinner poly, about 2 mil., is suitable for most indoor tarp fumigations

and for sealing of windows, doors and other openings in structures. However, 4 mil poly or thicker is more suitable for outdoor applications where wind or other mechanical stresses are likely to be encountered.

Tablets, pellets or bags may be applied to the tarped stack or bunker storage of bulk commodity through slits in the poly covering. Probing or other means of dosing may be used. Avoid application of large amounts of FUMIPHOS at any one point. The FUMIPHOS should be added below the surface of the commodity if condensation or other source of moisture is likely to form beneath the poly. The sitts in the cove - 'g should be carefully taped to prevent loss of gas once the dose has been applied. FUMIPHOS bags are recomined for the treatment of bagged commodities and processed foods although tablets and pellets on trays or sheets of Kraft paper may be used. Care should be taken to see that the poly is not allowed to cover the FUMIPHOS and prevent contact with moist air or confine the gas.

Distribution of hydrogen phosphide gas is generally not a problem in the treatment of bagged commodities and processed toods. However, fumigation of larger bunker storages containing bulk commodity will require proper application procedures to obtain adequate results.

Place warning placards at conspicuous on the enclosure.

- 8. Furnigation of Ships a. General Information
- 1, IMPORTANT shipboard, intransit ship or shiphold furnigation is also governed by U.S. Coast Guard Regulation 46 CFR 147A. Refer to this regulation prior to furnigation.
- 2. FUMIPHOS tablets, pellets, and bags are classified by EPA as restricted use pesticides due to the acute inhalation toxicity of hydrogen Phosphide (phosphine, PH3) gas. These products are for retail sale to and use only

by certified applicators for those uses covered by the applicators certification or persons trained in accordance with the Applicators Manual working under the direct supervision, and in the physical presence of the certified applicator. Physical presence means on site or on the premises. Read and follow the label and the PHOSFUME

CHEMICAL CO. a subsidiary of Midland Fumigant Co., Inc. Applicators married which contains complete instructions for the sale use of this pesticide.

- b. Pre-Voyage Furnigation Procedures

   Prior to furnigating a vessel for intransit cargo furnigation, the master of the vessel, or his representative, and the furnigator must determine whether the vessel is suitably designed and configured so as to allow for safe occupancy by the ships crew throughout the duration of the furnigation. If it is determined that the design and configuration of the vessel does not allow sale occupancy by the ships crew throughout the duration of the furnigation, then the vessel will not be furnigated unless all crew members are removed from the vessel. The crew members will not be allowed to reoccupy the vessel until the vessel has been properly aerated and a determination has been made by the master of the vessel and the furnigator that the vessel is safe for occupancy.
- 2. The person responsible for the fumigation must notify the master of the vessel, or his representative, of the requirements relating to person: "\_rotection equipment", detection equipment that a person qualified in the use of this equipment must accompany the vessel with cargo under fumigation. Emergency procedures, cargo ventilation, periodic monitoring and inspections, and first aid measures must be discussed with and understood by the master of the vessel or his representative.

Personal protection equipment means a NIOSH/MSHA approved respirator or gas mask fitted with an approved canister for phosphine. The canister is approved for use up to 15 ppm. SCUBA or its equivalent must be used above 15 ppm or at unknown concentrations.

- 3. Seal all chenings to the cargo hold or tank and lock or otherwise secure all openings, manways, etc., which might be used to the enter the hold. The overspace pressure relief system of each tank aboard tankers must be sealed by closing the appropriate valves and sealing the openings into the overspace with gas-tight materials.
  - 4. Placard all entrances to the treated spaces with furnigation warning signs.
- 5. If the furnigation is not completed and the vessel aerated before the manned vessel leaves port, the person in charge of the vessel shall ensure that at least two units of personal protection equipment and one gas or vapor detection device, and a person qualified in their operation be on board the vessel during the voyage.
- 6. During the furnigation or until a manned vessel leaves port or the cargo is aerated, the person in charge of the furnigation shall ensure that a qualified person using gas or vapor detection equipment tests spaces adjacent to spaces containing furnigated cargo and all regularly occupied spaces for furnigant leakage. If leakage of the furnigant is detected, the person in charge of the furnigation shall take action to correct the leakage, or shall inform the master of the vessel, or his representative of the leakage so that corrective action can be taken.
  - Review with the master, or his representative, the precautions and precedures for during the voyage.
  - c. Application Procedures for Bulk Dry Cargo Vessels and Trukers
- 1. Apply tablets, pellets or bags by scattering uniformly over the commodity surface or they may shallow or deep probed into the commodity mass.
- 2, Immediately after application of the furnigant, close and secure all hatch covers, tank tops, butterworth valves, manways, etc.
  - d, Intransit Furnigation of Containers Aboard Ships

Intransit furnigations of containers on ships is also governed by U.S. Coast Guard Regulation 46 CFR 147A as modified by U.S. Coast Guard Special Permit 52-75. This permit which must be obtained prior to the turnigation is available from:

> U.S. Coast Guard Hazardous Materials Branch MTH-1 Washington, D.C. 20593-0001

Application procedures for furnigation of raw commodities or processed foods in containers and other transport vehicles are described in section 3a.

- e, Precautions and Procedures During Voyage 1, Using appropriate gas detection equipment, monitor spaces adjacent to areas containing furnigated cargo and all regularly occupied areas for furnigant leakage. If leakage is detected, the area should be evacuated of all personnel, ventilated, and action taken to correct the leakage before allowing the area to be occupied.
- 2. Do not enter furnigated areas except under emergency conditions. If necessary to enter a furnigated area, appropriate personal protection equipment must be used. Never enter furnigated areas alone. At least one other person, wearing personal protection equipment, should be available to assist in case of an emergency.
  - Precautions and Procedures During Discharge.
- M necessary to enter holds prior to discharge, test spaces directly above grain surface for furnigant concentration, using appropriate gas detection and personal safety equipment. Do not allow entry to furnigant areas

without personal safety equipment, unless furnigant concentrations are at safe levels, as indicated by a suitable

Fumigation of Sarges
Berge fumigations are also requisted by U.S. Coast Guard regulation 46 CFR147A as modified by U.S.
Coast Guard Special Permit 2-75. This permit which must be obtained prior to the fumigation is available from:

U.S. Coast Guard Hazardous Materials Branch MTH-1 Washington, D.C. 20593-0001

Leaks are a common cause of failures in the treatment of commodities aboard barges. Cerefully inspect all hatch covers prior to application of FUMIPHOS and seal, if necessary. Notify consignee if the barge is to be

10. Fumigations in Small Seciable Enclosures

Excellent results may be attained in the treatment of small enclosures since it is often possible to control the furnigation and also to make the enclosure virtually gas light. Take care not to overdose during these furnigations. A single pellet, will treat a space of from 1.4 to 10 cubic feet. From 6.9 to 50 cubic feet may be furnigated with a single FUMIPHOS tablet or 1 FUMIPHOS bag.

11. Treatment of Beehives, Supers and other Beekeeping Equipment
FUMIP: 'OS tablets, pellets and bags may used for the control of the greater wax moth in store
supers and other 'beekeeping equipment and for the destruction of bees, Africanized bees, and disease. including those invested with trachest mites and foulbrood. The recommended dosage for this use is 30-45 tablets,

150-225 pellets or 3 begs per 1000 cu. ft.

Furnigations may be performed in chambers at atmospheric pressure, under tarpaulins, etc. by placing bag and the tablets or pellets on trays or in moisture permeable envelopes. Do not add more than 2 tablets or 10 pellets to each envelope. Floriery from treated hives or supers may only be used for bee food.

12. Burrowing Pest Control

a. List of Burrowing Pests
EList of Burrowing Pests
FUMIPHOS tablets, pellets and bags may be used out of doors only for the control of the following burrowing rodents and moles: Marmot sp. - Woodchucks and yellow-belly Marmots (Rockchucks), Prairie Dogs (except Utah Prairie Dogs), Norway and Roof Rats, Mice, Ground Squirrels, Moles, Voles, Gophers, and Chipmunk.

b. Directions for Use

Add from one 1 to 4 FUMIPHOS tablets, 5 to 20 pellets, or 2 to 6 bags to each burrow opening. Then seal tightly by shoveling soil over the entrance after first packing the opening with crumpled newspaper or something similar so as to prevent soil from covering the FUMIPHOS and slowing its action. Subsurface tunnels or runways should be treated every 5 to 10 feet with a dose of 2 to 4 tablets, 10 to 20 pellets, and 2 to 6 bags.

Use lower rates in smaller burrows in tight soils under moist soil conditions and higher rates in larger burrows in porous soils when soil moisture is low. Addition of several cups of water to the burrow prior to dosing with FUMIPHOS may improve efficacy in some porous soils. Treat reopened burrows and fresh runways a second time 1 to 3 days after the initial treatment.

FUMIPHOS may be used out of doors only for control of burrowing pests. Do not use within 15 feet (5 meters) of inhabited structures. Do not apply to burrows which may open under or into occupied buildings. For use on all

agricultural and noncropland areas. c. Environmental Hazarda

This product is very highly toxic to wildlife. Non-target organisms explained to phosphine gas it burrows will be killed. Do not apply directly to water or wetlands (swamps, bogs, marshes, and potholes). Do not contaminate water by cleaning of equipment, or disposal of wastes.

by cleaning of equipment, or disposal of wastes.
d. Endangered Species Restrictions
The use of FUMRPHOS in a manner that may kill or otherwise harm an endangered or threatened species or adversely modify their habitat is a violation of Federal laws. The use of this product is controlled to prevent death or harm to endangered or til restened species that occur in the following counties or elsewhere in their range. Use of this product in the areas listed below as prohibited without first contacting and obtaining permission from the integered Species Specialist at the nearest regional offices of the U.S. Fish and Wildlife Service (FWS).

## Areas inhabited by Endangered or Threatened Species

- Black-looted Ferret State of Arizona, Colorado, Kansas, Montana, Nebraska, New Mexico, North Dehota. Oldahoma, South Dakota, Texas, Utah and Wyoming.
- Blunt-nosed Leopard Lizard Counties of Kern, Kings, Fresno, Madera, Merced and Tulare in the State of California.
- 3. Desert Tortoise Washington County in the State of Utah
- 4. Es. tern Indigo Snake States of Florida and Georgia
- 5. San Joaquin Kit Fox Counties of Kern, Yings, Fresno, Merced, Monterey, San Benito, San Luis Obispo, Santa 🐫 🔞 Barbara, Tulare and Ventura in the State of California.

- e. Special Local Restrictions
- 1. North Carolina
- FUMIPHOS tablets, pellets, and bags may only be used for control of rats and mice in the State of North Carolina. Use against other pests is not permitted.

A special permit for black-tailed prairie dog control by poisoning is required in Oldshoms. Contact the Oldshoms State Department of Wildlife Conservation to obtain this permit.

A state permit is required for use of pesticides in Wisconsin to control small mammals, except rats or mice. Please contact your local Department of Natural Resources office for information.

Use of FUMIPHOS tablets, pellets, or bags for mole control is not legal in the State of Indiana.

A state permit is required for use of pesticide in Missouri to control small mammals, except rats and mice. Please contact the Missouri Department of Conservation office for information.

6. Kansas

A special permit for black-tailed prairie dog control by poisoning is required in Kansas. Contact the Kansas Fish and Game Commission to obtain this perr. it.

7. California

Use of FUMIPHOS tablets, pellets, and bags for chipmunk control is not legal in the State of California.

## SECTION 4 PROTECTIVE CLOTHING

Wear dry gloves of cotton or other material if contact with FUMIPHOS tablets, pellets or bags is tikely. Wash hands thoroughly after handling aluminum phosphide products. Aerate used gloves and other contaminated clothing in a well ventilated area prior to laundering.

#### **SECTION 5** RESPIRATORY PROTECTION

A. When Respiratory Protection Must Be Worn

A. When Respiratory Protection Must Be Worm
NIOSH/MSHA approved respiratory protection must be worn if worker exposure limits cannot be met through
controls (such as forced air ventilation) and/or worker practices. Respiratory protection is required if exposure is
likely to exceed the TWA of 0.03 ppm during application, or a 0.03ppm ceiting at any time afterwards. For example,
spiratory protection is required to be worn upon reentry into a partially aerated structure if the hydrogen Phosphide
centration is above .03 ppm. When required, gas concentration measurements for safety purposes may be
ade using low level detector tubes. See the section on Applicator and Worker Exposure for Monitoring requirements. Information on hydrogen phosphide (phosphire: PHC) detector tubes may be obtained from
DMOSETIBRE CMERATION.

PHOSFUME CHEMICAL CO. a subsidiary of Midland Fumigant Co., Inc. 1805 S. 2nd St., Leavenworth, KS 66048

### B. Permissible Gas Concentrations (langes for Respiratory Protection Devices

A NIOSH/MSHA approved, full-faced has mask-hydrogen phosphide canister combination may be used at levels up to 15 ppm or to escape from levels up to 1500 ppm. Above this level or situations where the hydrogen phosphide concentration is unknown, a NIOSH/MSHA approved, self-contained breathing apparatus (SCBA) or its equivalent must be used. The NIOSH/OSHA Pocket Guide, 8085 DHEW/NIOSH 78-210, lists these and other types of approved respirators and the concentration limits at which they may be used.

C. Requirements for Availability of Respiratory Protection

If FUMIP\* OS is to be applied from within the structure to be furnigated, an approved full-face mask gas mask prosphine canister combination or self-contained breathing apparatus (SCBA) or its equivalent must be available at the site of application in case it is needed. In addition, SCBA or its equivalent must be available locally,

for example, at fire station or rescue if it is not available at the furnigation site.

Respiratory protection need not be available for applications from outside the area to be furnigated such as addition of tablets or pellets to automatic dispensing devices, outdoor applications, etc. if exposures above the permitted exposure limits will not be encountered.

If monitoring equipment is not available on a farm and application of furnigant cannot be made from outside the structure, an approved canister respirator must be worn, during application from within, the structure being treated.

## SECTION 6

PLACARDING OF FUMIGATED AREAS

The applicator must placard or post all entrances to the structure under fumigation with signs bearing, in

The applicator must precere or poet an energia and Spanish:

1. The signal word DANGER/PELIGRO and the SKULL AND CROSSBONES symbol in red,
2. The statement "Area and/or commodity under furnigation, DO NOT ENTER/NO ENTRE".

3. The statement, This placard may only be removed after the furnigated area is aerated down to 0.3 ppm hydrogen Phosphide or below. Transfer of incompletely aerated commodity to a new site is permissible provided that the new storage is placarded if it contains more than 0.3 ppm Worker's must not be exposed to more than 0.3

4. The date and time fumigation begins and is completed.

5. Name of furnigant used.

6. Name, address and telephone number of the applicator.

All entrances to a furnigated area, must be placarded. Where possible, placards should be placed in advance of the furnigation to keep unauthorized persons away. For railroad hopper cars, placards must be placed on both

sides of the car near the ladders and next to the top hatches into which the furnigant is introduced.

Do Not remove placards until the treated commodity is aerated down to 0.3 ppm hydrogen Phosphide or less. To determine whether aeration is complete, each furnigated site or vehicle must be monitored and shown to contain 0.3 ppm or less hydrogen phosphide gas in the air space around and, if fear Lie, in the mass of the commodity. Transfer of incompletely aerated commodity to a new site is permissible, i lowever, the new storage must be placarded if it contains more than 0.3 ppm hydrogen phosphide. Workers who handle incompletely as rated commodity must be informed and appropriate measures taken (i.e. ventilation or respiratory protection) to prevent exposures from exposition 0.3 ppm hydrogen phosphide. exposures from exceeding 0.3 ppm hydrogen phosphide.

It is recommended that the persons responsible for removing placards be familiar with physical, chemical and toxicological properties of hydrogen phosphide. They should also be knowledgeable in making gas concentration measurements, exposure limits and symptoms and first aid treatment for hydrogen phosphide poisoning.

## SECTION 7 AERATION OF FUNIGATED COMMODITIES

A. Foods and Feeds

Tolerances for hydrogen phosphide residues have been established at 0.1 ppm for animal feeds and 0.01 ppm for finished foods. To guarantee compliance with these tolerances, it is necessary to aerate these commodities for 48 hours prior to offering to the end use consumer.

Tobacco must be aerated for at least three days (72 hours) when furnigated in hogshead and, for at least two days (48 hours) when furnigated in other containers. Tobacco furnigated in containers with plastic liners will probably require longer aeration periods to reach 0.3 ppm

#### **SECTION 8 EXPOSURE**

A. Hydrogen Phosphide Exposure Limits
Exposure to hydroge: phosphide may not exceed 0.3 ppm measured as an eight hour time weighted average (TWA), for applicators and workers during application. Application is defined as the time period covering the opening of the first containers, applying the appropriate dosage of fumigant and closing up the site to be fumigated. All persons in the treated site and in adjacent indoor areas are covered by its exposure standard.

After application, exposure for any person may not exceed a 0.3 ppm, ceiling for hydrogen phosphide. Such exposures may occur if the commodity or space under furnigation leaks, when treated commodity is transferred or

handled, if an unaerated or partially aerated space is entered, etc.

B. Application of Fumigant

Depending upon temperature and humidity, FUMIPHOS tablets, pellets and bags release hydrogen phosphide gas slowly upon exposure to moisture from the air. In most cases, this release is slow enough to permit applicators to deposit furnigant in the desired areas and then vacate the premises without significant exposure to the gas. If the furnigators is likely to exceed the eight hour TWA of 0.3 ppm, approve respiratory protection must be worn. When required gas concentration measurements for safety purposes may be made using low level detector tubes. See the write-up below on industrial Hygiene Monitoring, Information on hydrogen phosphide (phosphine, PH 3) detector tubes may be obtained from PHOSFUME CHEMICAL CO. a subsidiary of

## Midland Fumigant Co., Inc., 1805 S. 2nd St., Leavenworth, KS 66048.

It is often advisable to use respiratory protection during application of furnigant under hot and humid conditions, particularly when considerable time must be spent inside the structure being treated.

C. Leakage from Fumigated Sites

Hydrogen phosphide is highly mobile and given enough time may penetrate seemingly gas tight materials such as concrete and cinder blocks. Therefore, adjacent, enclosed areas likely to be occupied should be examined to ensure that significant leakage has not occurred. Sealing of the furnigated site and/or in flow into the occupied areas must be sufficient to meet exposure standards.

D. Aeration and Reentry

If the area is to be entered after furnigation, it must be aerated until the level of hydrogen phosphide gas is 0.3 ppm or below. The area or site must be monitored to ensure that liberation of gas from the treated commodity does not result in the development of unacceptable levels of hydrogen phosphide. Do not allow reenay into treated areas by any persons before this time unless protected by an approved respirator.

E. Handling Unserated Commodities

Workers must not be exposed to hydroç~n phosphide in excess of 0.3 ppm\_during moving, storage or processing of incompletely aerated commodities.

F. Industrial Hygiene Monitoring

F. Industrial Hyglene Monitoring
It is recommended that hydrogen phosphide exposures be documented in an operations log, or menual for
each site and operation where exposure may occur. The purpose of monitoring is to prevent excessive exposures
and to determine when and where respiratory protection is required. This mandatory although, once exposure have
been adequately characterized, subsequent monitoring is not routinely required. However, spot checks should be
made occasionally, especially if conditions change significantly or an unexpected gartic odor is detected. Gas
measurements should be made in the workers breathing zone. Monitoring is not required for outdoor operations.
If monitoring shows that workers are exposed to concentrations in excess of the permitted limits, then
engineering controls (such as forced air ventilation) and/ or appropriate work practices should be used, where
consiste in reduce exposure to within negritted limits.

possible, to reduce exposure to within permitted limits.

There are a number of devices on the market for measurement of hydrogen phosphide gas levels for industrial hygiene purposes. One of these is the hydrogen sampling pump. These devices are reliable, portable, simple to use, do not require extensi: a training and are relatively rapidly, inexpensive and accurate. Low level industrial hygiene

#### SECTION 9 STORAGE INSTRUCTIONS

Store FUMIPHOS in a dry, well ventilated area away from heat under lock and key. Post as pesticide storage area. Do not contaminate water, food or feed by storing pesticides in the same areas used to store these commodi-

Do not store in buildings where humans or domestic animals reside. Keep out of reach of children.

FUMIPHOS tablets, pellets and bags are supplied in gas tight, resealable aluminum flasks. Do not expose the product to atmospheric moisture any lc: ger than is necessary and seal tightly before returning opened flasks to

The shelf life of FUMIPHOS is virtually unlimited as long as the containers are ghtly sealed.

## DISPOSAL INSTRUCTIONS

A. General

1. Do not contaminate water, food or feed by storage or disposal.
2. Unreacted or partially reacted FUMIPHOS is acutely hazardous, Improper disposal of excess pesticides is a violation of Federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA

Regional Office for guidance. For specific instructions, see Section 11 of this manual, Spill and Leak Procedure

3. Some local and state waste disposal regulations may vary from the following recommendations. Disposal procedures should be reviewed with appropriate authorities to ensure compliance with local regulations. Contact your state Pesticide or Environmental Control Agency or Hazardous Waste Specialist at the nearest EPA regional Office for guidance.

4. Triole rinse flasks and stoppers with water. Then offer for recycling or reconditioning, or puncture and dispose of an a sanitary landfill or by other procedures approved by state and local authorities. Rinsate may be disposed of in a sanitary landfill by pouring it out onto the ground or by other approved procedures. Or , it is permissible to remove tids and expose empty flasks to atmospheric conditions until residue in flasks is reacted. Then puncture and dispose of in a sanitary landfill or other approved site, or by other procedures by state and local

If properly exposed, the residual dust remains after a furnigation with FUMIPHOS will be a grayish-white powder. This will be a non-hazardous waste and contain only a small amount of unreacted aluminum phosphide. However, residual dust from incompletely exposed FUMIPHOS, so called "green dust" will require special care.

B. Directions for Disposal of Residual Dust from FUMIPHOS

1. Confinement of partially spent residual dust, as in a closed container, or collection and storage of large quantities of dust may result in a fire hazard. Small amounts of hydrogen phosphide may be given off from unreacted aluminum phosphide, and confinement of the gas may result in a flash.

2. In open areas, small amounts of residual dust, up to about 5 to 8 kg., may be disposed of on site by burial.

or by spreading over the land surface away from inhabited buildings.

3. Spent residual dust from FUMIPHOS may also be collected and disposed of at a sanitary tandfill, incinerator or other approved sites or by other procedures approved by Federal, State or Local authorities. "Green Dust" must be further deactivated before disposal at a fundfill.

4. From 2 to 3 kg (4 to 7 lbs.) of spent dust from 2 to 3 flasks of FU'./IPHOS may be collected for disposal in a 1 gallon bucket. Larger amounts, up to about one-half case, may be collected in burlap, cotton or other types of porous doth bags for transportation in an open vehicle to the disposal site. Do to collect dust from more than 7 flasks of tablets or 10 flasks of peters (about 11 kg. or 25 lbs) in a single bag. Do not pile cloth bags together. Do not use this method for partially spent or "green" dust. Caution: Do not collect dust in large drums, dumosters, plastic bags or other containers where confinement may occur.

C. Directions for Descrivation of Partialty Spent Residual Dust from FUMIPHOS

1. Partially spent dust must be descrivated prior to ultimate disposal. This is repaid in cases of incomplete exposure which has resulted in so-called "green dust" or following a furnigation which has produced large quantities of partialty spent material. "Green dust" must be further descrivated prior to disposal in landfills.

2. Residual dust from FUMIPHOS may be descrivated as follows using the "Wet Method".

a. Descrivating solution is prepared by adding the appropriate amount of low audsing detergent or surface active -gent to a water in a drum or other suitable container. A 2% solution of detergent is suggested. The container should be filled with descrivating solution to within a few inches of the top.

b. Residual dust is poured slowly into descrivating solution and stirred so as to thoroughly wet all of the particles. This should be done in the open air and not in the furnigated structure. Dust from FUMIPHOS tablets, pellets, or begs should be mixed into no less th. 10 gallons of water-detergent solution for each case of material used. Weer appropriate -repiratory protection during wet descrivation of partially spent dust.

c. Dispose of the descrivated dust-water suspension, with or without preliminary decanting, at a sanitary landfill or other suitable site approved by local authorities. Where permissible, the sturry may be poured out onto the ground. If the sturry has been held it. 35 hours or more, it may be poured into a storm sewer.

d. Caution: Respiratory protection is required during wet descrivation of partially spent material. Do not cover the container at any time. Do not dispose of dust in a toilet. Do not allow quantities of dry residual dust from FUMIPHOS to be collected or stored without descrivation.

a. Extension of the furnigation period is the simplest method for further deactivation of "green dust" or partially spent dust prior to utilimate disposal

b. Small amounts of partially spent dust, from 2 to 3 kg. (4 to 7 lbs) may be further deactivated by storage in a 1-gallon bucket. Larger amounts of dust (about 11 kg. or 25 lbs) may be held for deactivation in porous cloth begs (burlap, cotton, etc.) Caution: Transport these bags in open vehicles, do not pile up bags and do not use this method

## SECTION 11 SPILL AND LEAK PROCEDURE

A. Gc. Precautions and Directions
A spill up ar than incidental to application or normal handling, may produce high levels of gas and, therefore attending personnel must wear SCBA or its equivalent when the concentration of hydrogen phosphide gas it aztending personnel must wear SCSA or its equivalent when the concentration of hydrogen phosphide gas is unknown. Other NIOSH/MSHA approved respiratory protection may be worn if the concentration is known. Do not use water at any time to clean up a spill of FUMIPHOS. Water in contact with unreacted tablets, pellets or bags will greatly accelerate the production of hydrogen phosphide gas which could result in a toxic and/ or fire hazard. Wear cotton gloves or other material when handling alumin. "In phosphide.

Return all intact aluminum flasks to fiberboard cases or other packaging which has been suitably constructed and marked according to DOT regulations. Notify consignee and shipper of damaged cases.

If aluminum tape or the FUMIPHOS may be transferred from the damaged flask to a sound metal container which should be sealed and properly labeled as aluminum phosphide. Transport the damaged containers to an area suitable for pesticide storage for inspection. Further instructions and recommendations may be obtained from

suitable for pesticide storage for inspection. Further instructions and recommendations may be obtained from

## PHOSFUME CHEMICAL CO. a subsidiary of Midland Furnigant Co., Inc.

If a spill has occurred which is only a few minutes old, collect the tablets , pellets and bags and place them back into the original flasks, if they are intact, and stopper tightly. Place the collected tablets, pellets, and bags in a sound metal container if the original flasks are damaged. Caution: these flasks may flash upon opening at some

If the age of the spill is unknown or if the tablets, pellets, and bags have been contaminated with soil, debris, water, etc. gather up the spillage and place it into small open bucket having a capacity no larger than about 1 gallon. Do not add more than one flask of spilled material, 1 to 1.5 kg. (2 to 3 lbs) to the bucket. If on-site, wet deactivation is not leasible, these containers should be transported in open vehicles to a suitable area. Wet deactivation may then be carried out as described in 11g. Alternatively, small amounts of spillage from 4 to 5 flasks (4 to 8 kg. 9 to 18 ibs) may be spread out in an open area from inhabited buildings by atmospheric moisture.

B. Directions for Deactivation by the Wet Method

If the contaminated material is not to be held until completely reacted by exposure to atmospheric moisture,

deactivate the product by the wet Method as follows:

1. Deactivating solution is prepared by adding the appropriate amount of low sudsing detergent or surface active agent to water in a drum or other suitable container. A 2% solution or 4 cups in 30 gallon is suggested. The container should be filled with deactivation solution to within a few inches of the top.

The tablets, pellets, or bags are poured slowly into the deactivating solution, and stirred so as to thoroughly wet all of the FUMIPHOS. This should be done in the open air. FUMIPHOS tablets, pellets, and bags should be mixed into no less, than about 15 gallons of water-detergent solution for each, case of spent material. Wear appropriate respiratory during wet deactivation.

3. Allow the mixture to stand, with occasional stirring, for about 36 hours. The resultant slurry will then be safe

to dispose of.

ė.

4. Dispose of the sturry of deactivated material, with or without preliminary decaming, at a sanitary landfill or other suitable site approved by local authorities. Where permissible, this sturry may be poured. Into a storm sewer or out onto the ground.

5. Caution: Respiratory protection is required during wet deactivation of unexposed FUMIPHOS. Never place pellets, tablets, or begs in a closed container such as a dumpster, sealed drum, plastic bag, etc. as flammable concentrations and a flash of hydrogen phosphide gas likely to develop.

6. The EPA has determined that proper disposal of aluminum phosphide will cause no unreasonable effects to

the environment.

FOR ASSISTANCE, CONTACT:

## PHOSFUME CHEMICAL CO., a subsidiary of Midland Fumigant Co., Inc. 1805 S. 2nd St. Leavenworth, KS 66048

FUMIPHOS Pellets EPA Reg. No. 43568-1 FUMIPHOS Bags EPA Reg. No. 43568-2 FUMIPHOS Tablets EPA Reg. No. 43568-3