

PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER

KEEP OUT OF REACH OF CHILDREN Corrosive. Causes severe eye and skin damage. Do not get in eyes, on skin or on clothing. Wear goggles or face shield and rubber gloves when handling. Harmful or fatal if swallowed. Avoid contamination of food.

STATEMENT OF PRACTICAL TREATMENT

In case of contact, immediately flush eye or skin with plenty of water for at least 15 minutes. For eyes, call a physician. Remove and wash contaminated clothing before reuse. If swallowed, drink promptly a large quantity of milk or egg whites, gelatin solution or if these are not available, drink large quantities of water. Avoid alcohol. Call a physician immediately.

NOTE TO PHYSICIAN

Probable mucousa damage may contraindicate the use of eye drops. Measures against circulatory shock as well as oxygen and measure to support breathing manually or mechanically may be needed. If eye contact occurs, eye may be irritated by the caustic intravenous solution. If contact with toxic material drug.

ENVIRONMENTAL HAZARDS

FISH AND WILDLIFE PRECAUTIONS

This pesticide is toxic to fish. Do not discharge into lake, stream, ponds, or other waters. Do not contaminate water by cleaning of equipment or disposal of waste.

STORAGE AND DISPOSAL

- DO NOT CONTAMINATE WATER, FOOD OR FEED BY STORAGE OR DISPOSAL
- OPEN BURNING IS PROHIBITED
- DO NOT REUSE EMPTY CONTAINER

PESTICIDE DISPOSAL

Pesticide containers that cannot be used or chemically reprocessed should be disposed of in a landfill approved for pesticides or kept in a safe place away from water supplies.

CONTAINER DISPOSAL

Do not reuse empty container or drum. Return to distributor and they will dispose of by perforating or crushing and burying in a safe place.

KLEER-TOWER ZR-6
INDUSTRIAL WATER COOLING TOWER ALGAEICIDE

Concentrated Algaecide for industrial re-circulating water cooling towers. Helps keep water cooling tower systems clear and free of visible algae slimes.

ACTIVE INGREDIENTS:

n-Alkyl (60 C ₁₂ , 30% C ₁₄ , 5 C ₁₂ , 5 C ₁₄) dimethyl benzyl ammonium chlorides	5.0
n-Alkyl (68 C ₁₂ , 32 C ₁₄) dimethyl ethylbenzyl ammonium chlorides	5.0
INERT INGREDIENTS	90.0

TOTAL 100.0

DANGER

KEEP OUT OF REACH OF CHILDREN

(See other precautions and First Aid Statement on side panel.)



Manufactured by

DAVIS SPECIALTY CHEMICALS, INC.

P. O. Box 12687
Jackson, Mississippi 39211

Net Contents

EPA Reg. No. 43602-1
EPA Est. No. 43602 MS-1

Gallons

It is a violation of Federal labeling.

KLEER-TOWER ZR-6 algae slime formation.

Initial Dose: 1.2 gallons per 100 gallons of water in the system. Periodic Dose: 1.3 gallons per 100 gallons of water in the system. For best results, clean heat exchanger or ammonia detoxify. TOWER ZR-6 Apply. Mixing will take place.

Do not be alarmed if during the first week KLEER-TOWER ZR-6 which tenaciously debris should be removed.

When KLEER-TOWER ZR-6 prevents the development of foul odors.

KLEER-TOWER ZR-6 but should not be used TOWER ZR-6 at all.

KLEER-TOWER ZR-6

INDUSTRIAL WATER COOLING TOWER ALGAECIDE

Concentrated Algaecide for industrial recirculating water cooling towers. Helps keep water cooling tower systems clear and free of visible algae slimes.

ACTIVE INGREDIENTS:

n-Alkyl (60% C ₁₂ , 30% C ₁₄ , 5% C ₁₆ , 5% C ₁₈) dimethyl benzyl ammonium chlorides	5.0
n-Alkyl (68% C ₁₂ , 32% C ₁₄) dimethyl ethylbenzyl ammonium chlorides	5.0

INERT INGREDIENTS	90%
TOTAL	100

DANGER

KEEP OUT OF REACH OF CHILDREN

(See other precautions and First Aid Statement on side panel.)



Manufactured by

DAVIS SPECIALTY CHEMICALS, INC.

P. O. Box 12687
Jackson, Mississippi 39211

Net Contents

EPA Reg. No. 43602-1
EPA Est. No. 43602 MS-1

Gallons

DIRECTIONS FOR USE

General Classification

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

KLEER-TOWER ZR-6 Industrial Water Cooling Algaecide is designed to prevent algae slime formation in cooling tower systems.

Initial Dose: 1-2 gallons KLEER-TOWER ZR-6 to each 5,000 gallons of water contained in the system. Repeat until control is evident. When system is in control, add **Periodic Dose:** 1-2 quarts KLEER-TOWER ZR-6 to each 5,000 gallons of water contained in the system every 7 days or sooner should visible growth appear. For heavily fouled or heavily contaminated systems before treatment with this product. If soap or emulsion detergent is used, rinse thoroughly before charging with KLEER-TOWER ZR-6. Apply KLEER-TOWER ZR-6 at a point in the system where uniform flow will take place.

On occasion, algaecide will cause a sudden appearance of organic debris in the system during the first few days of use. This is normal and is a good indication that KLEER-TOWER ZR-6 has effectively penetrated and dislodged dead organic material which has been growing on metal and wooden surfaces as living matter. This debris should be removed from the system to avoid clogging of screens and pipes.

When KLEER-TOWER ZR-6 is used as directed, it will aid in controlling and/or preventing the development of unsanitary slime conditions which are unsightly, produce foul odors and which are often the cause of equipment breakdown.

KLEER-TOWER ZR-6 is formulated with a variety of corrosion-inhibiting additives, but should not be used in the presence of caustic or other anionic detergents. KLEER-TOWER ZR-6 is not corrosive to inanimate hard surfaces.

25

43602-1