

Hydro-Engineering

930 ACCEPTED

43
JUN 5 1980
Under the Federal Insecticide
Fungicide and Rodenticide Act
as amended, for the pesticide
registered under
EPA Reg. No.

ACTIVE INGREDIENT:

Poly (oxyethylene (dimethyliminio) ethylene-
(dimethyliminio) ethylene aichloride)

60.0%

INERT INGREDIENT

40.0%

This product contains 5.76 lb of active ingredient per gallon and weighs 9.6 lb per gallon.

**KEEP OUT OF REACH OF CHILDREN
CAUTION**

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

CAUTION: Harmful if swallowed. Avoid breathing vapors. Avoid contact with skin, eyes, or clothing.

FIRST AID: If swallowed, drink promptly a large quantity of milk, egg whites, gelatin solution, or, if these are not available, drink large quantities of water. Avoid alcohol. Call a physician immediately.

ENVIRONMENTAL HAZARDS: This pesticide is toxic to fish. Keep out of lakes, streams, or ponds. Permits may be required for discharges containing this pesticide into lakes, streams, ponds or public water. For guidance, contact the regional office of the Environmental Protection Agency.

DIRECTIONS FOR USE GENERAL CLASSIFICATION

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

Hydro-Engineering 930 is used to control the growth of algae in swimming pools. For maximum effectiveness, pools containing heavy growth of algae should be cleaned prior to using **Hydro-Engineering 930**.

For pools having just visible algae growth add an initial dose of 11 to 17 fluid ounces of **Hydro-Engineering 930** per 10,000 gallons of water and remove settled algae debris by cleaning.

For treatment of a freshly cleaned and filled pool, add initially 6 to 11 fluid ounces of **Hydro-Engineering 930** per 10,000 gallons of water.

To maintain pools free of visible algae growth, subsequent additions of 2 to 4 fluid ounces of **Hydro-Engineering 930** per 10,000 gallons of water should be made every 5 to 7 days after the initial treatment.

Hydro-Engineering 930 is compatible with those chemicals normally used to treat pools and effective at both acid and alkaline pH. **Hydro-Engineering 930** can be used in pools treated with chlorine chemicals and may reduce the amount of those chemicals normally required. However, do not mix **Hydro-Engineering 930** with concentrated dry or liquid chlorine products.

STORAGE AND DISPOSAL. Keep container closed when not in use. Do not contaminate water, food, or feed by storage, disposal, or cleaning of equipment. Do not reuse empty container. Triple rinse (or equivalent) and dispose of container in an incinerator or in an approved landfill, or bury in a safe place. Rinseate that cannot be used or reprocessed should be disposed of in a landfill approved for pesticides or buried in a safe place away from water supplies. Open dumping is prohibited.

Manufactured by
Hydro-Engineering, Inc.

483 Gradle Drive
Carmel, IN 46032

EPA REG. NO. 43680-3

EPA EST. NO. 43680IN01

NET CONTENTS