C-960

(Nominal percentage equivalent chlorine of C-960 - 30%)

DANGER

..... 46%

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER: Highly corrosive. Causes skin and eye damage. May be fatal if swallowed. Do not get in eyes, on skin or clothing. Wear goggles or face shield and rubber gloves when handling. Irritating to nose and throat. Avoid breathing dust. Remove and wash contaminated clothing before reuse.

PRACTICAL TREATMENT: (FIRST AID): If swallowed, feed bread soaked in milk followed by olive oil or cooking oil. Call a physician immediately.

If on skin: Brushoff excess chemical and flush skin with cold water for at least 15 minutes. If irritation persists, get medical attention.

If in eyes: Flush with cold water for at least 15 minutes. Get medical attention.

ENWRONMENTAL HAZARDS: This product is toxic to fish. Do not discharge into lakes, streams, ponds, or public waters unless in accordance with an NPDES Permit. For guidance, contact the regional office of EPA

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

C-960 is used to control algae, bacteria, and fungi in recirculating

commercial and industrial water cooling towers. Prior to its use, systems must be cleaned to remove algal growth, microbiological slime, and other deposits. An initial slug addition of 3.0 to 16 fluid ounces of **C-960** per 1000 gallons of water to provide a concentration of 36 to 120 parts per million of **C-960** based on the total weight of water in the system, is recommended. Repeat initial dosage until control is evident.

Subsequent slug additions of **C-960** should be employed every 2 to 5 days, or as needed. The frequency of addition depends upon the relative amount of bleedoff and the severity of the micro-biological problem. Slug additions should be made in the sump of water cooling towers.

PHYSICAL AND CHEMICAL HAZARDS:

STRONG OXIDIZING AGENT: Strong Oxidizing Agent. Mix only with water. Use clean dry utensils. Do not add this product to any dispensing device containing remnants of any other product. Such use may cause a violent reaction leading to fire or explosion. Contamination with moisture, organic matter, or other chemicals may start a chemical reaction, with generation of heat, liberation of hazardous gases, and possible generation of fire and explosion. In case of contamination or decomposition, do not reseal container. If possible, isolate container in open air or well ventilated area. Flood with large volumes of water, if necessary.

STORAGE AND DISPOSAL: Keep product dry in tightly closed container when not in use. Store in a cool dry, well ventilated area away from heat or open flame. In case of decomposition isolate container, if possible, and flood with large amounts of water to dissolve all material before discarding. Place in trash collection or dispose in approved landfill area, or bury in a safe place.

WEAS ENGINEERING, INC.

P.O. Box 650 Carmel, IN 46032

EPA REG. NO. 43680-9

EPA EST. NO. 43680IN01