



# UNITED STATES ENVIRONMENTAL PROTECTION AGENCY WASHINGTON, DC 20460

JUN 10 2009

OFFICE OF PREVENTION, PESTICIDES AND TOXIC SUBSTANCES

William R. Goodwine Sr. Director, Regulatory Affairs & Product Development Janssen PMP, a Division of Janssen Pharmaceutica, N.V. 1125 Trenton-Harbourton Rd. Titusville, NJ 08560-0200

Subject:

Notification in Accordance with PR Notice 98-10

Wocosen 100 SL

EPA Registration Number: 43813-19

Application: May 11, 2009 Receipt Date: May 13, 2009

Dear Mr. Goodwine:

This will acknowledge receipt of your notification, submitted under the provisions of PR Notice 98-10, FIFRA section 3 (c) 9.

#### **Proposed Notification:**

Minor label changes per PR Notice 2007-4

#### **General Comment:**

Based on a review of the material submitted, the following comment applies.

The notification is acceptable.

Should you have any questions concerning this letter, please contact me by telephone at (703) 308-6415 or email address at: <a href="mailto:lantz.tracy@epa.gov">lantz.tracy@epa.gov</a>, or Lisa McKelvin by telephone at (703) 308-7496 or email address at: <a href="mailto:mckelvin.Lisa@epa.gov">mckelvin.Lisa@epa.gov</a>.

Sincerely,

Tracy Lantz

M(Acting) Product Manager 34

Regulatory Management Branch II Antimicrobials Division (7510P)



# United States Environmental Protection Agency Washington, DC 20460 Application, for Pest

Registration
Amendment
Other

**OPP Identifier Number** 

	Washi	ngton, DC 204	460			X (	Other				
	· · · · · · · · · · · · · · · · · · ·	Application	on for F	esticid	e - Sec	tion l					
1. Company/Product Number 43813-19				2. EPA Product Manager Tracy Lantz					posed C	<b>(</b> )	ation Restricted
4. Company/Product (Name) WOCOSEN 100 SL				PM# 34					j		
5. Name and Address of App Janssen PMP, a Division 1125 Trenton-Harbourto Titusville, NJ 08560-020	n of Janssen Pharr on Road	-	I.V.	(b)(i), my to: EPA Re	product	is simil	ar or iden	ance with	mpositio	on and	labeling
	· · · · · · · · · · · · · · · · · · ·		Sect	tion - II							
Amendment - Explain Resubmission in respo	onse to Agency letter	dated		- 🔲	Final printe Agency let "Me Too" / Other - Exp	ter date Applicat	d ion.	sé to			
Explanation: Use addition "Notification of label change EPA's regulations at 40 CFI Confidential Statement of F EPA. I further understand t 156.156, this product may be	e per PR Notice 2007 R 156.10, 156.140, 1 ormula for this produ hat if the amended la	-4. This notif 56.144, 156.1 ct. I understa ibel is not cor	fication is of 46, and 15 and that it is asistent wi	consistent 56.156. No s a violatio th the requ	o other cha n of 18 U.S irements o	anges h S.C. Se of 40 CF	ave been c. 1001 to R 156.10	made to the willfully ma , 156.140, 1	e labeling ike any f I56.144,	g or the alse sta 156.14	e atement to l6, and
			Sect	ion - III							
1. Material This Product Will Be Packaged In:  Child-Resistant Packaging  Yes  X No  If "Yes"  No. per		Ño. per	Water Soluble Packaging Yes X No If "Yes" No. pe				2. Type o	Container  Metal Plastic Glass Paper			
* Certification must be submitted	Unit Packaging wgt.		Packag		containe	r		Other (S	pecify)_		
3. Location of Net Contents:	nformation ontainer	4. Size(s) Re 2.6, 264 g	5		liters)	5. Loc	1	bel Directio	ine		<del></del>
6. Manner in Which Label is		× Lithog Paper Stenc	graph glued iled		Othe	·					
			Sect	ion - IV	7.						
1. Contact Point <i> Complete</i>   Name   William R. Goodwin		for identification	Title		contected,			Te ephon	e No. (in	clude A	rea Code)
I certify that the stater I acknowledge that am both under applicable i	y knowlinglly false or		all attach						Rece	Application of the Application o	•
2. Signatura William R. Loodwinl				tie for Director, Regulatory Affairs & Product Development							. •
4. Typod Name William R. Goodwine			May	ay 11, 2009							

## WOCOSEN™ 100SL

#### PRESERVATIVE FOR INDUSTRIAL & COMMERCIAL USE

### **KEEP OUT OF REACH OF CHILDREN**

#### **CAUTION**

,	PIRATAIN
	FIRST AID
If swallowed	-Call a poison control center or doctor immediately for treatment advice.
	-Have person sip a glass of water if able to swallow.
	<ul> <li>-Do not induce vomiting unless told to do so by a poison control center or doctor.</li> </ul>
	-Do not give anything by mouth to an unconscious person.
lf on skin or	-Take off contaminated clothing.
clothing	-Rinse skin immediately with plenty of water for 15-20 minutes.
	-Call a poison control center or doctor for treatment advice.
If inhaled	-Move person to fresh air.
	-If person is not breathing, call 911 or an ambulance, then give
	artificial respiration, preferably mouth-to-mouth if possible.
	-Call a poison control center or doctor for further treatment advice.
If in eyes	-Hold eye open and rinse slowly and gently with water for 15-20
•	minutes. Remove contact lenses, if present, after the first 5 minutes,
	then continue rinsing eye.
	-Call a poison control center or doctor for treatment advice.
	HOT LINE NUMBER:
For information	n on this pesticide product (including health concerns, medical
	or pesticide incidents) call the National Pesticide Telecommunications
	300-858-7378. For chemical emergency assistance (spill, leak, fire, or
	Chem Trec at 1-800-424-9300.
<u> </u>	
Have the product going for treatment	ct container or label with you when calling a poison control center or doctor, or ent
	NOTE TO PHYSICIAN
There is no spe	ecific antidote for WOCOSEN 100SL. Give a saline laxative and

NET CONTENTS: 264 gallons (1,000 liters)

EPA REG. NO. 43813-19

EPA EST. NO. 43813-BL-2

#### **JANSSEN PMP**

a Division of Janssen Pharmaceutica NV 1125 Trenton-Harbourton Road.

Titusville, NJ 08560-0200

## PRECAUTIONARY STATEMENT HAZARDS TO HUMANS & DOMESTIC ANIMALS

#### **CAUTION**

Harmful if swallowed, inhaled or absorbed through the skin. Avoid breathing spray mist. Avoid contact with skin, eyes or clothing. Wash thoroughly with soap and water after handling and before eating. Remove contaminated clothing and wash before reuse. In case of contact immediately flush eyes or skin with plenty of water. Get medical attention if irritation persists.

#### **ENVIRONMENTAL HAZARDS**

Do not apply directly to water or wetlands. Do not contaminate water by cleaning of equipment, or disposal of wastes. Apply this product only as specified on the label. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permit authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your local State Water Board or Regional Office of the EPA.

#### STORAGE AND DISPOSAL

Do not contaminate water, food, or feed by storage or disposal.

#### **PESTICIDE STORAGE**

Store in original container in a cool, dry place.

#### PESTICIDE DISPOSAL

Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA regional office for guidance.

#### CONTAINER HANDLING

Non-refillable container. Do not reuse or refill this container. Triple rinse container (or equivalent) promptly after emptying. Triple rinse as follows:

[For containers ≤ 5 gallons in size].—Empty the remaining contents into application equipment or a mix tank and drain for 10 seconds after the flow begins to drip. Fill the container ¼ full with water and recap. Shake for 10 seconds. Pour rinsate into application equipment or a mix tank or store rinsate for later use or disposal. Drain for 10 seconds after the flow begins to drip. Repeat this procedure two more times.

[For containers > 5 gallons in size] - Empty the remaining contents into application equipment or a mix tank. Fill the container ¼ full with water. Replace and tighten closures. Tip container on its side and roll it back and forth, ensuring at least one complete revolution, for 30 seconds. Stand the container on its end and tip it back and forth several times. Turn the container over onto its other end and tip it back and forth several times. Empty the rinsate into application equipment or a mix tank or store rinsate for later use or disposal. Repeat this procedure two more times.

Then offer for recycling if available or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities:

#### NOTICE OF WARRANTY

Janssen PMP, a Division of Janssen Pharmaceutica NV warrants that this product conforms to the chemical description on the label thereof and is reasonably fit for purposes stated on such label only when used in accordance with the directions under normal use conditions. It is impossible to eliminate all risks inherently associated with the use of this product. Ineffectiveness or other unintended consequences may result because of such factors as weather conditions, presence of other materials, or the manner of use or application, all of which are beyond the control of Janssen PMP. To the extent permitted by law, Janssen PMP disclaims any liability for consequential, special or indirect damages resulting from the use, handling, application, storage or disposal of this product or for damages in the nature of penalties, and the buyer and user waive any right that they may have to such damages. To the extent consistent with applicable law, Janssen PMP makes no warranties of merchantability or of fitness for a particular purpose or any other express or implied warranty except as stated above.

TMTrademark of Janssen Pharmaceutica.

Propiconazole is manufactured by Syngenta, Basel, Switzerland

05/09

**DIRECTIONS FOR USE:** It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

#### SAPSTAIN AND MOLD CONTROL:

Wocosen 100SL is used to control sapstain and mold in freshly cut hardwood and softwood lumber, poles, posts, timbers and other manufactured wood products. Examples of other wood products include:

<u>Logs:</u> Fungal staining can be inhibited in freshly debarked logs used for log home construction, export, yarding prior to sawing and other purposes.

<u>Wood Furnish:</u> Engineered wood composites, such as particle board, wafer board, oriented strand board, and similar products can be protected from fungal discoloration during storage by treatment with WOCOSEN 100SL.

<u>Wood Chips/Saw Dust:</u> Treatment of wood chips, saw dust or other similar by products intended for papermaking (Not for food grade/food contact paper or paper board) reduces fungal discoloration and lowers bleaching requirements for finished paper products.

<u>Plywood Veneer:</u> Treatment with WOCOSEN 100SL is effective for freshly peeled green veneer and other similar plywood furnish that can be especially subject to sapstain and mold development that can interfere with appearance or laminating adhesive performance.

Wocosen 100SL is applied by dipping or spraying the wood until complete surface wetting is achieved. For **bulk dip tanks** Wocosen 100SL is diluted by using 0.33 gallons (2.4 gallon Wocosen 100SL in 800 gallons water) to 2.5 gallons Wocosen 100SL in 100 gallons of water. Agitate vigorously until completely dispersed. For **conventional spray systems** a 0.6% to 5% Wocosen 100SL spray solution is used. For example, in a 100 gallon day tank, 0.6 to 5 gallons of Wocosen 100SL are added to the day tank and then enough water is added to bring the total volume up to 100 gallons of solution. In **electrostatic spray** applications, Wocosen 100SL dilution is not required, treatment strength is varied by number of application nozzles used and line speed. Rates, for all applications used, will vary according to temperature, humidity, wood moisture, storage conditions, etc. Contact your local Wocosen 100SL product representative for application advice.

Remove sawdust and other debris from treating solution on a regular basis to maintain correct concentration of Wocosen 100SL in application solution. To prevent fungal attack below the surface of the wood, freshly sawn lumber should be treated within 24 hours. Treated lumber should be protected from rain and removed from direct soil/ground contact.

#### **DECAY AND STAIN PROTECTION**

**Description:** WOCOSEN 100SL is a wood preservative concentrate that requires dilution with water prior to use on wood products to protect against decay (brown and white rot) and staining fungi (blue stain).

**Product Uses:** For application to millwork, shingles & shakes, siding, plywood, and structural lumber & composites that are used in above ground applications only. Do not use on wood which will come in contact with food.

Wood Preparation: Machine, cut, glue, and sand wood as desired before treating. Do not use over previously finished or stained wood without stripping off old finish. Wood must be clean and dry before treatment. Wood for pressure treatment should be kiln dried or air séasoned to a moisture content, of about 25% or less, that will permit adequate penetration of presorvative during treatment.

**Treatment:** Apply by immersion, roller coater, flood, spray, brush or pressure treatment processes (double vacuum, full-cell or modified full-cell). For non-pressure application methods, mix 5-10 gallons of Wocosen 100SL with water to achieve 100 gallons of treating solution at the concentration of 0.5 - 1% a.i., respectively. Wood products to be treated by the bundle-dipping process should be completely immersed for three (3) minutes. Individual wood pieces treated by immersion, roller-coater or flood shall be treated for not less than fifteen (15) seconds. Coverage for brush and spray application is approximately 150 square feet per gallon of treating solution, but varies by the species and condition of the wood. Pressure treatment should be performed according to the methods described in the American Wood Preservers' Association (AWPA) Standards. A minimum propiconazole retention level of 0.025 pounds per cubic foot (pcf) is recommended. All treated wood must be held on the drip pad until drippage has stopped. Any surface, cut after first treatment should be retreated using 1% a.i. concentration solution.

**Finishing:** Before glazing, staining, painting, varnishing, or application of water repellents, treated wood should be completely dry and odor-free. For non-pressure applications, allow 4-8 hours drying time under average temperature and humidity conditions; treated wood can be heat dried for plant production. Pressure treated wood requires drying after treatment to a moisture content suitable for the type of coating to be applied.

Clean-up: Use water to remove wet WOCOSEN 100SL wood preservative from all surfaces, brushes and rollers.

#### **COATINGS, CAULKS, SEALANTS, ADHESIVES, AND INKS:**

Not for use in coatings and adhesives which will come in contact with paper or paperboard.

Sufficient mixing to ensure adequate dispersion of the biocide is required. WOCOSEN 100SL should be used at levels between 0.5 and 12.5% based on the total weight of the formulation to inhibit fungal disfigurement and deterioration. For solvent-based formulations the WOCOSEN 100SL can be dissolved in aromatic solvents or combination of aromatic and aliphatic solvents and added in the letdown or added directly to the finished product. For water-thinned latex emulsion formulation, the WOCOSEN 100SL can be premixed with the wetting agent and added to the pigment slurry or simply added to the letdown or finished product.

#### **METALWORKING FLUIDS:**

Use Wocosen 100SL to inhibit fungal degradation of water based and water emulsifiable cutting fluids and coolants used in metalworking operations. Add Wocosen 100SL to the fluid concentrate or to the diluted metalworking fluid in an amount which will provide 50 to 700 ppm active ingredient in the diluted fluid.

#### **TEXTILES:**

For the control of odor and stain causing microorganisms in textiles of the following products: shower curtains, carpet backing, awnings, boat covers, canvas, cordage, tents, tarpaulins, and wall coverings.

Addition of up to 2000 ppm of this active ingredient (2% of product), based on weight of goods, can inhibit the growth of mold and mildew that cause stains, odors and product degradation in textiles, fabrics and fibers composed of acetate, acrylic, acrylonitrile butadiene styrene, natural fibers (cotton, paper, wool, etc.), nitrile copolymers, nylon, polyester, polyethylene, polypropylene, rayon, rubber (natural & synthetic), coatings/finishes composed of silicone, urethane or vinyl applied to such materials. The material should be added at an appropriate manufacturing step to ensure adequate mixing and complete, uniform coverage of the treated material. Product can be applied by dye incorporation, pad, exhaust, or spray application.