

U.S. ENVIRONMENTAL PROTECTION AGENCY

Office of Pesticide Programs
Antimicrobials Division (7510C)
1200 Pennsylvania Avenue NW
Washington, D.C. 20460

\ I (\T 'I	CF	ΔE		CTI	~ 11	٦ Ε.
M.	, , ,	1.6	l Jr	\mathbf{r}	. 7 1 1	1 411	

x Registration
Reregistration

EPA Reg. Number:

Date of

Issuance:

43813-43

November 29, 2005

Term of Issuance:

Conditional

Name of Pesticide Product:

WOCOSEN 450 EC

(under FIFRA, as amended)

Name and Address of Registrant (include ZIP Code):

Janssen Pharmaceutica Inc., 1125 Trenton-Harbourton Titusville, NJ 08560

Note: Changes in labeling differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Registration Division prior to use of the label in commerce. In any correspondence on this product always refer to the above EPA registration number.

On the basis of information furnished by the registrant, the above named pesticide is hereby registered/reregistered under the Federal Insecticide, Fungicide and Rodenticide Act.

Registration is in no way to be construed as an endorsement or recommendation of this product by the Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.

This product is conditionally registered in accordance with FIFRA sec 3(c)(7)(A) provided that you:

- 1. Submit and/or cite all data required for registration of your product under FIFRA sec. 3(c)(5) when the Agency requires all registrants of similar products to submit such data; and submit acceptable responses required for reregistration of your product under FIFRA section 4.
 - 2. Make the labeling changes listed below before you release the product for shipment:
 - a. Add the phrase "EPA Registration Number 43813-43.
 - b. The signal must be changed from caution to "WARNING" wherever it appears on the label.

Signature of Approving Official:

Adam Heyward

Product Manager Team-34

Regulatory Management Branch II Antimicrobials Division (7510C)

November 29, 2005

Date:

EPA Form 8570-6

c. Revise the first aid statement and its heading to read as follows:

FIRST AID

IF SWALLOWED: Call a poison Control Center or doctor immediately for treatment advice. Have person sip a glass of water if able to swallow. Do not induce vomiting unless told by a Poison Control Center or doctor. Do not give anything by mouth to an unconscious person.

IF INHALED: Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration preferably mouth-to-mouth if possible. Call a Poison Control Center or doctor for further treatment advice.

IF IN EYES: Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing. Call a Poison Control Center or doctor for treatment advice.

IF ON SKIN OR CLOTHING: Take off contaminated clothing. Rinse skin immediately with plenty of water for 1-20 minutes. Call Poison Control Center or doctor for treatment advice.

In case of emergency call (insert toll-free emergency number). Have the product container or label with you when calling a Poison Control Center or doctor or going in for treatment.

NOTE TO PHYSICIAN: "Probable mucosal damage may contraindicate the use of gastric lavage."

The following statements are suggested types of information that may be included, if applicable:

- technical information on symptomatology;
- use of supportive treatments to maintain life functions;
- medicine that will counteract the specific physiological effects of the pesticide;
- company telephone number to specific medical personnel who can provide specialized medical advice.
- e. Add the following Personal Protection Equipment language to the labeling:

Personal Protective Equipment

Applicators and other handlers must wear:

- Long sleeved shirt and long pants.
- Socks and shoes
- Chemical-resistant gloves (such as: Barrier Laminate, or any of the following gloves at ≥ 14 mils thickness: butlyl nitrile, neoprene rubber, polyvinyl chloride or Viton).
- Goggles or face shield.

3 7 7

f. Add the following User Safety Requirements and Recommendations:

"Follow manufacturer's instructions for cleaning/maintaining PPE. If no such instructions exist for washables, use detergent and hot water. Keep and wash PPE separately from other laundry."

"User Safety Recommendations"

"Users should wash hands before eating, drinking, chewing gum, using tobacco, or using the toilet."

"Users should remove clothing immediately if pesticide gets inside. Then wash thoroughly and put on clean clothing." User should remove personnel protective equipment immediately after handling this product. Wash outside of gloves before removing. As soon as possible wash thoroughly.

g. Revise the precautionary the statement to read as follows:

PRECAUTIONARY STATEMENT HAZARDS TO HUMANS AND DOMESTIC ANIMALS WARNING

Causes skin irritation and moderate eye irritation. Harmful if swallowed, absorbed through the skin, or inhaled. Do not get in eyes or on clothing. Avoid breathing spray mist. Wash hands before eating, drinking, chewing gum, using tobacco or using the toilet. Remove contaminated clothing and wash clothing before reuse.

4. Submit three (3) copies of the final printed label prior to releasing this product for sale.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA sec. 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

A stamped copy of the label is enclosed for your records.

٠.

Sincerely,

Adam Heyward

Product Manager 34

Regulatory Branch II

Antimicrobials Division (7510C)

Enclosure: (Stamped Label)

WOCOSEN® 450 EC

Fungicide for Material & Wood Preservation

ACCEPTED with COMMENTS **EPA Letter Dated:**

NOV 2 9 2005

Under the Federal Insecticide, Fungicide, and Rodenticide Act as amended for the pesticide, registered under EPA Reg. No. #3813-#3

ACTIVE INGREDIENT: (w/w) PROPICONAZOLE 34.0% IPBC: 3-iodo-2-propynyl butyl carbamate 16.0% INERT INGREDIENTS: (w/w)50.0% TOTAL......100.0%

Product weight: 9.3 lbs/gallon. Contains 2.8 lbs Propiconazole and 1.3 lbs IPBC per gallon.

KEEP OUT OF REACH OF CHILDREN

CAUTION

,	FIRST AID			
IF SWALLOWED	 Call a poison control center or doctor for further treatment advice. Have person sip a glass of water if able to swallow. 			
	Do not induce vomiting unless told to do so by the poison control center or doctor.			
	Do not give anything by mouth to an unconscious person.			
IF INHALED	Move person to fresh air.			
	If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth if possible.			
	-Call a poison control center or doctor for further treatment advice.			
IF IN EYES	 Hold eyelids open and rinse slowly and gently with water for 15 minutes. Remove contact lenses, if present, after the first 5 minutes. Then continue rinsing eye. 			
	Call a poison control center or doctor for further treatment advice.			
IF ON SKIN OR	Take off contaminated clothing.			
CLOTHING	Rinse skin immediately with plenty of water for 15 - 20 minutes.			
	Call a poison control center or doctor for further treatment advice			

HOT LINE NUMBER

For information on this pesticide product (including health concerns, medical emergencies, or pesticide incidents) call the National Pesticide Telecommunications Network at 1-800-858-7378. For chemical emergency assistance (spill, leak, fire, or accident), call Chem-Trec at 1-800-424-9300.

Have the product container or label with you when calling a poison control center or doctor, or going for treatment.

NET CONTENTS: 264 gallons (1000 L)

EPA REG. NO. 43813-

EPA EST. NO. 074263-DEU-001

JANSSEN

Pharmaceutica, Inc. 1125 Trenton-Harbourton Rd. Titusville, NJ 08560-0200

CAUTION

Harmful if swallowed, inhaled or absorbed through skin. Causes moderate eye irritation. Avoid breathing spray mist. Avoid contact with skin, eyes or clothing. Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, or using tobacco. Remove and wash contaminated clothing before reuse. Wear chemical resistant gloves such as butyl, nitrile, neoprene rubber, PVC polyethylene or Viton.

ENVIRONMENTAL HAZARDS

For terrestrial uses: Do not apply directly to water or to areas where surface water is present or to intertidal areas below the mean high water mark. Do not contaminate water when disposing of equipment wash water or rinsate. Apply this product only as specified on the label.

Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

DIRECTIONS FOR USE:

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

'OCOSEN 450 EC, containing propiconazole and IPBC fungicides, may be formulated into material and wood reservative end-use products that have a U.S. EPA registration, such as metal working fluids, paints & coatings, caulks, sealants, adhesives, inks, textiles, lumber, logs, engineered wood composite products, wood furnish and rood chips.

STORAGE AND DISPOSAL:

Do not contaminate water, food or feed by storage or disposal.

PESTICIDE STORAGE: Store in a cool, dry place.

PESTICIDE DISPOSAL: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture, or rinse water is a violation of Federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA regional office for guidance.

CONTAINER DISPOSAL: Triple rinse (or equivalent), then offer for recycling or reconditioning or puncture and dispose of in a sanitary landfill or incineration, or if allowed by state and local authorities, by burning. If burned, stay out of smoke.

PHYSICAL OR CHEMICAL HAZARDS: Do not use, pour, spill or store near heat or open flame.

6 3 7

WOCOSEN 450 EC is used to control sapstain and mold in freshly cut hardwood and softwood lumber, poles, posts, timbers and other manufactured wood products. Examples of other wood products include: Logs: Fungal staining can be inhibited in freshly debarked logs used for log home construction, export, yarding prior to sawing and other purposes.

Wood Furnish: Engineered wood composites, such as particle board, wafer board, oriented strand board, and similar products can be protected from fungal discoloration during storage by treatment with WOCOSEN 450 EC.

<u>Wood Chips/Saw Dust:</u> Treatment of wood chips, saw dust or other similar by products intended for papermaking (Not for food grade/food contact paper or paper board) reduces fungal discoloration and lowers bleaching requirements for finished paper products.

<u>Plywood Veneer:</u> Treatment with WOCOSEN 450 EC is effective for freshly peeled green veneer and other similar plywood furnish that can be especially subject to sapstain and mold development that can interfere with appearance or laminating adhesive performance.

WOCOSEN 450 EC is applied by dipping or spraying the wood until complete surface wetting is achieved. For **bulk dip tanks** WOCOSEN 450 EC treating solution is prepared by diluting 0.1 gallons (12.8 oz.) to 0.75 gallons WOCOSEN 450 EC in 100 gallons of water. Agitate vigorously until completely dispersed. For **conventional spray systems** a 0.2% to 1.5% WOCOSEN 450 EC spray solution is used. The treating solution is prepared by mixing 0.2 to 1.5 gallons of WOCOSEN 450 EC in 100 gallons water. In **electrostatic spray** applications, WOCOSEN 450 EC dilution is not required, treatment strength is varied by number of application nozzles used and line speed. Rates, for all applications used, rill vary according to temperature, humidity, wood moisture, storage conditions, etc. Contact your local OCOSEN 450 EC product representative for application advice.

Remove sawdust and other debris from treating solution on a regular basis to maintain correct concentration of WOCOSEN 450 EC in application solution. To prevent fungal attack below the surface of the wood, freshly sawn lumber should be treated within 24 hours. Treated lumber should be protected from rain and removed from direct soil/ground contact.

DECAY AND STAIN PROTECTION

Description: WOCOSEN 450 EC is a wood preservative concentrate that requires dilution with water prior to use on wood products to protect against decay (brown and white rot) and staining fungi (blue stain).

Product Uses: For application to millwork, shingles & shakes, siding, plywood, and structural lumber & composites that are used in above ground applications only. Do not use on wood which will come in contact yith food.

Wood Preparation: Machine, cut, glue, and sand wood as desired before treating. Do not use over reviously finished or stained wood without stripping off old finish. Wood must be clean and dry before reatment. Wood for pressure treatment should be kiln dried or air seasoned to a moisture content, of about 25% or less, that will permit adequate penetration of preservative during treatment.

Treatment: Apply by immersion, roller coater, flood, spray, brush or pressure treatment processes (double vacuum, full-cell or modified full-cell). For non-pressure application methods, mix 1.5 to 3 gallons of WOCOSEN 450 EC in 100 gallons of water. Wood products to be treated by the bundle-dipping process should be completely immersed for three (3) minutes. Individual wood pieces treated by immersion, roller-coater or flood shall be treated for not less than fifteen (15) seconds. Coverage for brush and spray application is approximately 150 square feet per gallon of treating solution, but varies by the species and condition of the wood. Pressure treatment should be performed according to the methods described in the American Wood Preservers' Association (AWPA) Standards. A retention level of 0.0375 pounds total active ingredient per cubic foot (pcf) is recommended. All treated wood must be held on the drip pad until drippage has stopped. Any surface, cut after first treatment should be retreated using 1.5% a.i. concentration solution.

Finishing: Before glazing, staining, inting, varnishing, or application of water spellents, treated wood should be completely dry and odor-kill For non-pressure applications, allow 4.8% ins drying time under average temperature and humidity conditions, treated wood can be heat dried for plant production. Pressure treated wood requires drying after treatment to a moisture content suitable for the type of coating to be applied.

Clean-up: Use water to remove wel WOCOSEN 450 EC wood preservative from all surfaces, brushes and rollers.

COATINGS, CAULKS, SEALANTS, ADHESIVES, AND INKS:

Not for use in coatings and adhesives which will come in contact with paper or paperboard.

Sufficient mixing to ensure adequate dispersion of the biocide is required. WOCOSEN 450 EC should be used at levels between 0:15 and 3:75% based on the total weight of the formulation to inhibit fungal disfigurement and deterioration.

METALWORKING FLUIDS:

se WOCOSEN 450 EC to inhibit tungal degradation of water based and water emulsifiable cutting fluids id coolants used in metalworking operations. Add WOCOSEN 450 EC to the fluid concentrate or to the diluted metalworking fluid in an amount that will provide 50 to 1,000 ppm active ingredient in the diluted ٠id.

TEXTILES, FABRICS, GANVAS AND CORDAGE:

For the control of odor and stain causing microorganisms in textiles, fabrics and fibers of the following products: FURNISHINGS: curtains edraperies furniture coverings, shower curtains: BUILDING MATERIALS: awnings, boat covers (carpet (fibers and backing), cordage; tents, tarpaulins, wall coverings. Not for use in fabrics for human wear-

Addition of up to 3,000 ppm total active ingredient (0.3% of WOCOSEN 450 EC), based on weight of goods, can inhibit the growth of mold and infloewith at eause status, odors end product degradation in textiles, fabrics and fibers composed of acetate, acryllo, acrylonlinile by action styrene, natural fibers (cotton, paper, wool, etc.), nitrie copolymers nylong polyester, polyethylene, polypropylene, rayon, rubber (natural & synthetic), coatings/finishes composed of silicone, prethane or vinyl applied to such materials. The material should be added at an appropriate manufacturing step to ensure adequate hixing and complete, uniform coverage of the treated material. Product can be applied by dye ncorporation, pad, exhaust, or spray application.

OTICE:OF WARRANTY

Ansen Pharmaceulica warrants that this product conforms to the chamical description on the label thereof and is reasonably, it is purposed stated on such label only when used in accordance with the directions under normal use concilions his impossible to eliminate all risks inherently associated with the use of this product. In arrive less of other unintended consequences may result because of such factors as weather conditions, presence of other materials, or the manner of use or application, all of which are beyond the control of Janssen Pharmaceutica. In no case shall be insected the insection of the product. All such risks shall be assumed by the Buyer. JANSSEN PHARMACEURICA MAKES NOWARRANNIES OF MERCHANNABILITY OR HINNESS FOR APARTICULAR PURPOSE NOR ANY OTHER EXPRESS OR IMPLIED WARRANNING SECTION ASSUATED ABOVE.

® Registered trademark of Janssen Pharmaceut Propiconazole is manufactured by Syngenta, Basel, Switzerland

PMP 02/05

