

4
Durant

MIL P-19451B
COLD PLASTIC ANTI-FOULING
SHIP BOTTOM PAINT
NAVY FORMULA 105

ACTIVE INGREDIENT32.27%
(CUPROUS OXIDE)
INERT INGREDIENT67.73%
.....100.00%

EPA REGISTRATION NUMBER
43923-1
EPA ESTABLISHMENT NUMBER
43923-MA-01

KEEP OUT OF REACH OF CHILDREN
WARNING
FEB 1987
ACCEPTED

SOLID
COVERING

DURANT PAINTS, INC.
Revere, Mass. 02151

CAUTION
Avoid prolonged contact with
skin or breathing of spray mist
Close container after each use
Do not take internally **KEEP OUT
OF REACH OF CHILDREN**

urant

**MIL P-19451B
OLD PLASTIC ANTI-FOULING
SHIP BOTTOM PAINT
HEAVY FORMULA 105**

ACTIVE INGREDIENT 32.27%
(CUPROUS OXIDE)
INERT INGREDIENT 67.73%
..... 100.00%

EPA REGISTRATION NUMBER
43923-1

EPA ESTABLISHMENT NUMBER
43923-MA-01

KEEP OUT OF REACH OF CHILDREN
WARNING

SEE CAN FOR ADDITIONAL PRECAUTIONS

ACCEPTED
FEB 3 1981

EASILY
APPLIED

URANT PAINTS, INC.

Revere, Mass. 02151

DIRECTIONS

Directions text is extremely faint and illegible.

STORAGE AND DISPOSAL

Storage and disposal text is extremely faint and illegible.

U.S. STANDAR

DIRECTIONS

PREPARE THE SURFACE The surface to be coated must be clean, free, dry, and free from all dirt, dust, grease, oil, wax, rust, contaminants, or other foreign matter. Remove all loose or scaling paint and as much of the previous coating as is possible.

APPLICATION

- Stir contents thoroughly and mix occasionally during use.
- Apply with brush, roller, or spray equipment.
- Apply directly from the can at package consistency without thinning.
- Dries in 3 to 5 hours under normal drying conditions. Allow 5 hours between coats.
- Brushes, rollers, and spray equipment should be promptly cleaned with mineral spirits or other solvents.

SPREADING RATE Apply at the rate of approximately 300 sq ft (27 sq meters) per gallon.

HOW MANY COATS? On previously painted surfaces and primed steel or fiberglass: 2 coats. On new or bare wood: 3 coats. (Fill seams with seam compound between the first and second coats.)

LAUNCHING The craft may be floated when the paint is dry (after approximately 5 hours) if exposed to direct sun or high temperature. Launching should not be delayed for more than 24 hours. In no case should launching be delayed beyond one week.

STORAGE AND DISPOSAL

PROHIBITIONS Do not contaminate water, food, or feed by storage or disposal. Open dumping is prohibited.

WASTE ANTIFOULING PAINT DISPOSAL Waste paint, paint-contaminated solvents, mixtures, or residues that cannot be used or chemically reprocessed should be disposed of in a landfill approved for pesticides or hazardous waste. (See the Navy Hazardous Waste Disposal Guide, NESG 29-2-111.)

CONTAINER DISPOSAL Triple rinse, if equivalent, and offer for recycling, reconditioning, or disposal. (See the Guide.)

GENERAL Consult Federal, State, or Local disposal authorities for approved alternative procedures.

A heavy-duty marine bottom coating with a high content of toxic marine growth-preventing material to prevent fouling of wood, fiberglass, or steel bottomed boats and yachts. This product is recommended for marine use only and it should not be used around the home or on any surface with which children could have contact. It is not designed for use on aluminum bottoms.

NOTE

This product meets military specification MIL-P-19451B.

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS

(1) ENVIRONMENTAL HAZARDS

Do Not contaminate water by cleaning of equipment or disposal of wastes.

(2) PHYSICAL OR CHEMICAL HAZARDS

FLAMMABLE: Keep away from heat and open flame.

WARNING

HARMFUL IF SWALLOWED Causes Eye Irritation. Do Not Get in Eyes. Use with adequate ventilation. Avoid contact with skin and breathing of vapor or spray mist. Close container after each use. Wear goggles or face shield and rubber gloves when handling. Use protective breathing mask and protective clothing when spraying or sanding.

FIRST AID: In case of contact with eyes, immediately flush with plenty of water. Get medical attention if irritation persists. In case of skin contact, wash hands and other exposed skin areas with soap and water after use. If swallowed, Do Not induce vomiting; call a physician immediately.

NOTE: When sanding, use in confined areas or applied by spraying wear a positive respirator jointly approved by the Mining Enforcement and Safety Administration (formerly the U.S. Bureau of Mines) and the National Institute for Occupational Safety and Health under the Provisions of 30 CFR 11.

40

U.S. STANDARD GALLON