Progressive Produ _s			
SPECTRO BLEND 1			
3614 East Pownee Wichita, Konses 67218 (316) 685-8185		EPTED 43-2 2 3 1980	YOU USE WATER
ACTIVE INGREDIENT Poly(oxysthylene (dime (dimenthyliminio) ethyle	as amended, revisiered ur the dichloride	ingrenie-	6.0%
WERT INGREDIENT			
This product contains 8.44 lb. per gallon.	0.5 lb. of acti	ive ingredient pe	r gallon and weighs
KEEP OUT		CH OF CH	ILDREN

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

CAUTION: Harmful if swallowed. Avoid breathing vapors. Avoid contact with skin, eyes, or clothing.

FIRST AID: If swallowed, drink promptly a large quantity of milk, egg whites, gelatin solution, or, if these are not available, drink large quantities of water. Avaid alcohol. Call a physician immediately.

ENVIRONMENTAL HAZARDS: This pesticide is toxic to fish. Keep out of lakes, streams, gr ponds. Permits may be required for discharges containing this pesticide into lakes, streams, poods or public water. For guidance, contact the regional office of the Evnironmental Protection Agency

DIRECTIONS FOR USE GENERAL CLASSIFICATION

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

SPECTRO BLEND 1 is used to control algae, bacteria, and fungi in recirculating commercial and industrial water cooling towers. Prior to its use, systems must be cleaned to remove algal growth, microbiological slime, and other deposits. An initial stug addition of 10.1 to 25.25 fluid ounces of SPECTRO BLEND 1 per 1000 gallons of water to provide a concentration of 80 to 200 parts per million of SPECTRO BLEND 1, based on the total weight of water in the system, is recommended. Repeat initial dosage until control is evident.

Subsequent slug additions of 2.52 to 25.25 fluid ounces of SPECTRO BLEND 1 per 1000 gallons of water (20 to 200 parts per million of SPECTRO BLEND 1) should be employed every 2 to 5 days, or as needed. The frequency of addition depends upon the relative amount of bleedoff and the severity of the microbiological problem. Slug additions should be made in the sump of water cooling towers.

SPECTRO BLEND 1 is used to control bacteria in industrial air-washing systems that maintain effective mist eliminating components. Prior to its use, systems should be cleaned to remove bacterial slime and other deposits. An initial slug dose of 37.12 to 62.44 fluid ounces of SPECTRO BLEND 1 per 1000 gallons of water is recommended. Repeat initial dosage until control is evident. Subsequent slug additions of 25.31 to 62.44 fluid ounces of SPECTRO BLEND 1 per 1000 gallons of water should be employed each 1 to 5 days, or as needed. The frequency of addition depends upon the relative amount of bleedoff and severity of the bacterial problem. Slug additions may be made to the sump or to the water collection trays of the airwash system.

STORAGE & DISPOSAL: Keep container closed when not in use. Do not contaminate water, food, or feed by storage, disposal, or cleaning of equipment. The container must be triple rinsed (or equivalent) and offered for recycling, reconditioning, or disposal in an approved landfill or buried in a safe place. Rinsate that cannot be used or reprocessed should be disposed of in a landfill approved for pesticides or buried in a sale place away from water supplies. Open dumping is prohibited.

21

 \mathcal{F}

1

Manufactured by: Progressive Products 3614 East Pawnee Wicht** KS 67218 EPA REG. NO. 44043-2 EPA EST. NO. NET CONTENTS

BEST DOCUMENT AVAILABLE