

ACTIVE INGREDIENT

· · · - · · · - · · · · · · · · · · · ·	
Disodium cyanodithioimidocarbonate	
Potassium N-methyldithiocarbamate	
INERT INGREDIENT	
TOTAL	
This product contains 3.57 lb. of active ingredients pe 10.2 lb. per gallon.	

KEEP OUT OF REACH OF CHILDREN WARNING

PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS AND DOMESTIC ANIMALS

WARNING: Causes eye damage and skin irritation. Do not get in eyes, on skin, or on clothing. Wear goggles or face shield and rubber gloves when handling. Harmful or fatal if swallowed. Avoid contamination of food.

"PRACTICAL TREATMENT": In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes. For eyes, call a physician. Remove and wash contaminated clothing before reuse. If swallowed, give patient doses of powdered charcoal immediately or all he can swallow of raw egg white, milk, gruel, or flour and water. Then induce vomiting with salt, soap, or mustard in warm water. Call a physician immediately.

ENVIRONMENTAL HAZARDS: This pesticide is toxic to fish. Do not discharge into lakes, streams, ponds, or public waters unless in accordance with an NPDES permit. For guidance contact your Regional Office of the EPA.

DIRECTIONS FOR USE GENERAL CLASSIFICATION

It is a violation of Federal law to use this product in a inconsistent with its labeling.

IWE 6135 is used to control algae, bacteria, and fungi in recip commercial and industrial water cooling towers. Prior to its use, must be cleaned to remove algal growth, microbiological slime, a deposits. An initial slug addition of 1.5 to 3.0 fluid ounces of IWE 1,000 gallons of water is recommended. Repeat initial dosage until is evident.

Subsequent additions of 0.5 to 3.0 fluid ounces of IWE 6135 p gallons of water should be employed every 1 to 5 days, or as need frequency of addition depends upon the relative amount of bleedoff severity of the microbiological problem. Slug additions should be the sump of water cooling towers.

STORAGE AND DISPOSAL

PROHIBITIONS: Do not contaminate water, food, or feed by sto disposal. Open dumping is prohibited.

PESTICIDE DISPOSAL: Pesticide, spray mixture, or rinsate that ca used or chemically reprocessed should be disposed of in a landfill apfor pesticides or buried in a safe place away from water supplies. CONTAINER DISPOSAL: Containers under 30-gallon capacity mus reused but should be triple rinsed and disposed of in an inciner landfill approved for pesticide containers or buried in a safe Containers over 30-gallon capacity should be resealed and offer reconditioning or triple rinsed (or equivalent) and offered for reconditioning, or disposal in an approved landfill, or buried in a safe GENERAL: Consult Federal, State, or Local disposal authorit approved alternative procedures.

Manufactured by:

INDUSTRIAL WATER ENGINEERING, INC. 7132 Jefferson NE Albuquerque, New Mexico 87109

EPA REG.	NO.	44220-5
----------	-----	---------


EPA EST. NO 44220-NM-

NET CONTENTS

HIS LABEL FOR PLASTIC CONTAINERS

ø:





FOR PLASTIC CONTAINERS

LABEL

GREDIENT

fanodithioimidocarbonate14.7	/%
f-methyldithiocarbamate	l%
REDIENT	1%
)%
contains 3.57 lb. of active ingredients per gallon and weightallon.	hs

P OUT OF REACH OF CHILDREN WARNING

PRECAUTIONARY STATEMENTS
3DS TO HUMANS AND DOMESTIC ANIMALS

tuses eye damage and skin irritation. Do not get in eyes, on thing. Wear goggles or face shield and rubber gloves when aful or fatal if swallowed. Avoid contamination of food.

REATMENT": In case of contact, immediately flush eyes or rof water for at least 15 minutes. For eyes, call a physician. ish contaminated clothing before reuse. If swallowed, give f powdered charcoal immediately or all he can swallow of tailk, gruel, or flour and water. Then induce vomiting with instard in warm water. Call a physician immediately.

AL HAZARDS: This pesticide is toxic to fish. Do not ixes, streams, ponds, or public waters unless in accordance permit. For guiunnee contact your Regional Office of the

DIRECTIONS FOR USE GENERAL CLASSIFICATION

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

IWE 6135 is used to control algae, bacteria, and fungi in recirculating commercial and industrial water cooling towers. Prior to its use, systems must be cleaned to remove algal growth, microbiological slime, and other deposits. An initial slug addition of 1.5 to 3.0 fluid ounces of IWE 6135 per 1,000 gallons of water is recommended. Repeat initial dosage until control is evident.

Subsequent additions of 0.5 to 3.0 fluid ounces of IWE 6135 per 1,000 \odot alons of water should be employed every 1 to 5 days, or as needed. The frequency of addition depends upon the relative amount of bleedoff and the severity of the microbiological problem. Slug additions should be made in the sump of water cooling towers.



STORAGE AND DISPOSAL

PROHIBITIONS: Do not contaminate water, food, or feed by storage or disposal. Open dumping is prohibited.

PESTICIDE DISPOSAL: Pesticide, spray mixture, or rinsate that cannot be used or chemically reprocessed should be disposed of in a landfill approved for pesticides or buried in a safe place away from water supplies.

CONTAINER DISPOSAL: Containers under 30-gallon capacity must not be reused but should be triple rinsed and disposed of in an incinerator or landfill approved for pesticide containers or buried in a safe place. Containers over 30-gallon capacity should be resealed and offered for reconditioning or triple rinsed (or equivalent) and offered for recycling, reconditioning, or disposal in an approved landfill, or buried in a safe place. GENERAL:Consult Federal, State, or Local disposal authorities for approved alternative procedures.

Manufactured by:

INDUSTRIAL WATER ENGINEERING, INC. 7132 Jefferson NE Albuquerque, New Mexico 87109

EPA REG. NO. 44220-5

EPA EST. NO 44220-NM-01

NET CONTENTS

25-11

. بعد