

DANGER: Corrosive, may cause severe skin irritation or chemical burns to broken skin. Causes eye damage. Do not get in eyes, on skin or on clothing. Wear goggles or face shield and rubber gloves when handling this product. Wash after handling. Avoid breathing vapors. Vacate poorly ventilated areas as soon as possible. Do not return until odors have dissipated.

PHYSICAL AND CHEMICAL HAZARDS:
STRONG OXIDIZING AGENT: Mix only with water according to label directions. Mixing this product with gross filth such as feces, urine, etc., or with ammonia, acids, detergents or other chemicals may release hazardous gases, irritating to eyes, lungs and mucous membranes.

manufactured by

EPA REG. NO. 44301-1 EPA EST. NO.
NET CONTENTS

ACCEPTED
44301-1
AUG 15 1981

Under the Federal Insecticide, Fungicide, and Rodenticide Act, as amended, for the pesticide registered and sold under EPA Reg. 10

Under the Federal Insecticide, Fungicide, and Rodenticide Act, as amended, for the pesticide registered under EPA Reg. No.

**"FOR SWIMMING POOL CHLORINATION
AND SANITIZING."**

ACTIVE INGREDIENT
SODIUM HYPOCHLORITE 5.20%
INERT INGREDIENTS 94.80%

KEEP OUT OF REACH OF CHILDREN
DANGER

FIRST AID: If on skin, wash with plenty of soap and water. If in eyes, flush with water for at least 15 minutes. Get medical attention. If swallowed, drink large quantities of milk, or gelatin solution or, if these are not available, drink large quantities of water. Do NOT give vinegar or other acids. Do NOT induce vomiting. Get prompt medical attention.

See additional precautions on side panel

IT IS A VIOLATION OF FEDERAL LAW TO USE THIS PRODUCT
IN A MANNER INCONSISTENT WITH ITS LABELING

DIRECTIONS FOR SWIMMING POOL CHLORINATION
For a new pool or for spring start-up, superchlorinate with one (1) pint (16 flu. ozs.) of this sodium hypochlorite solution for each 2500 gallons of water. This dosage is equivalent to 5 ppm available chlorine by weight.

DIRECTIONS FOR SWIMMING POOL CHLORINATION

DIRECTIONS FOR SWIMMING POOL CHLORINATION
 For a new pool or for spring start-up, superchlorinate with one (1) pint (16 fl. oz.) of this sodium hypochlorite solution for each 2500 gallons of water. This dosage is equivalent to 5 ppm available chlorine by weight.

For Fish Maintenance:

- A. Adjust pool water pH to 7.6 - 7.2 range and maintain.
- B. Add manually, or by a feeder, 1 ounce of the sodium hypochlorite solution at a rate to maintain an available chlorine residual of 3.0 to 1.0 ppm. One half pint (8 fl. oz.) of this sodium hypochlorite solution for each 6000 gallons of water will provide 1.0 ppm available chlorine by weight. Frequency of additions to maintain 3.0 to 1.0 ppm available chlorine will depend upon temperature and number of swimmers. The test kit to make water tests. Handwritten: frequency of additions to maintain 3.0 to 1.0 ppm available chlorine will depend upon temperature and number of swimmers. The test kit to make water tests. Handwritten: frequency of additions to maintain 3.0 to 1.0 ppm available chlorine will depend upon temperature and number of swimmers. The test kit to make water tests.

DIRECTIONS FOR DISINFECTION OF POTABLE WATER FOR HOME WELL WATER SYSTEMS

Each of the sodium hypochlorite solution tanks are equipped with a float valve to maintain a constant liquid level. The float valve is set to maintain a liquid level of 1.5 m. The tanks are equipped with a float valve to maintain a constant liquid level. The float valve is set to maintain a liquid level of 1.5 m. The tanks are equipped with a float valve to maintain a constant liquid level. The float valve is set to maintain a liquid level of 1.5 m.

DIRECTIONS FOR SANITIZING FOOD PROCESSING OR DAIRY EQUIPMENT

Apply 2 to 3 cups of this sodium hypochlorite solution to 100 square feet of lawn. Make a solution with 1 1/2 cups of this solution in 2 gallons of water. Use this water for the treatment with sodium hypochlorite solution. Do not soak overnight. Additional treatment: 2 cups of this sodium hypochlorite solution to 100 square feet of lawn. Use this water for the treatment with 2.0 cups available chlorine by weight.

NOTE: This product degrades with age. Use a chlorine test kit and increase dosage as necessary to obtain the required level of available chlorine.

STORAGE AND DISPOSAL:

3. OILAGE AND DISPOSAL: Oils, lubricants, coolants, hydraulic fluids, and other liquids spilled from direct sunlight in case of spill flood area with large quantities of water. If possible, use a spill container to thoroughly wash, and either return to manufacturer or dispose of by using a rashier or vacuum or using an approved landfill. Products or materials that can be disposed of should be mixed with water and disposed of in a sanitary sewer. Do not dump materials into feed bins, storage silos, or disposal or cleaning of equipment.