



**Manufactured by:**  
**AQUA-CHEM, INC.**

P.O. BOX 11225  
3100 STONEYBROOK DRIVE  
RALEIGH, NORTH CAROLINA 27604  
(919) 828-0296

EPA REG. NO. 43391-3

EPA EST. NO. 43391-3

**ACCEPTED**  
MAR 04 1981  
Under the Federal Insecticide, Fungicide, and Rodenticide Act, as amended, for the pesticide registered under EPA Reg. No. 44391-3

Ship To:

Address:

P. O. #

Date:

11225  
3100  
RALEIGH, NC 27604  
MAR 04 1981

**#C-122**

3

**Net Contents**

**ACTIVE INGREDIENTS:**

Disodium cyanodithioimidocarbonate ... 4.90%  
Potassium N-methyldithiocarbamate .... 6.76%

**INERT INGREDIENTS** ..... 88.34%  
**TOTAL** ..... 100.0 %

This product contains 1.03 lb. of active ingredients per gallon and weighs 8.88 lb. per gallon.

**STORAGE & DISPOSAL**

Keep container closed when not in use. Do not contaminate water, food, or feed by storage, disposal, or cleaning of equipment. The container must be triple rinsed (or equivalent). Rinsate that cannot be used or reprocessed should be disposed of in a landfill approved for pesticides or buried in a safe place away from water supplies. Open dumping prohibited.

METAL CONTAINERS: AFTER RINSING MAY BE OFFERED FOR RECYCLING RECONDITIONING, OR DISPOSAL IN AN APPROVED LANDFILL OR BURIED IN A SAFE PLACE

PLASTIC CONTAINERS: DO NOT REUSE EMPTY CONTAINER. INCINERATE OR DISPOSE AS ABOVE

**DIRECTIONS FOR USE**  
**GENERAL CLASSIFICATION**

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

#C-122 is used to control algae, bacteria, and fungi in recirculating commercial and industrial water cooling towers. Prior to its use, systems must be cleaned to remove algal growth, microbiological slime, and other deposits. An initial slug addition of 5.1 to 10.2 fluid ounces of #C-122 per 1000 gallons of water is recommended. Repeat initial dosage until control is evident.

Subsequent slug additions of 1.7 to 10.2 fluid ounces of #C-122 per 1000 gallons of water should be employed every 1 to 5 days, or as needed. The frequency of addition depends upon the relative amount of bleedoff and the severity of the microbiological problem. Slug additions should be made in the sump of water cooling towers.

**KEEP OUT OF REACH OF CHILDREN**

**WARNING**

**PRECAUTIONARY STATEMENTS**  
**HAZARDS TO HUMANS AND DOMESTIC ANIMALS**

**WARNING:** Causes eye damage and skin irritation. Do not get in eyes, on skin, or on clothing. Wear goggles or face shield and rubber gloves when handling. Harmful or fatal if swallowed. Avoid contamination of food.

**FIRST AID:** In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes. For eyes, call a physician. Remove and wash contaminated clothing before reuse. If swallowed, give patient doses of powdered charcoal immediately or all he can swallow of raw egg white, milk, gruel, or flour and water. Then induce vomiting with salt, soap, or mustard in warm water. Call a physician immediately.

**ENVIRONMENTAL HAZARDS:** This pesticide is toxic to fish. Do not discharge into lakes, streams, ponds, or public waters unless in accordance with an NPDES permit. For guidance contact your Regional Office of the EPA.

28