Polyfoxyethylene(dimenthuliminio)ethylene(dimenthuliminio)

ethylenedichloride]......30.0%

INERT INGREDIENTS:.....70.0%

TOTAL.....100.0%

ACTIVE INGREDIENTS:

information.

METAL: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.

CAUTION

| FIRST AID | |
|---------------------|--|
| If in Eyes | -Hold eyes open and rinse slowly and gently with water for 15-20 minutesRemove contact tenses, if present, after the first 5 minutes, then continue rinsing eyeCall a poison control center or doctor for further treatment advice. |
| If on Skin, Clothes | -Take off contaminated clothingRinse skin immediately with plenty of water for 15-20 minutesCall a poison control center or doctor for treatment advice. |
| If Swallowed | -Call poison control center or doctor immediately for treatment adviceHave person sip a glass of water, if able to swallowDo not induce vomitting unless told to do so by the poison control center or doctorDo not give anything by mouth to an unconscious person. |
| If Inhaled | -Move person to fresh airIf person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth if possibleCall a poison control center or doctor for further treatment advice. |
| HOT LINE NUMBER | |

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

Have the product container or label with you when calling a Poison Control Center or doctor or going for treatment. You may also contact CHEMTREC or 800-424-9300 for emergency medical treatment

CAUTION: Harmful if swallowed. Avoid breathing vapors. Avoid contact with skin, eyes, or clothing. Wash thoroughly with soap and water after handling.

ENVIRONMENTAL HAZARDS: This pesticide is toxic to fish and aquatic organisms. Do not contaminate water by cleaning of equipment or disposal of waste. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

MBC 130 is used to control algae, bacteria, and fungi in recirculating commercial and industrial water cooling towers and systems. Prior to its use, systems must be cleaned to remove algal growth, microbiological slime, and other deposits. An initial slug addition of 1.90 to 4.75 fluid ounces of MBC 130 per 1000 gallons of water to provide a concentration of 16 to 40 parts per million of MBC 130 based on the total weight of water in the system, is recommended. Repeat initial dosage until control is evident. Subsequently slug additions of 0.47 to 4.75 fluid ounces of MBC 130 per 1000 gallons of water (4 to 40 parts per million) of MBC 130 should be employed every 2 to 5 days, or as needed. The frequency of addition depends upon the relative amount of bleedoff and the severity of the microbiological problem. Slug additions should be made in the sump of water cooling towers.

MBC 130 is used to control bacteria in industrial air-washing systems that maintain effective mist eliminating components. Prior to its use, systems should be cleaned to remove bacterial slime and other deposits. An initial slug dose of 7.1 to 11.9 fluid ounces of MBC 130 per 1000 gallons of water is recommended. Repeat initial dosage until control is evident. Subsequent slug additions of 4.8 to 11.9 fluid ounces of MBC 130 per 1000 gallons of water should be employed every 1 to 5 days, or as needed. The frequency of addition depends upon the relative amount of bleedoff and severity of the bacterial problem. Slug addition may be made to the sump or to the water collection travs of the airwash system.

MBC 130 is used to control the growth of algae in swimming pools, exterior spas, whirlpools, hot tubs, decorative fountains, and ponds that do not contain fish. For maximum effectiveness, pools, spas, whirlpools, hot tubs, decorative fountains, and ponds containing heavy growth of algae should be cleaned prior to using MBC 130.

For pools having just visible algae growth, add an initial dose of 25 to 38.5 fluid bunces of MBC 130 per 10,000 gallions of water and remove settled algae debris by cleaning. For treatment of a freshly cleaned and lined pool, add initially 13.5 to 25 fluid ounces of MBC 130 per 10,000 gallions of water.

Subsequent additions of 4.5 to 9 fluid ounces of MBC 130 per 10,000 gallons of water should be made every 5 to 7 days after initial treatment for maintenance.

Spas, whirlpools, hot tubs, decorative fountains, and ponds having just visible algae growth require an initial dose of 2.5 to 4 fluid ounces of MBC 130 per 1000 gallons of water. For treatment of a freshly cleaned spa, whirlpool, hot tub, decorative fountain, or pond, add initially 1.5 to 2.5 fluid ounces of MBC 130 per 1000 gallons of water. Subsequent additions of 0.5 to 1 fluid ounces of MBC 130 should be made every 5 to 7 days after initial treatment for maintenance.

MBC 130 will prevent growth of most algae during the off-season winter months when pools are not in use. For pools, which have been properly treated during the swimming season and are free of visible algae, add 25 to 38.5 fluid ounces per 10,000 gallons. It is necessary that a uniform distribution of algaecide throughout the water and the pool be made for maximum effectiveness. If pool is not covered, it may be necessary to repeat the treatment one or more times during the season.

MBC 130 is compatible with those chemicals used to treat pools and spas and is effective at both acid and alkaline pH. MBC 130 can be used in pools and spas treated with chlorine chemicals and may reduce the amount of those chemicals normally required. However, do not mix MBC 130 with concentrated dry or liquid chlorine products.

MANUFACTURED BY: NASHVILLE CHEMICAL & EQUIPMENT CO., INC. 7001 WESTBELT DRIVE NASHVILLE, TN 37209

EPA Est. No. 44392-TN-01

EPA Reg. No. 44392-2

Product Weight 8.9 lbs/gal 1.07 kg/l

HMIS / NPCA Ratings

Last Revision

Health 1 Flammability 1 Reactivity 1

09/08/04

NET CONTENTS:

ACCEPTED

OCT 1 3 2005

Under the Federal Insecticide, Fungicide, and Rodenticide, Act as amended, for the pesticide, registered under EPA Reg. No. 44 392-2

(y

2

9

00