

# MBC 415

KEEP OUT OF REACH OF CHILDREN  
DANGER

ACTIVE INGREDIENTS:  
METHYLENE BIS(THIOCYANATE).....2.5%  
2-(THIOCYANOMETHYLTHIO)BENZOTHIADOLE.....2.5%  
INERT INGREDIENTS: .....95.0%

## PRECAUTIONARY STATEMENTS

### HAZARDS TO HUMANS AND DOMESTIC ANIMALS

**DANGER:** CORROSIVE, CAUSES IRREVERSIBLE EYE DAMAGE AND CAUSES SKIN DAMAGE. HARMFUL OR FATAL IF SWALLOWED OR ABSORBED THROUGH THE SKIN. THIS PRODUCT IS A POTENTIAL SKIN SENSITIZER. WORKMEN HANDLING THIS PRODUCT OR TREATED MATERIAL SHOULD WEAR IMPERVIOUS GLOVES, GOGGLES OR FACE SHIELD, AND PROTECTIVE CLOTHING. ALL PROTECTIVE CLOTHING, WORK SHOES OR BOOTS, AND EQUIPMENT MUST BE LEFT AT THE WORK SITE AT THE END OF THE DAY. EATING, DRINKING, OR SMOKING DURING USE OF THIS PRODUCT IS PROHIBITED.

**FIRST AID:** IN CASE OF SKIN CONTACT, WASH PROMPTLY AND THOROUGHLY WITH SOAP AND WATER AND FINALLY WITH GLYCERIN. IF PRODUCT GETS IN THE EYES, FLUSH IMMEDIATELY WITH COPIOUS AMOUNTS OF CLEAN, COOL WATER FOR 15 TO 30 MINUTES. GET MEDICAL ATTENTION IMMEDIATELY. IF PRODUCT IS SWALLOWED, CALL A PHYSICIAN OR POISON CONTROL CENTER. DRINK 1 OR 2 GLASSES OF WATER AND INDUCE VOMITING BY TOUCHING BACK OF THROAT WITH FINGER. DO NOT INDUCE VOMITING OR GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

**ENVIRONMENTAL HAZARDS:** THIS PESTICIDE IS TOXIC TO FISH. DO NOT APPLY DIRECTLY TO WATER OR WETLANDS. DO NOT DISCHARGE EFFLUENT CONTAINING THIS PRODUCT INTO LAKES, STREAMS, PONDS, ESTUARIES, OCEANS OR OTHER WATERS UNLESS IN ACCORDANCE WITH THE REQUIREMENTS OF A NATIONAL POLLUTANT DISCHARGE ELIMINATION SYSTEM (NPDES) PERMIT AND THE PERMITTING AUTHORITY HAS BEEN NOTIFIED IN WRITING PRIOR TO DISCHARGE. DO NOT DISCHARGE EFFLUENT CONTAINING THIS PRODUCT INTO SEWER SYSTEMS WITHOUT PREVIOUSLY NOTIFYING THE LOCAL SEWAGE TREATMENT PLANT AUTHORITY. FOR GUIDANCE CONTACT YOUR STATE WATER BOARD OR REGIONAL OFFICE OF THE EPA.

**PHYSICAL AND CHEMICAL HAZARDS:** DO NOT EXPOSE TO EXTREME TEMPERATURES.

### STORAGE & DISPOSAL

DO NOT CONTAMINATE WATER, FOOD, OR FEED BY STORAGE OR DISPOSAL.

**STORAGE:** DO NOT EXPOSE TO EXTREME TEMPERATURES. DO NOT STACK MORE THAN FIVE DRUMS HIGH. DRUMS SHOULD BE OPENED IN WELL-VENTILATED AREAS. LEAKING OR DAMAGED DRUMS SHOULD BE PLACED IN OVERPACK DRUMS FOR DISPOSAL. SPILLS SHOULD BE ABSORBED IN SAND/ST OR SAND AND DISPOSED OF IN A SANITARY LANDFILL. KEEP CONTAINER CLOSED WHEN NOT IN USE.

**PESTICIDE DISPOSAL:** PESTICIDE WASTES ARE ACUTELY HAZARDOUS. IMPROPER DISPOSAL OF EXCESS PESTICIDE, SPRAY MIXTURE, OR RINSATE IS A VIOLATION OF FEDERAL LAW. IF THESE WASTES CANNOT BE DISPOSED OF BY USE ACCORDING TO LABEL INSTRUCTIONS, CONTACT YOUR STATE PESTICIDE OR ENVIRONMENTAL CONTROL AGENCY, OR THE HAZARDOUS WASTE REPRESENTATIVE AT YOUR EPA REGIONAL OFFICE FOR GUIDANCE.

**CONTAINER DISPOSAL:** TRIPLE RINSE (OR EQUIVALENT). THEN OFFER FOR RECYCLING OR RECONDITIONING, OR PUNCTURE AND DISPOSE OF IN A SANITARY LANDFILL, BY INCINERATION, OR, IF ALLOWED BY STATE AND LOCAL AUTHORITIES, BY BURNING. IF BURNED, STAY OUT OF SMOKE.

### DIRECTIONS FOR USE

IT IS A VIOLATION OF FEDERAL LAW TO USE THIS PRODUCT IN A MANNER INCONSISTENT WITH ITS LABELING.

**COOLING TOWERS:** MBC 415 IS USED TO PROTECT COOLING TOWER WOOD AGAINST SOFT OR SURFACE ROT AND INTERNAL OR DRY ROT. IF APPLIED BY PAINTING A DISPERSION CONTAINING 2.0 TO 2.0X MBC 415 IN WATER UNTO THE CLEAN WOOD SURFACES

THE AMOUNT APPLIED SHOULD PROVIDE 2.4 TO 3.2 LB MBC 415 PER 1000 SQUARE FEET OF WOOD SURFACE. SOFT OR SURFACE ROT CAN ALSO BE INHIBITED BY PERIODIC SHOCK DOSES OF MBC 415 TO THE RECIRCULATING COOLING WATER AT THE TOWER BASIN OR COLD WELL. THE DOSAGE SHOULD PROVIDE 5.0 LB OF MBC 415 PER 1000 GAL OF WATER AND THE BLEEDOFF SHOULD BE STOPPED FOR 4 TO 6 HR AFTER TREATMENT. THE SHOCK TREATMENT SHOULD BE REPEATED EVERY FOUR MONTHS.

**COOLING WATER:** MBC 415 IS USED TO CONTROL ALGAE, BACTERIA, AND FUNGI IN INDUSTRIAL RECIRCULATING COOLING WATER SYSTEMS. BEFORE TREATMENT IS BEGUN, THE SYSTEM SHOULD BE CLEANED THOROUGHLY TO REMOVE OLD ALGAL GROWTH, MICROBIOLOGICAL SLIME, AND OTHER DEPOSITS. THE SYSTEM SHOULD THEN BE DRAINED, FLUSHED, REFILLED WITH WATER, AND TREATED WITH AN INITIAL DOSE OF 2.4 TO 14.8 FLUID OZ OF MBC 415 PER 1000 GAL WATER IN THE SYSTEM. SUBSEQUENT ADDITIONS OF 0.8 TO 4.8 FLUID OZ PER 1000 GAL SHOULD BE MADE EVERY 1 TO 5 DAYS, DEPENDING ON AMOUNT OF BLEEDOFF AND SEVERITY OF MICROBIOLOGICAL FOULING.

**DRILLING FLUIDS:** TO INHIBIT BACTERIAL AND FUNGAL DEGRADATION OF THE FLUIDS OR MUDS USED IN THE DRILLING OF WELLS, MBC 415 IS INCORPORATED IN THE DRILLING FLUID AT CONCENTRATIONS OF 0.2 TO 1.0Z BASED ON THE TOTAL NET WEIGHT OF THE FLUID.

**PETROLEUM SECONDARY RECOVERY:** MBC 415 IS USED TO CONTROL SULFATE-REDUCING BACTERIA, SLIME-FORMING BACTERIA AND FUNGI IN OIL-FIELD WATER, POLYMER, OR MICELLAR FLOODS, WATER-DISPOSAL SYSTEMS, AND OTHER OIL-FIELD WATER SYSTEMS AT DOSAGE RATES OF 15.6 TO 52.0 FL OZ OF MBC 415 PER 1000 GAL OF WATER TREATED. ADDITIONS SHOULD BE MADE CONTINUOUSLY OR INTERMITTENTLY BY MEANS OF A METERING PUMP AT THE FREE WATER KNOCKOUTS, BEFORE OR AFTER INJECTION PUMPS AND INJECTION WELL HEADERS.

**CONTINUOUS FEED METHOD:** WHEN SYSTEM IS NOTICEABLY FOULED, ADD 15.6 TO 52.0 FL OZ OF MBC 415 PER 1000 GAL OF WATER CONTINUOUSLY UNTIL DESIRED DEGREE OF CONTROL IS ACHIEVED. THEN TREAT WITH 15.6 TO 52.0 FL OZ MBC 415 PER 1000 GAL OF WATER CONTINUOUSLY, OR AS NEEDED TO MAINTAIN CONTROL. **INTERMITTENT OR SLUG METHOD:** WHEN SYSTEM IS NOTICEABLY FOULED, OR TO MAINTAIN CONTROL, ADD 15.6 TO 52.0 FL OZ MBC 415 PER 1000 GAL OF WATER FOR 4 TO 8 HR PER DAY AND 1 TO 4 TIMES PER WEEK, OR AS NEEDED TO MAINTAIN CONTROL.

**CRUDE AND REFINED OILS:** MBC 415 IS AN OIL-SOLUBLE PRESERVATIVE FOR THE CONTROL OF BACTERIA AND FUNGI THAT CAUSE THE DEGRADATION OF CRUDE OIL AND REFINED FUEL OILS DURING STORAGE. IT SHOULD BE ADDED TO THE OIL AS IT IS BEING TRANSFERRED FROM THE SHIPPING CONTAINER TO THE STORAGE TANK AT THE RATE OF 2.4 TO 24.0 FL OZ MBC 415 PER 1000 GAL OF OIL. ADDITION SHOULD BE MADE BATCHWISE WHERE MIXING OCCURS OR CONTINUOUSLY TO THE SUCTION SIDE OF THE TRANSFER PUMP.

PM 33  
44392-11  
8/12/98

ACCEPTED HEALTH 3 FLAMMABILITY 2 REACTIVITY 1 AUG 12 1998	THIS IS AN EPA RATING:
	PRODUCT WEIGHT: 8.6 LBS/GAL 1.03 KG/L NET CONTENTS MARKED ON CONTAINER
EPA REG. NO. 44392-11 EPA EST. NO. 44392-TN-01	

For the Federal Insecticide, Fungicide, and Herbicide Act as amended, for the pre-mixed registration under 192 Reg No. 44392-11

MANUFACTURED BY:  
NASHVILLE CHEMICAL & EQUIPMENT CO., INC.  
P.O. BOX 90246  
NASHVILLE, TN.  
615-350-7070