

44428-3

8-19-1982

1/3

U.S. ENVIRONMENTAL PROTECTION AGENCY  
OFFICE OF PESTICIDES PROGRAMS  
REGISTRATION DIVISION (WH-567)  
WASHINGTON, D.C. 20460

EPA REGISTRATION NO.

DATE OF ISSUANCE

44428-3

AUG 19 1982

TERM OF ISSUANCE

Conditional

NAME OF PESTICIDE PRODUCT

ANTI-FOULING BOTTOM PAINT  
030010

NOTICE OF PESTICIDE:  REGISTRATION  
 REREGISTRATION  
(Under the Federal Insecticide, Fungicide,  
and Rodenticide Act, as amended)

NAME AND ADDRESS OF REGISTRANT (Include ZIP code)

Best Available Copy

Jarvie Paint Mfg. Co.  
760 Alona Street  
Seattle, WA 98109

NOTE: Changes in labeling formula differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Registration Division prior to use of the label in commerce. In any correspondence on this product always refer to the above U.S. EPA registration number.

On the basis of information furnished by the registrant, the above named pesticide is hereby Registered/Reregistered under the Federal Insecticide, Fungicide, and Rodenticide Act.

A copy of the labeling accepted in connection with this Registration/Reregistration is returned herewith.

Registration is in no way to be construed as an endorsement or approval of this product by this Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.

This product is conditionally registered in accordance with FIFRA, Sec. 3(c)(7)(A) provided that you:

1. Submit and/or cite all data required for registration/reregistration of your product under FIFRA sec. 3(c)(5) when the Agency requires all registrants of similar product to submit such data.

2. Make the labeling changes listed below before you release the product for shipment:

- a. Add the phrase "EPA Registration No. 44428-3."
- b. The "EPA Establishment No." must appear on the label or the container. Contact the nearest EPA Regional Office regarding producing establishment registration number.
- c. Revise the front panel STATEMENT OF HAZARDOUS INFORMATION statements to read as follows:

If swallowed: Drink promptly a large quantity of milk, egg whites, gelatin solution, or if these are not available, drink large quantities of water. Avoid alcohol. Do not induce vomiting.

If in eyes: Flush with plenty of water. Get medical attention.

ATTACHMENT IS APPLICABLE: Wash with plenty of soap and water. Get medical attention.

SIGNATURE OF APPROVING OFFICIAL

DATE

AUG 19 1982

If inhaled: Remove victim to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. Get medical attention.

- d. Under HAZARDS TO HUMANS & DOMESTIC ANIMALS, second paragraph, delete "Wear a mask or respirator jointly approved by the Mining Enforcement and Safety Administration and the National Institute for Occupational Safety and Health." This precaution is covered in the first paragraph.
- e. Under PHYSICAL OR CHEMICAL HAZARDS: 1) Delete the present flammability statement and replace with "Flammable. Keep away from heat and open flame." 2) Delete the statement "Pesticide spray mixtures or rinse water that cannot be used ... under subtitle C of the Resources Conservation & Recovery Act."
- f. Under STORAGE AND DISPOSAL, add the following statements:
  - 1. Do not contaminate water, food, or feed by storage or disposal.
  - 2. Pesticide, spray mixture, or rinsate that cannot be used according to label instructions must be disposed of according to applicable Federal, state, or local procedures.


Revise the container disposal statement to read as follows:

Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other approved state and local procedures."

- g. Under DIRECTIONS, delete "While spraying and/or sanding boat surface, wear a mask or a respirator jointly approved ... Occupational Safety and Health" as this statement is repetitious.
  - h. Indicate how the paint is to be applied (rolling, spraying, etc.).
  - i. Indicate the number of applications (coats) recommended and coverage intended for contents of container.
  - j. Under PHYSICAL OR CHEMICAL HAZARDS, delete the hazard signal word "WARNING."
3. Submit five (5) copies of your final printed labeling before you release the product for shipment. Refer to the A-79 Enclosure for a further description of final printed labeling.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA sec. 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

A stamped copy of the label is enclosed for your records.

Richard F. Mountfort   
Product Manager (23)  
Fungicide-Herbicide Branch  
Registration Division (TS-767)

Enclosure

44428-3

GENERAL INFORMATION

Jarvie's Anti-Fouling Paint 030010 is a stuffing type of anti-fouling bottom paint designed for use on wood, plastic, metal and previously painted ship bottoms. This type of anti-fouling paint is extremely effective in preventing the accumulation and growth of barnacles, marine worms and other marine fouling organisms on ship bottoms. Follow instructions for maximum performance results.

DIRECTIONS

Stir paint thoroughly before using. While spraying and/or sanding boat surface, wear a mask or a respirator jointly approved by the Mining Enforcement and Safety Administration and the National Institute for Occupational Safety and Health.

MIX WOOD: Be sure all surfaces are clean and dry. Apply one coat of Bottom Paint reduced 10% with Synalux. Allow one hour drying time and apply a second coat.

PREVIOUSLY PAINTED WOOD: Remove all traces of loose paint, dirt, grease, etc. Sand the existing paint film well and apply two coats of Bottom Paint. Allow one hour drying time between coats.

NEW STEEL HULLS: When paint is to be used on a steel hull, it is essential that at least two coats of a premium grade, non-reactive, rust inhibiting metal primer be used as a barrier coat between the paint and the steel hull.

NOTE: A prime coat is absolutely essential due to the galvanic action between the paint and steel resulting in excessive corrosion to the hull.

PREVIOUSLY PAINTED STEEL HULLS: Scrape and wire brush to remove any rust or scale. Thoroughly abrade painting spot prime any bare steel following the procedure outlined for New Steel Hulls. Apply two coats of bottom paint, allowing one hour between coats.

LAUNCHING TIME: Boat can be launched immediately or any time within 24 hours after painting.

THINNING: Thin and clean with Synalux

BEST DOCUMENT AVAILABLE

ANTI-FOULING BOTTOM PAINT

030010

ACCEPTED AUG 9 1982

ACTIVE INGREDIENT: Cuprous Oxide-----27.45%  
INERT INGREDIENTS:-----72.55%  
TOTAL: 100.00%

This product contains petroleum distillates

KEEP OUT OF REACH OF CHILDREN

WARNING

STATEMENT OF PRACTICAL TREATMENT

IF SWALLOWED: Promptly drink a large quantity of milk, egg whites, gelatin solution or, if these are not available, drink large quantities of water. Avoid alcohol. Get medical attention. Hazardous Indicator: Oral LD 50

IF INHALED: Remove victim to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. Get medical attention. Hazardous Indicator: LC 50

IF ON SKIN: Wash with plenty of soap and water. Get medical attention if irritation persists. Hazardous Indicator: Normal LD 50

IF IN EYES: Flush with plenty of soap and water. Get medical attention.

SEE SIDE PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS

MFG BY: JARVIE PAINT MFG. COMPANY  
TOWN, STATE: 760 Aloha Street  
Seattle, WA 98109

NET CONTENTS: 1 GALLON

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS (6 DOMESTIC ANIMALS)

WARNING

While spraying and/or sanding boat surface, wear a mask or a respirator jointly approved by the Mining Enforcement and Safety Administration and the National Institute for Occupational Safety and Health.

Leaves eye irritation. Harmful if absorbed through skin. Avoid contact with skin, eyes or clothing. Wear protective clothing such as gloves, long-sleeved cotton shirt, long pants and hat. May be fatal if swallowed or inhaled. Do not breathe dust, vapor or spray. Avoid skin contact or contact with clothing. Avoid contact with food, drink, or occupational equipment. Approved by the Mining Enforcement and Safety Administration and the National Institute for Occupational Safety and Health. This product contains petroleum distillates. Wash thoroughly with soap and water after handling.

ENVIRONMENTAL HAZARDS

This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved land fill.

PHYSICAL OR CHEMICAL HAZARDS

WARNING

Extremely flammable. Keep away from fire, sparks, and heated surfaces. Avoid contact with acids or alkalis. Water resistant. Do not use according to label instructions. Must be disposed of according to Federal or approved state procedure under subtitle C of the Resources Conservation & Recovery Act.

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its label.

STORAGE AND DISPOSAL

Storage: Store full container in cool, dry area.

Disposal: Dispose of used containers with a compatible solvent (for equivalent). Then offer for recycling or reconditioning or dispose of in a sanitary landfill or by other approved state and local procedures.