

**PRECAUTIONARY STATEMENTS**  
**HAZARDS TO HUMANS AND DOMESTIC ANIMALS**  
**KEEP OUT OF THE REACH OF CHILDREN**

**Control**: Causes prevent eye damage and form an efficient barrier to inhalation. Protective clothing such as long-sleeved cotton shirt, long pants, flat-topped cap, and waterproof apron should be worn. Wash hands thoroughly with soap and water after handling. Remove contaminated clothing and wash before reuse. Avoid breathing vapor spray mist dust or dust particles by sanding. Use with adequate ventilation. When respirator is required, the user must wear a respirator properly approved by the Mining Equipment and Safety Approval Board of the National Institute for Occupational Safety and Health.

#### **STATEMENT OF PRACTICAL TREATMENT**

**If swallowed:** Drink promptly a large quantity of milk, egg whites, gelatin solution or if these are not available, drink two or more glasses of water. No laxative. Get medical attention.

**If inhaled:** Remove person to fresh air. If breathing is difficult, give oxygen. Get medical attention.

If in eyes: Flush thoroughly with water for at least 15 minutes.

**If in eyes:** Flush with plenty of water. Get medical attention.

**NOTE TO PHYSICIAN: Please read and sign before giving to patient.**

NON GOVTS IN SRI LANKA  
ENVIRONMENTAL ACTIVISTS

**ENVIRONMENTAL HAZARD:** This material is extremely flammable and may cause an explosion hazard if exposed to heat, sparks or flame. It may also cause dust explosions.

#### SUMMARY OF CHEMICAL HAZARDS

#### **PHYSICAL OR CHEMICAL HAZARD**

#### **FLAMMABLE LIQUIDS**

**STORAGE AND DISPOSAL:** Store in a cool, dry place away from incompatible materials. Do not contaminate water, food, or feed by storage or disposal.

BEST DOCUMENT AVAILABLE

## Nautical Coatings, Inc.

19. *Leucosia* *leucostoma* *leucostoma*



**KEEP OUT OF REACH  
DANGER  
FLAMMABLE - VAPO  
SEE SIDE PANEL FOR ADDITIONAL PR**

**ONE GALLON 3**

PRECAUTIONARY STATEMENTS  
ANIMALS AND DOMESTIC ANIMALS  
KEEP OUT OF REACH OF CHILDREN

**DANGER!**

Inhalation - Irritating if swallowed, absorbed through skin or breathing. Wear goggles or other shield of protection over eyes. Wash thoroughly with soap and water after handling. Do not use. Avoid breathing vapor, spray and dusts of product or spraying particles and residue. Wear a respirator. See the Material Safety Data Sheet for additional information.

Eyes: If in eyes, rinse immediately with plenty of water. Get medical attention.

Inhalation: If inhaled, move to fresh air. If breathing is difficult, give oxygen. Get medical attention.

General: Get medical attention.

Drinking water: Do not drink. If swallowed, get medical attention.

Drinking water: Do not drink. If swallowed, get medical attention.

Do not drink. Do not eat or smoke while using this product. Do not drink. Do not eat or smoke while using this product.

LE

Coatings, Inc.

100 S. KELLOGG ST.  
FORT COLLINS, CO 80524



KEEP OUT OF REACH OF CHILDREN  
**DANGER**  
FLAMMABLE - VAPOR HARMFUL  
SEE SIDE PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS

**ONE GALLON 3.785 LITERS**

## DIRECTIONS FOR USE

It is a violation of federal law to use this product in a manner inconsistent with its labeling.

### STIR WELL BEFORE USING

Reducing solids below 10% NGR is not recommended. **CAUTION** - Excessive thinning will adversely affect MIL thickness. For example, reducing MIL thickness can decrease film thickness by 10% for 100 solid units and increase film thickness.

### SURFACE

New surfaces - Apply one coat of the standard formulation to new, broken, weathered, 120 grit sandpaper and sandpaper until the surface is smooth. Apply one coat of the standard formulation to new, smooth, dry, OMP. After application, let it dry for 24 hours. Proper application is important; after application, previous recordings must be removed. A good way to do this is to paint with tape, allow to dry, remove the tape and wash off OMP. Anti-slip tape is recommended.

### APPLICATION

Follow the following directions for application to prevent damage due to attack by bacteria, fungi, or other microorganisms. It is recommended to apply the product in a single coat. Applying two coats of the product may result in a loss of adhesion. It is recommended to use a brush or roller to apply the product. A wide brush or roller is recommended for best results.

**LIMITED WARRANTY** The manufacturer warrants that the product will be free from defects in material and workmanship for a period of one year from the date of purchase. The manufacturer's liability is limited to the repair or replacement of the defective product at the manufacturer's option.

### FOR COMMERCIAL USE ONLY

EPA Registration No. 44891-2  
EPA Establishment No. 44891-11-01

© 2001 DOCUMENTS PUBLISHING

ting

STATEMENTS

IS

7  
1982

Mr. Robert G. Sims  
Nautical Coatings, Inc.  
12490 Belcher Road  
Largo, FL 33543

Dear Mr. Sims:

Subject: Antifouling Paint LIP  
Sea Hawk O.M.P. II 2231 Red ✓  
EPA Registration No. 44891-1  
Sea Hawk O.M.P. I 1201 Red  
EPA Registration No. 44891-2  
Your Submission of September 24, 1982

The amendment referred to above, submitted in connection with registration under FIFRA is acceptable, provided that you make the labeling changes listed below before you release the product for shipment bearing the amended labeling.

Correct the EPA registration numbers so they agree with the products given in the subject above. They were revised on the submitted label.

A standard copy of the labeling is enclosed for your records.

Sincerely yours,

Richard F. Mountford (RM)  
Project Manager (23)  
Fungicide-Herbicide Branch  
Registration Division (FS-767)

Enclosure

BEST DOCUMENT AVAILABLE