

2014

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY

2. Make the labeling changes listed below before you release the product for shipment:

a. Add the phrase "EPA Registration No. 44891-8".

b. Correct the spelling of the word: Shellfish.

Re: Environmental Hazard section.

c. Correct the spelling of the word: lavage.

Re: Note to Physican section.

d. Include the followling subheading: Pesticide Disposal

e. Include the heading: STORAGE AND DISPOSAL

f. Revise: Hazardous to humans and domestic animals

to read:

Hazards to Humans and Domestic Animals

g. Revise: It is a violation of Federal law to use this product inconsistent with its labelings.

to read:

It is a violation of Federal law to use this product in a manner inconsistent with its labelings.

h. Align the headings Active Ingredient and Inerts Ingredients to the same left margin.

i. Align the decimal points in the ingredients section.

j. Include the heading:

Statement of Practical Treatment

k. Add the following additional precautionary statements:

Corrosive. Causes skin burns. Wear protective clothing such as gloves, long-sleeved cotton shirt, long pants and hat.

CONCURRENCES

SYMBOL							
SURNAME							
DATE							

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY

3044

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA sec. 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

A stamped copy of the label is enclosed for your records.

Sincerely,

John H. Lee
Product Manager (31)
Antimicrobial Program Branch
Registration Division (H7505C)

Enclosures

CONCURRENCES

SYMBOL							
SURNAME							
DATE							

PRECAUTIONARY STATEMENTS

Hazardous to Humans and Domestic Animals
KEEP OUT OF THE REACH OF CHILDREN Children

SKIN AND EYE IRRITATION: May be fatal if swallowed. Harmful if absorbed through the skin or inhaled. This product may be a dermal sensitizer. Avoid contact with skin, eyes, or clothing. Avoid breathing vapors. Spray mist. Shut on chips. Use washing tank thoroughly with soap and water before eating and working. Use with adequate ventilation.

IF SWALLOWED: Promptly drink a large quantity of milk, egg whites, gelatin capsules, if these are not available, drink large quantity of water. Avoid alcohol. Get medical attention.

IF INHALED: Remove victim to fresh air. If victim is not breathing give artificial respiration, preferably mouth to mouth. Get medical attention.

IF IN EYES: Flush with plenty of water. Get medical attention.
IF ON SKIN: Wash with plenty of water and soap. Get medical attention.

NOTE TO PHYSICIAN:
 Prohibit further use of any contraindicated use of gastric 1
Physical OR CHEMICAL HAZARD:
FLAMMABLE: Keep away from heat and open flames.

ENVIRONMENTAL HAZARD:
 This pesticide is toxic to aquatic organisms including fish and shellfish. Do not apply directly to water by cleaning of equipment or disposal of waste. Dispose of paint debris in an approved land fill.

Do not contaminate water, food, or feed by storage or disposal. When dumping is prohibited, pesticide disposal and pesticide wastes are toxic. Improper disposal of organic pesticides, open flames, or flames is a violation of Federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency or the nearest waste representative of the nearest EPA regional office for guidance. Paint chips, spent abrasives, and any other waste materials from removal of old paint must be disposed of in a sanitary landfill (or, if required by Federal, State or local regulations, handle as hazardous waste).


If possible, use all of contents by application according to label instructions. Residual paint, sludge, or other application waste must be disposed of in accordance with Federal, State, or Environmental Control Agency, nearest EPA regional office or the nearest Superfund facility (204-534-3344) for waste disposal guidance.

While spraying and/or sanding boat surfaces, wear a mask or a respirator jointly approved by the Mining Enforcement and Safety Administration and the National Institute for Occupational Safety and Health.

CONTAINER DISPOSAL:
 This three component is intended for recycling or reconditioning. Empty the containers with small amounts of dried residue must be disposed of in sanitary landfill (or, if required by Federal, State, or local regulation, handle as a hazardous waste.)

NEW NAUTICAL COATINGS INC.
 4242 West Street South
 St. Petersburg, FL 33714

For use only on painted surfaces. Do not use on unpainted surfaces including shellfish. For use only on painted surfaces. Do not use on unpainted surfaces including shellfish. For use only on painted surfaces. Do not use on unpainted surfaces including shellfish.



Active ingredients:

Tribocyltin Methacrylate (as part of a polymer)	9.62
Tribocyltin Fluoride	3.0
Inert ingredients	\$2.63
	.02
Total tin content:	12.27%

PREMIUM QUALITY

BIOTIN

Fishing, Anti-Fouling Bottom Paint

COLOR: WHITE 1334

KEEP OUT OF REACH OF CHILDREN
DANGER

See back panel for additional precautionary statements.

PH21 4

It is a violation of Federal law to use this product on unpainted surfaces including shellfish. For use only on painted surfaces. Do not use on unpainted surfaces including shellfish.

During and after paint removal, methods must be used to remove TBT paint into a sanitary landfill.

Stir WELL BEFORE USING

We do not recommend thinning for application if such thinners should be used, but only if necessary.

NOTE: Excessive thinning will result in lower solids and increased surface.

This product is suitable for use on fiberglass and gel-coated surfaces. Fiberglass and gel-coated surfaces must be broken up and removed. S-80 Wax and Grease Remover must be used before and after application. New aluminum must be primed with S-75 catalyst followed by PRIMER, followed by two coats.

To insure good adhesion, clean and moisture-free surfaces are required.

APPLICATION:
 For use on fiberglass and gel-coated surfaces. Fiberglass and gel-coated surfaces must be broken up and removed. S-80 Wax and Grease Remover must be used before and after application. New aluminum must be primed with S-75 catalyst followed by PRIMER, followed by two coats. Allow 12 hours dry before recoating.

Registration No. 44891-6
 Establishment No. 44891-1