

44891-9

8/5/2003

Page 1 of 6

[FRONT PANEL]

# Sea Hawk


Yacht Finishes

(Picture of Sea Hawk here)

PREMIUM QUALITY

# MONTEREY

Water Borne Antifouling Coating



[Optional proposed text appears in brackets - the final label may include some or all of the optional text]

[Paint Color and Number]

<b>ACTIVE INGREDIENT:</b>	
Cuprous Oxide .....	54.67%
<b>OTHER INGREDIENTS:</b> .....	45.33%
<b>TOTAL:</b> .....	100.00%
Copper expressed as metallic 51.76%	

KEEP OUT OF REACH OF CHILDREN

**WARNING**

SEE BACK PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS

**LIMITED WARRANTY:** The manufacturer warrants all material sold by it against defects in the material. The manufacturer's liability under the sale and warranty of this material shall in any case be limited to replacement of material only. The manufacturer makes no other warranty for this product, expressed or implied.

276

[FRONT SIDE PANEL]

**Net Contents**  
**1 Gallon**  
**U.S. Measure**  
**3.785 Liters**

**NEW NAUTICAL COATINGS, INC.**  
**14805 49<sup>th</sup> Street North**  
**Clearwater, FL 33762**  
**[www.seahawkpaints.com](http://www.seahawkpaints.com)**

**RECEIVED**  
**AUG 05 2003**

Under the Federal Insecticide, Fungicide, and  
Rodenticide Act as amended, for the  
pesticide, registered under  
EPA Reg. No. **44891-9**

**[BACK PANEL]**

**DIRECTIONS FOR USE**

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.


**GENERAL DESCRIPTION**

Hard ablative, multi-seasonal, water-based antifoulant. Provides protection against algae, barnacles, annelids, tunicates, bryozoa, hydroids, zebra mussels and other fouling organisms. Monterey is abrasion resistant for scrubbing, trailering and dry storage. Reduces paint buildup. This product may only be used to treat the surfaces of hulls on boats and vessels. This product is intended for both salt and fresh water use. Monterey applies easily and dries quickly. It may be used over old antifouling finishes in good condition. Monterey is an antifouling paint in a high-technology vehicle that withstands frequent trailering, beaching and launching. Monterey should be not be used on aluminum without a proper barrier system. Please consult with your Sea Hawk Representative.

**SHAKE VIGOROUSLY FOR A MINIMUM OF 10 MINUTES BEFORE APPLICATION**

**PRODUCT INFORMATION**

Finish/Sheen:	Semi-Gloss
Converter:	One Pack
Copper Content:	58%
Volume Solids:	44% ± 2%
Mix Ratio:	One Pack
Shipping Weight:	21-22 Lbs./Gal.
Flash Point:	N/A
Film Thickness:	5 mils wet equals 2.2 dry per coat
Recommended Coats:	2 on entire hull and 3 at waterline
Theoretical Coverage:	320 Sq. Ft./Gal. @ recommended film thickness



**APPLICATION DETAILS**

Method:	Brush, roller or spray
Thinner:	Water
Cleaner:	Water

**Overcoating Internal**

**Drying Time (Hrs)**

Substrate Temp.	Touch	Min.	Max.	Launch
73° F (23° C)	2 Hrs	1 Hr	N/A	12 Hrs
95° F (35° C)	1 Hr	1 Hr	N/A	12 Hrs

Consult with your Sea Hawk representative for the system best suited for surfaces to be protected.

**[BACK PANEL CONTINUED]****REGULATORY DATA****VOC:** 113 Grams/Liter

**LIMITATIONS:** Apply in good weather when air and surface temperature are above 50° F (10° C). Surface temperature must be at least 50° F (10° C) above dew point. For optimum application properties, bring material to 70-80° F (21-27° C) temperature range prior to mixing and application. Unmixed material (in closed containers) should be maintained in protected storage between 40 and 100° F (4-38° C). Prolonged atmospheric exposure of this product may detract from performance. Technical and application data herein is for the purpose of establishing a general guideline for the coating and the proper coating application procedures. As application, environmental and design factors can vary significantly, due care should be exercised in the selection, verification of performance, and use of the coating.

**SURFACE PREPARATION:** Paint only clean, dry surfaces. Remove all grease, oil, wax, or other foreign material by solvent or detergent washing. (SSPC-SPI)

**New Construction:** As yard procedures may vary, consult with your Sea Hawk Representative.

**APPLICATION:** Apply by brush, roller or spray. Apply 5 mils wet, which will yield 2.2 mils dry per coat.

**EQUIPMENT**

**Brush:** China Bristle


**Roller:** Solvent Resistant Roller Cover 3/8" pile smooth to medium. Prewash Roller Cover to remove loose fibers prior to use.

**Airless Spray:** Minimum 28:1 ratio pump; 0.21-0.26" (533-660 microns) orifice tip; 3/8" ID high-pressure material hose; 90 PSI line pressure; 60 mesh tip filter.

**THINNING:** If thinning is necessary, thin up to a maximum of 10% with clean potable water.

**CLEANUP:** Clean all equipment immediately after use with water. It is good practice to periodically flush out spray equipment during the course of the day. Frequency depends upon the amount sprayed, temperature, elapsed time including delay, etc.

**SAFETY:** Read and observe all precautionary statements on this label.



**[BACK PANEL CONTINUED]****STORAGE AND DISPOSAL**

Do not contaminate food, feed or water by storage or disposal.

**STORAGE:** Keep container closed when not in use. Keep container tight and upright to prevent leakage. Do not store near heat or open flame. Store below 100° F/38° C. Store in well-ventilated area.

**PESTICIDE DISPOSAL:** Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal law. If these wastes cannot be disposed of by the use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.


**CONTAINER DISPOSAL:** Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.

**PRECAUTIONARY STATEMENTS  
HAZARDS TO HUMANS AND DOMESTIC ANIMALS**

**WARNING.** Causes substantial but temporary eye injury. May be fatal if swallowed or inhaled. Harmful if absorbed through skin. Do not get in eyes or clothing. Do not breathe vapor or spray mist, or dust or chips from sanding. Avoid contact with skin, eyes or clothing. Wear protective eyewear (goggles, face shield, or safety glasses). While spraying paint or sanding boat surface, wear a mask or pesticide respirator jointly approved by the Mine Safety and Health Administration and the National Institute for Occupational Safety and Health, unless air monitoring demonstrates vapor/mist levels are below applicable limits. Wear protective clothing (long-sleeved cotton shirt, long pants and hat) and waterproof gloves. Wash thoroughly with soap and water after handling and before eating, drinking or using tobacco. Remove contaminated clothing and wash before reuse.

**ENVIRONMENTAL HAZARDS**

This pesticide is toxic to fish. Do not apply directly to water by cleaning of equipment or disposing of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill.



**[BACK PANEL CONTINUED]**

<b>FIRST AID</b>	
<b>If in eyes</b>	<ul style="list-style-type: none"> <li>• Hold eye open and rinse slowly and gently with water for 15-20 minutes.</li> <li>• Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye.</li> <li>• Call a poison control center or doctor for treatment advice.</li> </ul>
<b>If swallowed</b>	<ul style="list-style-type: none"> <li>• Call poison control center or doctor immediately for treatment advice.</li> <li>• Have person sip a glass of water if able to swallow.</li> <li>• Do not induce vomiting unless told to do so by a poison control center or doctor.</li> <li>• Do not give anything by mouth to an unconscious person.</li> </ul>
<b>If inhaled</b>	<ul style="list-style-type: none"> <li>• Move person to fresh air.</li> <li>• If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth, if possible.</li> <li>• Call a poison control center or doctor for further treatment advice.</li> </ul>
<b>If on skin or clothing</b>	<ul style="list-style-type: none"> <li>• Take off contaminated clothing.</li> <li>• Rinse skin immediately with plenty of water for 15-20 minutes.</li> <li>• Call a poison control center or doctor for treatment advice.</li> </ul>
Have the product container or label with you when calling a poison control center or doctor, or going for treatment. You may also contact 1-800-528-0997 for emergency medical treatment information.	

**IN CASE OF SPILL OR LEAK:** Ventilate area. Absorb with an inert material and dispose of in accordance with applicable local regulations.

**IN CASE OF FIRE:** Use CO<sub>2</sub>, dry chemical, foam or water spray/fog. Cool closed containers with water.

EPA Reg. No. 44891-9

EPA Est. No. 44891-FL-1

REVISED: 06-04-03

S:MAINNEW NAUTICAL COATINGS, INC./LABELS/SEA HAWK MONTEREY WATER BORNE ANTIFOULING COATING

