

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY WASHINGTON, DC 20460

OFFICE OF CHEMICAL SAFETY AND POLLUTION PREVENTION

November 10, 2014

Kevin Kutcel Agent for New Nautical Coatings, Inc. KRK Consulting LLC 5807 Churchill Way Medina, OH 44256

Subject:

Label Notification per PRN 98-10 – Minor label amendments

Product Name: Sea Hawk Tropikote Anti-Fouling Bottom Paint

EPA Registration Number: 44891-10 Application Date: October 7, 2014

Decision Number: 496360

Dear Mr. Kutcel:

The Agency is in receipt of your Application for Pesticide Notification under Pesticide Registration Notice (PRN) 98-10 for the above referenced product. The Antimicrobials Division has conducted a review of this request for its applicability under PRN 98-10 and finds that the action requested falls within the scope of PRN 98-10.

The label submitted with the application has been stamped "Notification" and will be placed in our records.

If you have any questions, you may contact Jose Gayoso at (703) 347-8652 or via email at gayoso.jose@epa.gov.

Sincerely.

Seiichi Murasaki, Acting Product Manager 33

Regulatory Management Branch I Antimicrobials Division (7510P) Office of Pesticide Programs



Yacht Finishes

PREMIUMI QUALLERY

Anti-Fouling Bottom Paint

75.80% 24.20% Copper expressed as metallic 67.3% Contains petroleum distillates

KEEP OUT OF REACH OF CHILDREN

SEE BACK PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS

LIMITED WARRANTY: The manufacturer warrants all material sold by it against defects in the material. The manufacturer's liability under the sale and warranty of this material shall in any case be limited to replacement of material only. The manufacturer makes no other warranty of this product, expressed or implied.

> **Net Contents** 1 Gallon U.S. Measure **3.785 Liters**



NEW NAUTICAL COATINGS, INC.

14805 49th Street North Clearwater, FL 33762 www.seahawkpaints.com

Page 1 of 2

Care Reviewed: _______

Hoviewed By:

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

GENERAL DESCRIPTION

Hard epoxy-based antifoulant with over 75% copper in every color. Designed to control barnacles, algae and other marine foulings in any salt or fresh water, subtropical to tropical conditions. Ideal for power or sail. This product is only for use on the surfaces of hulls on boats and vessels.

Semi-Gloss

One Pack

6% ± 2%

One Pack

100°F/38°C

3 at waterline

24-25 Lbs./Gal.

2 on entire hull and

75.8%

PRODUCT INFORMATION

Finish/Sheen: Converter:

Copper Content: Volume Solids:

Mix Ratio: Shipping Weight: Flash Point: Film Thickness:

Recommended Coats:

Theoretical Coverage:

320 Sq. Ft./Gal @ recommended film thickness

Method: Thinner:

Brush, roller or spray Cleaner:

2033-2035 Sea Hawk Xylene 7130

SHAKE VIGOROUSLY FOR A MINIMUM OF 10 MINUTES BEFORE APPLICATION

5 mils wet equals 3 dry per coat

APPLICATION DETAILS

Overcoating Interval **Drying Time (Hrs)** Substrate Temp. Touch Min. 73°F (23°C) 2 Hrs 1 Hz N/A 12 Hrs 95°F (35°C) 12 Hrs 1 Hr 1 Hr N/A

REGULATORY DATA

VOC: 288 Grams/Liter

LIMITATIONS: Apply in good weather when air and surface temperature are above 50°F (10°C). Surface temperature must be at least 50°F (10°C) above dew point. For optimum application properties, bring material to 70-80°F (21-27°C) temperature range prior to mixing and application. Unmixed material (in closed containers) should be maintained in protected storage between 40 and 100°F (4-38°C). Prolonged atmospheric exposure of this product may detract from performance. Technical and application data herein is for the purpose of establishing a general guideline for the coating and the proper coating application procedures. As application, environmental and design factors can vary significantly, due care should be exercised in the selection, verification of performance and use of the coating

SURFACE PREPARATION: Paint only clean, dry surfaces. Remove all grease, oil, wax, or other foreign material by solvent or detergent washing. (SSPC-SPI)

New Construction: As yard procedures may vary, consult with your Sea Hawk

APPLICATION: Apply by brush, roller or spray. Apply 5 mils wet, which will yield 3 mils dry per coat. **EQUIPMENT**

Brush: China Bristle

Roller: Solvent resistant roller cover 3/8" pile smooth to medium. Prewash roller cover to remove loose fibers prior to use.

Airless Spray: Minimum 33:1-2 GPM ratio pump; "0.017-0.026" orifice tip; 3/8" ID high-pressure material hose; 90 PSI line pressure; 60 mesh filter.

THINNING: We do not recommend thinning. However, if thinning is necessary, thin up to a maximum of 10% with Sea Hawk 2033-2035 only.

CLEANUP: Clean all equipment immediately after use with xylene. It is good practice

to periodically flush out spray equipment during the course of the day. Frequency depends upon the amount sprayed, temperature, elapsed time including delay, etc. SAFETY: Read and observe all precautionary statements on this label.

STORAGE AND DISPOSAL

Do not contaminate food, feed or water by storage or disposal

Storage: Do not store near heat or open flame. Store below 100°F/38°C. Store in well-ventilated area.

Pesticide Disposal: Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by the use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

Container Disposal: Non-refillable container, do not reuse or refill this container. Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

WARNING. May be fatal if swallowed. Harmful if absorbed through skin or inhaled. Causes moderate eye irritation. Prolonged or frequently repeated skin contact may cause allergic reactions in some individuals. Avoid contact with skin, eyes or clothing. Do not breathe vapors, spray mist, or dust or chips from sanding. Wash thoroughly with soap and water after handling and before eating, drinking or using tobacco. Remove contaminated clothing and wash before reuse. Use with adequate ventilation.

ENVIRONMENTAL HAZARDS

This pesticide is toxic to fish. Do not apply directly to water by cleaning of equipment or disposing of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill.

PHYSICAL AND CHEMICAL HAZARDS

Combustible. Do not use or store near heat or open flame.

FIRST AID
 Immediately call a poison control center or doctor. Do not induce vomiting unless told to do so by a poison control center or doctor. Do not give any fliquid to the person. Do not give anything by mouth to an unconscious person.
 Take off contaminated clothing. Finse skin immediately with plenty of wate for 15 – 20 minutes. Call a poison control center or doctor for treatment advice.
 Move person to fresh air. • If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth, if possible. • Call a poison control center or doctor for further treatment advice.
 Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue insing eye. Call a poison control center or doctor for treatment advice.

For Non Emergencies call New Nautical Coatings Inc., Within the USA and Canada 1-800-528-0997, Outside USA and Canada +1-727-523-8053. NOTE TO PHYSICIAN: Contains petroleum distillate, vomiting may cause aspiration

E.P.A. Registration No. 44891-10 E.P.A. Establishment No. 44891-FL-1