



UNITED STATES ENVIRONMENTAL PROTECTION AGENCY
WASHINGTON, DC 20460

OFFICE OF CHEMICAL SAFETY
AND POLLUTION PREVENTION

June 26, 2018

Kevin Kutcel
Agent
New Nautical Coatings Inc.
14805 49th Street North
Clearwater, FL 33762

Subject: Notification per PRN 98-10 – Label revision
Product Name: Sea Hawk Tropikote Anti-Fouling Bottom Paint
EPA Registration Number: 44891-10
Application Date: March 9, 2018; April 9, 2018
Decision Number: 539783 & 540396

Dear Mr. Kutcel:

The Agency is in receipt of your Application for Pesticide Notification under Pesticide Registration Notice (PRN) 98-10 for the above referenced product. The Antimicrobials Division (AD) has conducted a review of this request for its applicability under PRN 98-10 and finds that the action requested falls within the scope of PRN 98-10.

The label submitted with the application has been stamped “Notification” and will be placed in our records.

Should you wish to add/retain a reference to the company’s website on your label, then please be aware that the website becomes labeling under the Federal Insecticide Fungicide and Rodenticide Act and is subject to review by the Agency. If the website is false or misleading, the product would be misbranded and unlawful to sell or distribute under FIFRA section 12(a)(1)(E). 40 CFR 156.10(a)(5) list examples of statements EPA may consider false or misleading. In addition, regardless of whether a website is referenced on your product’s label, claims made on the website may not substantially differ from those claims approved through the registration process. Therefore, should the Agency find or if it is brought to our attention that a website contains false or misleading statements or claims substantially differing from the EPA approved registration, the website will be referred to the EPA’s Office of Enforcement and Compliance.

If you have any questions, you may contact Mohammad Alavi at (703) 347-0522 or via email at Alavi.mohammad@epa.gov. Sincerely,

A handwritten signature in blue ink that reads "E. Miederhoff".

Eric Miederhoff
Product Manager 31
Regulatory Management Branch I
Antimicrobials Division (7510P)
Office of Pesticide Programs

HIGHLIGHTED

Notes to reviewer are bracketed []
Statements in parenthesis are optional or alternative text ()

[Brand Names]
Sea Hawk Tropikote Anti-Fouling Bottom Paint

[Alternative Brand Names]
Tropikote
Sea Hawk Tropikote

TROPIKOTE

Anti-Fouling Bottom Paint

NOTIFICATION

44891-10

The applicant has certified that no changes, other than those reported to the Agency have been made to the labeling. The Agency acknowledges this notification by letter dated:

06/26/2018

ACTIVE INGREDIENT	
Cuprous Oxide (CAS No. 1317-39-1)..	75.80%
OTHER INGREDIENTS.....	24.20%
TOTAL.....	100.00%
Copper expressed as metallic	67.3%
Contains petroleum distillates	

KEEP OUT OF REACH OF CHILDREN
WARNING

SEE BACK PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS **AND FIRST AID**

(**LIMITED WARRANTY:** The manufacturer warrants all material sold by it against defects in the material. The manufacturer's liability under the sale and warranty of this material shall in any case be limited to replacement of material only. The manufacturer makes no other warranty of this product, expressed or implied.)

[**OPTIONAL MARKETING STATEMENTS:**]

Sea Hawk
Yacht Finishes
Premium Quality
Antifouling Coating
Antifouling Bottom Paint
Hand Crafted in America!SM
Hand Crafted in the USA
American Owned and Hand Crafted

USA Hand Crafted
Hard Modified Epoxy
Multi Season
288 grams/liter VOC
Contains 288 grams/liter VOC
VOC 288 grams/liter
288g/l VOC
Contains 288 g/l
VOC 288 g/l
California Compliant
CA VOC Code Compliant
Premium Yacht Finishes
(2145 Black)
(2143 Green)
(2140 Dark Blue)
(2142 Blue)
(2141 Red)

[Optional Graphics]



PREMIUM QUALITY



8 11577 01595 9

[ABOVE BAR CODE WILL APPEAR ON EACH CAN AND THE NUMBERS WILL CORRESPOND WITH THE BAR CODE ISSUED FOR THAT PRODUCT.]



Boost with
Biocop TF



Above will be used with contents and manufacturer depending on the size [Net Contents:] (5-gallon pail 18.927), (Gallon 3.785 Liters), (Quart 0.9463 Liters) Batch Code) [to appear on front or back panel of the label or immediate container depending on the container type/size]

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

GENERAL DESCRIPTION

Hard epoxy-based antifoulant with over 75% copper in every color. Designed to control barnacles, algae and other marine foulings in any salt or fresh water, subtropical to tropical conditions. Ideal for power or sail. This product is only for use on the surfaces of hulls on boats and vessels.

PRODUCT INFORMATION

Finish/Sheen: Semi-Gloss
Converter: One Pack
Copper Content: 75.8%
Volume Solids: 60% ± 2%
Mix Ratio: One Pack
Shipping Weight: 24-25 Lbs./Gal.
Flash Point: 100°F/38°C
Theoretical Coverage: 320 Sq. Ft./Gal @ recommended film thickness

APPLICATION DETAILS

Method: Brush, roller or spray
Thinner: Sea Hawk 2033-2035 Sea Hawk 2053 for reduced VOC
Cleaner: Sea Hawk Xylene 7130

SHAKE VIGOROUSLY FOR A MINIMUM OF 10 MINUTES BEFORE APPLICATION

Overcoating Interval	Drying Time (Hrs)				
	Substrate Temp.	Touch	Min.	Max.	Launch
73°F (23°C)	2 Hrs	1 Hr	N/A	12 Hrs	
95°F (35°C)	1 Hr	1 Hr	N/A	12 Hrs	

REGULATORY DATA

VOC: 288 Grams/Liter

LIMITATIONS: Apply in good weather when air and surface temperature are above 50°F (10°C). Surface temperature must be at least 5°F (1°C) above dew point. For optimum application properties, bring material to 70-80°F (21-27°C) temperature range prior to mixing and application. Unmixed material (in closed containers) should be maintained in protected storage between 40 and 100°F (4-38°C). Prolonged atmospheric exposure of this product may detract from performance. Technical and application data herein is for the purpose of establishing a general guideline for the coating and the proper coating application procedures. As application, environmental and design factors can vary significantly, due care should be exercised in the selection, verification of performance and use of the coating.

SURFACE PREPARATION: Paint only clean, dry surfaces. Remove all grease, oil, wax, or other foreign material by solvent or detergent washing. (SSPC-SPI)

New Construction: As yard procedures may vary, consult with your Sea Hawk Representative.

APPLICATION: Apply at least two coats by brush, roller or spray.

EQUIPMENT

Brush: China Bristle

Roller: Solvent resistant roller cover 3/8" pile smooth to medium. Prewash roller cover to remove loose fibers prior to use.

Airless Spray: Minimum 33:1-2 GPM ratio pump; "0.017-0.026" orifice tip; 3/8" ID high-pressure material hose; 90 PSI line pressure; 60 mesh filter.

THINNING: We do not recommend thinning. However, if thinning is necessary, thin up to a maximum of 10% with Sea Hawk 2033-2035 only. Sea Hawk 2053 for reduced VOC

CLEANUP: Clean all equipment immediately after use with xylene. It is good practice to periodically flush out spray equipment during the course of the day. Frequency depends upon the amount sprayed, temperature, elapsed time including delay, etc.

SAFETY: Read and observe all precautionary statements on this label.

STORAGE AND DISPOSAL

Do not contaminate food, feed or water by storage or disposal.

Storage: Do not store near heat or open flame. Store below 100°F/38°C. Store in well-ventilated area.

Pesticide Disposal: Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by the use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

Container Disposal: Non-refillable container. Do not reuse or refill this container. Prior to container disposal, allow any remaining paint residue in the container to air dry. Dispose of the container in accordance with Federal, State or local disposal regulations.

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

WARNING. May be fatal if swallowed. Harmful if absorbed through skin or inhaled. Causes moderate eye irritation. Prolonged or frequently repeated skin contact may cause allergic reactions in some individuals. **Wear a minimum of a NIOSH-approved particulate filtering facepiece respirator with any N1, R, or P filter; OR a NIOSH-approved elastomeric particulate respirator with any N1, R, or P filter; OR a NIOSH-approved powered air purifying respirator with HE filters.** Avoid contact with skin, eyes or clothing. Do not breathe vapors, spray mist, or dust or chips from sanding. Wash thoroughly with soap and water after handling and before eating, drinking or using tobacco. Remove contaminated clothing and wash before reuse. Use with adequate ventilation.

ENVIRONMENTAL HAZARDS

This pesticide is toxic to fish. Do not apply directly to water by cleaning of equipment or disposing of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill. This material is toxic to fish and aquatic invertebrates. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

PHYSICAL AND CHEMICAL HAZARDS

Combustible. Do not use or store near heat or open flame.

FIRST AID	
IF SWALLOWED:	<ul style="list-style-type: none"> • Immediately call a poison control center or doctor. • Do not induce vomiting unless told to do so by a poison control center or doctor. • Do not give any liquid to the person. • Do not give anything by mouth to an unconscious person.
IF ON SKIN OR CLOTHING:	<ul style="list-style-type: none"> • Take off contaminated clothing. • Rinse skin immediately with plenty of water for 15 – 20 minutes. • Call a poison control center or doctor for treatment advice.
IF INHALED:	<ul style="list-style-type: none"> • Move person to fresh air. • If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth, if possible. • Call a poison control center or doctor for further treatment advice.
IF IN EYES:	<ul style="list-style-type: none"> • Hold eye open and rinse slowly and gently with water for 15-20 minutes. • Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. • Call a poison control center or doctor for treatment advice.
<p>For Hazardous Materials [or Dangerous Goods] Incident Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night. Within USA and Canada 1-800-424-9300. Outside USA and Canada +1-703-741-5970 CHEMTREC. Account #15570.</p> <p>Have the product container or label with you when calling poison control center or doctor, or going for treatment. For Non-Emergencies call New Nautical Coatings Inc., Within the USA and Canada 1-800-528-0997, Outside USA and Canada +1-727-523-8053.</p>	
NOTE TO PHYSICIAN: Contains petroleum distillate, vomiting may cause aspiration pneumonia.	

E.P.A. Registration No. 44891-10
E.P.A. Establishment No. 44891-FL-1