



U.S. ENVIRONMENTAL PROTECTION AGENCY
Office of Pesticide Programs
Registration Division (H7505C)
401 "M" St., S.W.
Washington, D.C. 20460

EPA Reg.
Number:

44891-11

Date of Issuance:

MAR 02 1998

NOTICE OF PESTICIDE:

 X Registration
 Reregistration

(under FIFRA, as amended)

Term of Issuance:

Name of Pesticide Product:

SeaHawk Shark Skin
Antifoulant Paint

Name and Address of Registrant (include ZIP Code):

New Nautical coatings
2181 - 34th Way North
Largo, FL 33771

Note: Changes in labeling differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Registration Division prior to use of the label in commerce. In any correspondence on this product always refer to the above EPA registration number.

On the basis of information furnished by the registrant, the above named pesticide is hereby registered/reregistered under the Federal Insecticide, Fungicide and Rodenticide Act.

Registration is in no way to be construed as an endorsement or recommendation of this product by the Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.

This product is conditionally registered in accordance with FIFRA sec. 3(c)(7)(A) provided that you:

1. Submit and/or cite all data required for registration of your product under FIFRA sec. 3(c)(5) when the Agency requires all registrants of similar products to submit such data; and submit acceptable responses required for reregistration of your product under FIFRA section 4.

2. Add the phrase EPA Registration Number "EPA Reg. No. "44891-11".

Signature of Approving Official:

Marshall Swindell *M. Swindell*
Product Manager 33
Regulatory Management Branch 1
Antimicrobial Division (7510W)

Date:

MAR 02 1998

page 2
EPA Reg. No. 44891-11

3. Submit two copies of the revised final printed label for the record.

The revised Confidential Statement of Formula dated August 22, 1997 is in compliance with PR Notice 91-2, it agrees with the label claim and is acceptable.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA sec. 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

A stamped copy of the label is enclosed for your records.

If you have any questions concerning this letter, please contact Martha Terry at (703) 308-6217.


Sincerely,



Marshall Swindell
Product Manager 33
Regulatory Management Branch 1
Antimicrobial Division (7510W)

Enclosure

7166-16



Sea Hawk

Yacht Finishes

COMMERCIAL USE
ONLY



PREMIUM QUALITY

SHARKSKIN

Antifouling Bottom Paint

Net Contents
1 Gallon
U.S. Measure
3.785 Liters

NEW NAUTICAL
COATINGS INC.
2181-34th Way
Largo, FL 33771

ACTIVE INGREDIENT: Cuprous Oxide 45.19%
INERT INGREDIENTS: 54.81%
100.00%
Copper expressed as metallic 42.21%
CONTAINS XYLOL

KEEP OUT OF REACH OF CHILDREN
WARNING

SEE BACK PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS

LIMITED WARRANTY: The manufacturer warrants all material sold by it against defects in the material. The manufacturer's liability under the sale and warranty of this material shall in any case be limited to replacement of material only. The manufacturer makes no other warranty of this product, expressed or implied.

with COMMENTS
in EPA Letter Dated:

MAR 02 1998
MAR 02 1998

Under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended, for the pesticide,
registered under EPA Reg. No.
44891-11

1-21-98

466

DIRECTIONS FOR USE

It is a violation of federal law to use this product in a manner inconsistent with its labeling.

GENERAL DESCRIPTION

This product is only for use on the surfaces of hulls on boats and vessels. This coating controls barnacles, algae and other marine foulings. It can be used in both salt and fresh water.

STIR WELL BEFORE USING. We do not recommend thinning. However, if spray equipment used for application is such that thinning is necessary, NCI Reducer #2033 should be used, but only the minimum needed for good application properties.

Note: Excessive thinning will adversely affect dry film thickness due to lower solids and increased spreading rate.

SURFACE

New Fiberglass or gel-coat - must be free of mold release compound and glaze must be broken with 80/120 grit sandpaper and sanding dust removed. S-80 Wax and Grease Remover is recommended for cleaning fiberglass before and after sanding for best results. Priming is not required.

Wooden Bents - Remove all residue before painting.

New wood - Reduce 25% with appropriate thinner and use it as its own primer. Follow with a minimum of one full coat without reduction.

Previously painted surfaces - Haul boat, pressure wash bottom clean. Remove all traces of loose and peeling paint. Sand all bare spots with 80 grit sandpaper. Buff entire bottom with Scotch Brite pad, wipe clean.

Clean bare spots with S-80 Wax and Grease Remover. Apply 2 coats of 1277 barrier coat, with 3 hours dry time between coats. Allow to dry overnight. Apply two coats of Tropikote to entire surface allowing 3 hours dry time between coats. A third coat may be applied to high wear areas.

Allow to dry 12 hours before launching.

E.P.A. Registration No. 44891-10/E.P.A. Establishment No. 44891-FL-1

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMAN AND DOMESTIC ANIMALS

KEEP OUT OF REACH OF CHILDREN

Causes eye irritation. May be fatal if swallowed or inhaled. Harmful if absorbed through skin or inhaled. This product may be a dermal sensitizer. Avoid contact with skin, eyes or clothing. Avoid breathing vapors, spray mist, dust or chips from sanding. Wash thoroughly with soap and water after handling and before eating and smoking. Use with adequate ventilation. Wear protective clothing such as gloves, long-sleeved cotton shirt, long pants and hat. Remove contaminated clothing and wash before reuse. While spraying paint or sanding boat surface, wear a mask or a respirator jointly approved by the Mining Enforcement and Safety Administration and the National Institute for Occupational Safety and Health.

STATEMENT OF PRACTICAL TREATMENT

If swallowed: Promptly drink a large quantity of milk, egg whites, gelatin solution or, if these are not available, drink large quantities of water. Avoid alcohol. Get medical attention.

If inhaled: Remove victim to fresh air. If victim is not breathing give artificial respiration, preferably mouth to mouth. Get medical attention.

If in eyes: Flush with plenty of water. Get medical attention.

If on skin: Wash with plenty of soap and water. Get medical attention.

ENVIRONMENTAL HAZARD:

This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill.

PHYSICAL AND CHEMICAL HAZARDS:

Do not use or store near heat or open flame.

STORAGE AND DISPOSAL

Pesticide Disposal Do not contaminate water, food or feed by storage nor disposal. Open dumping is prohibited. Pesticide disposal and pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency or the hazardous waste representative at the nearest EPA Regional Office for guidance.

Container Disposal - Container - Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of on a sanitary landfill, or by approved state and local procedures.

ACCEPTED

With COMMENTS
in EPA Letter Dated:

MAR 0 1 1990

Under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended, for the pesticide,
registered under EPA Reg. No.
44891-10

RECEIVED
1-21-98